

**NON-TITLE V PERMIT APPLICATION INSTRUCTIONS
COAL PREPARATION SOURCE DESCRIPTION FORM (APC 112)**

This form should be completed for all new permit applications and all renewals where source conditions have changed since the previous application. This form should be used for all coal preparation operations instead of the more general Process or Fuel Burning Source Description form (APC 102), and the Emission Point Description form (APC 101).

If any of the information requested is considered confidential, two application forms should be submitted, along with the Confidential Information Request form. One application form must be clearly marked to indicate that it contains confidential information, which is not to be made public and another application form, which does not contain the confidential information and can be placed in our general files. Emission data normally cannot be treated as confidential by the Division. Please contact the APC Division if there are any questions concerning confidentiality of information. The Confidential Information Request form can be found on the Division's website at: <http://tn.gov/environment/article/permit-air-other-information>.

The Tennessee Air Pollution Control Division prefers that application forms be submitted via email to the email address Air.Pollution.Control@TN.gov. All application forms should be scanned/combined into one PDF document and sent as an attachment to the email. If email is not available, then application forms can be mailed to the address on the form.

The items below give a brief explanation of the information being requested on the form. The following numbers refer to the specific box on the form:

1. The organization's legal name is the name under which the company is registered with the Tennessee Secretary of State (SOS). The organization's legal name and SOS control number can be found on the SOS website at <https://tnbear.tn.gov/Ecommerce/FilingSearch.aspx>. If the organization is not registered with the SOS, then the owner's name must be listed.
2. The Emission Source Reference Number(s) will be assigned by the Tennessee Air Pollution Control Division. It is an eight digit number in the following format NN-NNNN-NN.
3. Check "Yes" or "No" depending on whether the air contaminant source is subject to an NSPS rule (New Source Performance Standards) or NESHAP rule (National Emission Standard for Hazardous Air Pollutants). List the rule citation, including Part, Subpart, and applicable Sections. For example, a boiler may be subject to 40 CFR Part 60 Subpart Dc and sections §60.42c, §60.42c, §60.46c, §60.47c, and §60.48c.
4. Enter the approximate yearly tonnage received and shipped, by each mode of transportation.
5. Indicate what operations are conducted at the site. If operations other than those listed are conducted, please specify the operations.
6. List each piece of equipment such as jaw crusher, hammermill, front end loader, rotary dryer, etc. used for each major function. Show all the equipment and storage on a simple flow diagram to be included with application. Enter a flow diagram reference number, the design and maximum actual operating rate in tons per hour, along with the annual production rate in tons, and the appropriate installation date of each.
7. Emission estimates for each pollutant emitted from this source should be based on stack sampling results or engineering calculations. In certain cases, other estimates may be accepted. Calculations should be

attached on a separate sheet. Full details regarding the calculation method and emission factors used should be included. For example:

- (1) If U.S. EPA's Compilation of Air Emission Factors (AP-42) is used, submit the version, chapter, table, equation, etc. AP-42 can be found on the U.S. EPA's website: <https://www.epa.gov/air-emissions-factors-and-quantification/ap-42-compilation-air-emission-factors> .
- (2) Attach sample calculations and fully explain any assumptions, bottlenecks, etc.
- (3) Submit any supporting information such as manufacturer's data or safety data sheets (SDS).
- (4) If the emissions are from a source test, provide details on the source test such as the date of the test, was the test approved by the Department, etc. If the source test was not approved by the Department, submit the test details and results.
- (5) If multiple fuels are used, use the worst case fuel to calculate emissions for each pollutant, and list the fuel in the calculation method details. Include the percent sulfur in the fuel and the BTU content of fuel, when appropriate.

Average emissions (lbs./hr.) should be representative of the following: (1) For continuous or long-run, steady-state, operations it is the total weight of pollutant emitted to the atmosphere for the entire period of continuous operation or for a typical portion thereof divided by the number of hours of such period or portion thereof; (2) for cyclical or batch type operation, it is the total weight of the pollutant emitted to the atmosphere for a period which covers a complete or an integral number of cycles divided by the hours of actual process operation during such periods.

Maximum emissions (lbs./hr.) should be determined by dividing the total highest emissions possible during any 3 hour period with control equipment working properly, by 3. This will be dependent upon such things, either singly or in combination, as maximum possible operating rate, a particular input material, product, or fuel which may result in increased emissions; periods of highest emissions for cyclical or batch type operations, etc. Concentrations should be determined for stack emissions only and should reflect average exit gas concentrations reported in the units specified on the form.

Average emissions (ton/yr) should be calculated by multiplying the average emissions (lb/hr) by the normal operating hours (hr/yr) and converting the units from pounds (lb) to tons.

Potential emissions (ton/yr) or "Potential to emit" means the maximum capacity of a source to emit an air contaminant under its physical and operational design. Any physical or operational limitation on the capacity of the source to emit an air contaminant, including air contaminant control equipment and restrictions on hours of operation or on the type or amount of material combusted, stored, or processed, shall be treated as part of its design only if the limitation or the effect it would have on emissions is "legally enforceable." Secondary emissions do not count in determining the "potential to emit" of a source.

Emission estimation method code and control device descriptions, along with corresponding codes, can be found on the last page of these instructions. The codes which most accurately describe the estimation methods and control equipment should be used; along with the estimated control equipment efficiency for each pollutant present. Any estimation methods of control devices other than those listed in the tables should be described in the comments section.

Some hazardous air pollutants (HAPs) are considered both a HAP and an organic compound. Include these HAPs when determining organic compound totals. If necessary, additional HAPs can be listed in the Other (specify) areas or attached as an additional sheet.

- 8.** Include a description and the operating parameters of any control devices. Examples include bag house pressure drop, scrubber flow rate and pH of flow, temperature of thermal oxidizer, how often fabric filters are changed, etc. Typically this information can be found in the operating manual for the control device. If the control device is covered by a federal regulation, it is acceptable to cite the applicable section(s) of the federal regulation.
- 9.** If thermal drying is conducted, please indicate all fuel used. Enter the annual usage, the usage per ton of coal processed (in pounds per ton), percent sulfur, percent ash, and the BTU value of the fuel.
- 10.** For the stockpiles, enter the estimated annual tons, turnover rate (in tons per month), if the pile is wetted, the number of sides enclosed, and other dust control (specify in comments, line 12). Also, enter the loading method (for example, front end loader, conveyor, etc.)
- 11.** Indicate, by completing the appropriate spaces, the type of dust control for both plant and access roads. Indicate the approximate miles of paved and unpaved roads. If roads are watered, also indicate the approximate frequency of watering. Indicate only the approximate miles of road in each category that are actually traveled. The unpaved category should include total miles of traveled unpaved roads even if they are watered.
- 12.** Use the comments space for further descriptions or other needed information that was not included previously or information on modifications.
- 13.** If this form is being submitted at the same time as an APC 100 form, then a signature is not required on this form. Date this form regardless of whether a signature is provided. If this form is NOT being submitted at the same time as an APC 100 form, then a signature is required. Applications should be signed by the responsible person listed in Item 7 of the APC 100 form.

Table of Pollution Control Device and Method Codes

Note: For cyclones, settling chambers, wet scrubbers, and electrostatic precipitators; the efficiency ranges correspond to the following percentages:

High: 95-99%. Medium: 80-95% And Low: Less than 80%.

If the system has several pieces of connected control equipment, indicate the sequence. For example: 008, 010. If none of the below codes fit, use 999 as a code for other and specify in the comments.

No Equipment	000	Gas Adsorption Column -- Packed	050
Activated Carbon Adsorption	048	Gas Adsorption Column – Tray Type.....	051
Afterburner – Direct Flame	021	Gas Scrubber (General: Not Classified)	013
Afterburner – Direct Flame with Heat Exchanger..	022	Limestone Injection – Dry.....	041
Afterburner – Catalytic	019	Limestone Injection – Wet.....	042
Afterburner – Catalytic with Heat Exchanger	020	Liquid Filtration System	049
Alkalized Alumina.....	040	Mist Eliminator – High Velocity	014
Cartridge Filter.....	070	Mist Eliminator – Low Velocity	015
Catalytic Oxidation – Flue Gas Desulfurization	039	Process Enclosed	054
Cyclone – High Efficiency.....	007	Process Gas Recovery	060
Cyclone – Medium Efficiency.....	008	Settling Chamber – High Efficiency	004
Cyclone – Low Efficiency	009	Settling Chamber – Medium Efficiency	005
Dust Suppression by Chemical Stabilizers or		Settling Chamber – Low Efficiency	006
Wetting Agents	062	Spray Tower (Gaseous Control Only).....	052
Electrostatic Precipitator – High Efficiency	010	Sulfuric Acid Plant – Contact Process.....	043
Electrostatic Precipitator – Medium Efficiency.....	011	Sulfuric Acid Plant – Double Contact Process	044
Electrostatic Precipitator – Low Efficiency	012	Vapor Recovery System (Including Condensers,	
Fabric Filter – High Temperature	016	Hooding and Other Enclosures)	047
Fabric Filter – Medium Temperature.....	017	Venturi Scrubber (Gaseous Control Only).....	053
Fabric Filter – Low Temperature	018	Wet Scrubber – High Efficiency	001
Fabric Filter – Metal Screens (Cotton Gins).....	059	Wet Scrubber – Medium Efficiency	002
Flaring.....	023	Wet Scrubber – Low Efficiency	003
		Wet Suppression by Water Sprays	061

Table of Emission Estimation Method Codes

Not applicable / Emissions are known to be zero	0
Emissions based on source testing	1
Emissions based on material balance using engineering expertise and knowledge of process.....	2
Emissions calculated using emission factors from EPA publications No. AP-42 Compilation of Air Pollution	
Emissions Factors	3
Judgment.....	4
Emissions calculated using a special emission factor different from that in AP-42	5
Other (Specify in comments).....	6