

**Department of State  
Division of Publications**

312 Rosa L. Parks Avenue, 8th Floor Snodgrass/TN Tower  
Nashville, TN 37243  
Phone: 615-741-2650  
Email: [publications.information@tn.gov](mailto:publications.information@tn.gov)

**For Department of State Use Only**

Sequence Number: \_\_\_\_\_  
Rule ID(s): \_\_\_\_\_  
File Date: \_\_\_\_\_  
Effective Date: \_\_\_\_\_

# Rulemaking Hearing Rule(s) Filing Form

*Rulemaking Hearing Rules are rules filed after and as a result of a rulemaking hearing (Tenn. Code Ann. § 4-5-205).*

*Pursuant to Tenn. Code Ann. § 4-5-229, any new fee or fee increase promulgated by state agency rule shall take effect on July 1, following the expiration of the ninety (90) day period as provided in § 4-5-207. This section shall not apply to rules that implement new fees or fee increases that are promulgated as emergency rules pursuant to § 4-5-208(a) and to subsequent rules that make permanent such emergency rules, as amended during the rulemaking process. In addition, this section shall not apply to state agencies that did not, during the preceding two (2) fiscal years, collect fees in an amount sufficient to pay the cost of operating the board, commission or entity in accordance with § 4-29-121(b).*

<b>Agency/Board/Commission:</b>	Environment and Conservation
<b>Division:</b>	Solid Waste Management
<b>Contact Person:</b>	Jackie Okoreeh-Baah
<b>Address:</b>	William R. Snodgrass TN Tower 312 Rosa L. Parks Avenue, 14th Floor Nashville, Tennessee
<b>Zip:</b>	37243
<b>Phone:</b>	(615) 532-0825
<b>Email:</b>	<a href="mailto:Jackie.Okoreeh-Baah@tn.gov">Jackie.Okoreeh-Baah@tn.gov</a>

**Revision Type (check all that apply):**

- Amendment  
 New  
 Repeal

**Rule(s) Revised (ALL chapters and rules contained in filing must be listed here. If needed, copy and paste additional tables to accommodate multiple chapters. Please enter only ONE Rule Number/Rule Title per row)**

Chapter Number	Chapter Title
0400-12-01	Hazardous Waste Management
Rule Number	Rule Title
0400-12-01-.01	Hazardous Waste Management System: General
0400-12-01-.02	Identification and Listing of Hazardous Waste
0400-12-01-.03	Notification Requirements and Standards Applicable to Generators of Hazardous Waste
0400-12-01-.05	Interim Status Standards for Owners and Operators of Existing Hazardous Waste Treatment, Storage, and Disposal Facilities
0400-12-01-.06	Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities
0400-12-01-.07	Permitting of Hazardous Waste Treatment, Storage, and Disposal Facilities
0400-12-01-.08	Fee System for Transporters, Storers, Treaters, Disposers, and Certain Generators of Hazardous Waste and For Certain Used Oil Facilities or Transporters
0400-12-01-.09	Standards for the Management of Specific Hazardous Wastes and Specific Types of Hazardous Waste Management Facilities

(Place substance of rules and other info here. Statutory authority must be given for each rule change. For information on formatting rules go to <http://state.tn.us/sos/rules/1360/1360.htm>)

Chapter 0400-12-01  
Hazardous Waste Management

Amendments

Rule 0400-12-01-.01 Hazardous Waste Management System: General is amended by deleting it in its entirety and substituting instead the following:

0400-12-01-.01 HAZARDOUS WASTE MANAGEMENT SYSTEM: GENERAL.

(1) General

(a) Purpose, Scope, and Applicability

This rule provides definitions of terms, general standards and procedures, and overview information applicable to these rules.

(b) Use of Number and Gender

As used in these rules:

1. Words in the masculine gender also include the feminine and neuter genders; and
2. Words in the singular include the plural; and
3. Words in the plural include the singular.

(c) Rule Structure

These rules are organized, numbered, and referenced according to the following outline form:

(1) paragraph

(a) subparagraph

1. part

(i) subpart

(I) item

I. subitem

A. section

(A) subsection

(2) Definitions and References

(a) Definitions

When used in Rules 0400-12-01-.01 through .12, the following terms have the meanings given below unless otherwise specified:

"Above ground tank" means a device meeting the definition of "tank" in this subparagraph and that is situated in such a way that the entire surface area of the tank is completely above the

plane of the adjacent surrounding surface and the entire surface area of the tank (including the tank bottom) is able to be visually inspected.

"Accumulated speculatively" means accumulated speculatively as defined in subpart (1)(a)3(viii) of Rule 0400-12-01-.02.

"Act" means the Tennessee Hazardous Waste Management Act, as amended, Tennessee Code Annotated (T.C.A.) §§ 68-212-101 et seq.

"Active life" of a facility means the period from the initial receipt of hazardous waste at the facility until the Commissioner receives certification of final closure.

"Active portion" means that portion of a facility where treatment, storage, or disposal operations are being or have been conducted after the date one or more of the hazardous wastes handled by the facility first became subject to regulation under rules promulgated under the Act and which is not a closed portion. (See also "closed portion" and "inactive portion".)

"Administrator" means the Administrator of the Environmental Protection Agency, or his designee.

"Analogous raw material" means a material for which a hazardous secondary material substitutes and which serves the same function and has similar physical and chemical properties as the hazardous secondary material.

"Ancillary equipment" means any device including, but not limited to, such devices as piping, fittings, flanges, valves, and pumps, that is used to distribute, meter, or control the flow of hazardous waste from its point of generation to a storage or treatment tank(s), between hazardous waste storage and treatment tanks to a point of disposal onsite, or to a point of shipment for disposal off-site.

"Application" means the EPA standards national forms for applying for a permit, including any additions, revisions or modifications to the forms; or forms approved by EPA for use in approved States, including any approved modifications or revisions. Application also includes the information required by the Commissioner under subparagraph (5)(a) through paragraph (6) of Rule 0400-12-01-.07 (contents of Part B of the hazardous waste management permit application).

"Approved program or approved State" means a State which has been approved or authorized by EPA under 40 CFR Part 271.

"Aquifer" means a geologic formation, group of formations, or part of a formation capable of yielding a significant amount of ground water to wells or springs.

"ASTM" means the American Society for Testing and Materials.

"Authorized representative" means the person responsible for the overall operation of a facility or an operational unit (i.e., part of a facility), e.g., the plant manager, superintendent or person of equivalent responsibility.

"Battery" means a device consisting of one or more electrically connected electrochemical cells which is designed to receive, store, and deliver electric energy. An electrochemical cell is a system consisting of an anode, cathode, and an electrolyte, plus such connections (electrical and mechanical) as may be needed to allow the cell to deliver or receive electrical energy. The term battery also includes an intact, unbroken battery from which the electrolyte has been removed.

"Board" means the Underground Storage Tanks and Solid Waste Disposal Control Board established by T.C.A. §68-211-111.

"Boiler" means an enclosed device using controlled flame combustion and having the following characteristics:

1.
  - (i) The unit must have physical provisions for recovering and exporting thermal energy in the form of steam, heated fluids, or heated gases; and
  - (ii) The unit's combustion chamber and primary energy recovery section(s) must be of integral design. To be of integral design, the combustion chamber and the primary energy recovery section(s) (such as waterwalls and superheaters) must be physically formed into one manufactured or assembled unit. A unit in which the combustion chamber and the primary energy recovery section(s) are joined only by ducts or connections carrying flue gas is not integrally designed; however, secondary energy recovery equipment (such as economizers or air preheaters) need not be physically formed into the same unit as the combustion chamber and the primary energy recovery section. The following units are not precluded from being boilers solely because they are not of integral design: process heaters (units that transfer energy directly to a process stream), and fluidized bed combustion units; and
  - (iii) While in operation, the unit must maintain a thermal energy recovery efficiency of at least 60 percent, calculated in terms of the recovered energy compared with the thermal value of the fuel; and
  - (iv) The unit must export and utilize at least 75 percent of the recovered energy, calculated on an annual basis. In this calculation, no credit shall be given for recovered heat used internally in the same unit (examples of internal use are the preheating of fuel or combustion air, and the driving of induced or forced draft fans or feedwater pumps); or
2. The unit is one which the Commissioner has determined, on a case-by-case basis, to be a boiler, after considering the standards in subparagraph (4)(d) of this rule.

"By-product" means by-product as defined in subpart (1)(a)3(iii) of Rule 0400-12-01-.02.

"Carbon dioxide stream" means carbon dioxide that has been captured from an emission source (e.g., power plant), plus incidental associated substances derived from the source materials and the capture process, and any substances added to the stream to enable or improve the injection process.

"Carbon regeneration unit" means any enclosed thermal treatment device used to regenerate spent activated carbon.

"Cathode ray tube" or CRT means a vacuum tube, composed primarily of glass, which is the visual or video display component of an electronic device. A used, intact CRT means a CRT whose vacuum has not been released. A used, broken CRT means glass removed from its housing or casing whose vacuum has been released.

"Certification" means a statement of professional opinion based upon knowledge and belief.

"CFR" means the Code of Federal Regulations.

"Closed portion" means that portion of a facility which an owner or operator has closed in accordance with the approved facility closure plan and all applicable closure requirements. (See also "active portion" and "inactive portion".)

"Commissioner" means the Commissioner of the Tennessee Department of Environment and Conservation (formerly the Tennessee Department of Health and Environment) or his authorized representative.

"Component" means any constituent part of a unit or any group of constituent parts of a unit assembled to perform a specific function (e.g., a pump seal, pump, kiln liner, kiln thermocouple) when used in Rule 0400-12-01-.07 and, when used otherwise in these rules, means either the tank or ancillary equipment of a tank system.

"Confined aquifer" means an aquifer bounded above and below by impermeable beds or by beds of distinctly lower permeability than that of the aquifer itself; an aquifer containing confined ground water.

"Conglomerate Waste Stream" means the mixture of individual wastewater streams at the point of entry into either the headworks of an on-site wastewater treatment plant or the sewer system that leads to a publicly owned treatment works (POTW).

"Contained" means held in a unit (including a land-based unit as defined in this subparagraph) that meets the following criteria:

1. The unit is in good condition, with no leaks or other continuing or intermittent unpermitted releases of the hazardous secondary materials to the environment, and is designed, as appropriate for the hazardous secondary materials, to prevent releases of hazardous secondary materials to the environment. Unpermitted releases are releases that are not covered by a permit (such as a permit to discharge to water or air) and may include, but are not limited to, releases through surface transport by precipitation runoff, releases to soil and groundwater, wind-blown dust, fugitive air emissions, and catastrophic unit failures;
2. The unit is properly labeled or otherwise has a system (such as a log) to immediately identify the hazardous secondary materials in the unit; and
3. The unit holds hazardous secondary materials that are compatible with other hazardous secondary materials placed in the unit and is compatible with the materials used to construct the unit and addresses any potential risks of fires or explosions.

(Note: As used in this definition, "compatible" means that the commingling with other hazardous secondary materials will not produce heat or pressure, fire or explosion, violent reaction, toxic dusts, mists, fumes, or gases, or flammable fumes or gases; or that the placement in a particular unit will not cause detectable corrosion or decay of containment materials (e.g., container inner liners or tank walls.)

4. Hazardous secondary materials in units that meet the applicable requirements of Rule 0400-12-01-.05 or Rule 0400-12-01-.06 are presumptively contained.

"Container" means any portable device in which a material is stored, transported, treated, disposed of, or otherwise handled.

"Containment building" means a hazardous waste management unit that is used to store or treat hazardous waste under the provisions of Rule 0400-12-01-.06(33) and 0400-12-01-.05(30).

"Contingency plan" means a document setting out an organized, planned, and coordinated course of action to be followed in case of a fire, explosion, or release of hazardous waste or hazardous waste constituents which could threaten public health or the environment.

"Corrective action management unit" or "CAMU" means an area within a facility that is used only for managing remediation wastes for implementing corrective action or cleanup at the facility.

"Corrosion expert" means a person who, by reason of his knowledge of the physical sciences and the principles of engineering and mathematics, acquired by a professional education and related practical experience, is qualified to engage in the practice of corrosion control on buried or submerged metal piping systems and metal tanks. Such a person must be certified as being qualified by the National Association of Corrosion Engineers (NACE) or be a registered professional engineer who has certification or licensing that includes education and experience in corrosion control on buried or submerged metal piping systems and metal tanks.

"CRT collector" means a person who receives used, intact CRTs for recycling, repair, resale, or donation.

“CRT exporter” means any person in the United States who initiates a transaction to send used CRTs outside the United States or its territories for recycling or reuse, or any intermediary in the United States arranging for such export.

“CRT glass manufacturer” means an operation or part of an operation that uses a furnace to manufacture CRT glass.

“CRT processing” means conducting all of the following activities:

1. Receiving broken or intact CRTs; and
2. Intentionally breaking intact CRTs or further breaking or separating broken CRTs; and
3. Sorting or otherwise managing glass removed from CRT monitors.

“CWA” means the Clean Water Act (formerly referred to as the Federal Water Pollution Act or Federal Water Pollution Control Act amendments of 1972) Pub. L. 92-500, as amended by Publ. L. 92-217 and Publ. L. 95-576; 33 U.S. C. 1251 et seq.

"Department" means the Tennessee Department of Environment and Conservation (formerly Tennessee Department of Health and Environment).

"Designated facility" means:

1. A hazardous waste treatment, storage, or disposal facility which:
  - (i) Has received a permit (or interim status) in accordance with the requirements of Rule 0400-12-01-.07; or
  - (ii) Has received a permit (or interim status) from a State authorized in accordance with 40 CFR 271; or
  - (iii) Is regulated under subpart (1)(f)3(ii) of Rule 0400-12-01-.02 or paragraph (6) of Rule 0400-12-01-.09; and
  - (iv) Has been designated on the manifest by the generator pursuant to subparagraph (3)(a) of Rule 0400-12-01-.03.
2. Designated facility also means a generator site designated on the manifest to receive its waste as a return shipment from a facility that has rejected the waste in accordance with part (5)(c)6 of Rule 0400-12-01-.05 or Rule 0400-12-01-.06.
3. If a waste is destined to a facility in an authorized State which has not yet obtained authorization to regulate that particular waste as hazardous, then the designated facility must be a facility allowed by the receiving State to accept such waste.

“Destination facility” means a facility that treats, disposes of, or recycles a particular category of universal waste, except those management activities described in parts (2)(d)1 and 3 and (3)(d)1 and 3 of Rule 0400-12-01-.12. A facility at which a particular category of universal waste is only accumulated, is not a destination facility for purposes of managing that category of universal waste.

“Dike” means an embankment or ridge of either natural or man-made materials used to prevent the movement of liquids, sludges, solids, or other materials.

“Dioxins and furans” (D/F) means tetra-, penta-, hexa-, hepta-, and octa-chlorinated dibenzo dioxins and furans.

"Discharge" or "hazardous waste discharge" means the accidental or intentional spilling, leaking, pumping, pouring, emitting, emptying, or dumping of hazardous waste into or on any land or water.

"Disposal" means the discharge, deposit, injection, dumping, spilling, leaking, or placing of any hazardous waste into or on any land, water or air so that such hazardous waste or any constituent thereof may enter the environment or be emitted into the air or discharged into any waters, including ground waters.

"Disposal facility" means a facility or part of a facility at which hazardous waste is intentionally placed into or on any land or water, and at which waste will remain after closure. The term disposal facility does not include a corrective action management unit into which remediation wastes are placed.

"Division Director" or "Director" means the Director of the Division of Solid Waste Management of the Department, or his designee. This person also serves as the Technical Secretary to the Board, and functions as the chief of staff to both the Commissioner and the Board in matters relating to these rules and their implementation.

"DOT" means the U.S. Department of Transportation.

"Drip pad" is an engineered structure consisting of a curbed, free-draining base, constructed of non-earthen materials and designed to convey preservative kick-back or drippage from treated wood, precipitation, and surface water run-on to an associated collection system at wood preserving plants.

"Electronic manifest" or "e-Manifest" means the electronic format of the hazardous waste manifest that is obtained from EPA's national e-Manifest system and transmitted electronically to the system, and that is the legal equivalent of EPA Forms 8700-22 (Manifest) and 8700-22A (Continuation Sheet).

"Electronic manifest system" or "e-Manifest system" means EPA's national information technology system through which the electronic manifest may be obtained, completed, transmitted, and distributed to users of the electronic manifest and to regulatory agencies.

"Elementary neutralization unit" means a device which:

1. Is used for neutralizing wastes that are hazardous only because they exhibit the corrosivity characteristic defined in Rule 0400-12-01-.02(3)(c), or they are listed in Rule 0400-12-01-.02(4) only for this reason; and
2. Meets the definition of tank, tank system, container, transport vehicle, or vessel in this subparagraph.

"Emergency permit" means a hazardous waste management permit issued in accordance with Rule 0400-12-01-.07(1)(d).

"EPA" means the U.S. Environmental Protection Agency.

"EPA Identification Number" is synonymous with "Installation Identification Number."

"EPA region" means the states and territories found in any one of the following ten regions:

Region I - Maine, Vermont, New Hampshire, Massachusetts, Connecticut, and Rhode Island.

Region II - New York, New Jersey, Commonwealth of Puerto Rico, and the U.S. Virgin Islands.

Region III - Pennsylvania, Delaware, Maryland, West Virginia, Virginia, and the District of Columbia.

Region IV - Kentucky, Tennessee, North Carolina, Mississippi, Alabama, Georgia, South Carolina, and Florida.

Region V - Minnesota, Wisconsin, Illinois, Michigan, Indiana, and Ohio.

Region VI - New Mexico, Oklahoma, Arkansas, Louisiana, and Texas.

Region VII - Nebraska, Kansas, Missouri, and Iowa.

Region VIII - Montana, Wyoming, North Dakota, South Dakota, Utah, and Colorado.

Region IX - California, Nevada, Arizona, Hawaii, Guam, American Samoa, Commonwealth of the Northern Mariana Islands.

Region X - Washington, Oregon, Idaho, and Alaska.

"Equivalent method" means any testing or analytical method approved by the Commissioner under Rule 0400-12-01-.01(3).

"Existing hazardous waste management facility" or "existing facility" means a facility which was in operation, or for which construction had commenced, on or before the date on which one or more of the hazardous wastes handled or to be handled by the facility first became subject to regulation under rules promulgated under the Act. Construction has commenced if:

1. The owner or operator has obtained all necessary Federal, State, and local preconstruction approvals or permits; and either
2. (i) A continuous physical, on-site construction program has begun; or  
(ii) The owner or operator has entered into contractual obligations -- which cannot be canceled or modified without substantial loss -- for construction of the facility to be completed within a reasonable time.

"Existing portion" means that land surface area of an existing waste management unit, included in the original Part A permit application, on which wastes have been placed prior to the issuance of a permit.

"Existing tank system" or "existing component" means a tank system or component that is used for the storage or treatment of hazardous waste and that is in operation, or for which installation has commenced on or prior to July 14, 1986. Installation will be considered to have commenced if the owner or operator has obtained all Federal, State, and local approvals or permits necessary to begin physical construction of the site or installation of the tank system and if either (1) a continuous on-site physical construction or installation program has begun, or (2) the owner or operator has entered into contractual obligations - which cannot be canceled or modified without substantial loss - for physical construction of the site or installation of the tank system to be completed within a reasonable time.

"Explosives or munitions emergency" means a situation involving the suspected or detected presence of unexploded ordnance (UXO), damaged or deteriorated explosives or munitions, an improvised explosive device (IED), other potentially explosive material or device, or other potentially harmful military chemical munitions or device, that creates an actual or potential imminent threat to human health, including safety, or the environment, including property, as determined by an explosives or munitions emergency response specialist. Such situations may require immediate and expeditious action by an explosives or munitions emergency response specialist to control, mitigate, or eliminate the threat.



“Explosives or munitions emergency response” means all immediate response activities by an explosives and munitions emergency response specialist to control, mitigate, or eliminate the actual or potential threat encountered during an explosives or munitions emergency. An explosives or munitions emergency response may include in-place render-safe procedures, treatment or destruction of the explosives or munitions and/or transporting those items to another location to be rendered safe, treated, or destroyed. Any reasonable delay in the completion of an explosives or munitions emergency response caused by a necessary, unforeseen, or uncontrollable circumstance will not terminate the explosives or munitions emergency. Explosives and munitions emergency responses can occur on either public or private lands and are not limited to responses at RCRA facilities.

“Explosives or munitions emergency response specialist” means an individual trained in chemical or conventional munitions or explosives handling, transportation, render-safe procedures, or destruction techniques. Explosives or munitions emergency response specialists include Department of Defense (DOD) emergency explosive ordnance disposal (EOD), technical escort unit (TEU), and DOD-certified civilian or contractor personnel; and other Federal, State, or local government, or civilian personnel similarly trained in explosives or munitions emergency responses.

"Facility" means:

1. All contiguous land, and structures, other appurtenances, and improvements on the land, used for treating, storing, or disposing of hazardous waste, or for managing hazardous secondary materials prior to reclamation. A facility may consist of several treatment, storage, or disposal operational units (e.g., one or more landfills, surface impoundments, or combinations of them).
2. For the purpose of implementing corrective action under Rule 0400-12-01-.06(6)(l), all contiguous property under the control of the owner or operator seeking a permit under the Tennessee Hazardous Waste Management Act, T.C.A. §§ 68-212-101 et seq. This definition also applies to facilities implementing corrective action under T.C.A. § 68-212-111.
3. Notwithstanding part 2 of this definition, a remediation waste management site is not a facility that is subject to Rule 0400-12-01-.06(6)(l), but is subject to corrective action requirements if the site is located within such a facility.

"Facility mailing list" means the mailing list for a facility maintained by the Department in accordance with Rule 0400-12-01-.07(7)(e)3(i)(V).

"Federal agency" means any department, agency, or other instrumentality of the Federal Government, any independent agency or establishment of the Federal Government including any Government corporation, and the Government Printing Office.

“Federal, State and local approvals or permits necessary to begin physical construction” means permits and approvals required under Federal, State or local hazardous waste control statutes, regulations or ordinances.

“FIFRA” means the Federal Insecticide, Fungicide, and Rodenticide Act (7 U.S.C. 136-136y).

“Final authorization” means approval by EPA of a State program which has met the requirements of Section 3006(b) of RCRA and the applicable requirements of 40 CFR Part 271, Subpart A.

"Final closure" means the closure of all hazardous waste management units at the facility in accordance with all applicable closure requirements so that hazardous waste management activities under Rules 0400-12-01-.05 and 0400-12-01-.06 are no longer conducted at the facility unless subject to the provisions in Rule 0400-12-01-.03(4)(e).

"Food-chain crops" means tobacco, crops grown for human consumption, and crops grown for feed for animals whose products are consumed by humans.

"Freeboard" means the vertical distance between the top of a tank or surface impoundment dike, and the surface of the waste contained therein.

"Free liquids" means liquids which readily separate from the solid portion of a waste under ambient temperature and pressure.

"Functionally equivalent component" means a component which performs the same function or measurement and which meets or exceeds the performance specifications of another component.

"Furans" – see "Dioxins and furans".

"Generation" means the act or process of producing hazardous wastes.

"Generator" means any person, by site, whose act or process produces hazardous waste identified or listed in Rule 0400-12-01-.02 or whose act first causes a hazardous waste to become subject to regulation.

"Ground water" means water below the land surface in a zone of saturation.

"Hazardous secondary material" means a secondary material (e.g., spent material, by-product, or sludge) that, when discarded, would be identified as hazardous waste under Rule 0400-12-01-.02.

"Hazardous secondary material acceptance plan" means the plan used by the verified reclaimer or the verified intermediate facility that identifies the physical and chemical data necessary to determine if a hazardous secondary material is being legitimately reclaimed.

"Hazardous secondary material generator" means any person whose act or process produces hazardous secondary materials at the generating facility. For purposes of this definition, "generating facility" means all contiguous property owned, leased, or otherwise controlled by the hazardous secondary material generator. For the purposes of subpart (1)(d)1(xxiii) of Rule 0400-12-01-.02, a facility that collects hazardous secondary materials from other persons is not the hazardous secondary material generator.

"Hazardous waste" means a hazardous waste as defined in Rule 0400-12-01-.02(1)(c).

"Hazardous waste code" means the code assigned by the Department to each hazardous waste listed in Rule 0400-12-01-.02(4) and to each characteristic identified in Rule 0400-12-01-.02(3), and any derivation of such codes which may be assigned by the Department to an individual waste or class of wastes.

"Hazardous waste constituent" means a constituent that caused the Board to list the hazardous waste in Rule 0400-12-01-.02(4), or a constituent listed in Table 1 of Rule 0400-12-01-.02(3)(e).

"Hazardous waste management unit" is a contiguous area of land on or in which hazardous waste is placed, or the largest area in which there is significant likelihood of mixing hazardous waste constituents in the same area. Examples of hazardous waste management units include a surface impoundment, a waste pile, a land treatment area, a landfill cell, an incinerator, a tank and its associated piping and underlying containment system, and a container storage area. A container alone does not constitute a unit; the unit includes containers and the land or pad upon which they are placed.

"HWM facility" means Hazardous Waste Management facility.

"Inactive portion" means that portion of a facility which is not operated after the date one or more of the hazardous wastes handled by the facility first became subject to regulation under rules promulgated under the Act. (See also "active portion" and "closed portion".)

"Incinerator" means any enclosed device that:

1. Uses controlled flame combustion and neither meets the criteria for classification as a boiler, sludge dryer, or carbon regeneration unit, nor is listed as an industrial furnace; or
2. Meets the definition of infrared incinerator or plasma arc incinerator.

"Incompatible waste" means a hazardous waste which is unsuitable for:

1. Placement in a particular device or facility because it may cause corrosion or decay of containment materials (e.g., container inner liners or tank walls); or
2. Commingling with another waste or material under uncontrolled conditions because the commingling might produce heat or pressure, fire or explosion, violent reaction, toxic dusts, mists, fumes, or gases, or flammable fumes or gases.

(See Appendix V at Rule 0400-12-01-.05(53) and at Rule 0400-12-01-.06(57) for examples.)

"Individual generation site" means the contiguous site at or on which one or more hazardous wastes are generated. An individual generation site, such as a large manufacturing plant, may have one or more sources of hazardous waste but is considered a single or individual generation site if the site or property is contiguous.

"Industrial furnace" means any of the following enclosed devices that are integral components of manufacturing processes and that use thermal treatment to accomplish recovery of materials or energy:

1. Cement kilns
2. Lime kilns
3. Aggregate kilns
4. Phosphate kilns
5. Coke ovens
6. Blast furnaces
7. Smelting, melting and refining furnaces (including pyrometallurgical devices such as cupolas, reverberator furnaces, sintering machines, roasters, and foundry furnaces)
8. Titanium dioxide chloride process oxidation reactors
9. Methane reforming furnaces
10. Pulping liquor recovery furnaces
11. Combustion devices used in the recovery of sulfur values from spent sulfuric acid
12. Halogen acid furnaces (HAFs) for the production of acid from halogenated hazardous waste generated by chemical production facilities where the furnace is located on the site of a chemical production facility, the acid product has a halogen acid content of at least 3%, the acid product is used in a manufacturing process, and, except for hazardous waste burned as fuel, hazardous waste fed to the furnace has a minimum halogen content of 20% as-generated.
13. Such other devices as the Commissioner may, after notice and comment, add to this list on the basis of one or more of the following factors:

- (i) The design and use of the device primarily to accomplish recovery of material products;
- (ii) The use of the device to burn or reduce raw materials to make a material product;
- (iii) The use of the device to burn or reduce secondary materials as effective substitutes for raw materials, in processes using raw materials as principal feedstocks;
- (iv) The use of the device to burn or reduce secondary materials as ingredients in an industrial process to make a material product;
- (v) The use of the device in common industrial practice to produce a material product; and
- (vi) Other factors, as appropriate.

"Infrared incinerator" means any enclosed device that uses electric powered resistance heaters as a source of radiant heat followed by an afterburner using controlled flame combustion and which is not listed as an industrial furnace.

"Inground tank" means a device meeting the definition of "tank" in this subparagraph whereby a portion of the tank wall is situated to any degree within the ground, thereby preventing visual inspection of that external surface area of the tank that is in the ground.

"Injection well" means a well into which fluids are injected. "Class I" injection wells include wells used by generators of hazardous wastes or owners or operators of hazardous waste management facilities to inject hazardous waste, other than Class IV wells. "Class IV" injection wells include wells used by generators of hazardous wastes or owners or operators of hazardous waste management facilities to dispose of hazardous wastes into or above a formation which within one quarter mile of the well contains an underground source of drinking water. (See also "underground injection".)

"Inner liner" means a continuous layer of material placed inside a tank or container which protects the construction materials of the tank or container from the contained waste or reagents used to treat the waste.

"In operation" refers to a facility which is treating, storing, or disposing of hazardous waste.

"Installation identification number" ("EPA Identification Number") means the number assigned to each generator, transporter, and treatment, storage, or disposal facility by the Department or EPA. For generators and facilities in this state, and for transporters who pick up hazardous waste from, or deliver hazardous waste to, locations in this state, references in these rules to their installation identification number shall mean the number assigned by the Department. For other generators, transporters, and facilities, such references shall mean the number assigned by EPA.

"Installation inspector" means a person who, by reason of his knowledge of the physical sciences and the principles of engineering, acquired by a professional education and related practical experience, is qualified to supervise the installation of tank systems.

"Interim authorization" means approval by EPA of State hazardous waste program which has met the requirements of Section 3006(g)(2) of RCRA and applicable requirements of 40 CFR Part 271, Subpart B.

"Intermediate" when used in the context of a chemical reaction means a chemical substance either formed by chemical reaction or is purchased and quantitatively introduced in a chemical reaction to support the formation of a product. Multiple intermediates may be associated with a chemical reaction.

"Intermediate facility" means any facility that stores hazardous secondary materials for more than 10 days, other than a hazardous secondary material generator or reclaimer of such material.

"International shipment" means the transportation of hazardous waste into or out of the jurisdiction of the United States.

"Lamp," also referred to as "universal waste lamp," is defined as the bulb or tube portion of an electric lighting device. A lamp is specifically designed to produce radiant energy, most often in the ultraviolet, visible, and infra-red regions of the electromagnetic spectrum. Examples of common universal waste electric lamps include, but are not limited to, fluorescent, high intensity discharge, neon, mercury vapor, high pressure sodium, and metal halide lamps.

"Land-based unit" means an area where hazardous secondary materials are placed in or on the land before recycling. This definition does not include land-based production units.

"Land Disposal" when used with respect to a specified hazardous waste, shall be deemed to include, but not be limited to, any placement of such hazardous waste in a landfill, surface impoundment, waste pile, injection well, land treatment facility, salt dome formation, salt bed formation, or underground mine or cave.

"Landfill" means a disposal facility or part of a facility where hazardous waste is placed in or on land and which is not a pile, a land treatment facility, a surface impoundment, an underground injection well, a salt dome formation, a salt bed formation, an underground mine, a cave, or a corrective action management unit.

"Landfill cell" means a discrete volume of a hazardous waste landfill which uses a liner to provide isolation of wastes from adjacent cells or wastes. Examples of landfill cells are trenches and pits.

"Land treatment facility" means a facility or part of a facility at which hazardous waste is applied onto or incorporated into the soil surface; such facilities are disposal facilities if the waste will remain after closure.

"Large Quantity Handler of Universal Waste" means a universal waste handler (as defined in this subparagraph) who accumulates 5,000 kilograms or more total of universal waste (batteries, pesticides, thermostats, or lamps calculated collectively) at any time. This designation as a large quantity handler of universal waste is retained through the end of the calendar year in which 5,000 kilograms or more total of universal waste is accumulated.

"Leachate" means any liquid, including any suspended components in the liquid, that has percolated through or drained from hazardous waste.

"Leak-detection system" means a system capable of detecting the failure of either the primary or secondary containment structure or the presence of a release of hazardous waste or accumulated liquid in the secondary containment structure. Such a system must employ operational controls (e.g., daily visual inspections for releases into the secondary containment system of aboveground tanks) or consist of an interstitial monitoring device designed to detect continuously and automatically the failure of the primary or secondary containment structure or the presence of a release of hazardous waste into the secondary containment structure.

"Liner" means a continuous layer of natural or man-made materials, beneath or on the sides of a surface impoundment, landfill, or landfill cell, which restricts the downward or lateral escape of hazardous waste, hazardous waste constituents, or leachate.

"Major facility" means any facility or activity classified as such by the Regional Administrator, or, in the case of approved State programs, the Regional Administrator in conjunction with the State Director.

"Management" or "waste management" or "hazardous waste management" means the orderly control of storage, transportation, treatment, and disposal of hazardous waste.

"Manifest" means the shipping document EPA Form 8700-22 (including if necessary, EPA Form 8700-22A), or the electronic manifest originated and signed in accordance with the applicable requirements of Rules 0400-12-01-.03 through 0400-12-01-.06.

"Manifest tracking number" means the alphanumeric identification number (i. e., a unique three letter suffix preceded by nine numerical digits), which is pre-printed in Item 4 of the Manifest by a registered source.

"Mercury-containing equipment" means a device or part of a device (including thermostats, but excluding batteries and lamps) that contains elemental mercury integral to its function.

"Military munitions" means all ammunition products and components produced or used by or for the U.S. Department of Defense or the U.S. Armed Services for national defense and security, including military munitions under the control of the Department of Defense, the U.S. Coast Guard, the U.S. Department of Energy (DOE), and National Guard personnel. The term military munitions includes: confined gaseous, liquid, and solid propellants, explosives, pyrotechnics, chemical and riot control agents, smokes, and incendiaries used by DOD components, including bulk explosives and chemical warfare agents, chemical munitions, rockets, guided and ballistic missiles, bombs, warheads, mortar rounds, artillery ammunition, small arms ammunition, grenades, mines, torpedoes, depth charges, cluster munitions and dispensers, demolition charges, and devices and components thereof. Military munitions do not include wholly inert items, improvised explosive devices, and nuclear weapons, nuclear devices, and nuclear components thereof. However, the term does include non-nuclear components of nuclear devices, managed under DOE's nuclear weapons program after all required sanitization operations under the Atomic Energy Act of 1954, as amended, have been completed.

"Mining overburden returned to the mine site" means any material overlying an economic mineral deposit which is removed to gain access to that deposit and is then used for reclamation of a surface mine.

"Miscellaneous unit" means a hazardous waste management unit where hazardous waste is treated, stored, or disposed of and that is not a container, tank, surface impoundment, pile, land treatment unit, landfill, incinerator, boiler, industrial furnace, underground injection well with appropriate technical standards under 40 CFR part 146 (as that Federal Regulation exists on the effective date of these rules), containment building, corrective action management unit, unit eligible for a research, development, and demonstration permit under Rule 0400-12-01-.07(1)(g), or staging pile.

"Movement" means that hazardous waste transported to a facility in an individual vehicle.

"National Pollutant Discharge Elimination System" means the national program for issuing, modifying, revoking and reissuing, termination, monitoring and enforcing permits, and imposing and enforcing pretreatment requirements, under sections 307, 402, 318, and 405 of the CWA. The term includes an approved program.

"New hazardous waste management facility" or "new facility" means a facility which began operation, or for which construction commenced after October 31, 1980. (See also "existing hazardous waste management facility".)

"New tank system" or "new tank component" means a tank system or component that will be used for the storage or treatment of hazardous waste and for which installation has commenced after July 14, 1986; except, however, for purposes of Rules 0400-12-01-.05(10)(d)7(ii) and .06(10)(d)7(ii), a new tank system is one for which construction commences after July 14, 1986. (See also "existing tank system.")

"No free liquids," as used in subparts (1)(d)1(xxvi) and (1)(d)2(xviii) of Rule 0400-12-01-.02, means that solvent-contaminated wipes may not contain free liquids as determined by Method 9095B (Paint Filter Liquids Test), included in "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods" (EPA Publication SW-846), which is incorporated by reference in

subparagraph (b) of this paragraph, and that there is no free liquid in the container holding the wipes.

"NPDES" means National Pollutant Discharge Elimination System.

"Off-site" means any site which is not on-site.

"On ground tank" means a device meeting the definition of "tank" in this subparagraph and that is situated in such a way that the bottom of the tank is on the same level as the adjacent surrounding surface so that the external tank bottom cannot be visually inspected.

"On-site" means the same or geographically contiguous property which may be divided by public or private right-of-way, provided the entrance and exit between the properties is at a cross-roads intersection, and access is by crossing as opposed to going along the right-of-way. Non-contiguous properties owned by the same person but connected by a right-of-way which he controls and to which the public does not have access, are also considered on-site property.

"Open burning" means the combustion of any material without the following characteristics:

1. Control of combustion air to maintain adequate temperature for efficient combustion,
2. Containment of the combustion-reaction in an enclosed device to provide sufficient residence time and mixing for complete combustion, and
3. Control of emission of the gaseous combustion products. (See also "incineration" and "thermal treatment".)

"Operator" means the person responsible for the overall operation of a facility.

"Owner" means the person who owns a facility or part of a facility.

"Partial closure" means the closure of a hazardous waste management unit in accordance with the applicable closure requirements of Rules 0400-12-01-.05 and 0400-12-01-.06 at a facility that contains other active hazardous waste management units. For example, partial closure may include the closure of a tank (including its associated piping and underlying containment systems), landfill cell, surface impoundment, waste pile, or other hazardous waste management unit, while other units of the same facility continue to operate.

"Permit" means an authorization, license, or equivalent control document issued by the Commissioner to implement the requirements of Rule 0400-12-01-.07. Permit includes permit-by-rule (Rule 0400-12-01-.07(1)(c)), and emergency permit (Rule 0400-12-01-.07(1)(d)). Permit does not include interim status (Rule 0400-12-01-.07(3)), or any permit which has not been the subject of final agency action, such as a draft permit or a proposed permit.

"Permit-by-rule" means a provision of these regulations stating that a facility or activity is deemed to have a permit if it meets the requirements of the provision.

"Person" means an individual, trust, firm, joint stock company, corporation (including a government corporation), partnership, association, state, municipality, commission, political subdivision of a state, any interstate body, and governmental agency of this state and any department, agency, or instrumentality of the executive, legislative, and judicial branches of the federal government.

"Personnel" or "facility personnel" means all persons who work at, or oversee the operations of, a hazardous waste facility, and whose actions or failure to act may result in noncompliance with the requirements of Rules 0400-12-01-.05 or 0400-12-01-.06.

"Pesticide" means any substance or mixture of substances intended for preventing, destroying, repelling, or mitigating any pest, or intended for use as a plant regulator, defoliant, or desiccant, other than any article that:

1. Is a new animal drug under FFDCA section 201(w), or
2. Is an animal drug that has been determined by regulation of the Secretary of Health and Human Services not to be a new animal drug, or
3. Is an animal feed under FFDCA section 201(x) that bears or contains any substances described by parts 1 or 2 of this definition.

"Physical construction" means excavation, movement of earth, erection of forms or structures, or similar activity to prepare an HWM facility to accept hazardous waste.

"Pile" means any non-containerized accumulation of solid, nonflowing hazardous waste that is used for treatment or storage and that is not a containment building.

"Plasma arc incinerator" means any enclosed device using a high intensity electrical discharge or arc as a source of heat followed by an afterburner using controlled flame combustion and which is not listed as an industrial furnace.

"Point source" means any discernible, confined, and discrete conveyance, including, but not limited to any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, or vessel or other floating craft, from which pollutants are or may be discharged. This term does not include return flows from irrigated agriculture.

"Pollution Prevention" means source reduction as defined under the Pollution Prevention Act (42 U. S. C. 13101-13109). The definition is as follows:

1. Source reduction is any practice that:
  - (i) Reduces the amount of any hazardous substance, pollutant, or contaminant entering any waste stream or otherwise released into the environment (including fugitive emissions) prior to recycling, treatment or disposal; and
  - (ii) Reduces the hazards to public health and the environment associated with the release of such substances, pollutants, or contaminants.
2. The term source reduction includes equipment or technology modifications, process or procedure modifications, reformulation or redesign of products, substitutions of raw materials, and improvements in housekeeping, maintenance, training, or inventory control.
3. The term source reduction does not include any practice that alters the physical, chemical, or biological characteristics or the volume of a hazardous substance, pollutant, or contaminant through a process or activity which itself is not integral to and necessary for the production of a product or the providing of a service.

"PSC" which means the Tennessee Public Service Commission, was abolished. Pertinent functions are now handled by the "Tennessee Regulatory Commission."

"Publicly owned treatment works" or "POTW" means any device or system used in the treatment (including recycling and reclamation) of municipal sewage or industrial wastes of a liquid nature which is owned by the "State" or a "municipality" (as defined by Section 502(4) of CWA). This definition includes sewers, pipes, or other conveyances only if they convey wastewater to a POTW providing treatment.

"Qualified Ground-Water Scientist" means a scientist or engineer who has received a baccalaureate or post-graduate degree in the natural sciences or engineering, and has sufficient training and experience in ground-water hydrology and related fields as may be demonstrated by state registration, professional certifications, or completion of accredited university courses that



enable that individual to make sound professional judgments regarding ground-water monitoring and contaminant fate and transport.

"RCRA" means the Solid Waste Disposal Act as amended by the Resource Conservation and Recovery Act of 1976 (Pub. L. 94-580, as amended by Pub. L. 95-609 and Pub. L. 96-482, 42 U.S.C. 6901 et seq.)

"Reclaimed" means reclaimed as defined in subpart (1)(a)3(iv) of Rule 0400-12-01-.02.

"Recycled" means recycled as defined in subpart (1)(a)3(vii) of Rule 0400-12-01-.02.

"Regional Administrator" means the Regional Administrator for the EPA Region in which the facility is located, or his designee.

"Registered engineer" or "registered professional engineer" refers to a person authorized to perform engineering in Tennessee pursuant to Tennessee Code Annotated, Title 62, Chapter 2.

"Remanufacturing" means processing a higher-value hazardous secondary material in order to manufacture a product that serves a similar functional purpose as the original commercial-grade material. For the purpose of this definition, a hazardous secondary material is considered higher-value if it was generated from the use of a commercial-grade material in a manufacturing process and can be remanufactured into a similar commercial-grade material.

"Remedial Action Plan (RAP)" means a special form of RCRA permit that a facility owner or operator may obtain instead of a permit issued under paragraphs (1), (2), and (4)-(9) of Rule 0400-12-01-.07, to authorize the treatment, storage or disposal of hazardous remediation waste (as defined in this subparagraph) at a remediation waste management site.

"Remediation waste" means all solid and hazardous wastes, and all media (including groundwater, surface water, soils, and sediments) and debris, that are managed for implementing cleanup.

"Remediation waste management site" means a facility where an owner or operator is or will be treating, storing or disposing of hazardous remediation wastes. A remediation waste management site is not a facility that is subject to corrective action under Rule 0400-12-01-.06(6)(l), but is subject to corrective action requirements if the site is located in such a facility.

"Replacement unit" means a landfill, surface impoundment, or waste pile unit (1) from which all or substantially all of the waste is removed, and (2) that is subsequently reused to treat, store, or dispose of hazardous waste. "Replacement unit" does not apply to a unit from which waste is removed during closure, if the subsequent reuse solely involves the disposal of waste from that unit and other closing units or corrective action areas at the facility, in accordance with an approved closure plan or EPA or State approved corrective action.

"Representative sample" means a sample of a universe or whole (e.g., waste pile, lagoon, ground water) which can be expected to exhibit the average properties of the universe or whole.

"Run-off" means any rainwater, leachate, or other liquid that drains over land from any part of a facility.

"Run-on" means any rainwater, leachate, or other liquid that drains over land onto any part of a facility.

"Saturated zone" or "zone of saturation" means that part of the earth's crust in which all voids are filled with water.

"Schedule of compliance" means a schedule of remedial measures included in a permit, including an enforceable sequence of interim requirements (for example, actions, operations, or milestone events) leading to compliance with the Act and regulations.

“SDWA” means the Safe Drinking Water Act (Pub. L. 95-523, as amended by Pub. L. 95-1900; 42 U.S.C. 3001 et seq.)

“Site” means the land or water area where any facility or activity is physically located or conducted, including adjacent land used in connection with the facility or activity.

“Sludge” means any solid, semi-solid, or liquid waste generated from a municipal, commercial, or industrial wastewater treatment plant, water supply treatment plant, or air pollution control facility exclusive of the treated effluent from a wastewater treatment plant.

“Sludge dryer” means any enclosed thermal treatment device that is used to dehydrate sludge and that has a maximum total thermal input, excluding the heating value of the sludge itself, of 2,500 Btu/lb of sludge treated on a wet-weight basis.

“Small Quantity Generator” means a generator who generates less than 1000 kg of hazardous waste in a calendar month.

“Small Quantity Handler of Universal Waste” means a universal waste handler (as defined in this subparagraph) who does not accumulate more than 5,000 kilograms total of universal waste (batteries, pesticides, thermostats, or lamps calculated collectively) at any time.

“Solid waste” means a waste as defined in Rule 0400-12-01-.02(1)(b).

“Solvent-contaminated wipe” means:

1. A wipe that, after use or after cleaning up a spill, either:
  - (i) Contains one or more of the F001 through F005 solvents listed in subparagraph (4)(b) of Rule 0400-12-01-.02 or the corresponding P- or U- listed solvents found in subparagraph (4)(d) of Rule 0400-12-01-.02;
  - (ii) Exhibits a hazardous characteristic found in paragraph (3) of Rule 0400-12-01-.02 when that characteristic results from a solvent listed in paragraph (4) of Rule 0400-12-01-.02; and/or
  - (iii) Exhibits only the hazardous waste characteristic of ignitability found in subparagraph (3)(b) of Rule 0400-12-01-.02 due to the presence of one or more solvents that are not listed in paragraph (4) of Rule 0400-12-01-.02.
2. Solvent-contaminated wipes that contain listed hazardous waste other than solvents, or exhibit the characteristic of toxicity, corrosivity, or reactivity due to contaminants other than solvents, are not eligible for the exclusions at subparts (1)(d)1(xxvi) and (1)(d)2(xviii) of Rule 0400-12-01-.02.

“Sorbent” means a material that is used to soak up free liquids by either adsorption or absorption, or both. Sorb means to either adsorb or absorb, or both.

“Spent material” means spent material as defined in subpart (1)(a)3(i) of Rule 0400-12-01-.02.

“Staging pile” means an accumulation of solid, non-flowing remediation waste “as defined in this subparagraph) that is not a containment building and that is used only during remedial operations for temporary storage at a facility. Staging piles must be designated by the Director according to the requirements of Rule 0400-12-01-.06(22)(e).

“State” means the State of Tennessee.

“State/EPA Agreement” means an agreement between the Regional Administrator and the State which coordinates EPA and State activities, responsibilities and programs.

"Storage" means the containment of hazardous waste in such a manner as not to constitute disposal of such hazardous waste.

"Sump" means any pit or reservoir that meets the definition of tank and those troughs/trenches connected to it that serve to collect hazardous waste for transport to hazardous waste storage, treatment, or disposal facilities; except that as used in the landfill, surface impoundment, and waste pile rules, "sump" means any lined pit or reservoir that serves to collect liquids drained from a leachate collection and removal system or leak detection system for subsequent removal from the system.

"Surface impoundment" or "impoundment" means a facility or part of a facility which is a natural topographic depression, man-made excavation, or diked area formed primarily of earthen materials (although it may be lined with man-made materials), which is designed to hold an accumulation of liquid wastes or wastes containing free liquids, and which is not an injection well. Examples of surface impoundments are holding, storage, settling, and aeration pits, ponds, and lagoons.

"Tank" means a stationary device, designed to contain an accumulation of hazardous waste which is constructed primarily of non-earthen materials (e.g., wood, concrete, steel, plastic) which provide structural support.

"Tank system" means a hazardous waste storage or treatment tank and its associated ancillary equipment and containment system.

"T.C.A." means Tennessee Code Annotated.

"Tennessee Air Quality Act" means the Tennessee Air Quality Act, as amended, T.C.A §§ 68-201-101 et seq.

"Tennessee Regulatory Commission (TRC)" means the agency now handling pertinent functions formerly handled by the PSC.

"TEQ" means toxicity equivalence, the international method of relating the toxicity of various dioxin/furan congeners to the toxicity of 2, 3, 7, 8-tetrachlorodibenzo-p-dioxin.

"Thermal treatment" means the treatment of hazardous waste in a device which uses elevated temperatures as the primary means to change the chemical, physical, or biological character or composition of the hazardous waste. Examples of thermal treatment processes are incineration, molten salt, pyrolysis, calcination, wet air oxidation, and microwave discharge. (See also "incinerator" and "open burning".)

"Totally enclosed treatment facility" means a facility for the treatment of hazardous waste which is directly connected to an industrial production process and which is constructed and operated in a manner which prevents the release of any hazardous waste or any constituent thereof into the environment during treatment. An example is a pipe in which waste acid is neutralized.

"Transfer facility" means any transportation related facility, including loading docks, parking areas, storage areas and other similar areas where shipments of hazardous waste or hazardous secondary materials are held during the normal course of transportation.

"Transportation" means the movement of hazardous waste by air, rail, highway, or water.

"Transporter" means any person engaged in the transportation of hazardous waste.

"Transport vehicle" means a motor vehicle or rail car used for the transportation of cargo by any mode. Each cargo-carrying body (trailer, railroad freight car, etc.) is a separate transport vehicle.

"Treatability Study" means a study in which a hazardous waste is subjected to a treatment process to determine: (1) Whether the waste is amenable to the treatment process, (2) what pretreatment (if any) is required, (3) the optimal process conditions needed to achieve the desired

treatment, (4) the efficiency of a treatment process for a specific waste or wastes, or (5) the characteristics and volumes of residuals from a particular treatment process. Also included in this definition for the purpose of Rule 0400-12-01-.02(1)(d)5 and 6 exemptions are liner compatibility, corrosion, and other material compatibility studies and toxicological and health effects studies. A "treatability study" is not a means to commercially treat or dispose of hazardous waste.

"Treatment" means any method, technique, or process, including neutralization, designed to change the physical, chemical, or biological character or composition of any hazardous waste so as to neutralize such waste, or so as to recover energy or material resources from the waste, or so as to render such waste non-hazardous, or less hazardous; safer to transport, store, or dispose of; or amenable for recovery, amenable for storage, or reduced in volume.

"Treatment zone" means a soil area of the unsaturated zone of a land treatment unit within which hazardous waste constituents are degraded, transformed, or immobilized.

"24-hour, 25-year storm" means a storm of 24-hour duration with a probable recurrence interval of once in 25 years.

"UIC" means the Underground Injection Control Program under Part C of the Safe Drinking Water Act, including an approved program.

"Underground injection" means the subsurface emplacement of fluids through a bored, drilled or driven well; or through a dug well, where the depth of the dug well is greater than the largest surface dimension. (See also "injection well".)

"Underground source of drinking water (USDW)" means an aquifer or its portion:

1. (i) Which supplies any public water system; or
- (ii) Which contains a sufficient quantity of ground water to supply a public water system; and
  - (I) Currently supplies drinking water for human consumption; or
  - (II) Contains fewer than 10,000 mg/l total dissolved solids; and
2. Which is not an exempted aquifer.

"Underground tank" means a device meeting the definition of "tank" in this subparagraph whose entire surface area is totally below the surface of and covered by the ground.

"Unfit-for-use tank system" means a tank system that has been determined through an integrity assessment or other inspection to be no longer capable of storing or treating hazardous waste without posing a threat of release of hazardous waste to the environment.

"United States" means the 50 States, the District of Columbia, the Commonwealth of Puerto Rico, the U.S. Virgin Islands, Guam, American Samoa, and the Commonwealth of the Northern Mariana Islands.

"Universal Waste" means any of the hazardous wastes listed in Rule 0400-12-01-.12(1)(a) that are managed under the universal waste requirements of Rule 0400-12-01-.12.

"Universal Waste Handler":

1. Means:
  - (i) A generator (as defined in this subparagraph) of universal waste; or
  - (ii) The owner or operator of a facility, including all contiguous property, that receives universal waste from other universal waste handlers, accumulates universal

waste, and sends universal waste to another universal waste handler, to a destination facility, or to a foreign destination.

2. Does not mean:

- (i) A person who treats (except under the provisions of Rule 0400-12-01-.12(2)(d)1 or 3, or Rule 0400-12-01-.12(3)(d)1 or 3), disposes of, or recycles universal waste; or
- (ii) A person engaged in the off-site transportation of universal waste by air, rail, highway, or water, including a universal waste transfer facility.

“Universal Waste Transfer Facility” means any transportation-related facility including loading docks, parking areas, storage areas and other similar areas where shipments of universal waste are held during the normal course of transportation for ten days or less.

“Universal Waste Transporter” means a person engaged in the off-site transportation of universal waste by air, rail, highway, or water.

"Unsaturated zone" or "zone of aeration" means the zone between the land surface and the water table.

"Uppermost aquifer" means the geologic formation nearest the natural ground surface that is an aquifer, as well as lower aquifers that are hydraulically interconnected with this aquifer within the facility's property boundary.

"Used oil" means any oil that has been refined from crude oil, or any synthetic oil, that has been used and as a result of such use is contaminated by physical or chemical impurities.

“User of the electronic manifest system” means a hazardous waste generator, a hazardous waste transporter, an owner or operator of a hazardous waste treatment, storage, recycling, or disposal facility, or any other person that:

1. Is required to use a manifest to comply with:

- (i) Any federal or state requirement to track the shipment, transportation, and receipt of hazardous waste or other waste material that is shipped from the site of generation to an off-site designated facility for treatment, storage, recycling, or disposal; or
- (ii) Any federal or state requirement to track the shipment, transportation, and receipt of rejected wastes or regulated container residues that are shipped from a designated facility to an alternative facility, or returned to the generator; and

2. Elects to use the system to obtain, complete and transmit an electronic manifest format supplied by the EPA electronic manifest system, or

3. Elects to use the paper manifest form and submits to the system for data processing purposes a paper copy of the manifest (or data from such a paper copy), in accordance with item (5)(b)1(ii)(V) of Rule 0400-12-01-.05 or item (5)(b)1(ii)(V) of Rule 0400-12-01-.06. These paper copies are submitted for data exchange purposes only and are not the official copies of record for legal purposes.

“Verified intermediate facility” means an intermediate facility located in the United States that:

- 1. If located in the state of Tennessee, has been issued a Certificate to Operate by the Commissioner in accordance with part (4)(b)2 of this rule; and
- 2. If not located in the state of Tennessee, has been verified by EPA, in accordance with 40 CFR 260.30, 260.31(d) and 260.33, or verified by an EPA authorized state.

"Verified reclamation facility" means a reclamation facility located in the United States that:

1. If located in the state of Tennessee, has been issued a Certificate to Operate by the Commissioner in accordance with part (4)(b)2 of this rule; and
2. If not located in the state of Tennessee, has been verified by EPA, in accordance with 40 CFR 260.30, 260.31(d) and 260.33, or verified by an EPA authorized state.

"Vessel" includes every description of watercraft, used or capable of being used as a means of transportation on the water.

"Waste" means a solid waste as defined in Rule 0400-12-01-.02(1)(b).

"Wastewater treatment unit" means a device which:

1. Is part of a wastewater treatment facility that is subject to regulation under either section 402 or 307(b) of the Clean Water Act; and
2. Receives and treats or stores an influent wastewater that is a hazardous waste as defined in Rule 0400-12-01-.02(1)(c) or generates and accumulates a wastewater treatment sludge which is a hazardous waste as defined in Rule 0400-12-01-.02(1)(c), or treats or stores a wastewater treatment sludge which is a hazardous waste as defined in Rule 0400-12-01-.02(1)(c); and
3. Meets the definition of tank or tank system in this subparagraph.

"On-site wastewater treatment units" are those which receive solely wastes generated on-site (according to the definition of "on-site" found in this subparagraph). "Off-site wastewater treatment units" are those which receive wastes generated by facilities that are not on-site.

"Water (bulk shipment)" means the bulk transportation of hazardous waste which is loaded or carried on board a vessel without containers or labels.

"Water Quality Control Act" means the Water Quality Control Act of 1977, as amended, T.C.A §§ 69-3-101 et seq.

"Well" means any shaft or pit dug or bored into the earth, generally of a cylindrical form, and often walled with bricks or tubing to prevent the earth from caving in.

"Well injection": (See "underground injection".)

"Wipe" means a woven or non-woven shop towel, rag, pad, or swab made of wood pulp, fabric, cotton, polyester blends, or other material.

"Zone of engineering control" means an area under the control of the owner/operator that, upon detection of a hazardous waste release, can be readily cleaned up prior to the release of hazardous waste or hazardous constituents to ground water or surface water.

(b) References [40 CFR 260.11 and 40 CFR 270.6]

1. Here is a list of publications/materials referred to in these rules and where they may be obtained as set forth by EPA in 40 CFR 260.11 and 40 CFR 270.6.
2. These materials are listed as they exist on the effective date of these regulations.

(Note: 40 CFR 260.11 provides that:

- (a) When used in parts 260 through 268 and 278 of this chapter, the following publications are incorporated by reference. These incorporations by reference

were approved by the Director of the Federal Register pursuant to 5 U.S.C. 552(a) and 1 CFR part 51. These materials are incorporated as they exist on the date of approval and a notice of any change in these materials will be published in the Federal Register. Copies may be inspected at the Library, U.S. Environmental Protection Agency, 1200 Pennsylvania Ave., NW. (3403T), Washington, DC 20460, [libraryhq@epa.gov](mailto:libraryhq@epa.gov); or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to:

<http://www.archives.gov/federal-register/code-of-federal-regulations/ibr-locations.html>.

(b) The following materials are available for purchase from the American Society for Testing and Materials, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959.

- (1) ASTM D-93-79 or D-93-80, "Standard Test Methods for Flash Point by Pensky-Martens Closed Cup Tester," IBR approved for §261.21.
- (2) ASTM D-1946-82, "Standard Method for Analysis of Reformed Gas by Gas Chromatography," IBR approved for §§264.1033, 265.1033.
- (3) ASTM D 2267-88, "Standard Test Method for Aromatics in Light Naphthas and Aviation Gasolines by Gas Chromatography," IBR approved for §264.1063.
- (4) ASTM D 2382-83, "Standard Test Method for Heat of Combustion of Hydrocarbon Fuels by Bomb Calorimeter (High-Precision Method)," IBR approved for §§264.1033, 265.1033.
- (5) ASTM D 2879-92, "Standard Test Method for Vapor Pressure—Temperature Relationship and Initial Decomposition Temperature of Liquids by Isoteniscope," IBR approved for §265.1084.
- (6) ASTM D-3278-78, "Standard Test Methods for Flash Point for Liquids by Setaflash Closed Tester," IBR approved for §261.21(a).
- (7) ASTM E 168-88, "Standard Practices for General Techniques of Infrared Quantitative Analysis," IBR approved for §264.1063.
- (8) ASTM E 169-87, "Standard Practices for General Techniques of Ultraviolet-Visible Quantitative Analysis," IBR approved for §264.1063.
- (9) ASTM E 260-85, "Standard Practice for Packed Column Gas Chromatography," IBR approved for §264.1063.
- (10) ASTM E 926-88, "Standard Test Methods for Preparing Refuse-Derived Fuel (RDF) Samples for Analyses of Metals," Test Method C—Bomb, Acid Digestion Method.

(c) The following materials are available for purchase from the National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161; or for purchase from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, (202) 512-1800.

- (1) "APTI Course 415: Control of Gaseous Emissions," EPA Publication EPA-450/2-81-005, December 1981, IBR approved for §§264.1035 and 265.1035.
- (2) Method 1664, n-Hexane Extractable Material (HEM; Oil and Grease) and Silica Gel Treated n-Hexane Extractable Material SGT-HEM; Non-polar Material) by Extraction and Gravimetry:

- (i) Revision A, EPA-821-R-98-002, February 1999, IBR approved for Part 261, appendix IX.
  - (ii) Revision B, EPA-821-R-10-001, February 2010, IBR approved for Part 261, appendix IX.
- (3) The following methods as published in the test methods compendium known as “Test Methods for Evaluating Solid Waste, Physical/Chemical Methods,” EPA Publication SW-846, Third Edition. A suffix of “A” in the method number indicates revision one (the method has been revised once). A suffix of “B” in the method number indicates revision two (the method has been revised twice). A suffix of “C” in the method number indicates revision three (the method has been revised three times). A suffix of “D” in the method number indicates revision four (the method has been revised four times).
- (i) Method 0010, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.
  - (ii) Method 0020, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.
  - (iii) Method 0030, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.
  - (iv) Method 1320, dated September 1986 and in the Basic Manual, IBR approved for part 261, appendix IX.
  - (v) Method 1311, dated September 1992 and in Update I, IBR approved for part 261, appendix IX, and §§261.24, 268.7, 268.40.
  - (vi) Method 1330A, dated September 1992 and in Update I, IBR approved for part 261, appendix IX.
  - (vii) Method 1312 dated September 1994 and in Update III, IBR approved for part 261, appendix IX and § 278.3(b)(1).
  - (viii) Method 0011, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, and part 266, appendix IX.
  - (ix) Method 0023A, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, part 266, appendix IX, and §266.104.
  - (x) Method 0031, dated December 1996 and in Update III, IBR approved for part 261, appendix IX.
  - (xi) Method 0040, dated December 1996 and in Update III, IBR approved for part 261, appendix IX.
  - (xii) Method 0050, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, part 266, appendix IX, and §266.107.
  - (xiii) Method 0051, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, part 266, appendix IX, and §266.107.



- (xiv) Method 0060, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, §266.106, and part 266, appendix IX.
  - (xv) Method 0061, dated December 1996 and in Update III, IBR approved for part 261, appendix IX, §266.106, and part 266, appendix IX.
  - (xvi) Method 9071B, dated April 1998 and in Update IIIA, IBR approved for part 261, appendix IX.
  - (xvii) Method 1010A, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.
  - (xviii) Method 1020B, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.
  - (xix) Method 1110A, dated November 2004 and in Update IIIB, IBR approved for §261.22 and part 261, appendix IX.
  - (xx) Method 1310B, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.
  - (xxi) Method 9010C, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX and §§268.40, 268.44, 268.48.
  - (xxii) Method 9012B, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX and §§268.40, 268.44, 268.48.
  - (xxiii) Method 9040C, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX and §261.22.
  - (xxiv) Method 9045D, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.
  - (xxv) Method 9060A, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX, and §§264.1034, 264.1063, 265.1034, 265.1063.
  - (xxvi) Method 9070A, dated November 2004 and in Update IIIB, IBR approved for part 261, appendix IX.
  - (xxvii) Method 9095B, dated November 2004 and in Update IIIB, IBR approved, part 261, appendix IX, and §§264.190, 264.314, 265.190, 265.314, 265.1081, 267.190(a), 268.32.
- (d) The following materials are available for purchase from the National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269–9101.
- (1) “Flammable and Combustible Liquids Code” (1977 or 1981), IBR approved for §§264.198, 265.198, 367.202(b).
  - (2) [Reserved]
- (e) The following materials are available for purchase from the American Petroleum Institute, 1220 L Street, Northwest, Washington, DC 20005.

- (1) API Publication 2517, Third Edition, February 1989, "Evaporative Loss from External Floating-Roof Tanks," IBR approved for §265.1084.
- (2) [Reserved]
- (f) The following materials are available for purchase from the Environmental Protection Agency, Research Triangle Park, NC.
  - (1) "Screening Procedures for Estimating the Air Quality Impact of Stationary Sources, Revised", October 1992, EPA Publication No. EPA-450/R-92-019, IBR approved for part 266, appendix IX.
  - (2) [Reserved]
- (g) The following materials are available for purchase from the Organisation for Economic Co-operation and Development, Environment Directorate, 2 rue Andre Pascal, 75775 Paris Cedex 16, France.
  - (1) OECD Green List of Wastes (revised May 1994), Amber List of Wastes and Red List of Wastes (both revised May 1993) as set forth in Appendix 3, Appendix 4 and Appendix 5, respectively, to the OECD Council Decision C(92)39/FINAL (Concerning the Control of Transfrontier Movements of Wastes Destined for Recovery Operations), IBR approved for 262.89 of this chapter.
  - (2) [Reserved]

(Note: 40 CFR 270.6 provides that:

- (a) When used in part 270 of this chapter, the following publications are incorporated by reference. These incorporations by reference were approved by the Director of the Federal Register pursuant to 5 U.S.C. 552(a) and 1 CFR part 51. These materials are incorporated as they exist on the date of approval and a notice of any change in these materials will be published in the Federal Register. Copies may be inspected at the Library, U.S. Environmental Protection Agency, 1200 Pennsylvania Ave., NW., (3403T), Washington, DC 20460, libraryhq@epa.gov; or at the National Archives and Records Administration (NARA). For information on the availability of this material at NARA, call 202-741-6030, or go to:

[http://www.archives.gov/federal\\_register/code\\_of\\_federal\\_regulations/ibr\\_locations.html](http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html).

- (b) The following materials are available for purchase from the National Technical Information Service (NTIS), 5285 Port Royal Road, Springfield, VA 22161, (703) 605-6000 or (800) 553-6847; or for purchase from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402, (202) 512-1800:
  - (1) "APTI Course 415: Control of Gaseous Emissions," EPA Publication EPA-450/2-81-005, December 1981, IBR approved for §§270.24 and 270.25.
  - (2) [Reserved]

### (3) Petitions for Regulatory Exclusions

#### (a) General [40 CFR 260.20]

- 1. Any person may petition the Commissioner for a regulatory exclusion from any provision in Rules 0400-12-01-.01 through 0400-12-01-.06, 0400-12-01-.09, 0400-12-01-.10 and

0400-12-01-.12. This subparagraph sets forth general requirements which apply to all such petitions. Subparagraph (b) sets forth additional requirements for petitions to add a testing or analytical method to Rule 0400-12-01-.02, 0400-12-01-.05 or 0400-12-01-.06. Subparagraph (c) sets forth additional requirements for petitions to exclude a waste or waste-derived material at a particular facility from subparagraph (1)(c) of Rule 0400-12-01-.02 or the lists of hazardous wastes in paragraph (4) of Rule 0400-12-01-.02. Subparagraph (d) sets forth additional requirements for petitions to amend Rule 0400-12-01-.12 to include additional hazardous wastes or categories of hazardous waste as universal waste.

2. Each petition must be submitted to the Commissioner by certified mail and must include:
  - (i) The petitioner's name and address;
  - (ii) A statement of the petitioner's interest in the proposed action;
  - (iii) A description of the proposed action, including (where appropriate) suggested language; and
  - (iv) A statement of the need and justification for the proposed action, including any supporting tests, studies, or other information.
3. Except for petitions submitted in accordance with subparagraphs (b) and (c) of this paragraph, the Commissioner will make a tentative decision to grant or deny a petition and shall notify the petitioner of such tentative decision. If the Commissioner's tentative decision is to grant the petition, the Commissioner, with the concurrence of the board, shall initiate a rulemaking in accordance with T.C.A. § 4-5-201 et seq.
4. Petitions submitted in accordance with subparagraphs (b) and (c) of this paragraph shall be forwarded to EPA by the Commissioner for a determination.
5. A determination made by EPA pursuant to 40 CFR 260.21 Petitions for Equivalent Testing or Analytical Methods or 40 CFR 260.22 Petitions to Amend Part 261 to Exclude a Waste Produced at a Particular Facility shall be effective in Tennessee on the effective date of the EPA decision.

(b) Petitions for Equivalent Testing or Analytical Methods [40 CFR 260.21]

Petitions received by the Commissioner regarding Equivalent Testing or Analytical Methods shall be forwarded to EPA for a determination.

(Note: The authority for implementing this subparagraph remains with the U.S. Environmental Protection Agency.)

(c) Petitions to Exclude a Waste Produced at a Particular Facility as Nonhazardous [40 CFR 260.22]

Petitions received by the Commissioner regarding Excluding a Waste Produced at a Particular Facility as Nonhazardous shall be forwarded to EPA for a determination.

(Note: The authority for implementing this subparagraph remains with the U.S. Environmental Protection Agency.)

(d) Petitions to Amend Rule 0400-12-01-.12 to Include Additional Hazardous Wastes as Universal Wastes [40 CFR 260.23]

1. Any person seeking to add a hazardous waste or a category of hazardous waste to the universal waste regulations of Rule 0400-12-01-.12 may petition for a regulatory amendment under this subparagraph, subparagraph (a) of this paragraph and Rule 0400-12-01-.12(7).

2. To be successful, the petitioner must demonstrate to the satisfaction of the Commissioner that regulation under the universal waste regulations of Rule 0400-12-01-.12 is appropriate for the waste or category of waste; will improve management practices for the waste or category of waste; and will improve implementation of the hazardous waste program. The petition must include the information required by part (a)2 of this paragraph. The petition should also address as many of the factors listed in Rule 0400-12-01-.12(7)(b) as are appropriate for the waste or category of waste addressed in the petition.
3. The Commissioner shall consider the factors listed in Rule 0400-12-01-.12(7)(b).
4. The Commissioner may request additional information needed to evaluate the merits of the petition.
5. The Commissioner shall make a tentative decision. The tentative decision will be based on the weight of evidence showing that regulation under Rule 0400-12-01-.12 is appropriate for the waste or category of waste, will improve management practices for the waste or category of waste, and will improve implementation of the hazardous waste program.
6. The Commissioner shall comply with the requirements of part (a)3 of this paragraph regarding the tentative decision.

(4) Variances, Certificates to Operate, and Procedures

(a) Requirements for General Variances

1. Any person may petition the Commissioner for a variance from any provision in these rules. This subparagraph sets forth general requirements which apply to all such petitions.
2. Each petition must be submitted to the Commissioner by certified mail and must include:
  - (i) The petitioner's name and address;
  - (ii) A statement of the petitioner's interest in the proposed action;
  - (iii) A description of the proposed action, including (where appropriate) suggested language; and
  - (iv) A written description of the need and justification for the proposed action, including any supporting tests, studies, or other information.

(Note: See paragraph (9) of Rule 0400-12-01-.08 for the appropriate fee to be submitted along with the petition for a general variance.)

3. The Commissioner will make a tentative decision to grant or deny a petition and will notify the petitioner of this tentative decision. If the Commissioner makes a tentative decision to grant the petition, the Commissioner will give public notice of such tentative decision for written public comment. The public notice shall be published by the petitioner as required by the Commissioner.
4. Upon the written request of any interested person, the Commissioner may, at his discretion, hold an informal public hearing to consider oral comments on the tentative decision. A person requesting a hearing must state the issues to be raised and explain why written comments would not suffice to communicate the person's views. The Commissioner may in any case decide on his own motion to hold an informal public hearing. Notice of the public hearing shall be published by the petitioner as required by the Commissioner.

5. After evaluating all public comments the Commissioner will make a final decision to either grant or deny the petition, and will give a public notice of such decision. The petitioner shall publish this public notice as required by the Commissioner.
  6. Any variance granted pursuant to this subparagraph may be rescinded if it is discovered and determined by the Commissioner that:
    - (i) The variance has resulted or may result in a significant hazard to public health or the environment;
    - (ii) The factual basis for which the variance was granted has significantly changed;
    - (iii) The regulations, as amended, no longer support the variance;
    - (iv) The conditions issued by the Commissioner for the variance's approval have been violated; or
    - (v) The variance threatens program authorization with EPA.
  7. Any variance granted pursuant to this subparagraph shall remain valid as specified by the Commissioner, not to exceed five (5) years, or until rescinded in accordance with part 6 of this subparagraph.
  8. Any person with a valid variance granted in accordance with this subparagraph shall submit to the Commissioner:
    - (i) No later than March 1 of each year, a certification that the factual basis for which the variance was granted remains unchanged, the regulations, as amended, continue to support it and the conditions for its approval have not been violated; or
    - (ii) Within thirty (30) days of its discovery, a detailed description of any change in the factual basis for which the variance was granted, the impact any amended regulation has on the variance, or any noncompliance with a condition for its approval.
- (b) Non-waste determinations, variances from classification as a solid waste and Certificates to Operate for a hazardous secondary material reclamation facility or intermediate facility [40 CFR 260.30]
1. In accordance with the standards and criteria in subparagraphs (c) and (e) of this paragraph and the procedures in subparagraph (g) of this paragraph, the Commissioner may determine on a case-by-case basis that the following recycled materials are not solid wastes:
    - (i) Materials that are accumulated speculatively without sufficient amounts being recycled (as defined in Rule 0400-12-01-.02(1)(a)3(viii));
    - (ii) Materials that are reclaimed and then reused within the original production process in which they were generated;
    - (iii) Materials that have been reclaimed but must be reclaimed further before the materials are completely recovered;
    - (iv) Hazardous secondary materials that are reclaimed in a continuous industrial process; and
    - (v) Hazardous secondary materials that are indistinguishable in all relevant aspects from a product or intermediate.

2. In accordance with the standards and criteria in subparagraph (f) of this paragraph and the procedures in subparagraph (g) of this paragraph, the Commissioner may, on a case-by-case basis, issue a Certificate to Operate for a hazardous secondary material reclamation facility or intermediate facility where the management of the hazardous secondary materials is not addressed under a Part B permit issued under Rule 0400-12-01-.07 or the interim status standards of Rule 0400-12-01-.05.

(c) Standards and Criteria for Variances from Classification as a Solid Waste [40 CFR 260.31]

1. The Commissioner may grant requests for a variance from classifying as a solid waste those materials that are accumulated speculatively without sufficient amounts being recycled if the applicant demonstrates that sufficient amounts of the material will be recycled or transferred for recycling in the following year. If a variance is granted, it is valid only for the following year, but can be renewed, on an annual basis, by filing a new application. The Commissioner's decision will be based on the following criteria:
  - (i) The manner in which the material is expected to be recycled, when the material is expected to be recycled, and whether this expected disposition is likely to occur (for example, because of past practice, market factors, the nature of the material, or contractual arrangements for recycling);
  - (ii) The reason that the applicant has accumulated the material for one or more years without recycling 75 percent of the volume accumulated at the beginning of the year;
  - (iii) The quantity of material already accumulated and the quantity expected to be generated and accumulated before the material is recycled;
  - (iv) The extent to which the material is handled to minimize loss; and
  - (v) Other relevant factors.
2. The Commissioner may grant requests for a variance from classifying as a solid waste those materials that are reclaimed and then reused as feedstock within the original production process in which the materials were generated if the reclamation operation is an essential part of the production process. This determination will be based on a description of the reclamation operation and the following criteria:
  - (i) How economically viable the production process would be if it were to use virgin materials, rather than reclaimed materials;
  - (ii) The extent to which the material is handled before reclamation to minimize loss;
  - (iii) The time periods between generating the material and its reclamation, and between reclamation and return to the original primary production process;
  - (iv) The location of the reclamation operation in relation to the production process;
  - (v) Whether the reclaimed material is used for the purpose for which it was originally produced when it is returned to the original process, and whether it is returned to the process in substantially its original form;
  - (vi) Whether the person who generates the material also reclaims it; and
  - (vii) Other relevant factors.
3. The Commissioner may grant requests for a variance from classifying as a solid waste those hazardous secondary materials that have been partially reclaimed, but must be reclaimed further before recovery is completed, if the partial reclamation has produced a commodity-like material. A determination that a partially-reclaimed material for which the

variance is sought is commodity-like will be based on whether the hazardous secondary material is legitimately recycled as specified in subparagraph (5)(d) of this rule and on whether all of the following decision criteria are satisfied:

- (i) Whether the degree of partial reclamation the material has undergone is substantial as demonstrated by using a partial reclamation process other than the process that generated the hazardous waste;
- (ii) Whether the partially-reclaimed material has sufficient economic value that it will be purchased for further reclamation;
- (iii) Whether the partially-reclaimed material is a viable substitute for a product or intermediate produced from virgin or raw materials which is used in subsequent production steps;
- (iv) Whether there is a market for the partially-reclaimed material as demonstrated by known customer(s) who are further reclaiming the material (e.g., records of sales and/or contracts and evidence of subsequent use, such as bills of lading); and
- (v) Whether the partially-reclaimed material is handled to minimize loss;

(d) Variance to be classified as a boiler [40 CFR 260.32]

In accordance with the standards and criteria in subparagraph (2)(a) of this rule (definition of "boiler") and the procedures in subparagraph (g) of this paragraph, the Commissioner may determine on a case-by-case basis that certain enclosed devices using controlled flame combustion are boilers, even though they do not otherwise meet the definition of boiler contained in subparagraph (2)(a) of this rule, after considering the following criteria:

- 1. The extent to which the unit has provisions for recovering and exporting thermal energy in the form of steam, heated fluids, or heated gases; and
- 2. The extent to which the combustion chamber and energy recovery equipment are of integral design; and
- 3. The efficiency of energy recovery, calculated in terms of the recovered energy compared with the thermal value of the fuel; and
- 4. The extent to which exported energy is utilized; and
- 5. The extent to which the device is in common and customary use as a "boiler" functioning primarily to produce steam, heated fluids, or heated gases; and
- 6. Other factors, as appropriate.

(e) Standards and criteria for non-waste determinations [40 CFR 260.34]

- 1. An applicant may apply to the Commissioner for a formal determination that a hazardous secondary material is not discarded and therefore not a solid waste. The determinations will be based on the criteria contained in parts 2 and 3 of this subparagraph, as applicable. If an application is denied, the hazardous secondary material might still be eligible for a solid waste variance or exclusion (for example, one of the solid waste variances under subparagraph (c) of this paragraph).
- 2. The Commissioner may grant a non-waste determination for hazardous secondary material which is reclaimed in a continuous industrial process if the applicant demonstrates that the hazardous secondary material is a part of the production process and is not discarded. The determination will be based on whether the hazardous secondary material is legitimately recycled as specified in subparagraph (5)(d) of this rule and on the following criteria:

- (i) The extent that the management of the hazardous secondary material is part of the continuous primary production process and is not waste treatment;
  - (ii) Whether the capacity of the production process would use the hazardous secondary material in a reasonable time frame and ensure that the hazardous secondary material will not be abandoned (for example, based on past practices, market factors, the nature of the hazardous secondary material, or any contractual arrangements);
  - (iii) Whether the hazardous constituents in the hazardous secondary material are reclaimed rather than released to the air, water or land at significantly higher levels from either a statistical or from a health and environmental risk perspective than would otherwise be released by the production process; and
  - (iv) Other relevant factors that demonstrate the hazardous secondary material is not discarded, including why the hazardous secondary material cannot meet, or should not have to meet, the conditions of an exclusion under subparagraph (1)(b) or (d) of Rule 0400-12-01-.02.
3. The Commissioner may grant a non-waste determination for hazardous secondary material which is indistinguishable in all relevant aspects from a product or intermediate if the applicant demonstrates that the hazardous secondary material is comparable to a product or intermediate and is not discarded. The determination will be based on whether the hazardous secondary material is legitimately recycled as specified in subparagraph (5)(d) of this rule and on the following criteria:
- (i) Whether market participants treat the hazardous secondary material as a product or intermediate rather than a waste (for example, based on the current positive value of the hazardous secondary material, stability of demand, or any contractual arrangements);
  - (ii) Whether the chemical and physical identity of the hazardous secondary material is comparable to commercial products or intermediates;
  - (iii) Whether the capacity of the market would use the hazardous secondary material in a reasonable time frame and ensure that the hazardous secondary material will not be abandoned (for example, based on past practices, market factors, the nature of the hazardous secondary material, or any contractual arrangements);
  - (iv) Whether the hazardous constituents in the hazardous secondary material are reclaimed rather than released to the air, water or land at significantly higher levels from either a statistical or from a health and environmental risk perspective than would otherwise be released by the production process; and
  - (v) Other relevant factors that demonstrate the hazardous secondary material is not discarded, including why the hazardous secondary material cannot meet, or should not have to meet, the conditions of an exclusion under subparagraph (1)(b) or (d) of Rule 0400-12-01-.02.
- (f) The Commissioner may issue a Certificate to Operate for a hazardous secondary material reclamation facility or intermediate facility where the management of the hazardous secondary materials is not addressed under a Part B permit issued under Rule 0400-12-01-.07 or the interim status standards of Rule 0400-12-01-.05.
1. The Commissioner's decision will be based on the following criteria:
- (i) The reclamation facility or intermediate facility must demonstrate that the reclamation process for the hazardous secondary materials is legitimate pursuant



to subparagraph (5)(d) of this rule and its hazardous secondary material acceptance plan;

- (ii) The reclamation facility or intermediate facility must satisfy the financial assurance condition in subitem (1)(d)1(xxiv)(VI)VI of Rule 0400-12-01-.02;
- (iii) The reclamation facility or intermediate facility must not be subject to a formal enforcement action in the previous three years and not be classified as a significant non-complier under Rule Chapter 0400-12-01 or RCRA Subtitle C, or must provide credible evidence that the facility will manage the hazardous secondary materials properly. Credible evidence may include a demonstration that the facility has taken remedial steps to address the violations and prevent future violations, or that the violations are not relevant to the proper management of the hazardous secondary materials;
- (iv) The intermediate or reclamation facility must have the equipment and trained personnel needed to safely manage the hazardous secondary material and must meet emergency preparedness and response requirements under paragraph (13) of Rule 0400-12-01-.02;
- (v) If residuals are generated from the reclamation of the excluded hazardous secondary materials, the reclamation facility must have the permits required (if any) to manage the residuals, have a contract with an appropriately permitted facility to dispose of the residuals or present credible evidence that the residuals will be managed in a manner that is protective of human health and the environment; and
- (vi) The intermediate or reclamation facility must address the potential for risk to proximate populations from unpermitted releases of the hazardous secondary material to the environment (i.e., releases that are not covered by a permit, such as a permit to discharge to water or air), which may include, but are not limited to, potential releases through surface transport by precipitation runoff, releases to soil and groundwater, wind-blown dust, fugitive air emissions, and catastrophic unit failures, and must include consideration of potential cumulative risks from other nearby potential stressors.

2. To evaluate the criteria of subpart 1(vi) of this subparagraph, the Commissioner will require the petitioner to comply with subparts (i) and (ii) of this part.

- (i) Prior to applying for a Certificate to Operate, the petitioner must hold at least one meeting with the public in order to solicit questions from the community and inform the community of proposed hazardous secondary material management activities.
  - (I) At the meeting, the petitioner must:
    - I. Post a sign-in sheet or otherwise provide a voluntary opportunity for attendees to provide their names and addresses; and
    - II. Provide a community impact statement that includes the following:
      - A. A description of the hazardous secondary materials to be received at the facility, including quantities and methods of management;
      - B. A description of security procedures proposed for the facility;

- C. Information on hazard prevention and preparedness, including a summary of the arrangements with local emergency authorities;
  - D. A description of procedures, structures or equipment used to prevent employee exposure, hazards during unloading, runoff from handling areas, and contamination of water supplies;
  - E. A description of traffic patterns, traffic volume and control, condition of access roads, and the adequacy of traffic control signals; and
  - F. A description of the facility location information relative to flood plain and seismic activity.
- (II) The petitioner must submit documentation to the Commissioner of the public notices, the community impact statement, a summary of the meeting, along with the list of attendees and their addresses, and copies of any written comments or materials submitted at the meeting.
  - (III) The owner or operator must provide public notice of the community meeting at least thirty (30) days prior to the meeting.
  - (IV) The public notice required by item (III) of this subpart must contain language approved by the Commissioner and published in a manner specified by the Commissioner.
- (ii) The petitioner must describe how the facility is designed, constructed, operated and maintained to ensure protection of human health and the environment. Protection of human health and the environment includes, but is not limited to:
    - (I) Prevention of any releases that may have adverse effects on human health or the environment due to migration of hazardous constituents in the ground water or subsurface environment, considering:
      - I. The volume and physical and chemical characteristics of the hazardous secondary material to be managed at the facility, including its potential for migration through soil, liners, or other containing structures;
      - II. The hydrologic and geologic characteristics of the management units at the facility and the surrounding area;
      - III. The existing quality of ground water, including other sources of contamination and their cumulative impact on the ground water;
      - IV. The quantity and direction of ground-water flow;
      - V. The proximity to and withdrawal rates of current and potential ground-water users;
      - VI. The patterns of land use in the region;
      - VII. The potential for deposition or migration of hazardous constituents into subsurface physical structures, and into the root zone of food-chain crops and other vegetation;
      - VIII. The potential for health risks caused by human exposure to hazardous constituents; and

- IX. The potential for damage to domestic animals, wildlife, crops, vegetation, and physical structures caused by exposure to hazardous constituents.
- (II) Prevention of any releases that may have adverse effects on human health or the environment due to migration of hazardous constituents in surface water, or wetlands, or on the soil surface considering:
- I. The volume and physical and chemical characteristics of the hazardous secondary material to be managed at the facility;
  - II. The effectiveness and reliability of containing, confining, and collecting systems and structures in preventing migration;
  - III. The hydrologic characteristics of the facility and the surrounding area, including the topography of the land around the facility;
  - IV. The patterns of precipitation in the region;
  - V. The quantity, quality, and direction of ground-water flow;
  - VI. The proximity of the unit to surface waters;
  - VII. The current and potential uses of nearby surface waters and any water quality standards established for those surface waters;
  - VIII. The existing quality of surface waters and surface soils, including other sources of contamination and their cumulative impact on surface waters and surface soils;
  - IX. The patterns of land use in the region;
  - X. The potential for health risks caused by human exposure to hazardous constituents; and
  - XI. The potential for damage to domestic animals, wildlife, crops, vegetation, and physical structures caused by exposure to hazardous constituents.
- (III) Prevention of any releases that may have adverse effects on human health or the environment due to migration of hazardous constituents in the air, considering:
- I. The volume and physical and chemical characteristics of the hazardous secondary materials to be managed at the facility, including its potential for the emission and dispersal of gases, aerosols and particulates;
  - II. The effectiveness and reliability of systems and structures to reduce or prevent emissions of hazardous constituents to the air;
  - III. The operating characteristics of the units managing hazardous secondary materials;
  - IV. The atmospheric, meteorologic, and topographic characteristics of the units to be managing hazardous secondary materials at the facility and the surrounding area;

- V. The existing quality of the air, including other sources of contamination and their cumulative impact on the air;
  - VI. The potential for health risks caused by human exposure to hazardous constituents; and
  - VII. The potential for damage to domestic animals, wildlife, crops, vegetation, and physical structures caused by exposure to hazardous constituents.
- (g) Procedures for variances from classification as a solid waste, for issuing a Certificate to Operate for a hazardous secondary material reclamation facility or intermediate facility, for variances to be classified as a boiler, and for non-waste determinations [40 CFR 260.33]

The Commissioner will use the following procedures in evaluating applications for variances from classification as a waste, applications for obtaining a Certificate to Operate for a hazardous secondary material reclamation facility or intermediate facility, applications to classify particular enclosed controlled flame combustion devices as boilers, and applications for non-waste determinations.

1. The applicant must apply to the Commissioner for the variance, the Certificate to Operate or non-waste determination. The application must address the relevant criteria contained in subparagraph (c), (d), (e) or (f) of this paragraph, as applicable.
2. The Commissioner will evaluate the application and make a tentative decision to grant or deny the application and shall notify the petitioner of this tentative decision. If the Commissioner makes a tentative decision to grant the petition, the Commissioner shall give public notice of such tentative decision for written public comment. The public notice shall be provided by the applicant as prepared and required by the Commissioner in a newspaper advertisement or radio broadcast in the locality where the recycler is located. The applicant shall provide proof of the completion of all notice requirements to the Commissioner within ten days following conclusion of the public notice procedures. The Commissioner will accept comment on the tentative decision for thirty (30) days, and may also hold a public hearing upon request or at his discretion. Notice of the public hearing shall be given by the applicant and prepared as required by the Commissioner. The Commissioner will issue a final decision after receipt of comments and after the hearing (if any).
3.
  - (i) Except for the change described in subpart (ii) of this part. in the event of a change in circumstances that affects how a hazardous secondary material meets the relevant criteria contained in subparagraph (c), (d), (e) or (f) of this paragraph upon which a variance, Certificate to Operate or non-waste determination has been based, the applicant must send a description of the change in circumstances to the Commissioner. The Commissioner may issue a determination that the hazardous secondary material continues to meet the relevant criteria of the variance, Certificate to Operate, or non-waste determination or may require the facility to re-apply for the variance, Certificate to Operate or non-waste determination.
  - (ii) Any change made to the hazardous secondary material acceptance plan required under item (4)(d)1(xxiv)(VI)VIII of Rule 0400-12-01-.02 must be approved and the Certificate to Operate modified by the Commissioner after considering the applicable criteria of subparagraph (f) of this paragraph and following the procedures of this subparagraph prior to the change being implemented.
4. Variances, Certificates to Operate and non-waste determinations shall be effective for a fixed term not to exceed ten (10) years. No later than six (6) months prior to the end of this term, facilities must re-apply for a variance, Certificate to Operate, or non-waste determination. If a facility re-applies for a variance, Certificate to Operate, or non-waste

determination within six (6) months, the facility may continue to operate under an expired variance, Certificate to Operate or non-waste determination until receiving a decision on the facility's re-application from the Commissioner.

5. Facilities receiving a variance, Certificate to Operate or non-waste determination must provide notification as required by subparagraph (5)(c) of this rule.

(h) Causes for Termination of the Certificate to Operate

1. Failure of the owner or operator to comply with any condition of the Certificate to Operate;
2. The owner or operator's failure in the application or during the issuance process to disclose fully all relevant facts, or the owner or operator's misrepresentation of any relevant facts at any time;
3. A determination by the Commissioner that continuing the authorized activity endangers human health or the environment;
4. Failure of the owner or operator to timely pay the annual maintenance fees in accordance with Rule 0400-12-01-.08; or
5. At the request of the owner or operator, provided all hazardous secondary materials and residues have been removed to the satisfaction of the Commissioner.

(i) Duty to Comply with the Certificate to Operate

1. The owner or operator of the hazardous secondary material reclamation or intermediate facility shall comply with the conditions of the Certificate to Operate as determined necessary by the Commissioner.
2. Failure to comply with the conditions of the Certificate to Operate issued by the Commissioner shall subject the owner or operator of the hazardous secondary material reclamation or intermediate facility to an enforcement action, including, if applicable, operating a hazardous waste treatment, storage or disposal facility without a permit.

(5) Additional Requirements

(a) Additional Regulation of Certain Hazardous Waste Recycling Activities on a Case-by-Case Basis [40 CFR 260.40]

The Commissioner may decide on a case-by-case basis that persons accumulating or storing the recyclable materials described in Rule 0400-12-01-.02(1)(f)1(ii)(III) should be regulated under Rule 0400-12-01-.02(1)(f)2 and 3. The basis for this decision is that the materials are being accumulated or stored in a manner that does not protect human health and the environment because the materials or their toxic constituents have not been adequately contained, or because the materials being accumulated or stored together are incompatible. In making this decision, the Commissioner will consider the following factors:

1. The types of materials accumulated or stored and the amounts accumulated or stored;
2. The method of accumulation or storage;
3. The length of time the materials have been accumulated or stored before being reclaimed;
4. Whether any contaminants are being released into the environment, or are likely to be so released; and
5. Other relevant factors.

The procedures for this decision are set forth in subparagraph (b) of this paragraph.

(b) Procedures for Case-by-Case Regulation of Hazardous Waste Recycling Activities [40 CFR 260.41]

The Commissioner will use the following procedures when determining whether to regulate hazardous waste recycling activities described in Rule 0400-12-01-.02(1)(f)1(ii)(III) under the provisions of Rule 0400-12-01-.02(1)(f)2 and 3, rather than under the provisions of Rule 0400-12-01-.09(6).

1. If a generator is accumulating the waste, the Commissioner will issue a notice, published by the owner or operator, as prepared and required by the Commissioner, setting forth the factual basis for the decision and stating that the person must comply with the applicable requirements of paragraphs (1), (4), (5), and (6) of Rule 0400-12-01-.03. The notice will become final within 30 days, unless the person served requests a public hearing to challenge the decision. Upon receiving such a request, the Commissioner will hold a public hearing. The Commissioner will provide notice, published by the owner or operator as prepared and required by the Commissioner, of the hearing to the public and allow public participation at the hearing. The owner or operator shall provide proof of the completion of all notice requirements to the Commissioner within ten days following conclusion of the public notice procedures. The Commissioner will issue a final order after the hearing stating whether or not compliance with Rule 0400-12-01-.03 is required. The order becomes effective 30 days after service of the decision unless the Commissioner specifies a later date or unless review by the Board is requested. The order may be appealed to the Board by any person who participated in the public hearing. The Board may choose to grant or to deny the appeal. Final Department action occurs when a final order is issued and Department review procedures are exhausted.
2. If the person is accumulating the recyclable material as a storage facility, the notice will state that the person must obtain a permit in accordance with all applicable provisions of Rule 0400-12-01-.07. The owner or operator of the facility must apply for a permit within no less than 60 days and no more than six months of notice, as specified in the notice. If the owner or operator of the facility wishes to challenge the Commissioner's decision, he may do so in his permit application, in a public hearing held on the draft permit, or in comments filed on the draft permit, or on the notice of intent to deny the permit. The fact sheet accompanying the permit will specify the reasons for the determination. The question of whether the Commissioner's decision was proper will remain open for consideration during the public comment period discussed under Rule 0400-12-01-.07(7)(e) and in any subsequent hearing.

(c) Notification requirement for hazardous secondary materials. [40 CFR 260.42]

1. Facilities managing hazardous secondary materials under subparagraph (4)(b) of this rule, or subpart (1)(d)1(xxiii), (xxiv) or (xxvii) of Rule 0400-12-01-.02 must send a notification prior to operating under the regulatory provision and by March 1 of each even-numbered year thereafter to the Commissioner using forms provided by the department that include the following information:
  - (i) The name, address, and EPA ID number (if applicable) of the facility;
  - (ii) The name and telephone number of a contact person;
  - (iii) The NAICS code of the facility;
  - (iv) The regulation under which the hazardous secondary materials will be managed;
  - (v) When the facility began or expects to begin managing the hazardous secondary materials in accordance with the regulation;

- (vi) A list of hazardous secondary materials that will be managed according to the regulation (reported as hazardous waste codes that would apply if the hazardous secondary materials were managed as hazardous wastes);
- (vii) For each hazardous secondary material, whether the hazardous secondary material, or any portion thereof, will be managed in a land-based unit;
- (viii) The quantity of each hazardous secondary material to be managed annually; and
- (ix) The certification (included in the forms provided by the department) signed and dated by an authorized representative of the facility.

2. If a facility managing hazardous secondary materials has submitted a notification, but then subsequently stops managing hazardous secondary materials in accordance with subparagraph (4)(b) of this rule, or subpart (1)(d)1(xxiii), (xxiv) or (xxvii) of Rule 0400-12-01-.02 the facility must notify the Commissioner within thirty (30) days using forms provided by the department. For purposes of this part, a facility has stopped managing hazardous secondary materials if the facility no longer generates, manages and/or reclaims hazardous secondary materials under subparagraph (4)(b) of this rule, or subpart (1)(d)1(xxiii), (xxiv) or (xxvii) of Rule 0400-12-01-.02 and does not expect to manage any amount of hazardous secondary materials for at least one (1) year.

(d) Legitimate recycling of hazardous secondary materials [40 CFR 260.43]

1. Recycling of hazardous secondary materials for the purpose of the exclusions or exemptions from the hazardous waste regulations must be legitimate. Hazardous secondary material that is not legitimately recycled is discarded material and is a solid waste. In determining if their recycling is legitimate, persons must address all the requirements of this part.

(i) Legitimate recycling must involve a hazardous secondary material that provides a useful contribution to the recycling process or to a product or intermediate of the recycling process. The hazardous secondary material provides a useful contribution if it:

- (I) Contributes valuable ingredients to a product or intermediate; or
- (II) Replaces a catalyst or carrier in the recycling process; or
- (III) Is the source of a valuable constituent recovered in the recycling process; or
- (IV) Is recovered or regenerated by the recycling process; or
- (V) Is used as an effective substitute for a commercial product.

(ii) The recycling process must produce a valuable product or intermediate. The product or intermediate is valuable if it is:

- (I) Sold to a third party; or
- (II) Used by the recycler or the generator as an effective substitute for a commercial product or as an ingredient or intermediate in an industrial process.

(iii) The generator and the recycler must manage the hazardous secondary material as a valuable commodity when it is under their control. Where there is an analogous raw material, the hazardous secondary material must be managed, at a minimum, in a manner consistent with the management of the raw material or in an equally protective manner. Where there is no analogous raw material, the

hazardous secondary material must be contained. Hazardous secondary materials that are released to the environment and are not recovered immediately are discarded.

- (iv) The product of the recycling process must be comparable to a legitimate product or intermediate:
  - (I) Where there is an analogous product or intermediate, the product of the recycling process is comparable to a legitimate product or intermediate if:
    - I. The product of the recycling process does not exhibit a hazardous characteristic (as defined in paragraph (3) of Rule 0400-12-01-.02) that analogous products do not exhibit, and
    - II. The concentrations of any hazardous constituents found in appendix VIII of paragraph (30) of Rule 0400-12-01-.02 that are in the product or intermediate are at levels that are comparable to or lower than those found in analogous products or at levels that meet widely-recognized commodity standards and specifications, in the case where the commodity standards and specifications include levels that specifically address those hazardous constituents.
  - (II) Where there is no analogous product, the product of the recycling process is comparable to a legitimate product or intermediate if:
    - I. The product of the recycling process is a commodity that meets widely recognized commodity standards and specifications (e.g., commodity specification grades for common metals), or  
  
(Note: For specialty products such as specialty batch chemicals or specialty metal alloys, customer specifications would be sufficient.)
    - II. The hazardous secondary materials being recycled are returned to the original process or processes from which they were generated to be reused (e.g., closed loop recycling).  
  
(Note: There is no analogous product when the hazardous secondary material is recycled by being returned to the original production process or processes. Production process or processes includes those activities that tie directly into the manufacturing operation or those activities that are the primary operation at an establishment.)
  - (III) If the product of the recycling process has levels of hazardous constituents that are not comparable to or unable to be compared to a legitimate product or intermediate per item (I) or (II) of this subpart, the recycling still may be shown to be legitimate, if it meets the following specified requirements. The person performing the recycling must conduct the necessary assessment and prepare documentation showing why the recycling is, in fact, still legitimate. The recycling can be shown to be legitimate based on lack of exposure from toxics in the product, lack of the bioavailability of the toxics in the product, or other relevant considerations which show that the product made using recycled material does not contain levels of hazardous constituents that pose a significant human health or environmental risk. The documentation must include a certification statement that the recycling is legitimate and must be maintained on-site for three years after the recycling operation has



ceased. The person performing the recycling must notify the Commissioner of this activity using forms provided by the department.

(Note: To comply with the requirements of this subpart, a generator of the hazardous secondary material, product or intermediate may use its knowledge of the materials it recycles and of the recycling process to make legitimacy determinations.)

(Note: A person who meets the specific provisions included in 0400-12-01-.02(1)(b)3 Table 1, 0400-12-01-.02(1)(b)5, 0400-12-01-.02(1)(d)1(vi) through (xxii), 0400-12-01-.02(1)(f)1(ii)(III) and (IV), and 0400-12-01-.02(1)(f)1(iii)(I), are presumed to conduct legitimate recycling, except in those rare cases when it is necessary to document legitimacy in accordance with item 1(iv)(III) of this subparagraph. If, at any time, the Commissioner suspects that sham recycling may be occurring, in accordance with part (1)(b)6 of Rule 0400-12-01-.02, the Commissioner may require a person to demonstrate that the recycling in question is legitimate in accordance with this subparagraph.)

2. Reserved

3. Reserved

(6) Reserved

(7) Proprietary Information

(a) General

1. Purpose, Scope, and Applicability

Except as provided under subparts (i) and (ii) of this part, any information which is supplied to the Department by persons who are subject to these rules and which is designated as proprietary information (as defined in subpart 2(viii) of this subparagraph) shall be handled by the Department as specified in this paragraph to assure that its confidentiality is maintained. Unless it is claimed or designated as proprietary, any information supplied to the Department under or relating to these rules shall be available for public review at any time during the State's normal business hours.

(i) After the effective date of these rules, no claim of business confidentiality may be asserted by any person with respect to information entered on a Hazardous Waste Manifest (EPA Form 8700-22), a Hazardous Waste Manifest Continuation Sheet (EPA Form 8700-22A), or an electronic manifest format that may be prepared and used in accordance with subpart (3)(a)1(iii) of Rule 0400-12-01-.03.

(ii) The Department will make any electronic manifest that is prepared and used in accordance with subpart (3)(a)1(iii) of Rule 0400-12-01-.03, or any paper manifest that is submitted to the system under item (5)(b)1(ii)(V) of Rule 0400-12-01-.05 or item (5)(b)1(ii)(V) of Rule 0400-12-01-.06 available to the public under this paragraph when the electronic or paper manifest is a complete and final document. Electronic manifests and paper manifests submitted to the system are considered by the Department to be complete and final documents and publicly available information after 90 days have passed since the delivery to the designated facility of the hazardous waste shipment identified in the manifest.

(Note: See 40 CFR 260.2(b) for additional requirements.)

2. Definitions

The following terms shall be defined as indicated for the purposes of this paragraph and this paragraph only:

- (i) "Access" is the ability and opportunity to gain knowledge of Proprietary Information in any manner whatsoever.
- (ii) "Authorized person" is any person, including members of the Board, authorized to receive Proprietary Information. Except for members of the Board, such authorization shall be granted in writing by the Commissioner.
- (iii) "Document" is any recorded information regardless of its physical form or characteristics, including, but not limited to, written or printed material; processing cards and tapes; maps; charts; paintings; drawings; engravings; sketches; working papers and notes; reproduction of such things by any means or process; and sound, voice, or electronic recordings in any form.
- (iv) "Document Control Number" is the unique number assigned by the document control officer to any document containing Proprietary Information.
- (v) "Document Control Officer" is the individual authorized by the Commissioner in writing to be responsible for all incoming and outgoing documents identified as containing Proprietary Information.
- (vi) "Information" is knowledge which can be communicated by any means.
- (vii) "Instruction" is fully informing individuals in writing of their responsibilities for safeguarding Proprietary Information and the security procedures they shall follow.
- (viii) "Proprietary Information" means any confidential information that relates to a trade secret, product, apparatus, process, operation, style of work, or financial information which is owned (not necessarily exclusively) by or licensed to a person and claimed by that person to be proprietary and confidential; provided that the claim is accompanied by a written statement from such person relating the reasons why such information should be held confidential. Such information may be submitted to the Department by the owner/licensee of the trade secret, product, etc.; or by another governmental agency which has obtained the information. If submitted by the owner/licensee, the written statement accompanying the information claimed proprietary must, at a minimum, answer the questions in items (I) through (IV) of this subpart. If submitted by another governmental agency, the written statement need include only the accompanying statements/reasons obtained by that agency.
  - (I) Will disclosure of the information be likely to substantially harm your competitive position? If so, what would the harm be, and why should it be viewed as substantial? What is the relationship between disclosure and the harm?
  - (II) What measures have you taken to guard against undesired disclosure of the information to others?
  - (III) To what extent has the information been disclosed to others, and what precautions have you taken in connection with that disclosure?
  - (IV) Has the U.S. Environmental Protection Agency or any other Federal or State of Tennessee agency made a pertinent confidentiality determination? (If so, please include a copy of this determination, if available.)

### 3. Policy

Department employees are prohibited from disclosing, in any manner and to any extent not authorized by law or regulations, any Proprietary Information coming to them in the course of their employment or official duties. Proprietary Information is to be held in confidence, protected in accordance with the procedures described in this paragraph, and released only to authorized persons.

(b) Responsibilities

1. Commissioner

The Commissioner is responsible for:

- (i) Designating a document control officer;
- (ii) Assuring that all Department employees receiving and handling Proprietary Information receive instruction as to their responsibilities for controlling Proprietary Information;
- (iii) Maintaining a record which lists all employees who have authorized access to Proprietary Information;
- (iv) Obtaining a "Confidentiality Agreement" from all employees having access to Proprietary Information;
- (v) Obtaining a "Confidentiality Agreement upon Transfer or Termination" from all employees having access to Proprietary Information in the event such employees decide to terminate employment or are transferred to a position not requiring such access;
- (vi) Assuring that the appropriate requirements for storage and use are met, including control of access to keys and combinations;
- (vii) Taking appropriate disciplinary action concerning any Department employees who fail to comply with the requirements of this paragraph; and
- (viii) Notifying the person submitting Proprietary Information which has been disclosed in violation of the requirements of this paragraph of such occurrence.

2. Document Control Officer

The Document Control Officer is responsible for the maintenance, control and distribution of all Proprietary Information received by the Department as follows:

- (i) Logging of all Proprietary Information as received by the Department, both incoming and outgoing;
- (ii) Assigning a document control number to each document received containing Proprietary Information;
- (iii) Maintaining a system which identifies employees authorized to receive Proprietary Information;
- (iv) Releasing Proprietary Information only to persons from whom the confidentiality agreements of subparts 1(iv) and (v) of this subparagraph have been obtained;
- (v) Maintaining a system to insure that any Proprietary Information transmitted to field locations is received;
- (vi) Maintaining at Department offices a system for retrieval of documents that are furnished to other program offices;

- (vii) Authorizing and supervising the reproduction and destruction of Proprietary Information; and
- (viii) Assuring that recipients of Proprietary Information have proper storage capability prior to release of such documents, or, if they do not, requiring return of the released Proprietary Information the same day.

3. Employees

Employees are responsible for:

- (i) Controlling all Proprietary Information entrusted to them;
- (ii) Only discussing Proprietary Information with authorized persons;
- (iii) Never leaving the Proprietary Information unattended when not properly stored;
- (iv) Never discussing Proprietary Information over the telephone except upon approval of the document control officer should the Proprietary Information be needed in an emergency situation;
- (v) Storing the Proprietary Information as specified in part (c)5 of this paragraph when not in use and at the close of business;
- (vi) Not reproducing Proprietary Information documents. Additional copies must be obtained through the document control officer; and
- (vii) Reporting immediately possible violations of these regulations to the Commissioner.

(c) Procedures

1. Receipt and Handling

The document control officer shall:

- (i) Receive all information claimed as proprietary and confidential which is submitted to the Department;
- (ii) Log in all Proprietary Information received by the Department;
- (iii) Assign a document control number to all Proprietary Information;
- (iv) Attach a Proprietary Information cover sheet to the document;
- (v) Release Proprietary Information only to authorized persons; and
- (vi) Review the claim and, using the written statement accompanying the information claimed proprietary, the answers to the questions at items (a)2(viii)(I) through (IV) of this paragraph and other information as may be required, determine whether to approve or deny it, in part or in whole.

2. Transmission

- (i) Proprietary Information must be transmitted in a double envelope by Registered Mail, Return Receipt Requested. The inner envelope must reflect the address of the recipient with the following additional wording on the front side of the inner envelope:

"Confidential Business - To Be Opened By Document Control Officer Only."

The outer envelope must reflect the normal address without the additional wording.

- (ii) All requests to the document control officer for Proprietary Information must be in writing and signed by the requesting employee.
- (iii) Proprietary Information may be hand carried to other Department facilities by authorized persons providing the dispatching document control officer maintains a record and obtains a receipt from the receiving document control officer. Information being hand carried should be packaged as described in subpart (i) of this part.
- (iv) Proprietary Information within a Department office shall be hand delivered only by an authorized person. At no time shall Proprietary Information be transmitted through inner office mailing channels.

3. Reproduction

Proprietary Information shall not be reproduced except upon approval by and under the supervision of the document control officer. Any reproduction shall be limited by a document control system and be subject to the same control requirements as for the original.

4. Destruction

Proprietary Information shall not be destroyed except upon approval by and under the supervision of the document control officer. The document control officer shall keep a record of destruction in the appropriate log and notify the person submitting the Proprietary Information.

5. Storage

- (i) Documents containing Proprietary Information must be stored within a locked cabinet so as to limit access to authorized persons.
- (ii) Keys and/or combinations to cabinets and/or rooms where the data is stored must be issued only to an authorized person.

(d) Transmittal Outside Department Offices

Proprietary Information shall not be transmitted outside Department offices without the approval of the Commissioner and such information must be transmitted by the document control officer in accordance with part (c)2 of this paragraph. The person submitting the Proprietary Information shall be notified when such occurs.

(e) Release to EPA

Notwithstanding any requirement of this paragraph seemingly to the contrary, Proprietary Information may be released to the U.S. Environmental Protection Agency in connection with the Commissioner's or Board's implementation or his or its responsibilities pursuant to the Act or as necessary to comply with federal law. Any such release of Proprietary Information to EPA, however, will be made with a confidentiality claim and shall be accompanied by the written statement received by the Department pursuant to subpart (a)2(viii) of this paragraph. Any transmittal of Proprietary Information to EPA shall be subject to the requirements of subparagraph (d) of this paragraph. The Commissioner shall notify the submitter of Proprietary Information of the release of such information to EPA as soon as practicable - to be no later than 5 days after such release - following receipt of EPA's request for the information.

(8) Availability of Information

- (a) The Division will respond to all requests for records within 20 days after the date of receipt of such requests.
- (b) If a facility does not assert a claim of proprietary information at the first opportunity provided by the Division, the Division may release the information without further notice to the facility. In addition, in the case of any information submitted in connection with a permit, permit application or interim status under Rules 0400-12-01-.05, .06, and .07, any facility proprietary information claim must be asserted at the time of submission of the information to the Division.
- (c) If a proprietary information claim is asserted and cannot be resolved in the time period provided for the Division's response to a request, the requestor will be notified of the proprietary information claim within the maximum 20-day time limit provided for the Division's response. In addition, the requestor must be told that the Division has denied the request in order to resolve the proprietary information claim.

(9) Retention of Records

- (a) In order to protect public health, safety and welfare, to prevent degradation of the environment, conserve natural resources and provide a coordinated statewide hazardous waste management program it is necessary to manage and retain records. These records shall be managed in accordance with Chapter 1210-01 Rules of Public Records Commission.
- (b) As defined by paragraph (2) of Rule 1210-01-.02, permanent records have permanent administrative, fiscal, historical or legal value. The following types of records generated by or received by the Department while fulfilling its duties under T.C.A. §§ 68-212-101 et seq., and Chapter 0400-12-01 Hazardous Waste Management shall be managed as permanent records:

1. All records containing information, by site, of hazardous wastes or hazardous secondary materials that have been generated, treated, stored, disposed of and/or recycled, or hazardous waste or hazardous secondary material activities that have been conducted at the site, shall be managed as a permanent record. These records have historic value since there is a risk that these hazardous waste activities may have caused contamination that remains undetected for many years. When an exposure occurs these records would be required in order to facilitate an effective response. These records include, but are not limited to:
  - (i) Generator notifications, waste stream pages and annual reports;
  - (ii) Hazardous waste permits and permit applications;
  - (iii) Hazardous Waste Inspection reports and enforcement actions; and
  - (iv) Recycling determinations and investigations.
2. All records regarding hazardous waste or hazardous substance remedial action sites managed by the Division shall be managed as permanent records. Records regarding site characterization, monitoring, remedial actions, risk determination and enforcement actions have historic value since the long term effects of hazardous waste, hazardous waste constituents or hazardous substances are uncertain and could lead to future exposures. When an exposure occurs, these records would be required in order to facilitate an effective response.
3. All records regarding unregulated hazardous waste sites where unlawful hazardous waste treatment, storage, disposal or recycling was documented shall be managed as permanent records. These records have historic value since the long term effects of hazardous waste, hazardous waste constituents or hazardous substances are uncertain and could lead to future exposures. When an exposure occurs, these records would be required in order to facilitate an effective response.

Paragraph (1) of Rule 0400-12-01-.02 Identification and Listing of Hazardous Waste is amended by deleting it in its entirety and substituting instead the following:

(1) General [40 CFR 261 Subpart A]

(a) Purpose and Scope [40 CFR 261.1]

1. This rule identifies those solid wastes which are subject to regulation as hazardous wastes under Rules 0400-12-01-.03 through .07 and .10. In this rule:
  - (i) Paragraph (1) defines the terms "solid waste" and "hazardous waste", identifies those wastes which are excluded from regulation under Rules 0400-12-01-.03 through .07, .09 and .10 and establishes special management requirements for hazardous waste produced by conditionally exempt small quantity generators and hazardous waste which is recycled.
  - (ii) Paragraph (2) sets forth the criteria used by the Board to identify characteristics of hazardous waste and to list particular hazardous wastes.
  - (iii) Paragraph (3) identifies characteristics of hazardous waste.
  - (iv) Paragraph (4) lists particular hazardous wastes.
2.
  - (i) The definition of solid waste contained in this rule applies only to wastes that also are hazardous for purposes of the regulations implementing T.C.A. Title 68, Chapter 212. For example it does not apply to materials (such as non-hazardous scrap, paper, textiles, or rubber) that are not otherwise hazardous wastes and that are recycled.
  - (ii) This rule identifies only some of the materials which are solid wastes and hazardous wastes under T.C.A. Sections 68-212-105, 68-212-107, 68-212-111, 68-212-114 and 68-212-115. A material which is not defined as a solid waste in this rule, or is not a hazardous waste identified or listed in this rule, is still a solid waste and a hazardous waste for purposes of these statutory sections if:
    - (I) In the case of T.C.A. Section 68-212-107, the Commissioner has reason to believe that the material may be a solid waste within the meaning of T.C.A. Section 68-212-104(19) and a hazardous waste within the meaning of T.C.A. Section 68-212-104(8); or
    - (II) In the case of T.C.A. Sections 68-212-105, 68-212-111, 68-212-114 and 68-212-115, the statutory definition of a waste and a hazardous waste are established.
3. For the purposes of subparagraphs (b) and (f) of this paragraph:
  - (i) A "spent material" is any material that has been used and as a result of contamination can no longer serve the purpose for which it was produced without processing.

(Note: The term "spent material" includes any material that has been used and is no longer fit for use without being regenerated, reclaimed or otherwise reprocessed.)

(Note: As used in the definition of spent materials, "contamination" includes any impurity, factor, or circumstance which causes the material to be taken out of service.)

- (ii) "Sludge" has the same meaning used in Rule 0400-12-01-.01(2)(a).
- (iii) A "by-product" is a material that is not one of the primary products of a production process and is not solely or separately produced by the production process. Examples are process residues such as slags or distillation column bottoms. The term does not include a co-product that is produced for the general public's use and is ordinarily used in the form it is produced by the process.

(Note: The term "by-product" includes residues that result from manufacturing or other operations that are not one of the primary products that are produced.)

(Note: The term "co-product" means a material produced for use by the general public and suitable for end use essentially as-is.)
- (iv) A material is "reclaimed" if it is processed to recover a usable product, or if it is regenerated. Examples are recovery of lead values from spent batteries and regeneration of spent solvents. In addition, for purposes of subparts (d)1(xxiii) and (xxiv) of this paragraph, smelting, melting and refining furnaces are considered to be solely engaged in metals reclamation if the metal recovery from the hazardous secondary materials meets the same requirements as those specified for metals recovery from hazardous waste found in subparts (8)(a)4(i) through (iii) of Rule 0400-12-01-.09, and if the residuals meet the requirements specified in subparagraph (8)(m) of Rule 0400-12-01-.09.
- (v) A material is "used or reused" if it is either:
  - (I) Employed as an ingredient (including use as an intermediate) in an industrial process to make a product (for example, distillation bottoms from one process used as feedstock in another process). However, a material will not satisfy this condition if distinct components of the material are recovered as separate end products (as when metals are recovered from metal-containing secondary materials); or
  - (II) Employed in a particular function or application as an effective substitute for a commercial product (for example, spent pickle liquor used as phosphorous precipitant and sludge conditioner in wastewater treatment).
- (vi) "Scrap metal" is bits and pieces of metal parts (e.g., bars, turnings, rods, sheets, wire) or metal pieces that may be combined together with bolts or soldering (e.g., radiators, scrap automobiles, railroad box cars), which when worn or superfluous can be recycled.
- (vii) A material is "recycled" if it is used, reused, or reclaimed.
- (viii) A material is "accumulated speculatively" if it is accumulated before being recycled. A material is not accumulated speculatively, however, if the person accumulating it can show that the material is potentially recyclable and has a feasible means of being recycled; and that -- during the calendar year (commencing on January 1) -- the amount of material that is recycled, or transferred to a different site for recycling, equals at least 75 percent by weight or volume of the amount of that material accumulated at the beginning of the period. Materials must be placed in a storage unit with a label indicating the first date that the material began to be accumulated. If placing a label on the storage unit is not practicable, the accumulation period must be documented through an inventory log or other appropriate method. In calculating the percentage of turnover, the 75 percent requirement is to be applied to each material of the same type (e.g., slags from a single smelting process) that is recycled in the same way (i.e., from which the same material is recovered or that is used in the same way). Materials accumulating in units that would be exempt from regulation



under subpart (d)3(i) of this paragraph are not to be included in making the calculation. (Materials that are already defined as solid wastes also are not to be included in making the calculation.) Materials are no longer in this category once they are removed from accumulation for recycling, however.

(Note: The speculative accumulation requirements contained in this subpart are only applicable when specifically referenced by the exclusion or exemption conditions contained in this rule and Rule 0400-12-01-.09. For example, subparts (d)1(viii), (xiii), and (xxvi) of this paragraph do not require compliance with this subpart as a condition of the exclusions; subparts (d)1(vi) and (vii) of this paragraph and part (6)(a)3 of Rule 0400-12-01-.09 do require compliance with the subpart as a condition of the exclusion or exemption.)

- (ix) "Excluded scrap metal" is processed scrap metal, unprocessed home scrap metal, and unprocessed prompt scrap metal.
- (x) "Processed scrap metal" is scrap metal which has been manually or physically altered to either separate it into distinct materials to enhance economic value or to improve the handling of materials. Processed scrap metal includes, but is not limited to scrap metal which has been baled, shredded, sheared, chopped, crushed, flattened, cut, melted, or separated by metal type (i.e., sorted), and, fines, drosses and related materials which have been agglomerated. (Note: shredded circuit boards being sent for recycling are not considered processed scrap metal. They are covered under the exclusion from the definition of solid waste for shredded circuit boards being recycled (Rule 0400-12-01-.02(1)(d)1(xiv)).
- (xi) "Home scrap metal" is scrap metal as generated by steel mills, foundries, and refineries such as turnings, cuttings, punchings, and borings.
- (xii) "Prompt scrap metal" is scrap metal as generated by the metal working/fabrication industries and includes such scrap metal as turnings, cuttings, punchings, and borings. Prompt scrap is also known as industrial or new scrap metal.

(b) Definition of Solid Waste [40 CFR 261.2]

1. (i) A "solid waste" is any discarded material that is not excluded by part (d)1 of this paragraph or that is not excluded by variance granted under subparagraphs (4)(b) and (c) of Rule 0400-12-01-.01 or that is not excluded by a non-waste determination under subparagraphs (4)(b) and (e) of Rule 0400-12-01-.01.
  - (ii) (I) A "discarded material" is any material which is:
    - I. "Abandoned", as explained in part 2 of this paragraph; or
    - II. "Recycled", as explained in part 3 of this paragraph; or
    - III. Considered "inherently waste-like", as explained in part 4 of this subparagraph; or
    - IV. A military munition identified as a solid waste in subparagraph (13)(c) of Rule 0400-12-01-.09.
  - (II) Reserved
2. Materials are solid waste if they are "abandoned" by being:
  - (i) Disposed of; or

- (ii) Burned or incinerated; or
  - (iii) Accumulated, stored, or treated (but not recycled) before or in lieu of being abandoned by being disposed of, burned, or incinerated; or
  - (iv) Sham recycled, as explained in part 7 of this subparagraph.
3. Materials are solid wastes if they are "recycled" -- or accumulated, stored, or treated before recycling -- as specified in subparts (i) through (iv) of this part:
- (i) "Used in a manner constituting disposal".
    - (I) Materials noted with a "\*" in Column 1 of Table 1 are solid wastes when they are:
      - I. Applied to or placed on the land in a manner that constitutes disposal; or
      - II. Used to produce products that are applied to or placed on the land or are otherwise contained in products that are applied to or placed on the land (in which cases the product itself remains a solid waste).
    - (II) However, commercial chemical products listed in subparagraph (4)(d) of this rule are not solid wastes if they are applied to the land and that is their ordinary manner of use.
  - (ii) "Burning for energy recovery"
    - (I) Materials noted with a "\*" in column 2 of Table 1 are solid wastes when they are:
      - I. Burned to recover energy;
      - II. Used to produce a fuel or are otherwise contained in fuels (in which cases the fuel itself remains a solid waste).
    - (II) However, commercial chemical products listed in subparagraph (4)(d) of this rule are not solid wastes if they are themselves fuels.
  - (iii) "Reclaimed"
 

Materials noted with a "---" in column 3 of Table 1 are not solid wastes when reclaimed. Materials noted with a "\*" in column 3 of Table 1 are solid wastes when reclaimed unless they meet the requirements of subparts (d)1(xvii), (xxiii), (xxiv) or (xxvii) of this paragraph.
  - (iv) "Accumulated speculatively"
 

Materials noted with a "\*" in column 4 of Table 1 are solid wastes when accumulated speculatively.

Table 1

	Use constituting disposal (subpart (1)(b)3(i) of this rule)	Energy recovery/fuel (subpart (1)(b)3(ii) of this rule)	Reclamation (subpart (1)(b)3(iii) of this rule) except as provided in	Speculative accumulation (subpart (1)(b)3 (iv) of this rule)

			subpart (1)(d)1(xvii), (xxiii), (xxiv) or (xxvii) of this rule	
	(1)	(2)	(3)	(4)
Spent Materials	(*)	(*)	(*)	(*)
Sludges [listed in Rule 0400-12-01-.02(4)(b) or (c)]	(*)	(*)	(*)	(*)
Sludges exhibiting a characteristic of hazardous waste	(*)	(*)	-	(*)
By-products [listed in Rule 0400-12-01-.02(4)(b) or (c)]	(*)	(*)	(*)	(*)
By-products exhibiting a characteristic of hazardous waste	(*)	(*)	-	(*)
Commercial chemical products listed in Rule 0400-12-01-.02(4)(d)	(*)	(*)	-	-
Scrap metal that is not excluded under Rule 0400-12-01-.02(1)(d)1(xiii)	(*)	(*)	(*)	(*)

(Note: The terms "spent materials", "sludges", "by-products", "scrap metal" and "processed scrap metal" are defined in part (1)(a)3 of this rule.)

(Note: Unused commercial chemical products and unused manufactured articles, which are not listed in subparagraph (4)(d) of this rule, that exhibit a characteristic of hazardous waste in accordance with paragraph (3) of this rule shall have the same status as commercial chemical products listed in subparagraph (4)(d) of this rule when reclaimed. These non-listed commercial chemical products or manufactured articles are not solid waste when legitimately recycled except when they are recycled in ways that differ from their normal manner of use.)

#### 4. "Inherently waste-like materials"

The following materials are solid wastes when they are recycled in any manner:

- (i) Hazardous Waste Codes F020, F021 (unless used as an ingredient to make a product at the site of generation), F022, F023, F026, and F028.
- (ii) Secondary materials fed to a halogen acid furnace that exhibit a characteristic of a hazardous waste or are listed as a hazardous waste as defined in paragraph (3) or (4) of this rule, except for brominated material that meets the following criteria:
  - (I) The material must contain a bromine concentration of at least 45%; and
  - (II) The material must contain less than a total of 1% of toxic organic compounds listed in paragraph (30) Appendix VIII of this rule; and
  - (III) The material is processed continually on-site in the halogen acid furnace via direct conveyance (hard piping).
- (iii) The Board will use the following criteria to add wastes to that list:
  - (I) I. The materials are ordinarily disposed of, burned, or incinerated; or

- II. The materials contain toxic constituents listed in paragraph (30) Appendix VIII of this rule and these constituents are not ordinarily found in raw materials or products for which the materials substitute (or are found in raw materials or products in smaller concentrations) and are not used or reused during the recycling process; and
      - (II) The material may pose a substantial hazard to human health and the environment when recycled.
5. "Materials that are not solid waste when recycled"
- (i) Materials are not solid wastes when they can be shown to be recycled by being:
    - (I) Used or reused as ingredients in an industrial process to make a product, provided the materials are not being reclaimed; or
    - (II) Used or reused as effective substitutes for commercial products; or
    - (III) Returned to the original process from which they are generated, without first being reclaimed or land disposed. The material must be returned as a substitute for feedstock materials. In cases where the original process to which the material is returned is a secondary process, the materials must be managed such that there is no placement on the land. In cases where the materials are generated and reclaimed within the primary mineral processing industry, the conditions of the exclusion found at subpart (d)1(xvii) of this paragraph apply rather than this item.
  - (ii) The following materials are solid wastes, even if the recycling involves use, reuse, or return to the original process (described in items (i)(I) through (III) of this part):
    - (I) Materials used in a manner constituting disposal, or used to produce products that are applied to the land; or
    - (II) Materials burned for energy recovery, used to produce a fuel, or contained in fuels; or
    - (III) Materials accumulated speculatively; or
    - (IV) Materials listed in subparts 4(i) and 4(ii) of this subparagraph.
6. "Documentation of claims that materials are not solid wastes or are conditionally exempt from regulation".

Respondents in actions to enforce regulations implementing the Act and Chapter 0400-12-01 who raise a claim that a certain material is not a solid waste, or is conditionally exempt from regulation, must demonstrate that there is a known market or disposition for the material, and that they meet the terms of the exclusion or exemption. In doing so, they must provide appropriate documentation (such as contracts showing that a second person uses the material as an ingredient in a production process) to demonstrate that the material is not a waste, or is exempt from regulation. In addition, owners or operators of facilities claiming that they actually are recycling materials must show that they have the necessary equipment to do so.

7. Sham recycling.

A hazardous secondary material found to be sham recycled is considered discarded and a solid waste. Sham recycling is recycling that is not legitimate recycling as defined in

subparagraph (5)(d) of Rule 0400-12-01-.01.

(c) Definition of Hazardous Waste [40 CFR 261.3]

1. A solid waste, as defined in subparagraph (b) of this paragraph, is a hazardous waste if:
  - (i) It is not excluded from regulation as a hazardous waste under part (d)2 of this paragraph; and
  - (ii) It meets any of the following criteria:
    - (I) It exhibits any of the characteristics of hazardous waste identified in paragraph (3) of this rule. However, any mixture of a waste from the extraction, beneficiation, and processing of ores and minerals excluded under subpart (d)2(vii) of this paragraph and any other solid waste exhibiting a characteristic of hazardous waste under paragraph (3) of this rule is a hazardous waste only if it exhibits a characteristic that would not have been exhibited by the excluded waste alone if such mixture had not occurred or if it continues to exhibit any of the characteristics exhibited by the non-excluded wastes prior to mixture. Further, for the purposes of applying the Toxicity Characteristic to such mixtures, the mixture is also a hazardous waste if it exceeds the maximum concentration for any contaminant listed in Table 1 to subparagraph (3)(e) of this rule that would not have been exceeded by the excluded waste alone if the mixture had not occurred or if it continues to exceed the maximum concentration for any contaminant exceeded by the nonexempt waste prior to mixture.
    - (II) It is listed in paragraph (4) of this rule and has not been excluded from the lists in paragraph (4) of this rule under Rule 0400-12-01-.01(3)(a) and (c).
    - (III) (RESERVED) [261.3(a)(2)(iii)]
    - (IV) It is a mixture of solid waste and one or more hazardous wastes listed in paragraph (4) of this rule and has not been excluded from this subpart under Rule 0400-12-01-.01(3)(a) and (c), part 7 or 8 of this subparagraph; however, the following mixtures of solid wastes and hazardous wastes listed in paragraph (4) of this rule are not hazardous wastes (except by application of items (I) or (II) of this subpart) if the generator can demonstrate that the mixture consists of wastewater the discharge of which is subject to regulation under T.C.A. §§ 69-3-101 et seq. (including wastewater at facilities which have eliminated the discharge of wastewater) and:
      - I. One or more of the following spent solvents listed in subparagraph (4)(b) of this rule--benzene, carbon tetrachloride, tetrachloroethylene, trichloroethylene or the scrubber waters derived-from the combustion of these spent solvents - -provided that (1) the maximum total weekly usage of these solvents (other than the amounts that can be demonstrated not to be discharged to wastewater) divided by the average weekly flow of wastewater into the headworks of the facility's wastewater treatment or pretreatment system does not exceed 1 part per million or (2) the total measured concentration of these solvents entering the headworks of the facility's wastewater treatment system (at facilities subject to regulation under the Clean Air Act, as amended, at 40 CFR parts 60, 61, or 63, or the Tennessee Air Quality Act and Rule Division 1200-03 or at facilities subject to an enforceable limit in a federal or state operating permit that

minimizes fugitive emissions), does not exceed 1 part per million on an average weekly basis. Any facility that uses benzene as a solvent and claims this exemption must use an aerated biological wastewater treatment system and must use only lined surface impoundments or tanks prior to secondary clarification in the wastewater treatment system. Facilities that choose to measure concentration levels must file a copy of their sampling and analysis plan with the Division Director, as defined in Rule 0400-12-01-.01(2)(a). A facility must file a copy of a revised sampling and analysis plan only if the initial plan is rendered inaccurate by changes in the facility's operations. The sampling and analysis plan must include the monitoring point location (headworks), the sampling frequency and methodology, and a list of constituents to be monitored. A facility is eligible for the direct monitoring option once they receive confirmation that the sampling and analysis plan has been received by the Director. The Director may reject the sampling and analysis plan if he/she finds that, the sampling and analysis plan fails to include the above information; or the plan parameters would not enable the facility to calculate the weekly average concentration of these chemicals accurately. If the Director rejects the sampling and analysis plan or if the Director finds that the facility is not following the sampling and analysis plan, the Director shall notify the facility to cease the use of the direct monitoring option until such time as the bases for rejection are corrected; or

- II. One or more of the following spent solvents listed in subparagraph (4)(b) of this rule --methylene chloride, 1,1,1-trichloroethane, chlorobenzene, o-dichlorobenzene, cresols, cresylic acid, nitrobenzene, toluene, methyl ethyl ketone, carbon disulfide, isobutanol, pyridine, spent chlorofluorocarbon solvents, 2-ethoxyethanol, or the scrubber waters derived-from the combustion of these spent solvents- - provided that (1) the maximum total weekly usage of these solvents (other than the amounts that can be demonstrated not to be discharged to wastewater) divided by the average weekly flow of wastewater into the headworks of the facility's wastewater treatment or pretreatment system does not exceed 25 parts per million or (2) the total measured concentration of these solvents entering the headworks of the facility's wastewater treatment system (at facilities subject to regulation under the Clean Air Act, as amended, at 40 CFR parts 60, 61, or 63, or the Tennessee Air Quality Act and Rule Division 1200-03 or at facilities subject to an enforceable limit in a federal or state operating permit that minimizes fugitive emissions) does not exceed 25 parts per million on an average weekly basis. Facilities that choose to measure concentration levels must file a copy of their sampling and analysis plan with the Division Director, as defined in Rule 0400-12-01-.01(2)(a). A facility must file a copy of a revised sampling and analysis plan only if the initial plan is rendered inaccurate by changes in the facility's operations. The sampling and analysis plan must include the monitoring point location (headworks), the sampling frequency and methodology, and a list of constituents to be monitored. A facility is eligible for the direct monitoring option once they receive confirmation that the sampling and analysis plan has been received by the Director. The Director may reject the sampling and analysis plan if he/she finds that, the sampling and analysis plan fails to include the above information; or the plan parameters would not enable the facility to calculate the weekly average concentration of these

chemicals accurately. If the Director rejects the sampling and analysis plan or if the Director finds that the facility is not following the sampling and analysis plan, the Director shall notify the facility to cease the use of the direct monitoring option until such time as the bases for rejection are corrected; or

- III. One of the following wastes listed in subparagraph (4)(c) of this rule, provided that the wastes are discharged to the refinery oil recovery sewer before primary oil/water/solids separation - heat exchanger bundle cleaning sludge from the petroleum refining industry (Hazardous Waste Code K050), crude oil storage tanks sediment from petroleum refining operations (Hazardous Waste Code K169), clarified slurry oil tank sediment and/or in-line filter/separation solids from petroleum refining operations (Hazardous Waste Code K170), spent hydrotreating catalyst (Hazardous Waste Code K171), and spent hydrorefining catalyst (Hazardous Waste Code K172); or
- IV. A discarded hazardous waste, commercial chemical product, or chemical intermediate listed in subparagraphs (4)(b) through (4)(d) of this rule, arising from de minimis losses of these materials. For purposes of this subitem, de minimis losses are inadvertent releases to a wastewater treatment system, including those from normal material handling operations (e. g., spills from the unloading or transfer of materials from bins or other containers, leaks from pipes, valves or other devices used to transfer materials); minor leaks of process equipment, storage tanks or containers; leaks from well maintained pump packings and seals; sample purgings; relief device discharges; discharges from safety showers and rinsing and cleaning of personal safety equipment; and rinsate from empty containers or from containers that are rendered empty by that rinsing. Any manufacturing facility that claims an exemption for de minimis quantities of wastes listed in subparagraphs (4)(b) through (4)(c) of this rule or any nonmanufacturing facility that claims an exemption for de minimis quantities of wastes listed in paragraph (4) of this rule must either have eliminated the discharge of wastewaters or have included in its Clean Water Act or Tennessee Water Quality Control Act permit application or submission to its pretreatment control authority the constituents for which each waste was listed in Appendix VII of paragraph (30) of this rule; and the constituents in the table "Treatment Standards for Hazardous Wastes" in Rule 0400-12-01-.10(3)(a) for which each waste has a treatment standard (i.e., Land Disposal Restriction constituents). A facility is eligible to claim the exemption once the permit writer or control authority has been notified of possible de minimis releases via the Clean Water Act or Tennessee Water Quality Control Act permit application or the pretreatment control authority submission. A copy of the Clean Water Act or Tennessee Water Quality Control Act permit application or the submission to the pretreatment control authority must be placed in the facility's on-site files; or
- V. Wastewater resulting from laboratory operations containing toxic (T) wastes listed in paragraph (4) of this rule, provided that the annualized average flow of laboratory wastewater does not exceed one percent of total wastewater flow into the headworks of the facility's wastewater treatment or pre-treatment system, or provided the wastes, combined annualized average concentration does not exceed one part per million in the

headworks of the facility's wastewater treatment or pre-treatment facility. Toxic (T) wastes used in laboratories that are demonstrated not to be discharged to wastewater are not to be included in this calculation; or

- VI. One or more of the following wastes listed in subparagraph (4)(c) of this rule -- wastewaters from the production of carbamates and carbamoyl oximes (Hazardous Waste Code No. K157)- - provided that (1) the maximum weekly usage of formaldehyde, methyl chloride, methylene chloride, and triethylamine (including all amounts that cannot be demonstrated to be reacted in the process, destroyed through treatment, or is recovered, i.e., what is discharged or volatilized) divided by the average weekly flow of process wastewater prior to any dilution into the headworks of the facility's wastewater treatment system does not exceed a total of 5 parts per million by weight or (2) the total measured concentration of these chemicals entering the headworks of the facility's wastewater treatment system (at facilities subject to regulation under the Clean Air Act, as amended, at 40 CFR parts 60, 61, or 63, or the Tennessee Air Quality Act and Rule Division 1200-03 or at facilities subject to an enforceable limit in a federal or state operating permit that minimizes fugitive emissions) does not exceed 5 parts per million on an average weekly basis. Facilities that choose to measure concentration levels must file a copy of their sampling and analysis plan with the Division Director, as defined in Rule 0400-12-01-.01(2)(a). A facility must file a copy of a revised sampling and analysis plan only if the initial plan is rendered inaccurate by changes in the facility's operations. The sampling and analysis plan must include the monitoring point location (headworks), the sampling frequency and methodology, and a list of constituents to be monitored. A facility is eligible for the direct monitoring option once they receive confirmation that the sampling and analysis plan has been received by the Director. The Director may reject the sampling and analysis plan if he/she finds that, the sampling and analysis plan fails to include the above information; or the plan parameters would not enable the facility to calculate the weekly average concentration of these chemicals accurately. If the Director rejects the sampling and analysis plan or if the Director finds that the facility is not following the sampling and analysis plan, the Director shall notify the facility to cease the use of the direct monitoring option until such time as the bases for rejection are corrected; or
- VII. Wastewaters derived-from the treatment of one or more of the following wastes listed in subparagraph (4)(c) of this rule -- organic waste (including heavy ends, still bottoms, light ends, spent solvents, filtrates, and decantates) from the production of carbamates and carbamoyl oximes (Hazardous Waste Code No. K156)—provided that (1) the maximum concentration of formaldehyde, methyl chloride, methylene chloride, and triethylamine prior to any dilutions into the headworks of the facility's wastewater treatment system does not exceed a total of 5 milligrams per liter or (2) the total measured concentration of these chemicals entering the headworks of the facility's wastewater treatment system (at facilities subject to regulation under the Clean Air Act, as amended, at 40 CFR parts 60, 61, or 63, or the Tennessee Air Quality Act and Rule Division 1200-03 or at facilities subject to an enforceable limit in a federal or state operating permit that minimizes fugitive emissions) does not



exceed 5 milligrams per liter on an average weekly basis. Facilities that choose to measure concentration levels must file a copy of their sampling and analysis plan with the Division Director, as defined in Rule 0400-12-01-.01(2)(a). A facility must file a copy of a revised sampling and analysis plan only if the initial plan is rendered inaccurate by changes in the facility's operations. The sampling and analysis plan must include the monitoring point location (headworks), the sampling frequency and methodology, and a list of constituents to be monitored. A facility is eligible for the direct monitoring option once they receive confirmation that the sampling and analysis plan has been received by the Director. The Director may reject the sampling and analysis plan if he/she finds that, the sampling and analysis plan fails to include the above information; or the plan parameters would not enable the facility to calculate the weekly average concentration of these chemicals accurately. If the Director rejects the sampling and analysis plan or if the Director finds that the facility is not following the sampling and analysis plan, the Director shall notify the facility to cease the use of the direct monitoring option until such time as the bases for rejection are corrected.

(V) Rebuttable presumption for used oil

Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste because it has been mixed with halogenated hazardous waste listed in paragraph (4) of this rule. Persons may rebut this presumption by demonstrating that the used oil does not contain hazardous waste (for example, to show that the used oil does not contain significant concentrations of halogenated hazardous constituents listed in appendix VIII of paragraph (30) of this rule).

- I. The rebuttable presumption does not apply to metalworking oils/fluids containing chlorinated paraffins, if they are processed, through a tolling agreement, to reclaim metalworking oils/fluids. The presumption does apply to metalworking oils/fluids if such oils/fluids are recycled in any other manner, or disposed.
- II. The rebuttable presumption does not apply to used oils contaminated with chlorofluorocarbons (CFCs) removed from refrigeration units where the CFCs are destined for reclamation. The rebuttable presumption does apply to used oils contaminated with CFCs that have been mixed with used oil from sources other than refrigeration units.

2. A solid waste which is not excluded from regulation under part (d)2 of this paragraph becomes a hazardous waste when any of the following events occur:

- (i) In the case of a waste listed in paragraph (4) of this rule, when the waste first meets the listing description set forth in paragraph (4) of this rule.
- (ii) In the case of a mixture of solid waste and one or more listed hazardous wastes, when a hazardous waste listed in paragraph (4) of this rule is first added to the solid waste.
- (iii) In the case of any other waste (including a waste mixture), when the waste exhibits any of the characteristics identified in paragraph (3) of this rule.

3. Unless and until it meets the criteria of part 4 below:

- (i) A hazardous waste will remain a hazardous waste.
- (ii) (I) Except as otherwise provided in item (II) of this subpart, part 7 or part 8 of this subparagraph, any solid waste generated from the treatment, storage, or disposal of a hazardous waste, including any sludge, spill residue, ash, emission control dust, or leachate (but not including precipitation run-off) is a hazardous waste. (However, materials that are reclaimed from solid wastes and that are used beneficially are not solid wastes and hence are not hazardous wastes under this provision unless the reclaimed material is burned for energy recovery or used in a manner constituting disposal.)
- (II) The following solid wastes are not hazardous even though they are generated from the treatment, storage, or disposal of a hazardous waste, unless they exhibit one or more of the characteristics of hazardous waste:
  - I. Waste pickle liquor sludge generated by lime stabilization of spent pickle liquor from the iron and steel industry (SIC Codes 331 and 332).
  - II. Waste from burning any of the materials exempted from regulation by items (f)1(iii)(III) and (IV) of this paragraph.
  - III. A. Nonwastewater residues, such as slag, resulting from high temperature metals recovery (HTMR) processing of K061, K062 or F006 waste, in units identified as rotary kilns, flame reactors, electric furnaces, plasma arc furnaces, slag reactors, rotary hearth furnace/electric furnace combinations or industrial furnaces (as defined in items (vi), (vii) and (xiii) of the definition for "Industrial furnace" in Rule 0400-12-01-.01(2)(a) that are disposed in a Class I or Class II Disposal Facility subject to a permit issued in accordance with Chapter 0400-11-01, provided that these residues meet the generic exclusion levels identified in the tables in this paragraph for all constituents, and exhibit no characteristics of hazardous waste. Testing requirements must be incorporated in a facility's waste analysis plan or a generator's self-implementing waste analysis plan; at a minimum, composite samples of residues must be collected and analyzed quarterly and/or when the process or operation generating the waste changes. Persons claiming this exclusion in an enforcement action will have the burden of proving by clear and convincing evidence that the material meets all of the exclusion requirements.

Constituent	Maximum for any single composite sample-TCLP (mg/l)
Generic exclusion levels for K061 and K062 nonwastewater HTMR residues	
Antimony	0.10
Arsenic	0.50
Barium	7.6
Beryllium	0.010
Cadmium	0.050

Chromium (total)	0.33
Lead	0.15
Mercury	0.009
Nickel	1.0
Selenium	0.16
Silver	0.30
Thallium	0.020
Zinc	70

---

Generic exclusion levels for F006 nonwastewater HTMR residues

---

Antimony	0.10
Arsenic	0.50
Barium	7.6
Beryllium	0.010
Cadmium	0.050
Chromium (total)	0.33
Cyanide (total) (mg/kg)	1.8
Lead	0.15
Mercury	0.009
Nickel	1.0
Selenium	0.16
Silver	0.30
Thallium	0.020
Zinc	70

---

- B. A one-time notification and certification must be placed in the facility's files and sent to the Division Director for K061, K062 or F006 HTMR residues that meet the generic exclusion levels for all constituents and do not exhibit any characteristics that are sent to a Class I or Class II Disposal Facility subject to a permit issued in accordance with Chapter 0400-11-01. The notification and certification that is placed in the generators or treaters files must be updated if the process or operation generating the waste changes and/or if the Class I or Class II Disposal Facility receiving the waste changes. However, the generator or treater need only notify the Division Director on an annual basis if such changes occur. Such notification and certification should be sent to the Division Director by the end of the calendar year, but no later than December 31. The notification must include the following information: The name and address of the Class I or Class II Disposal Facility receiving the waste shipments; the Hazardous Waste Code(s) and treatability group(s) at the initial point of generation; and,

the treatment standards applicable to the waste at the initial point of generation. The certification must be signed by an authorized representative and must state as follows: "I certify under penalty of law that the generic exclusion levels for all constituents have been met without impermissible dilution and that no characteristic of hazardous waste is exhibited. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine and imprisonment. As specified in Tennessee Code Annotated Section 39-16-702(a)(4), this declaration is made under penalty of perjury."

- IV. Biological treatment sludge from the treatment of one of the following wastes listed in subparagraph (4)(c) - organic waste (including heavy ends, still bottoms, light ends, spent solvents, filtrates, and decantates) from the production of carbamates and carbamoyl oximes (Hazardous Waste Code K156), and wastewaters from the production of carbamates and carbamoyl oximes (Hazardous Waste Code K157).
  - V. Catalyst inert support media separated from one of the following wastes listed in subparagraph (4)(c) of this rule -- Spent hydrotreating catalyst (Hazardous Waste Code K171) and Spent hydrorefining catalyst (Hazardous Waste Code K172).
4. Any solid waste described in part 3 of this subparagraph is not a hazardous waste if it meets the following criteria:
- (i) In the case of any solid waste, it does not exhibit any of the characteristics of hazardous waste identified in paragraph (3) of this rule. (However, wastes that exhibit a characteristic at the point of generation may still be subject to the requirements of Rule 0400-12-01-.10, even if they no longer exhibit a characteristic at the point of land disposal.)
  - (ii) In the case of a waste which is a listed waste under paragraph (4) of this rule, contains a waste listed under paragraph (4) of this rule or is derived from a waste listed in paragraph (4) of this rule, it also has been excluded from part 3 of this subparagraph under Rule 0400-12-01-.01(3)(a) and (c).
5. (RESERVED) [40 CFR 261.3(e)]
6. Notwithstanding parts 1 through 4 of this subparagraph and provided the debris as defined in Rule 0400-12-01-.10 does not exhibit a characteristic identified at paragraph (3) of this rule, the following materials are not subject to regulation under Rules 0400-12-01-.01 through .07, .09 and .10:
- (i) Hazardous debris as defined in Rule 0400-12-01-.10 that has been treated using one of the required extraction or destruction technologies specified in Table 1 of Rule 0400-12-01-.10(3)(f); persons claiming this exclusion in an enforcement action will have the burden of proving by clear and convincing evidence that the material meets all of the exclusion requirements; or
  - (ii) Debris as defined in Rule 0400-12-01-.10 that the Commissioner, considering the extent of contamination, has determined is no longer contaminated with hazardous waste.
7. (i) A hazardous waste that is listed in paragraph (4) of this rule solely because it exhibits one or more characteristics of ignitability as defined under subparagraph (3)(b) of this rule, corrosivity as defined under subparagraph (3)(c) of this rule, or

reactivity as defined under subparagraph (3)(d) of this rule is not a hazardous waste, if the waste no longer exhibits any characteristic of hazardous waste identified in paragraph (3) of this rule.

- (ii) The exclusion described in subpart (i) of this part also pertains to:
  - (I) Any mixture of a solid waste and a hazardous waste listed in paragraph (4) of this rule solely because it exhibits the characteristics of ignitability, corrosivity, or reactivity as regulated under item 1(ii)(IV) of this subparagraph; and
  - (II) Any solid waste generated from treating, storing, or disposing of a hazardous waste listed in paragraph (4) of this rule solely because it exhibits the characteristics of ignitability, corrosivity, or reactivity as regulated under item 3(ii)(I) of this subparagraph.
- (iii) Wastes excluded under this part are subject to Rule 0400-12-01-.10 (as applicable), even if they no longer exhibit a characteristic at the point of land disposal.
- (iv) Any mixture of a solid waste excluded from regulation under subpart (d)2(vii) of this paragraph and a hazardous waste listed in paragraph (4) of this rule solely because it exhibits one or more of the characteristics of ignitability, corrosivity, or reactivity as regulated under item 1(ii)(IV) of this subparagraph is not a hazardous waste, if the mixture no longer exhibits any characteristic of hazardous waste identified in paragraph (3) of this rule for which the hazardous waste listed in paragraph (4) of this rule was listed.

- 8. (i) Hazardous waste containing radioactive waste is no longer a hazardous waste when it meets the eligibility criteria and conditions of paragraph (14) of Rule 0400-12-01-.09 (“eligible radioactive mixed waste”).
- (ii) The exemption described in subpart (i) of this part also pertains to:
  - (I) Any mixture of a solid waste and an eligible radioactive waste; and
  - (II) Any solid waste generated from treating, storing, or disposing of an eligible radioactive mixed waste.
- (iii) Waste exempted under this part must meet the eligibility criteria and specified conditions in part (14)(b)6 of Rule 0400-12-01-.09 and part (14)(b)11 of Rule 0400-12-01-.09 (for storage and treatment) and in part (14)(m)1 of Rule 0400-12-01-.09 and part (14)(n)1 of Rule 0400-12-01-.09 (for transportation and disposal). Waste that fails to satisfy these eligibility criteria and conditions is regulated as hazardous waste.

(d) Exclusions [40 CFR 261.4] & [40 CFR 262.70]

- 1. Materials which are not solid wastes. The following materials are not solid wastes for the purpose of this rule:
  - (i) (I) Domestic sewage; and
  - (II) Any mixture of domestic sewage and other wastes that passes through a sewer system to a publicly-owned treatment works (POTW) for treatment. "Domestic sewage" means untreated sanitary wastes that pass through a sewer system.

(Comment: This exclusion does not exclude waste/wastewaters while they are being generated, collected, stored, or treated before entering

the sewer system. This exclusion applies when the material enters the sewer system where it will mix with sanitary wastes at any point before reaching the POTW whereupon this material is regulated under water pollution statutes and regulations. This material is subject to all applicable reporting, monitoring, and permitting requirements of the T.C.A. §§ 68-221-101, 69-3-101, et seq. and the associated regulations. Management of this material must be in compliance with all applicable authorization (permits, etc.) associated with disposal into a POTW for subsequent treatment.)

- (ii) Industrial wastewater discharges that are point source discharges subject to regulation under section 402 of the Clean Water Act, as amended or under the Water Quality Control Act.

(Comment: This exclusion applies only to the actual point source discharge. It does not exclude industrial wastewaters while they are being collected, stored or treated before discharge, nor does it exclude sludges that are generated by industrial wastewater treatment.)

- (iii) Irrigation return flows.
- (iv) Source, special nuclear or by-product material as defined by the Atomic Energy Act of 1954, as amended, 42 U.S.C. 2011 et seq.
- (v) Materials subjected to in-situ mining techniques which are not removed from the ground as part of the extraction process.
- (vi) Pulping liquors (i.e., black liquor) that are reclaimed in a pulping liquor recovery furnace and then reused in the pulping process, unless it is accumulated speculatively as defined in subpart (a)3(viii) of this paragraph.
- (vii) Spent sulfuric acid used to produce virgin sulfuric acid, unless it is accumulated speculatively as defined in subpart (a)3(viii) of this paragraph.
- (viii) Secondary materials that are reclaimed and returned to the original process or processes in which they were generated where they are reused in the production process provided:

- (I) Only tank storage is involved, and the entire process through completion of reclamation is closed by being entirely connected with pipes or other comparable enclosed means of conveyance;
- (II) Reclamation does not involve controlled flame combustion (such as occurs in boilers, industrial furnaces, or incinerators);
- (III) The secondary materials are never accumulated in such tanks for over twelve months without being reclaimed; and
- (IV) The reclaimed material is not used to produce a fuel, or used to produce products that are used in a manner constituting disposal.

(Note: As used in this subpart, "production process" includes those activities that tie directly into the manufacturing operation or those activities that are the primary operation at an establishment.)

- (ix) (I) Spent wood preserving solutions that have been reclaimed and are reused for their original intended purpose;
- (II) Wastewaters from the wood preserving process that have been reclaimed and are reused to treat wood; and

- (III) Prior to reuse, the wood preserving wastewaters and spent wood preserving solutions described in item (I) and (II) of this subpart, so long as they meet all of the following conditions:
  - I. The wood preserving wastewaters and spent wood preserving solutions are reused on-site at water borne plants in the production process for their original intended purpose;
  - II. Prior to reuse, the wastewaters and spent wood preserving solutions are managed to prevent release to either land or groundwater or both;
  - III. Any unit used to manage wastewaters and/or spent wood preserving solutions prior to reuse can be visually or otherwise determined to prevent such releases;
  - IV. Any drip pad used to manage the wastewaters and/or spent wood preserving solutions prior to reuse complies with the standards in Rule 0400-12-01-.05(23), regardless of whether the plant generates a total of less than 100 kg/month of hazardous waste; and
  - V. Prior to operating pursuant to this exclusion, the plant owner or operator prepares a one-time notification stating that the plant intends to claim the exclusion, giving the date on which the plant intends to begin operating under the exclusion, and containing the following language: "I have read the applicable regulation establishing an exclusion for wood preserving wastewaters and spent wood preserving solutions and understand it requires me to comply at all times with the conditions set out in the regulation." The plant must maintain a copy of that document in its on-site records until closure of the facility. The exclusion applies only so long as the plant meets all of the conditions. If the plant goes out of compliance with any condition, it may apply to the Commissioner for reinstatement. The Commissioner may reinstate the exclusion upon finding that the plant has returned to compliance with all conditions and that violations are not likely to recur.
- (x) Hazardous Waste Codes K060, K087, K141, K142, K143, K144, K145, K147, and K148, and any wastes from the coke by-products processes that are hazardous only because they exhibit the Toxicity Characteristic (TC) specified in subparagraph (3)(e) of this rule when, subsequent to generation, these materials are recycled to coke ovens, to the tar recovery process as a feedstock to produce coal tar, or mixed with coal tar prior to the tar's sale or refining. This exclusion is conditioned on there being no land disposal of the wastes from the point they are generated to the point they are recycled to coke ovens or tar recovery or refining processes, or mixed with coal tar.
- (xi) Nonwastewater splash condenser dross residue from the treatment of K061 in high temperature metals recovery units, provided it is shipped in drums (if shipped) and not land disposed before recovery.
- (xii) (I) Oil-bearing hazardous secondary materials (i.e., sludges, byproducts, or spent materials) that are generated at a petroleum refinery (SIC code 2911) and are inserted into the petroleum refining process (SIC code 2911 - including, but not limited to distillation, catalytic cracking, fractionation, or thermal cracking units (i.e., cokers)) unless the material is placed on the land, or speculatively accumulated before being so

recycled. Materials inserted into thermal cracking units are excluded under this item provided that the coke product also does not exhibit a characteristic of hazardous waste. Oil-bearing hazardous secondary materials may be inserted into the same petroleum refinery where they are generated, or sent directly to another petroleum refinery, and still be excluded under this provision. Except as provided in item (II) of this subpart, oil-bearing hazardous secondary materials generated elsewhere in the petroleum industry (i.e., from sources other than petroleum refineries) are not excluded under this subpart. Residuals generated from processing or recycling materials excluded under this item, where such materials as generated would have otherwise met a listing under paragraph (4) of this rule, are designated as F037 listed wastes when disposed of or intended for disposal.

- (II) Recovered oil that is recycled in the same manner and with the same conditions as described in item (I) of this subpart. Recovered oil is oil that has been reclaimed from secondary materials (including wastewater generated from normal petroleum industry practices, including refining, exploration and production, bulk storage, and transportation incident thereto (SIC codes 1311, 1321, 1381, 1382, 1389, 2911, 4612, 4613, 4922, 4923, 4789, 5171, and 5172)). Recovered oil does not include oil-bearing hazardous wastes listed in paragraph (4) of this rule; however, oil recovered from such wastes may be considered recovered oil. Recovered oil does not include used oil as defined in subparagraph (1)(a) of Rule 0400-12-01-.11.
- (xiii) Excluded scrap metal (processed scrap metal, unprocessed home scrap metal, and unprocessed prompt scrap metal) being recycled.
- (xiv) Shredded circuit boards being recycled provided that they are:
  - (I) Stored in containers sufficient to prevent a release to the environment prior to recovery; and
  - (II) Free of mercury switches, mercury relays and nickel-cadmium batteries and lithium batteries.
- (xv) Condensates derived from the overhead gases from kraft mill steam strippers that are used to comply with 40 CFR 63.446(e). The exemption applies only to combustion at the mill generating the condensates.
- (xvi) Reserved.
- (xvii) Spent materials (as defined in subparagraph (a) of this paragraph) (other than hazardous wastes listed in paragraph (4) of this rule) generated within the primary mineral processing industry from which minerals, acids, cyanide, water or other values are recovered by mineral processing or by beneficiation, provided that:
  - (I) The spent material is legitimately recycled to recover minerals, acids, cyanide, water or other values.
  - (II) The spent material is not accumulated speculatively.
  - (III) Except as provided in item (IV) of this subpart, the spent material is stored in tanks, containers, or buildings meeting the following minimum integrity standards: a building must be an engineered structure with a floor, walls, and a roof all of which are made of non-earthen materials providing structural support (except smelter buildings may have partially earthen floors provided the secondary material is stored on the non-



earthen portion), and have a roof suitable for diverting rainwater away from the foundation; a tank must be free standing, not be a surface impoundment (as defined in subparagraph (2)(a) of Rule 0400-12-01-.01), and be manufactured of a material suitable for containment of its contents; a container must be free standing and be manufactured of a material suitable for containment of its contents. If tanks or containers contain any particulate which may be subject to wind dispersal, the owner/operator must operate these units in a manner which controls fugitive dust. Tanks, containers, and buildings must be designed, constructed and operated to prevent significant releases to the environment of these materials.

- (IV) The Commissioner may make a site-specific determination, after public review and comment, that only solid mineral processing spent materials may be placed on pads, rather than in tanks, containers, or buildings. Solid mineral processing spent materials do not contain any free liquid. The decision-maker must affirm that pads are designed, constructed and operated to prevent significant releases of the spent material into the environment. Pads must provide the same degree of containment afforded by the tanks, containers and buildings eligible for exclusion as provided in item (III) of this subpart.
- I. The decision-maker must also consider if storage on pads poses the potential for significant releases via groundwater, surface water, and air exposure pathways. Factors to be considered for assessing the groundwater, surface water, air exposure pathways are: the volume and physical and chemical properties of the spent material, including its potential for migration off the pad; the potential for human or environmental exposure to hazardous constituents migrating from the pad via each exposure pathway, and the possibility and extent of harm to human and environmental receptors via each exposure pathway.
  - II. Pads must meet the following minimum standards: be designed of non-earthen material that is compatible with the chemical nature of the mineral processing spent material, capable of withstanding physical stresses associated with placement and removal, have run-on/runoff controls, be operated in a manner which controls fugitive dust, and have integrity assurance through inspections and maintenance programs.
  - III. Before making a determination under this subpart, the Commissioner must provide public notice and the opportunity for comment to all persons potentially interested in the determination. This shall be accomplished by the owner or operator placing a notice as prepared and required by the Commissioner, of this action in local newspapers, or broadcasting notice over local radio stations. The owner or operator shall provide proof of the completion of all notice requirements to the Commissioner within ten days following conclusion of the public notice procedures.
- (V) The owner or operator provides notice to the Commissioner, providing the following information: the types of materials to be recycled; the type and location of the storage units and recycling processes; and the annual quantities expected to be placed in land-based units. This notification must be updated when there is a change in the type of materials recycled or the location of the recycling process.
- (VI) For purposes of subpart 2(vii) of this subparagraph, mineral processing

spent materials must be the result of mineral processing and may not include any listed hazardous wastes. Listed hazardous wastes and characteristic hazardous wastes generated by non-mineral processing industries are not eligible for the conditional exclusion from the definition of solid waste.

- (xviii) Petrochemical recovered oil from an associated organic chemical manufacturing facility, where the oil is to be inserted into the petroleum refining process (SIC code 2911) along with normal petroleum refinery process streams, provided:
  - (I) The oil is hazardous only because it exhibits the characteristic of ignitability (as defined in subparagraph (3)(b) of this rule) and/or toxicity for benzene (subparagraph (3)(e) of this rule, waste code D018); and
  - (II) The oil generated by the organic chemical manufacturing facility is not placed on the land, or speculatively accumulated before being recycled into the petroleum refining process. An "associated organic chemical manufacturing facility" is a facility where the primary SIC code is 2869, but where operations may also include SIC codes 2821, 2822, and 2865; and is physically co-located with a petroleum refinery; and where the petroleum refinery to which the oil being recycled is returned also provides hydrocarbon feedstocks to the organic chemical manufacturing facility. "Petrochemical recovered oil" is oil that has been reclaimed from secondary materials (i.e., sludges, byproducts, or spent materials, including wastewater) from normal organic chemical manufacturing operations, as well as oil recovered from organic chemical manufacturing processes.
- (xix) Spent caustic solutions from petroleum refining liquid treating processes used as a feedstock to produce cresylic or naphthenic acid unless the material is placed on the land, or accumulated speculatively as defined in subpart (1)(a)3(viii) of this rule.
- (xx) Hazardous secondary materials used to make zinc fertilizers, provided that the conditions specified below are satisfied:
  - (I) Hazardous secondary materials used to make zinc micronutrient fertilizers must not be accumulated speculatively, as defined in subpart (1)(a)3(viii) of this rule.
  - (II) Generators and intermediate handlers of zinc-bearing hazardous secondary materials that are to be incorporated into zinc fertilizers must:
    - I. Submit a one-time notice to the Commissioner which contains the name, address and installation identification number of the generator or intermediate handler facility, provides a brief description of the secondary material that will be subject to the exclusion, and identifies when the manufacturer intends to begin managing excluded, zinc-bearing hazardous secondary materials under the conditions specified in this subpart.
    - II. Store the excluded secondary material in tanks, containers, or buildings that are constructed and maintained in a way that prevents releases of the secondary materials into the environment. At a minimum, any building used for this purpose must be an engineered structure made of non-earthen materials that provide structural support, and must have a floor, walls and a roof that prevent wind dispersal and contact with rainwater. Tanks used for this purpose must be structurally sound and, if outdoors, must have roofs or covers that prevent contact with

wind and rain. Containers used for this purpose must be kept closed except when it is necessary to add or remove material, and must be in sound condition. Containers that are stored outdoors must be managed within storage areas that:

- A. Have containment structures or systems sufficiently impervious to contain leaks, spills and accumulated precipitation; and
  - B. Provide for effective drainage and removal of leaks, spills and accumulated precipitation; and
  - C. Prevent run-on into the containment system.
- III. With each off-site shipment of excluded hazardous secondary materials, provide written notice to the receiving facility that the material is subject to the conditions of this subpart.
- IV. Maintain at the generator's or intermediate handler's facility for no less than three years records of all shipments of excluded hazardous secondary materials. For each shipment these records must at a minimum contain the following information:
- A. Name of the transporter and date of the shipment;
  - B. Name and address of the facility that received the excluded material, and documentation confirming receipt of the shipment; and
  - C. Type and quantity of excluded secondary material in each shipment.
- (III) Manufacturers of zinc fertilizers or zinc fertilizer ingredients made from excluded hazardous secondary materials must:
- I. Store excluded hazardous secondary materials in accordance with the storage requirements for generators and intermediate handlers, as specified in subitem (II) of this subpart.
  - II. Submit a one-time notification to the Commissioner that, at a minimum, specifies the name, address and installation identification number of the manufacturing facility, and identifies when the manufacturer intends to begin managing excluded, zinc-bearing hazardous secondary materials under the conditions specified in this subpart.
  - III. Maintain for a minimum of three (3) years records of all shipments of excluded hazardous secondary materials received by the manufacturer, which must at a minimum identify for each shipment the name and address of the generating facility, name of the transporter and the date the materials were received, the quantity received, and a brief description of the industrial process that generated the material.
  - IV. Submit to the Commissioner an annual report that identifies the total quantities of all excluded hazardous secondary materials that were used to manufacture zinc fertilizers or zinc fertilizer ingredients in the previous year, the name and address of each generating facility, and the industrial process(es) from which they were generated.

- (IV) Nothing in this subpart preempts, overrides or otherwise negates the provision in subparagraph (1)(b) of Rule 0400-12-01-.03 which requires any person who generates a solid waste to determine if that waste is a hazardous waste.
- (V) Interim status and permitted storage units that have been used to store only zinc-bearing hazardous wastes prior to the submission of the one-time notice described in subitem (II) of this subpart, and that afterward will be used only to store hazardous secondary materials excluded under this subpart, are not subject to the closure requirements of Rules 0400-12-01-.05 and .06.
- (xxi) Zinc fertilizers made from hazardous wastes, or hazardous secondary materials that are excluded under subpart (xx) of this part, provided that:
  - (I) The fertilizers meet the following contaminate limits:

I. For metal contaminants:

Constituent	Maximum Allowable Total Concentration in Fertilizer, per Unit (1%) of Zinc (ppm)
Arsenic	0.3
Cadmium	1.4
Chromium	0.6
Lead	2.8
Mercury	0.3

- II. For dioxin contaminants the fertilizer must contain no more than eight (8) parts per trillion of dioxin, measured as toxic equivalent (TEQ).
- (II) The manufacturer performs sampling and analysis of the fertilizer product to determine compliance with the contaminant limits for metals no less than every six months, and for dioxins no less than every twelve months. Testing must also be performed whenever changes occur to manufacturing processes or ingredients that could significantly affect the amounts of contaminants in the fertilizer product. The manufacturer may use any reliable analytical method to demonstrate that no constituent of concern is present in the product at concentrations above the applicable limits. It is the responsibility of the manufacturer to ensure that the sampling and analysis are unbiased, precise, and representative of the product(s) introduced into commerce.
- (III) The manufacturer maintains for no less than three years records of all sampling and analyses performed for purposes of determining compliance with the requirements of item (II) of this subpart. Such records must at a minimum include:
  - I. The dates and times product samples were taken, and the dates the samples were analyzed;
  - II. The names and qualifications of the person(s) taking the samples;
  - III. A description of the methods and equipment used to take the samples;
  - IV. The name and address of the laboratory facility at which

analyses of the samples were performed;

- V. A description of the analytical methods used, including any cleanup and sample preparation methods; and
- VI. All laboratory analytical results used to determine compliance with the contaminant limits specified in this subpart.

(xxii) Used cathode ray tubes (CRTs)

- (I) Used, intact CRTs as defined in subparagraph (2)(a) of Rule 0400-12-01-.01 are not solid wastes within the United States unless they are disposed, or unless they are speculatively accumulated as defined in subpart (1)(a)3(viii) of this rule by CRT collectors or glass processors.
- (II) Used, intact CRTs as defined in subparagraph (2)(a) of Rule 0400-12-01-.01 are not solid wastes when exported for recycling provided that they meet the requirements of subparagraph (5)(c) of this rule.
- (III) Used, broken CRTs as defined in subparagraph (2)(a) of Rule 0400-12-01-.01 are not solid wastes provided that they meet the requirements of subparagraph (5)(b) of this rule.
- (IV) Glass removed from CRTs is not a solid waste provided that it meets the requirements of part (5)(b)3 of this rule.

(xxiii) Hazardous secondary material generated and legitimately reclaimed within the United States or its territories and under the control of the generator, provided that the material complies with items (I) and (II) of this subpart:

- (I)
  - I. The hazardous secondary material is generated and reclaimed at the generating facility (for purposes of this definition, generating facility means all contiguous property owned, leased, or otherwise controlled by the hazardous secondary material generator); or
  - II. The hazardous secondary material is generated and reclaimed at different facilities, if the reclaiming facility is controlled by the generator or if both the generating facility and the reclaiming facility are controlled by a person as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, and if the generator provides one of the following certifications: “on behalf of [insert generator facility name], I certify that this facility will send the indicated hazardous secondary material to [insert reclaimer facility name], which is controlled by [insert generator facility name] and that [insert name of either facility] has acknowledged full responsibility for the safe management of the hazardous secondary material; and as specified in Tennessee Code Annotated Section 39-16-702(a)(4), this declaration is made under penalty of perjury,” or “on behalf of [insert generator facility name], I certify that this facility will send the indicated hazardous secondary material to [insert reclaimer facility name], that both facilities are under common control, and that [insert name of either facility] has acknowledged full responsibility for the safe management of the hazardous secondary material; and as specified in Tennessee Code Annotated Section 39-16-702(a)(4), this declaration is made under penalty of perjury.” For purposes of this subitem, “control” means the power to direct the policies of the facility, whether by the ownership of stock, voting rights, or otherwise, except that contractors who operate facilities

on behalf of a different person as defined in subparagraph (2)(a) of Rule 0400-12-01-.01 shall not be deemed to “control” such facilities. The generating and receiving facilities must both maintain at their facilities for no less than three years records of hazardous secondary materials sent or received under this exclusion. In both cases, the records must contain the name of the transporter, the date of the shipment, and the type and quantity of the hazardous secondary material shipped or received under the exclusion. These requirements may be satisfied by routine business records (e.g., financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations); or

III. The hazardous secondary material is generated pursuant to a written contract between a tolling contractor and a toll manufacturer and is reclaimed by the tolling contractor, if the tolling contractor certifies the following: “On behalf of [insert tolling contractor name], I certify that [insert tolling contractor name] has a written contract with [insert toll manufacturer name] to manufacture [insert name of product or intermediate] which is made from specified unused materials, and that [insert tolling contractor name] will reclaim the hazardous secondary materials generated during this manufacture. On behalf of [insert tolling contractor name], I also certify that [insert tolling contractor name] retains ownership of, and responsibility for, the hazardous secondary materials that are generated during the course of the manufacture, including any releases of hazardous secondary materials that occur during the manufacturing process. As specified in Tennessee Code Annotated Section 39-16-702(a)(4), this declaration is made under penalty of perjury.” The tolling contractor must maintain at its facility for no less than three years records of hazardous secondary materials received pursuant to its written contract with the tolling manufacturer, and the tolling manufacturer must maintain at its facility for no less than three years records of hazardous secondary materials shipped pursuant to its written contract with the tolling contractor. In both cases, the records must contain the name of the transporter, the date of the shipment, and the type and quantity of the hazardous secondary material shipped or received pursuant to the written contract. These requirements may be satisfied by routine business records (e.g., financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations). For purposes of this subitem, tolling contractor means a person who arranges for the production of a product or intermediate made from specified unused materials through a written contract with a toll manufacturer. Toll manufacturer means a person who produces a product or intermediate made from specified unused materials pursuant to a written contract with a tolling contractor.

(II) I. The hazardous secondary material is contained as defined in subparagraph (2)(a) of Rule 0400-12-01-.01. A hazardous secondary material released to the environment is discarded and a solid waste unless it is immediately recovered for the purpose of reclamation. Hazardous secondary material managed in a unit with leaks or other continuing or intermittent unpermitted releases is discarded and a solid waste.

II. The hazardous secondary material is not speculatively accumulated, as described in subpart (a)3(viii) of this paragraph.

- III. Notice is provided as required by subparagraph (5)(c) of Rule 0400-12-01-.01.
  - IV. The material is not otherwise subject to material-specific management conditions under part 1 of this subparagraph when reclaimed, and it is not a spent lead-acid battery (see subparagraph (7)(a) of Rule 0400-12-01-.09 and subparagraph (1)(d) of Rule 0400-12-01-.12).
  - V. Persons performing the recycling of hazardous secondary materials under this exclusion must maintain documentation of their legitimacy determination on-site. Documentation must be a written description of how the recycling meets all four factors in part (5)(d)1 of Rule 0400-12-01-.01. Documentation must be maintained for three years after the recycling operation has ceased.
  - VI. The emergency preparedness and response requirements found in paragraph (13) of this rule are met.
- (xxiv) Hazardous secondary material that is generated and then transferred to a verified reclamation facility, as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, for the purpose of reclamation is not a solid waste, provided that:
- (I) The material is not speculatively accumulated, as defined in subpart (a)3(viii) of this paragraph;
  - (II) The material is not handled by any person or facility other than the hazardous secondary material generator, the transporter, an intermediate facility or a reclaimer, and, while in transport, is not stored for more than ten (10) days at a transfer facility, as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, and is packaged according to applicable Department of Transportation regulations at 49 CFR parts 173, 178, and 179 while in transport;
  - (III) The material is not otherwise subject to material-specific management conditions under part 1 of this subparagraph when reclaimed, and it is not a spent lead-acid battery (see subparagraph (7)(a) of Rule 0400-12-01-.09 and subparagraph (1)(d) of Rule 0400-12-01-.12);
  - (IV) The reclamation of the material is legitimate, as specified under subparagraph (5)(d) of Rule 0400-12-01-.01;
  - (V) The hazardous secondary material generator satisfies all of the following conditions:
    - I. The material must be contained as defined in subparagraph (2)(a) of Rule 0400-12-01-.01. A hazardous secondary material released to the environment is discarded and a solid waste unless it is immediately recovered for the purpose of recycling. Hazardous secondary material managed in a unit with leaks or other continuing releases is discarded and a solid waste.
    - II. The hazardous secondary material generator must arrange for transport of hazardous secondary materials to a verified reclamation facility (or facilities), as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, in the United States or to a reclamation facility where the management of the hazardous secondary materials is addressed under a Part B permit issued

under Rule 0400-12-01-.07 or interim status standards under Rule 0400-12-01-.05 or, if not in Tennessee, under a RCRA Part B permit or interim status standards in another state. If the hazardous secondary material will be passing through an intermediate facility, the intermediate facility must be a verified intermediate facility, as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, or the management of the hazardous secondary materials at that facility must be addressed under a Part B permit issued under Rule 0400-12-01-.07 or interim status standards under Rule 0400-12-01-.05, or, if not in Tennessee, under a RCRA Part B permit or interim status standards in another state, and the hazardous secondary material generator must make contractual arrangements with the intermediate facility to ensure that the hazardous secondary material is sent to the reclamation facility identified by the hazardous secondary material generator.

- III. The hazardous secondary material generator must maintain at the generating facility for no less than three (3) years records of all off-site shipments of hazardous secondary materials. For each shipment, these records must, at a minimum, contain the following information:
    - A. Name of the transporter and date of the shipment;
    - B. Name and address of each reclaimer and, if applicable, the name and address of each intermediate facility to which the hazardous secondary material was sent; and
    - C. The type and quantity of hazardous secondary material in the shipment.
  - IV. The hazardous secondary material generator must maintain at the generating facility for no less than three (3) years confirmations of receipt from each reclaimer and, if applicable, each intermediate facility for all off-site shipments of hazardous secondary materials. Confirmations of receipt must include the name and address of the reclaimer (or intermediate facility), the type and quantity of the hazardous secondary materials received and the date which the hazardous secondary materials were received. This requirement may be satisfied by routine business records (e.g., financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations of receipt);
  - V. The hazardous secondary material generator must comply with the emergency preparedness and response conditions in paragraph (13) of this rule.
- (VI) Reclaimers of hazardous secondary material excluded from regulation under this exclusion and verified intermediate facilities, as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, satisfy all of the following conditions:
- I. The reclaimer and intermediate facility must maintain at its facility for no less than three (3) years records of all shipments of hazardous secondary material that were received at the facility and, if applicable, for all shipments of hazardous secondary materials that were received and subsequently sent off-site from the facility for further reclamation. For each shipment, these records must at a minimum contain the following information:



- A. Name of the transporter and date of the shipment;
  - B. Name and address of the hazardous secondary material generator and, if applicable, the name and address of the reclaimer or intermediate facility which the hazardous secondary materials were received from;
  - C. The type and quantity of hazardous secondary material in the shipment; and
  - D. For hazardous secondary materials that, after being received by the reclaimer or intermediate facility, were subsequently transferred off-site for further reclamation, the name and address of the (subsequent) reclaimer and, if applicable, the name and address of each intermediate facility to which the hazardous secondary material was sent.
- II. The intermediate facility must send the hazardous secondary material to the reclaimer(s) designated by the hazardous secondary materials generator.
  - III. The reclaimer and intermediate facility must send to the hazardous secondary material generator confirmations of receipt for all off-site shipments of hazardous secondary materials, within thirty (30) days of receipt. Confirmations of receipt must include the name and address of the reclaimer (or intermediate facility), the type and quantity of the hazardous secondary materials received and the date which the hazardous secondary materials were received. This requirement may be satisfied by routine business records (e.g., financial records, bills of lading, copies of DOT shipping papers, or electronic confirmations of receipt).
  - IV. The reclaimer and intermediate facility must manage the hazardous secondary material in a manner that is at least as protective as that employed for analogous raw material and must be contained. An "analogous raw material" is a raw material for which a hazardous secondary material is a substitute and serves the same function and has similar physical and chemical properties as the hazardous secondary material.
  - V. Any residuals that are generated from reclamation processes will be managed in a manner that is protective of human health and the environment. If any residuals exhibit a hazardous characteristic according to paragraph (3) of this rule, or if they themselves are specifically listed in paragraph (4) of this rule, such residuals are hazardous wastes and must be managed in accordance with the applicable requirements of Rules 0400-12-01-.01 through 0400-12-01-.10.
  - VI. The reclaimer and intermediate facility have financial assurance as required under paragraph (8) of this rule,
  - VII. The reclaimer and intermediate facility have been issued a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 or have a Part B permit issued under Rule 0400-12-01-.07 or interim status standards under Rule 0400-12-01-.05 that address the management of the hazardous secondary materials;

- VIII. If not operating under a Part B permit issued under Rule 0400-12-01-.07 or interim status standards under Rule 0400-12-01-.05 that address the management of the hazardous secondary materials, the reclaimer and intermediate facility develops and maintains a hazardous secondary material acceptance plan. The reclaimer only accepts hazardous secondary materials for reclamation that comply with the hazardous waste acceptance plan as approved by the Commissioner under part (4)(b)2 of Rule 0400-12-01-.01; and
- (VII) All persons claiming the exclusion under this subpart provide notification as required under subparagraph (5)(c) of Rule 0400-12-01-.01.
- (xxv) Reserved
- (xxvi) Solvent-contaminated wipes that are sent for cleaning and reuse are not solid wastes from the point of generation, provided that:
  - (I) The solvent-contaminated wipes, when accumulated, stored, and transported, are contained in non-leaking, closed containers that are labeled "Excluded Solvent-Contaminated Wipes." The containers shall be able to contain free liquids, should free liquids occur. During accumulation, a container is considered closed when there is complete contact between the fitted lid and the rim, except when it is necessary to add or remove solvent-contaminated wipes. When the container is full, or when the solvent-contaminated wipes are no longer being accumulated, or when the container is being transported, the container shall be sealed with all lids properly and securely affixed to the container and all openings tightly bound or closed sufficiently to prevent leaks and emissions;
  - (II) The solvent-contaminated wipes are accumulated by the generator for no more than 180 days from the start date of accumulation for each container prior to being sent for cleaning;
  - (III) At the point of being sent for cleaning on-site or at the point of being transported off-site for cleaning, the solvent-contaminated wipes must contain no free liquids as defined in paragraph (2) of Rule 0400-12-01-.01;
  - (IV) Free liquids removed from the solvent-contaminated wipes or from the container holding the wipes shall be managed according to the applicable regulations found in Rules 0400-12-01-.01 through 0400-12-01-.12;
  - (V) Generators shall maintain at their site the following documentation:
    - I. Name and address of the laundry or dry cleaner that is receiving the solvent-contaminated wipes;
    - II. Documentation that the 180-day accumulation time limit in item (II) of this subpart is being met;
    - III. Description of the process the generator is using to ensure the solvent-contaminated wipes contain no free liquids at the point of being laundered or dry cleaned on-site or at the point of being transported off-site for laundering or dry cleaning; and
  - (VI) The solvent-contaminated wipes are sent to a laundry or dry cleaner whose discharge, if any, is regulated under T.C.A. §§ 69-3-101 et seq.,

or sections 301 and 402 or section 307 of the Clean Water Act.

- (xxvii) Hazardous secondary material that is generated and then transferred to another person for the purpose of remanufacturing is not a solid waste, provided that:
- (I) The hazardous secondary material consists of one or more of the following spent solvents: Toluene, xylenes, ethylbenzene, 1,2,4-trimethylbenzene, chlorobenzene, n-hexane, cyclohexane, methyl tert-butyl ether, acetonitrile, chloroform, chloromethane, dichloromethane, methyl isobutyl ketone, NN-dimethylformamide, tetrahydrofuran, n-butyl alcohol, ethanol, and/or methanol;
  - (II) The hazardous secondary material originated from using one or more of the solvents listed in item (I) of this subpart in a commercial grade for reacting, extracting, purifying, or blending chemicals (or for rinsing out the process lines associated with these functions) in the pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and/or the paints and coatings manufacturing sectors (NAICS 325510).
  - (III) The hazardous secondary material generator sends the hazardous secondary material spent solvents listed in item (I) of this subpart to a remanufacturer in the pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and/or the paints and coatings manufacturing sectors (NAICS 325510).
  - (IV) After remanufacturing one or more of the solvents listed in item (I) of this subpart, the use of the remanufactured solvent shall be limited to reacting, extracting, purifying, or blending chemicals (or for rinsing out the process lines associated with these functions) in the pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and the paints and coatings manufacturing sectors (NAICS 325510) or to using them as ingredients in a product. These allowed uses correspond to chemical functional uses enumerated under the Chemical Data Reporting Rule of the Toxic Substances Control Act (40 CFR parts 704, 710-711), including Industrial Function Codes U015 (solvents consumed in a reaction to produce other chemicals) and U030 (solvents become part of the mixture);
  - (V) After remanufacturing one or more of the solvents listed in item (I) of this subpart, the use of the remanufactured solvent does not involve cleaning or degreasing oil, grease, or similar material from textiles, glassware, metal surfaces, or other articles. (These disallowed continuing uses correspond to chemical functional uses in Industrial Function Code U029 under the Chemical Data Reporting Rule of the Toxics Substances Control Act.); and
  - (VI) Both the hazardous secondary material generator and the remanufacturer must:
    - I. Notify EPA or the State Director, if the state is authorized for the program, and update the notification every two years per subparagraph (5)(c) of Rule 0400-12-01-.01;
    - II. Develop and maintain an up-to-date remanufacturing plan which identifies:
      - A. The name, address and EPA ID number of the

generator(s) and the remanufacturer(s);

- B. The types and estimated annual volumes of spent solvents to be remanufactured;
  - C. The processes and industry sectors that generate the spent solvents;
  - D. The specific uses and industry sectors for the remanufactured solvents; and
  - E. A certification from the remanufacturer stating "on behalf of [insert remanufacturer facility name], I certify that this facility is a remanufacturer under pharmaceutical manufacturing (NAICS 325412), basic organic chemical manufacturing (NAICS 325199), plastics and resins manufacturing (NAICS 325211), and/or the paints and coatings manufacturing sectors (NAICS 325510), and will accept the spent solvent(s) for the sole purpose of remanufacturing into commercial-grade solvent(s) that will be used for reacting, extracting, purifying, or blending chemicals (or for rinsing out the process lines associated with these functions) or for use as product ingredient(s). I also certify that the remanufacturing equipment, vents, and tanks are equipped with and are operating air emission controls in compliance with the appropriate Tennessee Air Quality Act regulations under Rule Division 1200-03, or, absent such Air Quality Act standards for the particular operation or piece of equipment covered by the remanufacturing exclusion, are in compliance with the appropriate standards in paragraphs (27) (vents), (28) (equipment) and (29) (tank storage).";
- III. Maintain records of shipments and confirmations of receipts for a period of three years from the dates of the shipments;
  - IV. Prior to remanufacturing, store the hazardous spent solvents in tanks or containers that meet technical standards found in paragraphs (9) and (10) of this rule, with the tanks and containers being labeled or otherwise having an immediately available record of the material being stored;
  - V. During remanufacturing, and during storage of the hazardous secondary materials prior to remanufacturing, the remanufacturer certifies that the remanufacturing equipment, vents, and tanks are equipped with and are operating air emission controls in compliance with the appropriate Tennessee Air Quality Act regulations under Rule Division 1200-03; or, absent such Air Quality Act standards for the particular operation or piece of equipment covered by the remanufacturing exclusion, are in compliance with the appropriate standards in paragraphs (27) (vents), (28) (equipment) and (29) (tank storage); and
  - VI. Meet the requirements prohibiting speculative accumulation per subpart (a)3(viii) of this paragraph.

## 2. Wastes Which Are Not Hazardous Wastes

The following wastes are not hazardous wastes:

- (i) Household waste, including household waste that has been collected, transported, stored, treated, disposed, recovered (e.g., refuse-derived fuel) or reused. "Household waste" means any material (including garbage, trash and sanitary wastes in septic tanks) derived from households (including single and multiple residences, hotels and motels, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds and day-use recreation areas). A resource recovery facility managing municipal waste shall not be deemed to be treating, storing, disposing of, or otherwise managing hazardous wastes for the purposes of regulation under Chapter 0400-12-01, if such facility:
  - (I) Receives and burns only
    - I. Household waste (from single and multiple dwellings, hotels, motels, and other residential sources) and
    - II. Waste from commercial or industrial sources that does not contain hazardous waste; and
  - (II) Such facility does not accept hazardous wastes and the owner or operator of such facility has established contractual requirements or other appropriate notification or inspection procedures to assure that hazardous wastes are not received at or burned in such facility.
- (ii) The following wastes generated within a farm and incidental to the operation of that farm:
  - (I) Wastes from the growing and harvesting of agricultural crops or from the raising of animals (including animal manures), which are returned to the soil as fertilizers; and [40 CFR 261.4(b)(2)]
  - (II) Waste pesticides, provided the farmer triple-rinses each emptied pesticide container (using a capable solvent) and disposes of the pesticide residues on his own farm in a manner consistent with the disposal instructions on the pesticide label. [40 CFR 262.70]
- (iii) Mining overburden returned to the mine site.
- (iv) (I) Fly ash waste, bottom ash waste, slag waste, and flue gas emission control waste, generated primarily from the combustion of coal or other fossil fuels, except as provided by subparagraph (8)(m) of Rule 0400-12-01-.09 for facilities that burn or process hazardous waste.
  - (II) The following wastes generated primarily from processes that support the combustion of coal or other fossil fuels that are co-disposed with the wastes in item (I) of this subpart, except as provided by subparagraph (8)(m) of Rule 0400-12-01-.09 for facilities that burn or process hazardous waste:
    - I. Coal pile run-off. For purposes of this subitem, coal pile run-off means any precipitation that drains off coal piles.
    - II. Boiler cleaning solutions. For purposes of this subitem, boiler cleaning solutions means water solutions and chemical solutions used to clean the fire-side and water-side of the boiler.
    - III. Boiler blowdown. For purposes of this subitem, boiler blowdown means water purged from boilers used to generate steam.
    - IV. Process water treatment and demineralizer regeneration wastes.

For purposes of this subitem, process water treatment and demineralizer regeneration wastes means sludges, rinses, and spent resins generated from processes to remove dissolved gases, suspended solids, and dissolved chemical salts from combustion system process water.

- V. Cooling tower blowdown. For purposes of this subitem, cooling tower blowdown means water purged from a closed cycle cooling system. Closed cycle cooling systems include cooling towers, cooling ponds, or spray canals.
  - VI. Air heater and precipitator washes. For purposes of this subitem, air heater and precipitator washes means wastes from cleaning air preheaters and electrostatic precipitators.
  - VII. Effluents from floor and yard drains and sumps. For purposes of this subitem, effluents from floor and yard drains and sumps means wastewaters, such as wash water, collected by or from floor drains, equipment drains, and sumps located inside the power plant building; and wastewaters, such as rain runoff, collected by yard drains and sumps located outside the power plant building.
  - VIII. Wastewater treatment sludges. For purposes of this subitem, wastewater treatment sludges refers to sludges generated from the treatment of wastewaters specified in subitems I through VI of this item.
- (v) Drilling fluids, produced waters, and other wastes associated with the exploration, development, or production of crude oil, natural gas or geothermal energy.
- (vi) (I) Wastes which fail the test for the Toxicity Characteristic because chromium is present or are listed in paragraph (4) of this rule due to the presence of chromium, which do not fail the test for the Toxicity Characteristic for any other constituent or are not listed due to the presence of any other constituent, and which do not fail the test for any other characteristic, if a waste generator demonstrates to the satisfaction of the Director, by submitting an evaluation request and supporting documentation, that:
- I. The chromium in the waste is exclusively (or nearly exclusively) trivalent chromium; and
  - II. The waste generated from an industrial process is trivalent chromium exclusively (or nearly exclusively) and the process does not contain more than minimal amounts of hexavalent chromium<sup>1</sup>; and
  - III. The waste is managed by the waste generator in non-oxidizing environments.
- (II) The waste generator shall also submit to the Department a Chromium Evaluation Review Fee identified in Rule 0400-12-01-.08(11) prior to the Director's review of the submitted documentation.
- (III) This exemption shall be effective only after approval in writing by the Director. Waste generators who obtain this exemption shall:

---

<sup>1</sup> Hexavalent chromium concentrations below 5 mg/l currently are considered minimal.

- I. Annually recertify the accuracy of the information in a letter to the Director that there has been no change in the waste stream or the process generating the waste since the Director determined that waste satisfies the conditions for the exemption;
  - II. Submit all recertifications as required by subitem I of this item by March 1 of each succeeding year following the Director's determination that the waste satisfies the conditions of the exemption; and
  - III. Submit a new evaluation and review fee to the Director within 30 days, if a change in the waste stream or the process generating the waste has occurred since the Director's determination.
- (IV) Specific wastes which meet the standard in item (I) of this subpart (so long as they do not fail the test for the toxicity characteristic for any other constituent, and do not exhibit any other characteristic) are:
- I. Chrome (blue) trimmings generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.
  - II. Chrome (blue) shavings generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; shearling.
  - III. Buffing dust generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue.
  - IV. Sewer screenings generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.
  - V. Wastewater treatment sludges generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; retan/wet finish; no beamhouse; through-the-blue; and shearling.
  - VI. Wastewater treatment sludges generated by the following subcategories of the leather tanning and finishing industry: Hair pulp/chrome tan/retan/wet finish; hair save/chrome tan/retan/wet finish; and through-the-blue.
  - VII. Waste scrap leather from the leather tanning industry, the shoe manufacturing industry, and other leather product manufacturing industries.
  - VIII. Wastewater treatment sludges from the production of TiO<sub>2</sub> pigment using chromium-bearing ores by the chloride process.

(vii) Solid waste from the extraction, beneficiation, and processing of ores and

minerals (including coal, phosphate rock and overburden from the mining of uranium ore), except as provided by Rule 0400-12-01-.09(8)(m) for facilities that burn or process hazardous waste.

- (I) For purposes of this subpart, beneficiation of ores and minerals is restricted to the following activities: crushing; grinding; washing; dissolution; crystallization; filtration; sorting; sizing; drying; sintering; pelletizing; briquetting; calcining to remove water and/or carbon dioxide; roasting, autoclaving, and/or chlorination in preparation for leaching (except where the roasting (and/or autoclaving and/or chlorination)/leaching sequence produces a final or intermediate product that does not undergo further beneficiation or processing); gravity concentration; magnetic separation; electrostatic separation; flotation; ion exchange; solvent extraction; electrowinning; precipitation; amalgamation; and heap, dump, vat, tank, and in situ leaching.
  
- (II) For the purpose of this subpart, solid waste from the processing of ores and minerals includes only the following wastes as generated:
  - I. Slag from primary copper processing;
  - II. Slag from primary lead processing;
  - III. Red and brown muds from bauxite refining;
  - IV. Phosphogypsum from phosphoric acid production;
  - V. Slag from elemental phosphorus production;
  - VI. Gasifier ash from coal gasification;
  - VII. Process wastewater from coal gasification;
  - VIII. Calcium sulfate wastewater treatment plant sludge from primary copper processing;
  - IX. Slag tailings from primary copper processing;
  - X. Fluorogypsum from hydrofluoric acid production;
  - XI. Process wastewater from hydrofluoric acid production;
  - XII. Air pollution control dust/sludge from iron blast furnaces;
  - XIII. Iron blast furnace slag;
  - XIV. Treated residue from roasting/leaching of chrome ore;
  - XV. Process wastewater from primary magnesium processing by the anhydrous process;
  - XVI. Process wastewater from phosphoric acid production;
  - XVII. Basic oxygen furnace and open hearth furnace air pollution control dust/sludge from carbon steel production;
  - XVIII. Basic oxygen furnace and open hearth furnace slag from carbon steel production;
  - XIX. Chloride process waste solids from titanium tetrachloride



production;

XX. Slag from primary zinc processing.

- (III) A residue derived from co-processing mineral processing secondary materials with normal beneficiation raw materials or with normal mineral processing raw materials remains excluded under this part if the owner or operator:
- I. Processes at least 50 percent by weight normal beneficiation raw materials or normal mineral processing raw materials; and,
  - II. Legitimately reclaims the secondary mineral processing materials.
- (viii) Cement kiln dust waste, except as provided by Rule 0400-12-01-.09(8)(m) for facilities that burn or process hazardous waste.
- (ix) Waste which consists of discarded arsenical-treated wood or wood products which fails the test for the Toxicity Characteristic for Hazardous Waste Codes D004 through D017 and which is not a hazardous waste for any other reason if the waste is generated by persons who utilize the arsenical-treated wood and wood products for these materials' intended end use.
- (x) Petroleum-contaminated media and debris that fail the test for the Toxicity Characteristic of subparagraph (3)(e) of this rule (Hazardous Waste Codes D018 through D043 only) and are subject to the corrective action regulations under 40 CFR Part 280 or Chapter 0400-18-01 (as these regulations exist on the effective date of these rules).
- (xi) Injected groundwater that is hazardous only because it exhibits the Toxicity Characteristic (Hazardous Waste Codes D018 through D043 only) in subparagraph (3)(e) of this rule that is reinjected through an underground injection well pursuant to free phase hydrocarbon recovery operations undertaken at petroleum refineries, petroleum marketing terminals, petroleum bulk plants, petroleum pipelines, and petroleum transportation spill sites until January 25, 1993. This extension applies to recovery operations in existence, or for which contracts have been issued, on or before March 25, 1991. New operations involving injection wells (beginning after March 25, 1991) will qualify for this compliance date extension (until January 25, 1993) only if operations are performed pursuant to a written state agreement issued under the Tennessee Water Quality Control Act (T.C.A. §69-3-101 et seq.) that includes a provision to assess the groundwater and the need for further remediation once the free phase recovery is completed.
- (xii) Used chlorofluorocarbon refrigerants from totally enclosed heat transfer equipment, including mobile air conditioning systems, mobile refrigeration, and commercial and industrial air conditioning and refrigeration systems that use chlorofluorocarbons as the heat transfer fluid in a refrigeration cycle, provided the refrigerant is reclaimed for further use.
- (xiii) Non-terne plated used oil filters that are not mixed with wastes listed in paragraph (4) of this rule if these oil filters have been gravity hot-drained using one of the following methods:
- (I) Puncturing the filter anti-drain back valve or the filter dome end and hot-draining;
  - (II) Hot-draining and crushing;

- (III) Dismantling and hot-draining; or
- (IV) Any other equivalent hot-draining method which will remove used oil.
- (xiv) Used oil re-refining distillation bottoms that are used as feedstock to manufacture asphalt products.
- (xv) Leachate or gas condensate collected from landfills where certain solid wastes have been disposed, provided that:
  - (I) The solid wastes disposed would meet one or more of the listing descriptions for hazardous Waste Codes K169, K170, K171, K172, K174, K175, K176, K177, K178, and K181 if these wastes had been generated after the effective date of the listing;
  - (II) The solid wastes described in item (I) of this subpart were disposed prior to the effective date of the listing;
  - (III) The leachate or gas condensate do not exhibit any characteristic of hazardous waste nor are derived from any other listed hazardous waste;
  - (IV) Discharge of the leachate or gas condensate, including leachate or gas condensate transferred from the landfill to a POTW by truck, rail, or dedicated pipe, is subject to regulation under sections 307(b) or 402 of the Clean Water Act, as amended or under the Water Quality Control Act; and
  - (V) As of February 13, 2001, leachate or gas condensate derived from K169-K172 is no longer exempt if it is stored or managed in a surface impoundment prior to discharge. As of November 21, 2003, leachate or gas condensate derived from K176, K177, and K178 is no longer exempt if it is stored or managed in a surface impoundment prior to discharge. After February 26, 2007, leachate or gas condensate derived from K181 will no longer be exempt if it is stored or managed in a surface impoundment prior to discharge. There is one exception: if the surface impoundment is used to temporarily store leachate or gas condensate in response to an emergency situation (e. g., shutdown of wastewater treatment system), provided the impoundment has a double liner, and provided the leachate or gas condensate is removed from the impoundment and continues to be managed in compliance with the conditions of this item (V) after the emergency ends.
- (xvi) Reserved
- (xvii) Reserved
- (xviii) Solvent-contaminated wipes, except for wipes that are hazardous waste due to the presence of trichloroethylene, that are sent for disposal are not hazardous wastes from the point of generation provided that:
  - (I) The solvent-contaminated wipes, when accumulated, stored, and transported, are contained in non-leaking, closed containers that are labeled "Excluded Solvent-Contaminated Wipes." The containers shall be able to contain free liquids, should free liquids occur. During accumulation, a container is considered closed when there is complete contact between the fitted lid and the rim, except when it is necessary to add or remove solvent-contaminated wipes. When the container is full, or when the solvent-contaminated wipes are no longer being accumulated, or when the container is being transported, the container shall be sealed with all lids properly and securely affixed to the container and all

openings tightly bound or closed sufficiently to prevent leaks and emissions;

- (II) The solvent-contaminated wipes are accumulated by the generator for no more than 180 days from the start date of accumulation for each container prior to being sent for disposal;
- (III) At the point of being transported for disposal, the solvent-contaminated wipes must contain no free liquids as defined in paragraph (2) of Rule 0400-12-01-.01;
- (IV) Free liquids removed from the solvent-contaminated wipes or from the container holding the wipes shall be managed according to the applicable regulations found in Rules 0400-12-01-.01 through 0400-12-01-.12;
- (V) Generators shall maintain at their site the following documentation:
  - I. Name and address of the landfill or combustor that is receiving the solvent-contaminated wipes;
  - II. Documentation that the 180 day accumulation time limit in item (II) of this subpart is being met;
  - III. Description of the process the generator is using to ensure solvent-contaminated wipes contain no free liquids at the point of being transported for disposal; and
- (VI) The solvent-contaminated wipes are sent for disposal:
  - I. To a municipal solid waste landfill regulated under Chapter 0400-11-01, including Rule 0400-11-01-.04 regarding a Class I disposal facility, or to a hazardous waste landfill regulated under Rules 0400-12-01-.05 or 0400-12-01-.06; or
  - II. To a municipal waste combustor or other combustion facility regulated under T.C.A. §§ 68-201-101 et seq. or to a hazardous waste combustor, boiler, or industrial furnace regulated under Rules 0400-12-01-.05 or 0400-12-01-.06 or paragraph (8) of Rule 0400-12-01-.09.

### 3. Hazardous Wastes Which Are Exempted From Certain Regulations

- (i) A hazardous waste which is generated in a product or raw material storage tank, a product or raw material transport vehicle or vessel, a product or raw material pipeline, or in a manufacturing process unit or an associated non-waste-treatment manufacturing unit, is not subject to regulation under these rules except as specified in subpart (ii) of this part until it exits the unit in which it was generated, unless the unit is a surface impoundment, or unless the hazardous waste remains in the unit more than 90 days after the unit ceases to be operated for manufacturing, or for storage or transportation of product or raw materials.
- (ii) A hazardous waste as described in subpart (i) of this part shall be subject to the generator notification requirement of Rule 0400-12-01-.03(2), and shall be subject to such requirement irrespective of how the waste is managed after it exits the units in which it was generated (e.g., even if it exits directly into a domestic sewer system), except as provided otherwise in Rule 0400-12-01-.03(2)(a)2. Such a waste shall also be subject to the annual reporting requirements of Rule 0400-12-01-.03(5)(b) for the years in which it is removed

from the units in which it was generated.

4. Samples

- (i) Except as provided in subpart (ii) of this part, a sample of solid waste or a sample of water, soil, or air, which is collected for the sole purpose of testing to determine its characteristics or composition, is not subject to any requirements of these rules when:
  - (I) The sample is being transported to a laboratory for the purpose of testing; or
  - (II) The sample is being transported back to the sample collector after testing; or
  - (III) The sample is being stored by the sample collector before transport to a laboratory for testing; or
  - (IV) The sample is being stored in a laboratory before testing; or
  - (V) The sample is being stored in a laboratory after testing but before it is returned to the sample collector; or
  - (VI) The sample is being stored temporarily in the laboratory after testing for a specific purpose (for example, until the conclusion of a court case or enforcement action where further testing of the sample may be necessary).
- (ii) In order to qualify for the exemption in items (i)(I) and (II) of this part a sample collector shipping samples to a laboratory and a laboratory returning samples to a sample collector must:
  - (I) Comply with U.S. Department of Transportation (DOT), U.S. Postal Service (USPS), or any other applicable shipping requirements; or
  - (II) Comply with the following requirements if the sample collector determines that DOT, USPS, or other shipping requirements do not apply to the shipment of the sample:
    - I. Assure that the following information accompanies the sample:
      - A. The sample collector's name, mailing address, and telephone number;
      - B. The laboratory's name, mailing address, and telephone number;
      - C. The quantity of the sample;
      - D. The date of shipment; and
      - E. A description of the sample.
    - II. Package the sample so that it does not leak, spill, or vaporize from its packaging.
- (iii) This exemption does not apply if the laboratory determines that the waste is hazardous but the laboratory is no longer meeting any of the conditions stated in subpart (i) of this part.

5. Treatability Study Samples

- (i) Except as provided in subpart (ii) of this part, persons who generate or collect samples for the purpose of conducting treatability studies as defined in Rule 0400-12-01-.01(2)(a), are not subject to any requirement of Rule 0400-12-01-.02, .03 and .04, nor are such samples included in the quantity determinations of paragraph (e) of this rule and Rule 0400-12-01-.03(4)(e)6 when:
  - (I) The sample is being collected and prepared for transportation by the generator or sample collector; or
  - (II) The sample is being accumulated or stored by the generator or sample collector prior to transportation to a laboratory or testing facility; or
  - (III) The sample is being transported to the laboratory or testing facility for the purpose of conducting a treatability study.
- (ii) The exemption in subpart (i) of this part is applicable to samples of hazardous waste being collected and shipped for the purpose of conducting treatability studies provided that:
  - (I) The generator or sample collector uses (in "treatability studies") no more than 10,000 kg of media contaminated with non-acute hazardous waste, 1000 kg of non-acute hazardous waste other than contaminated media, 1 kg of acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste for each process being evaluated for each generated waste stream; and
  - (II) The mass of each sample shipment does not exceed 10,000 kg; the 10,000 kg quantity may be all media contaminated with non-acute hazardous waste, or may include 2500 kg of media contaminated with acute hazardous waste, 1000 kg of hazardous waste, and 1 kg of acute hazardous waste; and
  - (III) The sample must be packaged so that it will not leak, spill, or vaporize from its packaging during shipment and the requirements of subitem I or II of this part are met.
    - I. The transportation of each sample shipment complies with U.S. Department of Transportation (DOT), U.S. Postal Service (USPS), or any other applicable shipping requirements; or
    - II. If the DOT, USPS, or other shipping requirements do not apply to the shipment of the sample, the following information must accompany the sample:
      - A. The name, mailing address, and telephone number of the originator of the sample;
      - B. The name, address, and telephone number of the facility that will perform the treatability study;
      - C. The quantity of the sample;
      - D. The date of shipment; and
      - E. A description of the sample, including its Hazardous Waste Code.
  - (IV) The sample is shipped to a laboratory or testing facility which is exempt

under part 6 of this subparagraph or has an appropriate permit or interim status.

- (V) The generator or sample collector maintains the following records for a period ending 3 years after completion of the treatability study:
  - I. Copies of the shipping documents;
  - II. A copy of the contract with the facility conducting the treatability study;
  - III. Documentation showing:
    - A. The amount of waste shipped under this exemption;
    - B. The name, address, and Installation Identification Number of the laboratory or testing facility that received the waste;
    - C. The date the shipment was made; and
    - D. Whether or not unused samples and residues were returned to the generator.

- (VI) The generator reports the information required under subitem (V)III of this subpart in its annual report.

(iii) The Commissioner may grant requests on a case-by-case basis for up to an additional two years for treatability studies involving bioremediation. The Commissioner may grant requests on a case-by-case basis for quantity limits in excess of those specified in items (ii)(I) and (II) of this part and subpart 6(iv) of this subparagraph, for up to an additional 5000 kg of media contaminated with non-acute hazardous waste, 500 kg of non-acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste and 1 kg of acute hazardous waste:

- (I) In response to requests for authorization to ship, store and conduct treatability studies on additional quantities in advance of commencing treatability studies. Factors to be considered in reviewing such requests include the nature of the technology, the type of process (e.g., batch versus continuous), size of the unit undergoing testing (particularly in relation to scale-up considerations), the time/quantity of material required to reach steady state operating conditions, or test design considerations such as mass balance calculations.
- (II) In response to requests for authorization to ship, store and conduct treatability studies on additional quantities after initiation or completion of initial treatability studies, when: There has been an equipment or mechanical failure during the conduct of a treatability study; there is a need to verify the results of a previously conducted treatability study; there is a need to study and analyze alternative techniques within a previously evaluated treatment process; or there is a need to do further evaluation of an ongoing treatability study to determine final specifications for treatment.
- (III) The additional quantities and timeframes allowed in items (I) and (II) of this subpart are subject to all the provisions in subpart (i) and items (III) through (VI) of subpart (ii) of this part. The generator or sample collector must apply to the Commissioner and provide in writing the following information:

- I. The reason why the generator or sample collector requires additional time or quantity of sample for treatability study evaluation and the additional time or quantity needed;
- II. Documentation accounting for all samples of hazardous waste from the waste stream which have been sent for or undergone treatability studies including the date each previous sample from the waste stream was shipped, the quantity of each previous shipment, the laboratory or testing facility to which it was shipped, what treatability study processes were conducted on each sample shipped, and the available results on each treatability study;
- III. A description of the technical modifications or change in specifications which will be evaluated and the expected results;
- IV. If such further study is being required due to equipment or mechanical failure, the applicant must include information regarding the reason for the failure or breakdown and also include what procedures or equipment improvements have been made to protect against further breakdowns; and
- V. Such other information that the Commissioner considers necessary.

6. Samples Undergoing Treatability Studies at Laboratories and Testing Facilities

Samples undergoing treatability studies and the laboratory or testing facility conducting such treatability studies (to the extent such facilities are not otherwise subject to the requirements under this Chapter) are not subject to any requirement of this Chapter provided that the conditions of subparts (i) through (xi) of this part are met. A mobile treatment unit (MTU) may qualify as a testing facility subject to subparts (i) through (xi) of this part. Where a group of MTUs are located at the same site, the limitations specified in subparts (i) through (xi) of this part apply to the entire group of MTUs collectively as if the group were one MTU.

- (i) No less than 45 days before conducting treatability studies, unless a shorter period is approved by the Commissioner, the facility notifies the Commissioner, in writing that it intends to conduct treatability studies under this paragraph.
- (ii) The laboratory or testing facility conducting the treatability study has an Installation Identification Number.
- (iii) No more than a total of 10,000 kg of "as received" media contaminated with non-acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste or 250 kg of other "as received" hazardous waste is subject to initiation of treatment in all treatability studies in any single day. "As received" waste refers to the waste as received in the shipment from the generator or sample collector.
- (iv) The quantity of "as received" hazardous waste stored at the facility for the purpose of evaluation in treatability studies does not exceed 10,000 kg, the total of which can include 10,000 kg of media contaminated with non-acute hazardous waste, 2500 kg of media contaminated with acute hazardous waste, 1000 kg of non-acute hazardous wastes other than contaminated media, and 1 kg of acute hazardous waste. This quantity limitation does not include treatment materials (including nonhazardous solid waste) added to "as received" hazardous waste.
- (v) No more than 90 days have elapsed since the treatability study for the sample was completed, or no more than one year (two years for treatability studies

involving bioremediation) have elapsed since the generator or sample collector shipped the sample to the laboratory or testing facility, whichever date first occurs. Up to 500 kg of treated material from a particular waste stream from treatability studies may be archived for future evaluation up to five years from the date of initial receipt. Quantities of materials archived are counted against the total storage limit for the facility.

- (vi) The treatability study does not involve the placement of hazardous waste on the land or open burning of hazardous waste.
- (vii) The facility maintains records for 3 years following completion of each study that show compliance with the treatment rate limits and the storage time and quantity limits. The following specific information must be included for each treatability study conducted:
  - (I) The name, address, and Installation Identification Number of the generator or sample collector of each waste sample;
  - (II) The date the shipment was received;
  - (III) The quantity of waste accepted;
  - (IV) The quantity of "as received" waste in storage each day;
  - (V) The date the treatment study was initiated and the amount of "as received" waste introduced to treatment each day;
  - (VI) The date the treatability study was concluded;
  - (VII) The date any unused sample or residues generated from the treatability study were returned to the generator or sample collector or, if sent to a designated facility, the name of the facility and the Installation Identification Number.
- (viii) The facility keeps, on-site, a copy of the treatability study contract and all shipping papers associated with the transport of treatability study samples to and from the facility for a period ending 3 years from the completion date of each treatability study.
- (ix) The facility prepares and submits a report to the Commissioner by March 15 of each year that includes the following information for the previous calendar year:
  - (I) The name, address, and Installation Identification Number of the facility conducting the treatability studies;
  - (II) The types (by process) of treatability studies conducted;
  - (III) The names and addresses of persons for whom studies have been conducted (including their Installation Identification Numbers);
  - (IV) The total quantity of waste in storage each day;
  - (V) The quantity and types of waste subjected to treatability studies;
  - (VI) When each treatability study was conducted;
  - (VII) The final disposition of residues and unused sample from each treatability study.
- (x) The facility determines whether any unused sample or residues generated by the



treatability study are hazardous waste under subparagraph (1)(c) of this rule and, if so, are subject to Chapter 0400-12-01, unless the residues and unused samples are returned to the sample originator under exemption under part 5 of this subparagraph.

- (xi) The facility notifies the Commissioner by letter when the facility is no longer planning to conduct any treatability studies at the site.
7. Dredged material that is not a hazardous waste. Dredged material that is subject to the requirements of a permit that has been issued under 404 of the Federal Water Pollution Control Act (33 U.S.C. 1344) or section 103 of the Marine Protection, Research, and Sanctuaries Act of 1972 (33 U.S.C. 1413) is not a hazardous waste. For this part 7, the following definitions apply:
- (i) The term “dredged material” has the same meaning as defined in 40 CFR 232.2;
  - (ii) The term “permit” means:
    - (I) A permit issued by the U.S. Army Corps of Engineers (Corps) or an approved State under section 404 of the Federal Water Pollution Control Act (33 U.S.C. 1344);
    - (II) A permit issued by the Corps under section 103 of the Marine Protection, Research, and Sanctuaries Act of 1972 (33 U.S.C. 1413); or
    - (III) In the case of Corps civil works projects, the administrative equivalent of the permits referred to in items (ii)(I) and (II) of this part, as provided for in Corps regulations (for example, see 33 CFR 336.1, 336.2, and 337.6).
8. Carbon dioxide stream injected for geologic sequestration. Carbon dioxide streams that are captured and transported for purposes of injection into an underground injection well subject to the requirements for Class VI Underground Injection Control wells, including the requirements in 40 CFR Parts 144 and 146 of the Underground Injection Control Program of the Safe Drinking Water Act and Chapter 0400-45-06 Underground Injection Control, are not a hazardous waste, provided the following conditions are met:
- (i) Transportation of the carbon dioxide stream shall be in compliance with U.S. Department of Transportation requirements, including the pipeline safety laws (49 U.S.C. 60101 et seq.) and regulations (49 CFR Parts 190-199) of the U.S. Department of Transportation, and pipeline safety regulations adopted and administered by a state authority pursuant to a certification under 49 U.S.C. 60105, as applicable;
  - (ii) Injection of the carbon dioxide stream shall be in compliance with the applicable requirements for Class VI Underground Injection Control wells, including the applicable requirements in 40 CFR Parts 144 and 146 and Tennessee Chapter 0400-45-06;
  - (iii) No hazardous wastes shall be mixed with, or otherwise co-injected with, the carbon dioxide stream; and
  - (iv) (I) Any generator of a carbon dioxide stream, who claims that a carbon dioxide stream is excluded under this part, shall have an authorized representative (as defined in subparagraph (2)(a) of Rule 0400-12-01-.01) sign a certification statement worded as follows:

“I certify under penalty of law that the carbon dioxide stream that I am claiming to be excluded under part (1)(d)8 of Rule 0400-12-01-.02 has not been mixed with hazardous wastes, and I have transported the carbon dioxide stream in compliance with (or have contracted with a

pipeline operator or transporter to transport the carbon dioxide stream in compliance with) Department of Transportation requirements, including the pipeline safety laws (49 U.S.C. 60101 et seq.) and regulations (49 CFR Parts 190-199) of the U.S. Department of Transportation, and the pipeline safety regulations adopted and administered by a state authority pursuant to a certification under 49 U.S.C. 60105, as applicable, for injection into a well subject to the requirements for the Class VI Underground Injection Control Program of the Safe Drinking Water Act and Tennessee Chapter 0400-45-06. As specified in Tennessee Code Annotated Section 39-16-702(a)(4), this declaration is made under penalty of perjury.”

- (II) Any Class VI Underground Injection Control well owner or operator, who claims that a carbon dioxide stream is excluded under this part, shall have an authorized representative (as defined in subparagraph (2)(a) of Rule 0400-12-01-.01) sign a certification statement worded as follows:

“I certify under penalty of law that the carbon dioxide stream that I am claiming to be excluded under part (1)(d)8 of Rule 0400-12-01-.02 has not been mixed with, or otherwise co-injected with, hazardous waste at the Underground Injection Control (UIC) Class VI permitted facility, and that injection of the carbon dioxide stream is in compliance with the applicable requirements for UIC Class VI wells, including the applicable requirements in 40 CFR Parts 144 and 146 and Tennessee Chapter 0400-45-06. As specified in Tennessee Code Annotated Section 39-16-702(a)(4), this declaration is made under penalty of perjury.”

- (III) The signed certification statement shall be kept on-site for no less than three years, and shall be made available within 72 hours of a written request from the Commissioner. The signed certification statement shall be renewed every year that the exclusion is claimed, by having an authorized representative (as defined in subparagraph (2)(a) of Rule 0400-12-01-.01) annually prepare and sign a new copy of the certification statement within one year of the date of the previous statement. The signed certification statement shall also be readily accessible on the facility's publicly-available website (if such website exists) as a public notification with the title of “Carbon Dioxide Stream Certification” at the time the exclusion is claimed.

(e) Special Requirements For Hazardous Waste Generated By Conditionally Exempt Small Quantity Generators [40 CFR 261.5]

1. A generator is a conditionally exempt small quantity generator in a calendar month if he generates no more than 100 kilograms of hazardous waste in that month.
2. Except for those wastes identified in parts 5, 6, 7, and 10 of this subparagraph, a conditionally exempt small quantity generator's hazardous wastes are not subject to regulation under Rules 0400-12-01-.03 through .10, provided the generator complies with the requirements of parts 6, 7 and 10 of this subparagraph.
3. When making the quantity determinations of this rule and Rule 0400-12-01-.03, the generator must include all hazardous waste that it generates, except hazardous waste that:
  - (i) Is exempt from regulation under parts (d)3 through 6 subparts (f)1(iii), subpart (g)1(i), or subparagraph (h) of this paragraph; or
  - (ii) Is managed immediately upon generation only in on-site elementary neutralization units, wastewater treatment units, or totally enclosed treatment facilities as defined in Rule 0400-12-01-.01(2)(a); or

- (iii) Is recycled, without prior storage or accumulation, only in an on-site process subject to regulation under subpart (f)3(ii) of this paragraph; or
- (iv) Is used oil managed under the requirements of subpart (f)1(iv) of this paragraph and Rule 0400-12-01-.11; or
- (v) Is spent lead-acid batteries managed under the requirements of Rule 0400-12-01-.09(7); or
- (vi) Is universal waste managed under Rule 0400-12-01-.02(1)(j) and Rule 0400-12-01-.12; or
- (vii) Is a hazardous waste that is an unused commercial chemical product (listed in Paragraph (4) of this rule or exhibiting one or more characteristics in paragraph (3) of this rule) that is generated solely as a result of a laboratory clean-out conducted at an eligible academic entity pursuant to paragraph (12) of Rule 0400-12-01-.03. For purposes of this provision, the term eligible academic entity shall have the meaning as defined in paragraph (12) of Rule 0400-12-01-.03.
- (viii) Is managed immediately upon generation in a collection system (sewer system) where the wastewaters will mix with sanitary wastes at any point before reaching a publicly owned treatment works (POTW).

4. In determining the quantity of hazardous waste generated, a generator need not include:
  - (i) Hazardous waste when it is removed from on-site storage; or
  - (ii) Hazardous waste produced by on-site treatment (including reclamation) of his hazardous waste, so long as the hazardous waste that is treated was counted once; or
  - (iii) Spent materials that are generated, reclaimed, and subsequently reused on-site, so long as such spent materials have been counted once.
5. If a generator generates acute hazardous waste in a calendar month in quantities greater than set forth below, all quantities of that acute hazardous waste are subject to full regulation under Chapter 0400-12-01:
  - (i) A total of one kilogram of acute hazardous wastes listed in subparagraph (4)(b) or part (4)(d)5 of this rule.
  - (ii) A total of 100 kilograms of any residue or contaminated soil, waste, or other debris resulting from the cleanup of a spill, into or on any land or water, of any acute hazardous wastes listed in subparagraph (4)(b) or part (4)(d)5 of this rule.

(Comment: "Full regulation" means those regulations applicable to generators of 1000 kg or greater of hazardous waste in a calendar month.)

6. In order for acute hazardous wastes generated by a generator of acute hazardous wastes in quantities equal to or less than those set forth in subparts 5(i) or (ii) of this subparagraph to be excluded from full regulation under this subparagraph, the generator must comply with the following requirements:
  - (i) The generator must perform the hazardous waste determination of Rule 0400-12-01-.03(1)(b) and keep records thereof as required by Rule 0400-12-01-.03(5)(a)3;
  - (ii) The generator may accumulate acute hazardous waste on-site. If he accumulates at any time acute hazardous wastes in quantities greater than those

set forth in subparts 5(i) or 5(ii) of this subparagraph, all of those accumulated wastes are subject to regulation under Chapter 0400-12-01. The time period of Rule 0400-12-01-.03(4)(e)2, for accumulation of wastes on-site, begins when the accumulated wastes exceed the applicable exclusion limit.

- (iii) A conditionally exempt small quantity generator may either treat or dispose of his acute hazardous waste in an on-site facility or ensure delivery to an off-site treatment, storage or disposal facility, either of which, if located in the U.S., is:
  - (I) Permitted under Rule 0400-12-01-.07;
  - (II) In interim status under Rule 0400-12-01-.05 and 0400-12-01-.07;
  - (III) Authorized to manage hazardous waste by a State with a hazardous waste management program approved under 40 CFR Part 271;
  - (IV) Permitted, licensed, or registered by a State to manage municipal solid waste and, if managed in a municipal solid waste landfill, is subject to 40 CFR Part 258;
  - (V) Permitted, licensed, or registered by a State to manage non-municipal non-hazardous waste and, if managed in a non-municipal non-hazardous waste disposal unit after January 1, 1998, is subject to the requirements in 40 CFR Parts 257.5 through 257.30; or
  - (VI) A facility which:
    - I. Beneficially uses or reuses, or legitimately recycles or reclaims its waste; or
    - II. Treats its waste prior to beneficial use or reuse, or legitimate recycling or reclamation; or
  - (VII) For universal waste managed under Rule 0400-12-01-.12, a universal waste handler or destination facility subject to the requirements of Rule 0400-12-01-.12.

7. In order for hazardous waste generated by a conditionally exempt small quantity generator in quantities of 100 kilograms or less of hazardous waste during a calendar month to be excluded from full regulation under this subparagraph, the generator must comply with the following requirements:

- (i) The conditionally exempt small quantity generator must perform the hazardous waste determination of Rule 0400-12-01-.03(1)(b) and keep records thereof as required by Rule 0400-12-01-.03(5)(a)3.
- (ii) The conditionally exempt small quantity generator may accumulate hazardous waste on-site. If he accumulates at any time more than a total of 1000 kilograms of his hazardous wastes, all of those accumulated wastes are subject to regulation under the special provisions of Rule 0400-12-01-.03 applicable to generators of greater than 100 kg and less than 1000 kg of hazardous waste in a calendar month as well as the requirements of Rule 0400-12-01-.04 through 0400-12-01-.10. The time period of Rule 0400-12-01-.03(4)(e)6 for accumulation of wastes on-site begins for a conditionally exempt small quantity generator when the accumulated wastes exceed 1000 kilograms;
- (iii) A conditionally exempt small quantity generator may either treat or dispose of his hazardous waste in an on-site facility or ensure delivery to an off-site treatment, storage or disposal facility, either of which, if located in the U.S., is:

- (I) Permitted under Rule 0400-12-01-.07;
  - (II) In interim status under Rules 0400-12-01-.05 and 0400-12-01-.07;
  - (III) Authorized to manage hazardous waste by a State with a hazardous waste management program approved under 40 CFR Part 271;
  - (IV) Permitted, licensed, or registered by a State to manage municipal solid waste and, if managed in a municipal solid waste landfill, is subject to 40 CFR Part 258;
  - (V) Permitted, licensed, or registered by a State to manage non-municipal non-hazardous waste and, if managed in a non-municipal non-hazardous waste disposal unit after January 1, 1998, is subject to the requirements in 40 CFR Parts 257.5 through 257.30; or
  - (VI) A facility which:
    - I. Beneficially uses or reuses or legitimately recycles or reclaims its waste; or
    - II. Treats its waste prior to beneficial use or reuse, or legitimate recycling or reclamation; or
  - (VII) For universal waste managed under Rule 0400-12-01-.12, a universal waste handler or destination facility subject to the requirements of Rule 0400-12-01-.12.
- (iv) Management of Containers with Liquids
- (I) A container holding hazardous waste volatile liquids must always be closed during storage, except when it is necessary to add or remove waste.
  - (II) A container holding hazardous waste liquids must not be opened, handled, or stored in a manner which may rupture the container or cause it to leak.
  - (III) The facility may take reasonable measures that deviate from this standard if required for safety due to the intrinsic nature of the container's contents.
8. Hazardous waste subject to the reduced requirements of this subparagraph may be mixed with non-hazardous waste and remain subject to these reduced requirements even though the resultant mixture exceeds the quantity limitations identified in this subparagraph, unless the mixture meets any of the characteristics of hazardous waste identified in paragraph (3) of this rule.
9. If any person mixes a solid waste with a hazardous waste that exceeds a quantity exclusion level of this subparagraph, the mixture is subject to full regulation.
10. If a conditionally exempt small quantity generator's wastes are mixed with used oil, the mixture is subject to Rule 0400-12-01-.11 provided the resultant mixture does not exhibit the characteristic of ignitability, corrosivity or reactivity in accordance with subparagraphs (3)(b), (c) or (d) of this rule.
- (i) Any material derived from such non-hazardous mixture by processing, blending, or other treatment is also regulated under part (2)(a)5 of Rule 0400-12-01-.11; and

- (ii) If the resultant mixture exhibits the characteristic of ignitability, corrosivity or reactivity, in accordance with subparagraphs (3)(b), (c) or (d) of this rule, and if the resultant hazardous waste mixture exceeds the quantity limitations identified in this subparagraph, then the mixture is no longer conditionally exempt under this subparagraph and is subject to regulation under Rules 0400-12-01-.03 through .10.

(NOTE: Any used oil that is not recycled is a solid waste subject to a hazardous waste determination per Rule 0400-12-01-.03(1)(b).)

(f) Requirements for recyclable material [40 CFR 261.6]

- 1. (i) Hazardous wastes that are recycled are subject to the requirements for generators, transporters, and storage facilities of parts 2 and 3 of this subparagraph, except for the materials listed in subparts (ii) and (iii) of this part. Hazardous wastes that are recycled will be known as "recyclable materials."

- (ii) The following recyclable materials are not subject to the requirements of this subparagraph but are regulated under paragraphs (3), (6), (7), (8), (13) and (14) of Rule 0400-12-01-.09 and all applicable provisions in Rules 0400-12-01-.07 and 0400-12-01-.10:

- (I) Recyclable materials used in a manner constituting disposal (Rule 0400-12-01-.09(3));
- (II) Hazardous wastes burned (as defined in Rule 0400-12-01-.09(8)(a)1) in boilers and industrial furnaces that are not regulated under paragraph (15) of Rule 0400-12-01-.05 or Rule 0400-12-01-.06;
- (III) Recyclable materials from which precious metals are reclaimed (Rule 0400-12-01-.09(6));
- (IV) Spent lead-acid batteries that are being reclaimed (Rule 0400-12-01-.09(7)).

- (iii) The following recyclable materials are not subject to regulation under Chapter 0400-12-01:

- (I) Industrial ethyl alcohol that is reclaimed except that, unless provided otherwise in an international agreement as specified in Rule 0400-12-01-.03(6)(i):

- I. A person initiating a shipment for reclamation in a foreign country, and any intermediary arranging for the shipment, must comply with the requirements applicable to a primary exporter in Rule 0400-12-01-.03(6)(d), (g)1(i) through (iv) and (vi), (g)2, and (h), export such materials only upon consent of the receiving country and in conformance with the EPA Acknowledgment of Consent as defined in Rule 0400-12-01-.03(6), and provide a copy of the EPA Acknowledgment of Consent to the shipment to the transporter transporting the shipment for export;
- II. Transporters transporting a shipment for export may not accept a shipment if he knows the shipment does not conform to the EPA Acknowledgment of Consent, must ensure that a copy of the EPA Acknowledgment of Consent accompanies the shipment and must ensure that it is delivered to the facility designated by the person initiating the shipment.

- (II) Scrap metal that is not excluded under subpart (d)1(xiii) of this

paragraph;

- (III) Fuels produced from the refining of oil-bearing hazardous waste along with normal process streams at a petroleum refining facility if such wastes result from normal petroleum refining, production, and transportation practices (this exemption does not apply to fuels produced from oil recovered from oil-bearing hazardous waste, where such recovered oil is already excluded under Rule 0400-12-01-.02(1)(d)1(xii));
- (IV)
  - I. Hazardous waste fuel produced from oil-bearing hazardous wastes from petroleum refining, production, or transportation practices, or produced from oil reclaimed from such hazardous wastes, where such hazardous wastes are reintroduced into a process that does not use distillation or does not produce products from crude oil so long as the resulting fuel meets the used oil specification under Rule 0400-12-01-.11(2)(b) and so long as no other hazardous wastes are used to produce the hazardous waste fuel;
  - II. Hazardous waste fuel produced from oil-bearing hazardous waste from petroleum refining production, and transportation practices, where such hazardous wastes are reintroduced into a refining process after a point at which contaminants are removed, so long as the fuel meets the used oil fuel specification under Rule 0400-12-01-.11(2)(b); and
  - III. Oil reclaimed from oil-bearing hazardous wastes from petroleum refining, production, and transportation practices, which reclaimed oil is burned as a fuel without reintroduction to a refining process, so long as the reclaimed oil meets the used oil fuel specification under Rule 0400-12-01-.11(2)(b).
- (iv) Used oil that is recycled and is also a hazardous waste solely because it exhibits a hazardous characteristic is not subject to the requirements of Rule 0400-12-01-.01 through .06, .09, and .10, but is regulated under Rule 0400-12-01-.11. Used oil that is recycled includes any used oil which is reused, following its original use, for any purpose (including the purpose for which the oil was originally used). Such term includes, but is not limited to, oil which is re-refined, reclaimed, burned for energy recovery, or reprocessed.
- (v) (Reserved) [40 CFR 261.6(a)(5)]
- 2. Generators and transporters of recyclable materials are subject to the applicable requirements of Rule 0400-12-01-.03 and .04, except as provided in part 1 of this subparagraph.
- 3.
  - (i) Owners and operators of facilities that store recyclable materials before they are recycled are regulated under all applicable provisions of paragraphs (1) through (12), (27), (28) and (29) of Rule 0400-12-01-.05 and paragraphs (1) through (12), (30), (31) and (32) of Rule 0400-12-01-.06, and under Rules 0400-12-01-.07, .09, and .10, and the notification requirements under Rule 0400-12-01-.07(2)(b) and (d), except as provided in part 1 of this subparagraph. (The recycling process itself is exempt from regulation except as provided in part 4 of this subparagraph.)
  - (ii) Owners or operators of facilities that recycle recyclable materials without storing them before they are recycled are subject to the following requirements, except as provided in part 1 of this subparagraph:
    - (I) Such owners or operators must notify the Division Director of their

activities using forms provided by the Department and completed per accompanying instructions;

(II) Such owners or operators must comply with Rule 0400-12-01-.05(5)(b) and (c) (dealing with the use of the manifest and manifest discrepancies);

(III) Rule 0400-12-01-.02(1)(f)4.

4. Owners or operators of facilities subject to the permitting requirements with hazardous waste management units that recycle hazardous wastes are subject to the requirements of paragraphs (27) and (28) of Rule 0400-12-01-.05 and paragraphs (30) and (31) of Rule 0400-12-01-.06.

5. Generators of recyclable materials must notify the Department describing the recyclable materials they generate, how such materials are generated, and how they are managed. Such notifications must be filed with the Department within 90 days of the effective date of this part (for existing generators) or within 90 days of the date a generator first becomes subject to this subparagraph (for new generators). Such notification must be submitted on forms provided by the Department. The form must be completed according to the accompanying instructions.

(g) Residues of hazardous waste in empty containers [40 CFR 261.7]

1. (i) Any hazardous waste remaining in either (1) an empty container or (2) an inner liner removed from an empty container, as defined in part 2 of this subparagraph, is not subject to regulation under these rules.

(ii) Any hazardous waste in either (1) a container that is not empty or (2) an inner liner removed from a container that is not empty, as defined in part 2 of this subparagraph, is subject to regulation under these rules.

2. (i) A container or an inner liner removed from a container that has held any hazardous waste, except a waste that is a compressed gas or that is identified as an acute hazardous waste listed in subparagraph (4)(b) or part (4)(d)5 of this rule is empty if:

(I) All wastes have been removed that can be removed using the practices commonly employed to remove materials from that type of container, e.g., pouring, pumping, and aspirating, and

(II) No more than 2.5 centimeters (one inch) of residue remain on the bottom of the container or inner liner, or

(III) I. No more than 3 percent by weight of the total capacity of the container remains in the container or inner liner if the container is less than or equal to 119 gallons in size, or

II. No more than 0.3 percent by weight of the total capacity of the container remains in the container or inner liner if the container is greater than 119 gallons in size.

(ii) A container that has held a hazardous waste that is a compressed gas is empty when the pressure in the container approaches atmospheric.

(iii) A container or an inner liner removed from a container that has held an acute hazardous waste listed in subparagraph (4)(b) or part (4)(d)5 of this subparagraph is empty if:

(I) The container or inner liner has been triple rinsed using a solvent



capable of removing the commercial chemical product or manufacturing chemical intermediate;

- (II) The container or inner liner has been cleaned by another method that has been shown in the scientific literature, or by tests conducted by the generator, to achieve equivalent removal; or
- (III) In the case of a container, the inner liner that prevented contact of the commercial chemical product or manufacturing chemical intermediate with the container, has been removed.

(h) PCB wastes regulated under Toxic Substance Control Act [40 CFR 261.8]

The disposal of PCB-containing dielectric fluid and electric equipment containing such fluid authorized for use and regulated under part 761 and that are hazardous only because they fail the test for the Toxicity Characteristic (Hazardous Waste Codes D018 through D043 only) are exempt from regulation under Rule 0400-12-01-.02 through .08 and .10.

(i) Management of Excluded Wastes

Nothing in these rules shall exclude persons whose waste is nonhazardous or otherwise excluded from these rules from the requirements of the "Tennessee Solid Waste Disposal Act" (T.C.A. §68-211-101 et seq.) and applicable regulations or from other applicable State, local or Federal laws.

(j) Requirements for Universal Waste [40 CFR 261.9]

The wastes listed in Rule 0400-12-01-.12(1)(a) are exempt from regulation under Rules 0400-12-01-.03 through .07, .09 and .10 except as specified in Rule 0400-12-01-.12 and, therefore, are not fully regulated as hazardous waste.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Paragraphs (5) and (6) of Rule 0400-12-01-.02 Identification and Listing of Hazardous Waste are amended by deleting them in their entirety and substituting instead the following:

(5) Exclusion/Exemptions [40 CFR 261 Subpart E]

(a) Reserved. [40 CFR 261.38]

(b) Conditional Exclusion for Used, Broken Cathode Ray Tubes (CRTs) and Processed CRT Glass Undergoing Recycling [40 CFR 261.39]

Used, broken CRTs are not solid wastes if they meet the following conditions:

1. Prior to processing:

These materials are not solid wastes if they are destined for recycling and if they meet the following requirements:

(i) Storage

The broken CRTs must be either:

- (I) Stored in a building with a roof, floor, and walls, or
- (II) Placed in a container (i.e., a package or a vehicle) that is constructed, filled, and closed to minimize releases to the environment of CRT glass (including fine solid materials).

(ii) Labeling

Each container in which the used, broken CRT is contained must be labeled or marked clearly with one of the following phrases: "Used cathode ray tube(s)-contains leaded glass" or "Leaded glass from televisions or computers." It must also be labeled: "Do not mix with other glass materials."

(iii) Transportation

The used, broken CRTs must be transported in a container meeting the requirements (i)(II) and subpart (ii) of this part.

(iv) Speculative accumulation and use constituting disposal

The used, broken CRTs are subject to the limitations on speculative accumulation as defined in subpart (1)(a)3(viii) of this rule. If they are used in a manner constituting disposal, they must comply with the applicable requirements of Rule 0400-12-01-.09(3) instead of the requirements of this subparagraph.

(v) Exports

[Note: The implementation of this subpart (Rule 0400-12-01-.02(5)(b)1(v) Exports) remains the responsibility of EPA.]

In addition to the applicable conditions specified in subparts (i) through (iv) of this part, exporters of used, broken CRTs must comply with the following requirements:

- (I) Notify EPA of an intended export before the CRTs are scheduled to leave the United States. A complete notification should be submitted sixty (60) days before the initial shipment is intended to be shipped off-site. This notification may cover export activities extending over a twelve (12) month or lesser period. The notification must be in writing, signed by the exporter, and include the following information:
  - I. Name, mailing address, telephone number and EPA ID number (if applicable) of the exporter of the CRTs.
  - II. The estimated frequency or rate at which the CRTs are to be exported and the period of time over which they are to be exported.
  - III. The estimated total quantity of CRTs specified in kilograms.
  - IV. All points of entry to and departure from each foreign country through which the CRTs will pass.
  - V. A description of the means by which each shipment of the CRTs will be transported (e.g., mode of transportation vehicle (air, highway, rail, water, etc.), type(s) of container (drums, boxes, tanks, etc.)).
  - VI. The name and address of the recycler or recyclers and the estimated quantity of used CRTs to be sent to each facility, as well as the names of any alternate recycler.
  - VII. A description of the manner in which the CRTs will be recycled in the foreign country that will be receiving the CRTs.
  - VIII. The name of any transit country through which the CRTs will be

sent and a description of the approximate length of time the CRTs will remain in such country and the nature of their handling while there.

- (II) Notifications submitted by mail should be sent to the following mailing address: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, 1200 Pennsylvania Ave., N.W., Washington, D.C. 20460. Hand-delivered notifications should be sent to: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, Ariel Rios Bldg., Room 6144, 1200 Pennsylvania Ave., N.W., Washington, D.C. In both cases, the following shall be prominently displayed on the front of the envelope: "Attention: Notification of Intent to Export CRTs."
- (III) Upon request by EPA, the exporter shall furnish to EPA any additional information which a receiving country requests in order to respond to a notification.
- (IV) EPA will provide a complete notification to the receiving country and any transit countries. A notification is complete when EPA receives a notification which EPA determines satisfies the requirements of item (I) of this subpart. Where a claim of confidentiality is asserted with respect to any notification information required by item (I) of this subpart, EPA may find the notification not complete until any such claim is resolved in accordance with 40 CFR 260.2.
- (V) The export of CRTs is prohibited unless the receiving country consents to the intended export. When the receiving country consents in writing to the receipt of the CRTs, EPA will forward an Acknowledgment of Consent to Export CRTs to the exporter. Where the receiving country objects to receipt of the CRTs or withdraws a prior consent, EPA will notify the exporter in writing. EPA will also notify the exporter of any responses from transit countries.
- (VI) When the conditions specified on the original notification change, the exporter must provide EPA with a written renotification of the change, except for changes to the telephone number in subitem (I) of this subpart and decreases in the quantity indicated pursuant to subitem (I)III of this subpart. The shipment cannot take place until consent of the receiving country to the changes has been obtained (except for changes to information about points of entry and departure and transit countries pursuant to subitems IV and VIII of this subpart and the exporter of CRTs receives from EPA a copy of the Acknowledgment of Consent to Export CRTs reflecting the receiving country's consent to the changes.
- (VII) A copy of the Acknowledgment of Consent to Export CRTs must accompany the shipment of CRTs. The shipment must conform to the terms of the Acknowledgment.
- (VIII) If a shipment of CRTs cannot be delivered for any reason to the recycler or the alternate recycler, the exporter of CRTs must renotify EPA of a change in the conditions of the original notification to allow shipment to a new recycler in accordance with item (VI) of this subpart and obtain another Acknowledgment of Consent to Export CRTs.
- (IX) Exporters must keep copies of notifications and Acknowledgments of Consent to Export CRTs for a period of three years following receipt of the Acknowledgment.

- (X) CRT exporters must file with EPA no later than March 1 of each year, an annual report summarizing the quantities (in kilograms), frequency of shipment, and ultimate destination(s) (i.e., the facility or facilities where the recycling occurs) of all used CRTs exported during the previous calendar year. Such reports must also include the following:
  - I. The name, EPA ID number (if applicable), and mailing and site address of the exporter;
  - II. The calendar year covered by the report; and
  - III. A certification signed by the CRT exporter that states:
 

“I certify under penalty of law that I have personally examined and am familiar with the information submitted in this and all attached documents and that, based on my inquiry of those individuals immediately responsible for obtaining this information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.”
- (XI) Annual reports must be submitted to the office specified in item (II) of this subpart. Exporters must keep copies of each annual report for a period of at least three years from the due date of the report.

2. Requirements for used CRT processing

Used, broken CRTs undergoing CRT processing as defined in subparagraph (2)(a) of Rule 0400-12-01-.01 are not solid wastes if they meet the following requirements:

(i) Storage

Used, broken CRTs undergoing processing are subject to the requirement of subpart 1(iv) of this subparagraph.

(ii) Processing

(I) All activities specified in parts 2 and 3 of the definition of “CRT processing” in subparagraph (2)(a) of Rule 0400-12-01-.01 must be performed within a building with a roof, floor, and walls; and

(II) No activities may be performed that use temperatures high enough to volatilize lead from CRTs.

3. Processed CRT glass sent to CRT glass making or lead smelting

Glass from used CRTs that is destined for recycling at a CRT glass manufacturer or a lead smelter after processing is not a solid waste unless it is speculatively accumulated as defined in subpart (1)(a)3(viii) of this rule.

4. Use constituting disposal

Glass from used CRTs that is used in a manner constituting disposal must comply with the requirements of paragraph (3) of Rule 0400-12-01-.09 instead of the requirements of this subparagraph.

(c) Conditional Exclusion for Used, Intact Cathode Ray Tubes (CRTs) Exported for Recycling [40 CFR 261.40]

[Note: The implementation of this subparagraph remains the responsibility of EPA.]

Used, intact CRTs exported for recycling are not solid wastes if they meet the notice and consent conditions of subpart (b)1(v) of this paragraph, and if they are not speculatively accumulated as defined in subpart (1)(a)3(viii) of this rule.

- (d) Notification and Recordkeeping for Used, Intact Cathode Ray Tubes (CRTs) Exported for Reuse [40 CFR 261.41]

[Note: The implementation of this subparagraph remains the responsibility of EPA.]

1. CRT exporters who export used, intact CRTs for reuse must send a notification to EPA. This notification may cover export activities extending over a twelve (12) month or lesser period.

(i) The notification must be in writing, signed by the exporter, and include the following information:

(I) Name, mailing address, telephone number, and EPA ID number (if applicable) of the exporter of the used, intact CRTs;

(II) The estimated frequency or rate at which the used, intact CRTs are to be exported for reuse and the period of time over which they are to be exported;

(III) The estimated total quantity of used, intact CRTs specified in kilograms;

(IV) All points of entry to and departure from each transit country through which the used, intact CRTs will pass, a description of the approximate length of time the used, intact CRTs will remain in such country, and the nature of their handling while there;

(V) A description of the means by which each shipment of the used, intact CRTs will be transported (e.g., mode of transportation vehicle (air, highway, rail, water, etc.), type(s) of container (drums, boxes, tanks, etc.));

(VI) The name and address of the ultimate destination facility or facilities where the used, intact CRTs will be reused, refurbished, distributed, or sold for reuse and the estimated quantity of used, intact CRTs to be sent to each facility, as well as the name of any alternate destination facility or facilities;

(VII) A description of the manner in which the used, intact CRTs will be reused (including reuse after refurbishment) in the foreign country that will be receiving the used, intact CRTs; and

(VIII) A certification signed by the CRT exporter that states:

"I certify under penalty of law that the CRTs described in this notice are intact and fully functioning or capable of being functional after refurbishment and that the used CRTs will be reused or refurbished and reused. I certify under penalty of law that I have personally examined and am familiar with the information submitted in this and all attached documents and that, based on my inquiry of those individuals immediately responsible for obtaining the information, I believe that the submitted information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment."

- (ii) Notifications submitted by mail should be sent to the following mailing address: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, 1200 Pennsylvania Ave. N.W., Washington, D.C. 20460. Hand-delivered notifications should be sent to: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, William Jefferson Clinton Building, Room 6144, 1200 Pennsylvania Ave. N.W., Washington, D.C. 20004. In both cases, the following shall be prominently displayed on the front of the envelope: "Attention: Notification of Intent to Export CRTs."

- 2. CRT exporters of used, intact CRTs sent for reuse must keep copies of normal business records, such as contracts, demonstrating that each shipment of exported used, intact CRTs will be reused. This documentation must be retained for a period of at least three years from the date the CRTs were exported. If the documents are written in a language other than English, CRT exporters of used, intact CRTs sent for reuse must provide both the original, non-English version of the normal business records as well as a third-party translation of the normal business records into English within 30 days upon request by EPA.

(6)–(7) Reserved [40 CFR Subparts F-- G]

(8) Financial Requirements for Management of Excluded Hazardous Secondary Material [40 CFR 261 Subpart H]

(a) Applicability. [40 CFR 261.140]

- 1. The requirements of this paragraph apply to owners or operators of reclamation and intermediate facilities managing hazardous secondary materials excluded under subpart (1)(d)1(xxiv) of this rule, except as provided otherwise in part 2 of this subparagraph.
- 2. States and the federal government are exempt from the financial assurance requirements of this subpart.

(b) Definitions of terms as used in this paragraph. [40 CFR 261.141]

The terms defined in parts (8)(b)5, 7, 8 and 9 of Rule 0400-12-01-.05 have the same meaning in this paragraph as they do in subparagraph (8)(b) of Rule 0400-12-01-.05.

(c) Cost estimate. [40 CFR 261.142]

- 1. The owner or operator must have a detailed written estimate, in current dollars, of the cost of disposing of any hazardous secondary material as listed or characteristic hazardous waste, and the potential cost of closing the facility as a treatment, storage, and disposal facility.

(Note: To determine the potential cost of closing the facility as a treatment, storage and disposal facility, the Commissioner expects the owner or operator to develop and provide the information consistent with information required in a closure plan developed in accordance with part (7)(c)2 of Rule 0400-12-01-.05.)

- (i) The estimate must equal the cost of conducting the activities described in this part at the point when the extent and manner of the facility's operation would make these activities the most expensive; and
- (ii) The cost estimate must be based on the costs to the owner or operator of hiring a third party to conduct these activities. A third party is a party who is neither a parent nor a subsidiary of the owner or operator. (See definition of parent

corporation in part (8)(b)5 of Rule 0400-12-01-.05.) The owner or operator may use costs for on-site disposal in accordance with applicable requirements if he can demonstrate that on-site disposal capacity will exist at all times over the life of the facility.

- (iii) The cost estimate may not incorporate any salvage value that may be realized with the sale of hazardous secondary materials, or hazardous or non-hazardous wastes if applicable under part (7)(d)4 of Rule 0400-12-01-.05, facility structures or equipment, land, or other assets associated with the facility.
- (iv) The owner or operator may not incorporate a zero cost for hazardous secondary materials, or hazardous or non-hazardous wastes if applicable under (7)(d)4 of Rule 0400-12-01-.05 that might have economic value.

2. During the active life of the facility, the owner or operator must adjust the cost estimate for inflation within 60 days prior to the anniversary date of the establishment of the financial instrument(s) used to comply with subparagraph (d) of this paragraph. For owners and operators using the financial test or corporate guarantee, the cost estimate must be updated for inflation within 30 days after the close of the firm's fiscal year and before submission of updated information to the Commissioner as specified in subpart (d)5(iii) of this paragraph. The adjustment may be made by recalculating the cost estimate in current dollars, or by using an inflation factor derived from the most recent Implicit Price Deflator for Gross National Product published by the U.S. Department of Commerce in its Survey of Current Business, as specified in subparts (i) and (ii) of this part. The inflation factor is the result of dividing the latest published annual Deflator by the Deflator for the previous year.

- (i) The first adjustment is made by multiplying the cost estimate by the inflation factor. The result is the adjusted cost estimate.
- (ii) Subsequent adjustments are made by multiplying the latest adjusted cost estimate by the latest inflation factor.

3. During the active life of the facility, the owner or operator must revise the cost estimate no later than 30 days after a change in a facility's operating plan or design that would increase the costs of conducting the activities described in part 1 of this subparagraph or no later than 60 days after an unexpected event which increases the cost of conducting the activities described in part 1 of this subparagraph. The revised cost estimate must be adjusted for inflation as specified in part 2 of this subparagraph.

4. The owner or operator must keep the following at the facility during the operating life of the facility: The latest cost estimate prepared in accordance with parts 1 and 3 and, when this estimate has been adjusted in accordance with part 2 of this subparagraph, the latest adjusted cost estimate.

(d) Financial assurance condition. [40 CFR 261.143]

Per subitem (1)(d)1(xxiv)(VI)VI of this rule, an owner or operator of a reclamation or intermediate facility must have financial assurance as a condition of the exclusion as required under subpart (1)(d)1(xxiv). He must choose from the options as specified in parts 1 through 7 of this subparagraph. The Commissioner may accept alternative financial assurance mechanisms proposed by the owner or operator in writing, if the Commissioner determines that such mechanisms will provide protection to human health and the environment that is equivalent to other allowable financial assurance mechanisms.

1. Trust fund.

- (i) An owner or operator may satisfy the requirements of this subparagraph by establishing a trust fund which conforms to the requirements of this part and submitting an originally signed duplicate of the trust agreement to the

Commissioner. The trustee must be an entity which has the authority to act as a trustee and whose trust operations are regulated and examined by a federal or state agency.

- (ii) The wording of the trust agreement must be identical to the wording specified in subpart (l)1(i) of this paragraph, and the trust agreement must be accompanied by a formal certification of acknowledgment (for example, see subpart (l)1(ii) of this paragraph). Schedule A of the trust agreement must be updated within 60 days after a change in the amount of the current cost estimate covered by the agreement.
- (iii) The trust fund must be funded for the full amount of the current cost estimate before it may be relied upon to satisfy the requirements of this part.
- (iv) Whenever the current cost estimate changes, the owner or operator must compare the new estimate with the trustee's most recent annual valuation of the trust fund. If the value of the fund is less than the amount of the new estimate, the owner or operator, within 60 days after the change in the cost estimate, must either deposit an amount into the fund so that its value after this deposit at least equals the amount of the current cost estimate, or obtain other financial assurance as specified in this subparagraph to cover the difference.
- (v) If the value of the trust fund is greater than the total amount of the current cost estimate, the owner or operator may submit a written request to the Commissioner for release of the amount in excess of the current cost estimate.
- (vi) If an owner or operator substitutes other financial assurance as specified in this subparagraph for all or part of the trust fund, he may submit a written request to the Commissioner for release of the amount in excess of the current cost estimate covered by the trust fund.
- (vii) Within 60 days after receiving a request from the owner or operator for release of funds as specified in subpart (v) or (vi) of this part, the Commissioner will instruct the trustee to release to the owner or operator such funds as the Commissioner specifies in writing. If the owner or operator begins final closure under paragraph (7) of Rules 0400-12-01-.05 or 0400-12-01-.06, an owner or operator may request reimbursements for partial or final closure expenditures by submitting itemized bills to the Commissioner. The owner or operator may request reimbursements for partial closure only if sufficient funds are remaining in the trust fund to cover the maximum costs of closing the facility over its remaining operating life. No later than 60 days after receiving bills for partial or final closure activities, the Commissioner will instruct the trustee to make reimbursements in those amounts as the Commissioner specifies in writing, if the Commissioner determines that the partial or final closure expenditures are in accordance with the approved closure plan, or otherwise justified. If the Commissioner has reason to believe that the maximum cost of closure over the remaining life of the facility will be significantly greater than the value of the trust fund, he may withhold reimbursements of such amounts as he deems prudent until he determines, in accordance with part (8)(d)3 of Rule 0400-12-01-.05 that the owner or operator is no longer required to maintain financial assurance for final closure of the facility. If the Commissioner does not instruct the trustee to make such reimbursements, he will provide to the owner or operator a detailed written statement of reasons.
- (viii) The Commissioner will agree to termination of the trust when:
  - (I) An owner or operator substitutes alternate financial assurance as specified in this subparagraph; or
  - (II) The Commissioner releases the owner or operator from the requirements of this part in accordance with part 11 of this subparagraph.



2. Surety bond guaranteeing payment.

- (i) An owner or operator may satisfy the requirements of this subparagraph by obtaining a surety bond which conforms to the requirements of this part and submitting the bond to the Commissioner. The surety company issuing the bond must, at a minimum, be licensed to do business as a surety in Tennessee and must be among those listed as acceptable sureties on federal bonds in Circular 570 of the U.S. Department of the Treasury.
- (ii) The wording of the surety bond must be identical to the wording specified in part (l)2 of this paragraph.
- (iii) Under the terms of the bond, the surety will become liable on the bond obligation when the operator fails to perform as guaranteed by the bond. Following a determination by the Commissioner that the hazardous secondary materials do not meet the conditions of the exclusion under subpart (1)(d)1(xxiv) the surety will forfeit the amount of the penal sum to the Commissioner.
- (iv) The bond must guarantee that the owner or operator will provide alternate financial assurance as specified in this part, and obtain the Commissioner's written approval of the assurance provided, within 90 days after receipt by both the owner or operator and the Commissioner of a notice of cancellation of the bond from the surety:
- (v) The penal sum of the bond must be in an amount at least equal to the current cost estimate, except as provided in part 8 of this subparagraph.
- (vi) Whenever the current cost estimate increases to an amount greater than the penal sum, the owner or operator, within 60 days after the increase, must either cause the penal sum to be increased to an amount at least equal to the current cost estimate and submit evidence of such increase to the Commissioner, or obtain other financial assurance as specified in this part to cover the increase. Whenever the current cost estimate decreases, the penal sum may be reduced to the amount of the current cost estimate following written approval by the Commissioner.
- (vii) Under the terms of the bond, the surety may cancel the bond by sending notice of cancellation by certified mail to the owner or operator and to the Commissioner. Cancellation may not occur, however, during the 120 days beginning on the date of receipt of the notice of cancellation by both the owner or operator and the Commissioner, as evidenced by the return receipts.
- (viii) The owner or operator may cancel the bond if the Commissioner has given prior written consent based on his receipt of evidence of alternate financial assurance as specified in this part.

3. Letter of credit.

- (i) An owner or operator may satisfy the requirements of this subparagraph by obtaining an irrevocable standby letter of credit which conforms to the requirements of this part and submitting the letter to the Commissioner. The issuing institution must be an entity which has the authority to issue letters of credit and whose letter-of-credit operations are regulated and examined by a federal or state agency.
- (ii) The wording of the letter of credit must be identical to the wording specified in part (l)3 of this paragraph.

- (iii) The letter of credit must be accompanied by a letter from the owner or operator referring to the letter of credit by number, issuing institution, and date, and providing the following information: The EPA Identification Number (if any issued), name, and address of the facility, and the amount of funds assured for the facility by the letter of credit.
- (iv) The letter of credit must be irrevocable and issued for a period of at least 1 year. The letter of credit must provide that the expiration date will be automatically extended for a period of at least 1 year unless, at least 120 days before the current expiration date, the issuing institution notifies both the owner or operator and the Commissioner by certified mail of a decision not to extend the expiration date. Under the terms of the letter of credit, the 120 days will begin on the date when both the owner or operator and the Commissioner have received the notice, as evidenced by the return receipts.
- (v) The letter of credit must be issued in an amount at least equal to the current cost estimate, except as provided in part 8 of this subparagraph.
- (vi) Whenever the current cost estimate increases to an amount greater than the amount of the credit, the owner or operator, within 60 days after the increase, must either cause the amount of the credit to be increased so that it at least equals the current cost estimate and submit evidence of such increase to the Commissioner, or obtain other financial assurance as specified in this subparagraph to cover the increase. Whenever the current cost estimate decreases, the amount of the credit may be reduced to the amount of the current cost estimate following written approval by the Commissioner.
- (vii) Following a determination by the Commissioner that the hazardous secondary materials do not meet the conditions of the exclusion under subpart (1)(d)1(xxiv), the Commissioner may draw on the letter of credit.
- (viii) If the owner or operator does not establish alternate financial assurance as specified in this part and obtain written approval of such alternate assurance from the Commissioner within 90 days after receipt by both the owner or operator and the Commissioner of a notice from the issuing institution that it has decided not to extend the letter of credit beyond the current expiration date, the Commissioner may draw on the letter of credit. The Commissioner may delay the drawing if the issuing institution grants an extension of the term of the credit. During the last 30 days of any such extension the Commissioner will draw on the letter of credit if the owner or operator has failed to provide alternate financial assurance as specified in this subparagraph and obtain written approval of such assurance from the Commissioner.
- (ix) The Commissioner will return the letter of credit to the issuing institution for termination when:
  - (i) An owner or operator substitutes alternate financial assurance as specified in this subparagraph; or
  - (ii) The Commissioner releases the owner or operator from the requirements of this part in accordance with part 11 of this subparagraph.

4. Insurance.

- (i) An owner or operator may satisfy the requirements of this subparagraph by obtaining insurance which conforms to the requirements of this part. The owner or operator must submit a signed duplicate original of the Hazardous Secondary Material Facility Endorsement to the Commissioner. If requested by the Commissioner, the owner or operator must provide a signed duplicate original of the insurance policy. The insurer must be licensed to transact the business of

insurance, or eligible to provide insurance as an excess or surplus lines insurer, in the State of Tennessee and have an A. M. Best rating of at least A or A- or have special approval from the Commissioner. An insurer that is a “captive insurance company”, as that term is used in T.C.A. §§ 56-13-106 through 56-13-133, may not be utilized unless the Commissioner determines that such captive insurance company offers coverage that is equivalent in protection to other insurance companies or other allowable financial assurance mechanisms.

- (ii) Each insurance policy must be amended by attachment of the Hazardous Secondary Material Facility Endorsement. The wording of the endorsement must be identical to the wording specified in part (l)4 of this paragraph.
- (iii) The insurance policy must be issued for a face amount at least equal to the current cost estimate, except as provided in part 8 of this subparagraph. The term “face amount” means the total amount the insurer is obligated to pay under the policy. Actual payments by the insurer will not change the face amount, although the insurer’s future liability will be lowered by the amount of the payments.
- (iv) The insurance policy must guarantee that funds will be available whenever needed to pay the cost of removal of all hazardous secondary materials from the unit, to pay the cost of decontamination of the unit, to pay the costs of the performance of activities required under paragraph (7) of Rule 0400-12-01-.05 or 0400-12-01-.06, as applicable, for the facilities covered by this policy. The policy must also guarantee that once funds are needed, the insurer will be responsible for paying out funds, up to an amount equal to the face amount of the policy, upon the direction of the Commissioner, to such party or parties as the Commissioner specifies.
- (v) After beginning partial or final closure under Rule 0400-12-01-.05 or 0400-12-01-.06, as applicable, an owner or operator or any other authorized person may request reimbursements for closure expenditures by submitting itemized bills to the Commissioner. The owner or operator may request reimbursements only if the remaining value of the policy is sufficient to cover the maximum costs of closing the facility over its remaining operating life. Within 60 days after receiving bills for closure activities, the Commissioner will instruct the insurer to make reimbursements in such amounts as the Commissioner specifies in writing if the Commissioner determines that the expenditures are in accordance with the approved plan or otherwise justified. If the Commissioner has reason to believe that the maximum cost over the remaining life of the facility will be significantly greater than the face amount of the policy, he may withhold reimbursement of such amounts as he deems prudent until he determines, in accordance with part 11 of this subparagraph, that the owner or operator is no longer required to maintain financial assurance for the particular facility. If the Commissioner does not instruct the insurer to make such reimbursements, he will provide to the owner or operator a detailed written statement of reasons.
- (vi) The owner or operator must maintain the policy in full force and effect until the Commissioner consents to termination of the policy by the owner or operator as specified in subpart (x) of this part. Failure to pay the premium, without substitution of alternate financial assurance as specified in this part, will constitute a significant violation of these regulations warranting such remedy as the Commissioner deems necessary. Such violation will be deemed to begin upon receipt by the Commissioner of a notice of future cancellation, termination, or failure to renew due to nonpayment of the premium, rather than upon the date of expiration.
- (vii) Each policy must contain a provision allowing assignment of the policy to a successor owner or operator. Such assignment may be conditional upon consent of the insurer, provided such consent is not unreasonably refused.

- (viii) The policy must provide that the insurer may not cancel, terminate, or fail to renew the policy except for failure to pay the premium. The automatic renewal of the policy must, at a minimum, provide the insured with the option of renewal at the face amount of the expiring policy. If there is a failure to pay the premium, the insurer may elect to cancel, terminate, or fail to renew the policy by sending notice by certified mail to the owner or operator and the Commissioner. Cancellation, termination, or failure to renew may not occur, however, during the 120 days beginning with the date of receipt of the notice by both the Commissioner and the owner or operator, as evidenced by the return receipts. Cancellation, termination, or failure to renew may not occur and the policy will remain in full force and effect in the event that on or before the date of expiration:
  - (I) The Commissioner deems the facility abandoned; or
  - (II) Conditional exclusion or interim status is lost, terminated, or revoked; or
  - (III) Closure is ordered by the Commissioner or a U.S. district court or other court of competent jurisdiction; or
  - (IV) The owner or operator is named as debtor in a voluntary or involuntary proceeding under Title 11 (Bankruptcy), U.S. Code; or
  - (V) The premium due is paid.
- (ix) Whenever the current cost estimate increases to an amount greater than the face amount of the policy, the owner or operator, within 60 days after the increase, must either cause the face amount to be increased to an amount at least equal to the current cost estimate and submit evidence of such increase to the Commissioner, or obtain other financial assurance as specified in this subparagraph to cover the increase. Whenever the current cost estimate decreases, the face amount may be reduced to the amount of the current cost estimate following written approval by the Commissioner.
- (x) The Commissioner will give written consent to the owner or operator that he may terminate the insurance policy when:
  - (I) An owner or operator substitutes alternate financial assurance as specified in this subparagraph; or
  - (ii) The Commissioner releases the owner or operator from the requirements of this subparagraph in accordance with part 11 of this subparagraph.

5. Financial test and corporate guarantee.

- (i) An owner or operator may satisfy the requirements of this subparagraph by demonstrating that he passes a financial test as specified in this part. To pass this test the owner or operator must meet the criteria of either item (I) or (II) of this subpart:
  - (I) The owner or operator must have:
    - I. Two of the following three ratios: A ratio of total liabilities to net worth less than 2.0; a ratio of the sum of net income plus depreciation, depletion, and amortization to total liabilities greater than 0.1; and a ratio of current assets to current liabilities greater than 1.5; and
    - II. Net working capital and tangible net worth each at least six times the sum of the current cost estimates; and

- III. Tangible net worth of at least \$10 million; and
  - IV. Assets located in the United States amounting to at least 90 percent of total assets or at least six times the sum of the current cost estimates.
- (II) The owner or operator must have:
- I. A current rating for his most recent bond issuance of AAA, AA, A, or BBB as issued by Standard and Poor's or Aaa, Aa, A, or Baa as issued by Moody's; and
  - II. Tangible net worth at least six times the sum of the current cost estimates; and
  - III. Tangible net worth of at least \$10 million; and
  - IV. Assets located in the United States amounting to at least 90 percent of total assets or at least six times the sum of the current cost estimates.
- (ii) The phrase "current cost estimates" as used in subpart (i) of this part refers to the cost estimates required to be shown in paragraphs 1 through 9 of the letter from the owner's or operator's chief financial officer (part (I)5 of this paragraph).
- (iii) To demonstrate that he meets this test, the owner or operator must submit the following items to the Commissioner:
- (I) A letter signed by the owner's or operator's chief financial officer and worded as specified in part (I)5 of this paragraph; and
  - (II) A copy of the independent certified public accountant's report on examination of the owner's or operator's financial statements for the latest completed fiscal year; and
  - (III) If the chief financial officer's letter providing evidence of financial assurance includes financial data showing that the owner or operator satisfies item 5(i)(I) of this subparagraph that are different from the data in the audited financial statements referred to in item (II) of this subpart or any other audited financial statement or data filed with the SEC, then a special report from the owner's or operator's independent certified public accountant to the owner or operator is required. The special report shall be based upon an agreed upon procedures engagement in accordance with professional auditing standards and shall describe the procedures performed in comparing the data in the chief financial officer's letter derived from the independently audited, year-end financial statements for the latest fiscal year with the amounts in such financial statements, the findings of the comparison, and the reasons for any differences.
- (iv) The owner or operator may obtain an extension of the time allowed for submission of the documents specified in subpart (iii) of this part if the fiscal year of the owner or operator ends during the 90 days prior to the effective date of these regulations and if the year-end financial statements for that fiscal year will be audited by an independent certified public accountant. The extension will end no later than 90 days after the end of the owner's or operator's fiscal year. To obtain the extension, the owner's or operator's chief financial officer must send, by the effective date of these rules, a letter to the Commissioner. This letter from the chief financial officer must:

- (I) Request the extension;
  - (II) Certify that he has grounds to believe that the owner or operator meets the criteria of the financial test;
  - (III) Specify for each facility to be covered by the test the EPA Identification Number (if any issued), name, address, and current cost estimates to be covered by the test;
  - (IV) Specify the date ending the owner's or operator's last complete fiscal year before the effective date of these rules in this paragraph;
  - (V) Specify the date, no later than 90 days after the end of such fiscal year, when he will submit the documents specified in subpart (iii) of this part; and
  - (VI) Certify that the year-end financial statements of the owner or operator for such fiscal year will be audited by an independent certified public accountant.
- (v) After the initial submission of items specified in subpart (iii) of this part, the owner or operator must send updated information to the Commissioner within 90 days after the close of each succeeding fiscal year. This information must consist of all three items specified in subpart (iii) of this part.
  - (vi) If the owner or operator no longer meets the requirements of subpart (i) of this part, he must send notice to the Commissioner of intent to establish alternate financial assurance as specified in this subparagraph. The notice must be sent by certified mail within 90 days after the end of the fiscal year for which the year-end financial data show that the owner or operator no longer meets the requirements. The owner or operator must provide the alternate financial assurance within 120 days after the end of such fiscal year.
  - (vii) The Commissioner may, based on a reasonable belief that the owner or operator may no longer meet the requirements of subpart (i) of this part, require reports of financial condition at any time from the owner or operator in addition to those specified in subpart (iii) of this part. If the Commissioner finds, on the basis of such reports or other information, that the owner or operator no longer meets the requirements of subpart (i) of this part, the owner or operator must provide alternate financial assurance as specified in this subparagraph within 30 days after notification of such a finding.
  - (viii) The Commissioner may disallow use of this test on the basis of qualifications in the opinion expressed by the independent certified public accountant in his report on examination of the owner's or operator's financial statements (see item (iii)(II) of this part). An adverse opinion or a disclaimer of opinion will be cause for disallowance. The Commissioner will evaluate other qualifications on an individual basis. The owner or operator must provide alternate financial assurance as specified in this subparagraph within 30 days after notification of the disallowance.
  - (ix) The owner or operator is no longer required to submit the items specified in subpart (iii) of this part when:
    - (I) An owner or operator substitutes alternate financial assurance as specified in this subparagraph; or
    - (II) The Commissioner releases the owner or operator from the requirements of this part in accordance with part 11 of this subparagraph.

- (x) An owner or operator may meet the requirements of this part by obtaining a written guarantee. The guarantor must be the direct or higher-tier parent corporation of the owner or operator, a firm whose parent corporation is also the parent corporation of the owner or operator, or a firm with a “substantial business relationship” with the owner or operator. The guarantor must meet the requirements for owners or operators in subparts (i) through (viii) of this part and must comply with the terms of the guarantee. The wording of the guarantee must be identical to the wording specified in subpart (l)7(i) of this paragraph. A certified copy of the guarantee must accompany the items sent to the Commissioner as specified in subpart (iii) of this part. One of these items must be the letter from the guarantor's chief financial officer. If the guarantor's parent corporation is also the parent corporation of the owner or operator, the letter must describe the value received in consideration of the guarantee. If the guarantor is a firm with a “substantial business relationship” with the owner or operator, this letter must describe this “substantial business relationship” and the value received in consideration of the guarantee. The terms of the guarantee must provide that:
  - (I) Following a determination by the Commissioner that the hazardous secondary materials at the owner or operator's facility covered by this guarantee do not meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of this rule, the guarantor will dispose of any hazardous secondary material as hazardous waste and close the facility in accordance with closure requirements found in Rule 0400-12-01-.05 or 0400-12-01-.06, as applicable, or establish a trust fund as specified in part 1 of this subparagraph in the name of the owner or operator in the amount of the current cost estimate.
  - (II) The corporate guarantee will remain in force unless the guarantor sends notice of cancellation by certified mail to the owner or operator and to the Commissioner. Cancellation may not occur, however, during the 120 days beginning on the date of receipt of the notice of cancellation by both the owner or operator and the Commissioner, as evidenced by the return receipts.
  - (III) If the owner or operator fails to provide alternate financial assurance as specified in this subparagraph and obtain the written approval of such alternate assurance from the Commissioner within 90 days after receipt by both the owner or operator and the Commissioner of a notice of cancellation of the corporate guarantee from the guarantor, the guarantor will provide such alternate financial assurance in the name of the owner or operator.

6. Personal Bond Supported by Certificate of Deposit

- (i) An owner or operator may satisfy the requirements of this subparagraph by filing his or her personal performance guarantee accompanied by collateral in the form of a certificate of deposit.
- (ii) The wording of the personal bond must be identical to the wording specified in subparagraph (l) of this paragraph.
- (iii) The certificate of deposit must be in an amount at least equal to the current cost estimate, except as provided in part 8 of this subparagraph.
- (iv) The certificate of deposit shall meet the following requirements:
  - (I) The certificate of deposit shall be registered as follows, except that the phrase “Corporation XYZ” should be replaced by the name of the owner/operator: “Corporation XYZ and Tennessee Department of

Environment and Conservation or Tennessee Department of Environment and Conservation”.

- (II) The institution holding the funds shall be a commercial financial institution regulated by a federal agency or regulated by the Tennessee Department of Financial Institutions.
- (III) The certificate of deposit shall be automatically annually renewed with the earned interest released to the principal as accrued.
- (IV) The original certificate of deposit or safekeeping receipt of the deposit shall be submitted to and held by the Division of Financial Responsibility of the Tennessee Department of Environment and Conservation.
- (V) Accompanying the certificate of deposit or safekeeping receipt shall be a letter from an officer of the issuing financial institution on the institution's letterhead that contains the certificate of deposit number, the name of the owner/operator, the date the certificate of deposit was issued, and the following statement:

“Notwithstanding any contrary term or condition of the above described Certificate of Deposit, [INSERT NAME OF FINANCIAL INSTITUTION] (the “Financial Institution”) hereby covenants, warrants and represents that said Certificate of Deposit shall not be subject to any right, charge, security interest, lien or claim of any kind in favor of the Financial Institution. The Financial Institution further agrees that it shall not release the Certificate of Deposit or the proceeds thereof to anyone other than to the Tennessee Department of Environment and Conservation (the “Department”) without the written consent of the Department.”

7. Personal Bond Supported by Cash

- (i) An owner or operator may satisfy the requirements of this subparagraph by filing his or her personal performance guarantee accompanied by collateral in the form of cash deposited with the treasurer of the state of Tennessee.
- (ii) The cash deposit must be in an amount at least equal to the current cost estimate, except as provided in part 8 of this subparagraph.
- (iii) The wording of the personal bond must be identical to the wording specified in subparagraph (I) of this paragraph.

8. Use of multiple financial mechanisms. An owner or operator may satisfy the requirements of this subparagraph by establishing more than one financial mechanism per facility. These mechanisms are limited to trust funds, surety bonds, letters of credit, insurance, and personal bonds. The mechanisms must be as specified in parts 1 through 4, 6 or 7 of this subparagraph, respectively, except that it is the combination of mechanisms, rather than the single mechanism, which must provide financial assurance for an amount at least equal to the current cost estimate. The Commissioner may use any or all of the mechanisms to provide for the facility.

9. Use of a financial mechanism for multiple facilities. An owner or operator may use a financial assurance mechanism specified in this subparagraph to meet the requirements of this subparagraph for more than one facility. Evidence of financial assurance submitted to the Commissioner must include a list showing, for each facility, the EPA Identification Number (if any issued), name, address, and the amount of funds assured by the mechanism. The amount of funds available through the mechanism must be no less than the sum of funds that would be available if a separate mechanism had been established and maintained for each facility. In directing funds available through the mechanism for any of the facilities covered by the mechanism, the Commissioner may direct only the



amount of funds designated for that facility, unless the owner or operator agrees to the use of additional funds available under the mechanism.

10. Removal and Decontamination Plan for Release

- (i) An owner or operator of a reclamation facility or an intermediate facility who wishes to be released from his financial assurance obligations under subitem (1)(d)1(xxiv)(VI)VI of this rule must submit a plan for removing all hazardous secondary material residues to the Commissioner at least 180 days prior to the date on which he expects to cease to operate under the exclusion.
- (ii) The plan must include, at least:
  - (I) For each hazardous secondary materials storage unit subject to financial assurance requirements under subitem (1)(d)1(xxiv)(VI)VI of this rule, a description of how all excluded hazardous secondary materials will be recycled or sent for recycling, and how all residues, contaminated containment systems (liners, etc.), contaminated soils, subsoils, structures, and equipment will be removed or decontaminated as necessary to protect human health and the environment, and
  - (II) A detailed description of the steps necessary to remove or decontaminate all hazardous secondary material residues and contaminated containment system components, equipment, structures, and soils including, but not limited to, procedures for cleaning equipment and removing contaminated soils, methods for sampling and testing surrounding soils, and criteria for determining the extent of decontamination necessary to protect human health and the environment; and
  - (III) A detailed description of any other activities necessary to protect human health and the environment during this timeframe, including, but not limited to, leachate collection, run-on and run-off control, etc.; and
  - (IV) A schedule for conducting the activities described which, at a minimum, includes the total time required to remove all excluded hazardous secondary materials for recycling and decontaminate all units subject to financial assurance under subitem (1)(d)1(xxiv)(VI)VI of this rule and the time required for intervening activities which will allow tracking of the progress of decontamination.
- (iii) The Commissioner will provide the owner or operator and the public, through a newspaper notice, the opportunity to submit written comments on the plan and request modifications to the plan no later than 30 days from the date of the notice. He will also, in response to a request or at his discretion, hold a public hearing whenever such a hearing might clarify one or more issues concerning the plan. The Commissioner will give public notice of the hearing at least 30 days before it occurs. (Public notice of the hearing may be given at the same time as notice of the opportunity for the public to submit written comments, and the two notices may be combined.) The Commissioner will approve, modify, or disapprove the plan within 90 days of its receipt. If the Commissioner does not approve the plan, he shall provide the owner or operator with a detailed written statement of reasons for the refusal and the owner or operator must modify the plan or submit a new plan for approval within 30 days after receiving such written statement. The Commissioner will approve or modify this plan in writing within 60 days. If the Commissioner modifies the plan, this modified plan becomes the approved plan. The Commissioner must assure that the approved plan is consistent with this part. A copy of the modified plan with a detailed statement of reasons for the modifications must be mailed to the owner or operator.

- (iv) Within 60 days of completion of the activities described for each hazardous secondary materials management unit, the owner or operator must submit to the Commissioner, by registered mail, a certification that all hazardous secondary materials have been removed from the unit and the unit has been decontaminated in accordance with the specifications in the approved plan. The certification must be signed by the owner or operator and by a qualified Professional Engineer. Documentation supporting the Professional Engineer's certification must be furnished to the Commissioner, upon request, until he releases the owner or operator from the financial assurance requirements for subitem (1)(d)1(xxiv)(VI)VI of this rule.
11. Release of the owner or operator from the requirements of this subparagraph. Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that all hazardous secondary materials have been removed from the facility or a unit at the facility and the facility or a unit has been decontaminated in accordance with the approved plan per part 10 of this subparagraph, the Commissioner will notify the owner or operator in writing that he is no longer required under subitem (1)(d)1(xxiv)(VI)VI of this rule to maintain financial assurance for that facility or a unit at the facility, unless the Commissioner has reason to believe that all hazardous secondary materials have not been removed from the facility or unit at a facility or that the facility or unit has not been decontaminated in accordance with the approved plan. The Commissioner shall provide the owner or operator a detailed written statement of any such reason to believe that all hazardous secondary materials have not been removed from the unit or that the unit has not been decontaminated in accordance with the approved plan.
  12. In meeting the requirements of this paragraph, an owner or operator may substitute alternate financial assurance meeting the requirements of this paragraph for the financial assurance already filed with the Commissioner for the facility. However, the existing financial assurance shall not be released by the Commissioner until the substitute financial assurance has been received and approved by him or her.
  13. When a transfer of ownership or operational control occurs, the previous owner or operator of the facility shall comply with the financial security requirements of this paragraph until the new owner or operator has demonstrated that he or she is complying with the requirements of this paragraph. Upon demonstration to the Commissioner by the new owner or operator of compliance with this paragraph, the Commissioner shall notify the previous owner or operator that he or she no longer needs to comply with this rule as of the date of demonstration.
  14. Procedures for Forfeiture of Financial Assurance
    - (i) Upon receipt of a notice of cancelation or non-renewal of a financial instrument from the issuing institution, the owner or operator will have 90 days from the Commissioner's and the owner's or operator's receipt of such notice to provide alternate financial assurance. If the owner or operator has failed to provide alternate financial assurance and obtain written approval of such financial assurance from the Commissioner during the 90 days following receipt of such notice by the Commissioner, the financial institution will forfeit the amount of such financial assurance to the Department as directed by the Commissioner; or
    - (ii) Upon his or her determination that the hazardous secondary materials at the facility covered by financial assurance do not meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, the Division Director shall cause a notice of non-compliance to be served upon the owner or operator. Such notice shall be hand delivered or forwarded by certified mail. The notice of non-compliance shall specify in what respects the owner or operator has failed to perform as required, and shall establish a schedule of compliance leading to compliance as soon as possible.

- (iii) If the Division Director determines that the owner or operator has failed to perform as specified in the notice of non-compliance, or as specified in any subsequent compliance agreement which may have been reached by the owner or operator and the Division Director, the Division Director shall cause a notice of show cause meeting to be served upon the owner or operator. Such notice shall be signed by the Division Director and either hand-delivered or forwarded by certified mail to the owner or operator. The notice of show cause meeting shall establish the date, time, and location of a meeting scheduled to provide the owner or operator with the opportunity to show cause why the Division Director should not pursue forfeiture of the financial assurance filed to guarantee such performance.
- (iv) If no mutual compliance agreement is reached at the show cause meeting, or upon the Division Director's determination that the owner or operator has failed to perform as specified in the mutual compliance agreement, the Division Director shall request the Commissioner or Board, as appropriate, to order forfeiture of the financial assurance filed to guarantee such performance.
- (v) The Commissioner or Board, as appropriate, shall order forfeiture of the financial assurance upon his/her or its validation of the Division Director's determinations and upon his/her or its determination that the procedures of this subparagraph have been followed. The Commissioner or Board may, however, at his/her or its discretion, provide opportunity for the owner or operator to be heard before issuing such order. Upon issuance, a copy of the order shall be hand delivered or forwarded by certified mail to the owner or operator. Any such order issued by the Commissioner or Board shall become effective 30 days after receipt by the owner or operator unless it is appealed to the Board as provided in T.C.A. § 68-212-113 of the Act.
- (vi) If necessary, upon the effective date of the order of forfeiture, the Commissioner shall give notice to the State Attorney General who shall collect the forfeiture.
- (vii) All forfeited funds shall be deposited in a special account entitled "the hazardous waste trust fund," for use by the Commissioner as set forth in T.C.A. § 68-212-108(c)(6) of the Act.

(e) - (g) Reserved [40 CFR 261.144-261.146]

(h) Liability requirement. [40 CFR 261.147]

1. Coverage for sudden accidental occurrences

An owner or operator of a hazardous secondary material reclamation facility or an intermediate facility subject to financial assurance requirements under subitem (1)(d)1(xxiv)(VI)VI of this rule, or a group of such facilities, must demonstrate financial responsibility for bodily injury and property damage to third parties caused by sudden accidental occurrences arising from operations of the facility or group of facilities. The owner or operator must have and maintain liability coverage for sudden accidental occurrences in the amount of at least \$1 million per occurrence with an annual aggregate of at least \$2 million, exclusive of legal defense costs. This liability coverage may be demonstrated as specified in subpart (i), (ii), (iii), (iv), (v) or (vi) of this part:

- (i) An owner or operator may demonstrate the required liability coverage by having liability insurance as specified in this subpart.
  - (I) Each insurance policy must be amended by attachment of the Hazardous Secondary Material Facility Liability Endorsement. The wording of the endorsement must be identical to the wording specified in part (I)8 of this paragraph. The owner or operator must submit a signed duplicate original of the endorsement to the Commissioner. If requested

by the Commissioner, the owner or operator must provide a signed duplicate original of the insurance policy.

- (II) The insurer must be licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in the state of Tennessee and have an A. M. Best rating of at least A or A- or have special approval from the Commissioner. An insurer that is a “captive insurance company”, as that term is used in T.C.A. §§ 56-13-106 through 56-13-133, may not be utilized unless the Commissioner determines that such captive insurance company offers coverage that is equivalent in protection to other insurance companies or other allowable financial assurance mechanisms.
- (ii) An owner or operator may meet the requirements of this part by passing a financial test or using the guarantee for liability coverage as specified in parts 6 and 7 of this subparagraph.
- (iii) An owner or operator may meet the requirements of this part by obtaining a letter of credit for liability coverage as specified in part 8 of this subparagraph.
- (iv) An owner or operator may meet the requirements of this part by obtaining a surety bond for liability coverage as specified in part 9 of this subparagraph.
- (v) An owner or operator may meet the requirements of this part by obtaining a trust fund for liability coverage as specified in part 10 of this subparagraph.
- (vi) An owner or operator may demonstrate the required liability coverage through the use of combinations of insurance, financial test, guarantee, letter of credit, surety bond, and trust fund, except that the owner or operator may not combine a financial test covering part of the liability coverage requirement with a guarantee unless the financial statement of the owner or operator is not consolidated with the financial statement of the guarantor. The amounts of coverage demonstrated must total at least the minimum amounts required by this part. If the owner or operator demonstrates the required coverage through the use of a combination of financial assurances under this subpart, the owner or operator shall specify at least one such assurance as “primary” coverage and shall specify other assurance as “excess” coverage.
- (vii) An owner or operator shall notify the Commissioner in writing within 30 days whenever:
  - (i) A claim results in a reduction in the amount of financial assurance for liability coverage provided by a financial instrument authorized in subparts (i) through (vi) of this part; or
  - (ii) A Certification of Valid Claim for bodily injury or property damages caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous secondary material reclamation facility or intermediate facility is entered between the owner or operator and third-party claimant for liability coverage under subparts (i) through (vi) of this part; or
  - (iii) A final court order establishing a judgment for bodily injury or property damage caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous secondary material reclamation facility or intermediate facility is issued against the owner or operator or an instrument that is providing financial assurance for liability coverage under subparts (i) through (vi) of this part.

## 2. Coverage for nonsudden accidental occurrences

An owner or operator of a hazardous secondary material reclamation facility or intermediate facility with land-based units, as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, which are used to manage hazardous secondary materials excluded under subpart (1)(d)1(xxiv) of this rule or a group of such facilities, must demonstrate financial responsibility for bodily injury and property damage to third parties caused by nonsudden accidental occurrences arising from operations of the facility or group of facilities. The owner or operator must have and maintain liability coverage for nonsudden accidental occurrences in the amount of at least \$3 million per occurrence with an annual aggregate of at least \$6 million, exclusive of legal defense costs. An owner or operator who must meet the requirements of this part may combine the required per-occurrence coverage levels for sudden and nonsudden accidental occurrences into a single per-occurrence level, and combine the required annual aggregate coverage levels for sudden and nonsudden accidental occurrences into a single annual aggregate level. Owners or operators who combine coverage levels for sudden and nonsudden accidental occurrences must maintain liability coverage in the amount of at least \$4 million per occurrence and \$8 million annual aggregate. This liability coverage may be demonstrated as specified in subpart (i), (ii), (iii), (iv), (v), or (vi) of this part:

- (i) An owner or operator may demonstrate the required liability coverage by having liability insurance as specified in this part.
  - (I) Each insurance policy must be amended by attachment of the Hazardous Secondary Material Facility Liability Endorsement. The wording of the endorsement must be identical to the wording specified in part (I)8 of this paragraph. The owner or operator must submit a signed duplicate original of the endorsement or the certificate of insurance to the Commissioner. If requested by the Commissioner, the owner or operator must provide a signed duplicate original of the insurance policy.
  - (II) The insurer must be licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer, in the state of Tennessee and have an A. M. Best rating of at least A or A- or have special approval from the Commissioner. An insurer that is a "captive insurance company", as that term is used in T.C.A. §§ 56-13-106 through 56-13-133, may not be utilized unless the Commissioner determines that such captive insurance company offers coverage that is equivalent in protection to other insurance companies or other allowable financial assurance mechanisms.
- (ii) An owner or operator may meet the requirements of this part by passing a financial test or using the guarantee for liability coverage as specified in parts 6 and 7 of this subparagraph.
- (iii) An owner or operator may meet the requirements of this part by obtaining a letter of credit for liability coverage as specified in part 8 of this subparagraph.
- (iv) An owner or operator may meet the requirements of this part by obtaining a surety bond for liability coverage as specified in part 9 of this subparagraph.
- (v) An owner or operator may meet the requirements of this part by obtaining a trust fund for liability coverage as specified in part 10 of this subparagraph.
- (vi) An owner or operator may demonstrate the required liability coverage through the use of combinations of insurance, financial test, guarantee, letter of credit, surety bond, and trust fund, except that the owner or operator may not combine a financial test covering part of the liability coverage requirement with a guarantee unless the financial statement of the owner or operator is not consolidated with the financial statement of the guarantor. The amounts of coverage demonstrated must total at least the minimum amounts required by this part. If the owner or

operator demonstrates the required coverage through the use of a combination of financial assurances under this subpart, the owner or operator shall specify at least one such assurance as “primary” coverage and shall specify other assurance as “excess” coverage.

- (vii) An owner or operator shall notify the Commissioner in writing within 30 days whenever:
  - (I) A claim results in a reduction in the amount of financial assurance for liability coverage provided by a financial instrument authorized in subparts (i) through (vi) of this part; or
  - (II) A Certification of Valid Claim for bodily injury or property damages caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous secondary material treatment and/or storage facility is entered between the owner or operator and third-party claimant for liability coverage under subparts (i) through (vi) of this part; or
  - (III) A final court order establishing a judgment for bodily injury or property damage caused by a sudden or non-sudden accidental occurrence arising from the operation of a hazardous secondary material treatment and/or storage facility is issued against the owner or operator or an instrument that is providing financial assurance for liability coverage under parts (i) through (vi) of this part.

### 3. Request for variance

If an owner or operator can demonstrate to the satisfaction of the Commissioner that the levels of financial responsibility required by part 1 or 2 of this subparagraph are not consistent with the degree and duration of risk associated with treatment and/or storage at the facility or group of facilities, the owner or operator may obtain a variance from the Commissioner. The request for a variance must be submitted in writing to the Commissioner. If granted, the variance will take the form of an adjusted level of required liability coverage, such level to be based on the Commissioner's assessment of the degree and duration of risk associated with the ownership or operation of the facility or group of facilities. The Commissioner may require an owner or operator who requests a variance to provide such technical and engineering information as is deemed necessary by the Commissioner to determine a level of financial responsibility other than that required by part 1 or 2 of this subparagraph.

### 4. Adjustments by the Commissioner

If the Commissioner determines that the levels of financial responsibility required by part 1 or 2 of this subparagraph are not consistent with the degree and duration of risk associated with treatment and/or storage at the facility or group of facilities, the Commissioner may adjust the level of financial responsibility required under part 1 or 2 of this subparagraph as may be necessary to protect human health and the environment. This adjusted level will be based on the Commissioner's assessment of the degree and duration of risk associated with the ownership or operation of the facility or group of facilities. In addition, if the Commissioner determines that there is a significant risk to human health and the environment from nonsudden accidental occurrences resulting from the operations of a facility that is not a surface impoundment, pile, or land treatment facility, he may require that an owner or operator of the facility comply with part 2 of this subparagraph. An owner or operator must furnish to the Commissioner, within a reasonable time, any information which the Commissioner requests to determine whether cause exists for such adjustments of level or type of coverage.

### 5. Period of coverage

Within 60 days after receiving certifications from the owner or operator and a qualified Professional Engineer that all hazardous secondary materials have been removed from the facility or a unit at the facility and the facility or a unit has been decontaminated in accordance with the approved plan per part (d)8 of this paragraph, the Commissioner will notify the owner or operator in writing that he is no longer required under item (1)(d)1(xxiv)(VI)VI of this rule to maintain liability coverage for that facility or a unit at the facility, unless the Commissioner has reason to believe that that all hazardous secondary materials have not been removed from the facility or unit at a facility or that the facility or unit has not been decontaminated in accordance with the approved plan.

6. Financial test for liability coverage

(i) An owner or operator may satisfy the requirements of this subparagraph by demonstrating that he passes a financial test as specified in this part. To pass this test the owner or operator must meet the criteria of item (I) or (II) of this subpart:

(I) The owner or operator must have:

- I. Net working capital and tangible net worth each at least six times the amount of liability coverage to be demonstrated by this test; and
- II. Tangible net worth of at least \$10 million; and
- III. Assets in the United States amounting to either:
  - A. At least 90 percent of his total assets; or
  - B. At least six times the amount of liability coverage to be demonstrated by this test.

(II) The owner or operator must have:

- I. A current rating for his most recent bond issuance of AAA, AA, A, or BBB as issued by Standard and Poor's, or Aaa, Aa, A, or Baa as issued by Moody's; and
- II. Tangible net worth of at least \$10 million; and
- III. Tangible net worth at least six times the amount of liability coverage to be demonstrated by this test; and
- IV. Assets in the United States amounting to either:
  - A. At least 90 percent of his total assets; or
  - B. At least six times the amount of liability coverage to be demonstrated by this test.

(ii) The phrase "amount of liability coverage" as used in subpart (i) of this part refers to the annual aggregate amounts for which coverage is required under parts 1 and 2 of this subparagraph and the annual aggregate amounts for which coverage is required under parts (8)(n)1 and 2 of Rules 0400-12-01-.05 and 0400-12-01-.06.

(iii) To demonstrate that he meets this test, the owner or operator must submit the following three items to the Commissioner:

- (I) A letter signed by the owner's or operator's chief financial officer and worded as specified in part (l)6 of this paragraph. If an owner or operator is using the financial test to demonstrate both assurance as specified by part (d)5 of this paragraph, and liability coverage, he must submit the letter specified in part (l)6 of this paragraph to cover both forms of financial responsibility; a separate letter as specified in part (l)5 of this paragraph is not required.
  - (II) A copy of the independent certified public accountant's report on examination of the owner's or operator's financial statements for the latest completed fiscal year.
  - (III) If the chief financial officer's letter providing evidence of financial assurance includes financial data showing that the owner or operator satisfies item (i)(l) of this part that are different from the data in the audited financial statements referred to in item (II) of this subpart or any other audited financial statement or data filed with the SEC, then a special report from the owner's or operator's independent certified public accountant to the owner or operator is required. The special report shall be based upon an agreed upon procedures engagement in accordance with professional auditing standards and shall describe the procedures performed in comparing the data in the chief financial officer's letter derived from the independently audited, year-end financial statements for the latest fiscal year with the amounts in such financial statements, the findings of the comparison, and the reasons for any difference.
- (iv) The owner or operator may obtain a one-time extension of the time allowed for submission of the documents specified in subpart (iii) of this part if the fiscal year of the owner or operator ends during the 90 days prior to the effective date of these rules and if the year-end financial statements for that fiscal year will be audited by an independent certified public accountant. The extension will end no later than 90 days after the end of the owner's or operator's fiscal year. To obtain the extension, the owner's or operator's chief financial officer must send, by the effective date of these rules, a letter to the Commissioner. This letter from the chief financial officer must:
- (I) Request the extension;
  - (II) Certify that he has grounds to believe that the owner or operator meets the criteria of the financial test;
  - (III) Specify for each facility to be covered by the test the EPA Identification Number, name, address, the amount of liability coverage and, when applicable, current closure and post-closure cost estimates to be covered by the test;
  - (IV) Specify the date ending the owner's or operator's last complete fiscal year before the effective date of these regulations;
  - (V) Specify the date, no later than 90 days after the end of such fiscal year, when he will submit the documents specified in subpart (iii) of this part; and
  - (VI) Certify that the year-end financial statements of the owner or operator for such fiscal year will be audited by an independent certified public accountant.
- (v) After the initial submission of items specified in subpart (iii) of this part, the owner or operator must send updated information to the Commissioner within 90 days



after the close of each succeeding fiscal year. This information must consist of all three items specified in subpart (iii) of this part.

- (vi) If the owner or operator no longer meets the requirements of subpart (i) of this part, he must obtain insurance, a letter of credit, a surety bond, a trust fund, or a guarantee for the entire amount of required liability coverage as specified in this part. Evidence of liability coverage must be submitted to the Commissioner within 90 days after the end of the fiscal year for which the year-end financial data show that the owner or operator no longer meets the test requirements.
- (vii) The Commissioner may disallow use of this test on the basis of qualifications in the opinion expressed by the independent certified public accountant in his report on examination of the owner's or operator's financial statements (see item (iii)(II) of this part). An adverse opinion or a disclaimer of opinion will be cause for disallowance. The Commissioner will evaluate other qualifications on an individual basis. The owner or operator must provide evidence of insurance for the entire amount of required liability coverage as specified in this part within 30 days after notification of disallowance.

7. Guarantee for liability coverage

- (i) Subject to subpart (ii) of this part, an owner or operator may meet the requirements of this subparagraph by obtaining a written guarantee, hereinafter referred to as "guarantee." The guarantor must be the direct or higher-tier parent corporation of the owner or operator, a firm whose parent corporation is also the parent corporation of the owner or operator, or a firm with a "substantial business relationship" with the owner or operator. The guarantor must meet the requirements for owners or operators in subparts 7(i) through (vi) of this subparagraph. The wording of the guarantee must be identical to the wording specified in subpart (I)7(ii) of this paragraph. A certified copy of the guarantee must accompany the items sent to the Commissioner as specified in subpart 7(iii) of this subparagraph. One of these items must be the letter from the guarantor's chief financial officer. If the guarantor's parent corporation is also the parent corporation of the owner or operator, this letter must describe the value received in consideration of the guarantee. If the guarantor is a firm with a "substantial business relationship" with the owner or operator, this letter must describe this "substantial business relationship" and the value received in consideration of the guarantee.
  - (I) If the owner or operator fails to satisfy a judgment based on a determination of liability for bodily injury or property damage to third parties caused by sudden or nonsudden accidental occurrences (or both as the case may be), arising from the operation of facilities covered by this corporate guarantee, or fails to pay an amount agreed to in settlement of claims arising from or alleged to arise from such injury or damage, the guarantor will do so up to the limits of coverage.
  - (II) Reserved
- (ii) (I) In the case of corporations incorporated in the United States, a guarantee may be used to satisfy the requirements of this part only if the Attorneys General or Insurance Commissioners of:
  - I. The state in which the guarantor is incorporated; and
  - II. Each state in which a facility covered by the guarantee is located has submitted a written statement to the Commissioner and the EPA that a guarantee executed as described in this part and subpart (I)7(ii) of this paragraph is a legally valid and enforceable obligation in that state.

- (II) In the case of corporations incorporated outside the United States, a guarantee may be used to satisfy the requirements of this section only if:
  - I. The non-U.S. corporation has identified a registered agent for service of process in each state in which a facility covered by the guarantee is located and in the state in which it has its principal place of business; and if
  - II. The Attorney General or Insurance Commissioner of each state in which a facility covered by the guarantee is located and the state in which the guarantor corporation has its principal place of business, has submitted a written statement to the Commissioner and the EPA that a guarantee executed as described in this part and subpart (I)7(ii) of this paragraph is a legally valid and enforceable obligation in that state.

8. Letter of credit for liability coverage

- (i) An owner or operator may satisfy the requirements of this subparagraph by obtaining an irrevocable standby letter of credit that conforms to the requirements of this part and submitting a copy of the letter of credit to the Commissioner.
- (ii) The financial institution issuing the letter of credit must be an entity that has the authority to issue letters of credit and whose letter of credit operations are regulated and examined by a federal or state agency.
- (iii) The wording of the letter of credit must be identical to the wording specified in part (I)9 of this paragraph.

9. Surety bond for liability coverage

- (i) An owner or operator may satisfy the requirements of this subparagraph by obtaining a surety bond that conforms to the requirements of this part and submitting a copy of the bond to the Commissioner.
- (ii) The surety company issuing the bond must be licensed to do business as a surety in Tennessee and must be among those listed as acceptable sureties on federal bonds in the most recent Circular 570 of the U.S. Department of the Treasury.
- (iii) The wording of the surety bond must be identical to the wording specified in part (I)10 of this paragraph.
- (iv) A surety bond may be used to satisfy the requirements of this subparagraph only if the Attorneys General or Insurance Commissioners of:
  - (I) The state in which the surety is incorporated; and
  - (II) Each state in which a facility covered by the surety bond is located has submitted a written statement to the Commissioner and the EPA that a surety bond executed as described in this part and part (I)10 of this paragraph is a legally valid and enforceable obligation in that state.

10. Trust fund for liability coverage

- (i) An owner or operator may satisfy the requirements of this subparagraph by establishing a trust fund that conforms to the requirements of this part and submitting an originally signed duplicate of the trust agreement to the Commissioner.

- (ii) The trustee must be an entity which has the authority to act as a trustee and whose trust operations are regulated and examined by a federal or state agency.
- (iii) The trust fund for liability coverage must be funded for the full amount of the liability coverage to be provided by the trust fund before it may be relied upon to satisfy the requirements of this subparagraph. If at any time after the trust fund is created the amount of funds in the trust fund is reduced below the full amount of the liability coverage to be provided, the owner or operator, by the anniversary date of the establishment of the Fund, must either add sufficient funds to the trust fund to cause its value to equal the full amount of liability coverage to be provided, or obtain other financial assurance as specified in this subparagraph to cover the difference. For purposes of this paragraph, “the full amount of the liability coverage to be provided” means the amount of coverage for sudden and/or nonsudden occurrences required to be provided by the owner or operator by this subparagraph, less the amount of financial assurance for liability coverage that is being provided by other financial assurance mechanisms being used to demonstrate financial assurance by the owner or operator.
- (iv) The wording of the trust fund must be identical to the wording specified in part (l)11 of this paragraph.

(i) Incapacity of owners or operators, guarantors, or financial institutions

1. An owner or operator must notify the Commissioner by certified mail of the commencement of a voluntary or involuntary proceeding under Title 11 (Bankruptcy), U.S. Code, naming the owner or operator as debtor, within 10 days after commencement of the proceeding. A guarantor of a corporate guarantee as specified in part (d)5 of this paragraph must make such a notification if he is named as debtor, as required under the terms of the corporate guarantee.
2. An owner or operator who fulfills the requirements of subparagraph (d) or (h) by obtaining a trust fund, surety bond, letter of credit, or insurance policy will be deemed to be without the required financial assurance or liability coverage in the event of bankruptcy of the trustee or issuing institution, or a suspension or revocation of the authority of the trustee institution to act as trustee or of the institution issuing the surety bond, letter of credit, or insurance policy to issue such instruments. The owner or operator must establish other financial assurance or liability coverage within 60 days after such an event.

(j) Reserved [40 CFR 261.149]

(k) Reserved [40 CFR. 261.150]

(l) Wording of the instruments

The wording of the financial instruments must be as follows or otherwise approved for use by the Commissioner:

1. (i) A trust agreement for a trust fund, as specified in part (d)1 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Trust Agreement

Trust Agreement, the “Agreement,” entered into as of [date] by and between [name of the owner or operator], a [name of State] [insert “corporation,” “partnership,” “association,” or “proprietorship”], the “Grantor,” and [name of corporate trustee], [insert “incorporated in the State of \_\_\_\_\_” or “a national bank”], the “Trustee.”

Whereas, the Underground Storage Tanks and Solid Waste Disposal Control Board, an agency of the State of Tennessee, has established certain rules applicable to the Grantor, requiring that an owner or operator of a facility regulated under Rule 0400-12-01-.05, or 0400-12-01-.06, or satisfying the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02 shall provide assurance that funds will be available if needed for care of the facility under paragraph (7) of Rule 0400-12-01-.05 or 0400-12-01-.06, as applicable,

Whereas, the Grantor has elected to establish a trust to provide all or part of such financial assurance for the facilities identified herein,

Whereas, the Grantor, acting through its duly authorized officers, has selected the Trustee to be the trustee under this agreement, and the Trustee is willing to act as trustee,

Now, Therefore, the Grantor and the Trustee agree as follows:

#### Section 1. Definitions.

As used in this Agreement:

- (a) The term "Grantor" means the owner or operator who enters into this Agreement and any successors or assigns of the Grantor.
- (b) The term "Trustee" means the Trustee who enters into this Agreement and any successor Trustee.
- (c) The term "Commissioner" means the Commissioner of the Tennessee Department of Environment and Conservation.

#### Section 2. Identification of Facilities and Cost Estimates.

This Agreement pertains to the facilities and cost estimates identified on attached Schedule A [on Schedule A, for each facility list the EPA Identification Number (if available), name, address, and the current cost estimates, or portions thereof, for which financial assurance is demonstrated by this Agreement].

#### Section 3. Establishment of Fund.

The Grantor and the Trustee hereby establish a trust fund, the "Fund," for the benefit of the Tennessee Department of Environment and Conservation in the event that the hazardous secondary materials of the grantor no longer meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02. The Grantor and the Trustee intend that no third party have access to the Fund except as herein provided. The Fund is established initially as consisting of the property, which is acceptable to the Trustee, described in Schedule B attached hereto. Such property and any other property subsequently transferred to the Trustee is referred to as the Fund, together with all earnings and profits thereon, less any payments or distributions made by the Trustee pursuant to this Agreement. The Fund shall be held by the Trustee, IN TRUST, as hereinafter provided. The Trustee shall not be responsible nor shall it undertake any responsibility for the amount or adequacy of, nor any duty to collect from the Grantor, any payments necessary to discharge any liabilities of the Grantor established by the Commissioner.

#### Section 4. Payments from the Fund.

The Trustee shall make payments from the Fund as the Commissioner shall direct, in writing, to provide for the payment of the costs of the performance of activities required under paragraph (7) of Rules 0400-12-01-.05 or 0400-12-01-.06 for the facilities covered by this Agreement. The Trustee shall reimburse the Grantor or other persons as specified by the Commissioner from the Fund for expenditures for such activities in such amounts as the beneficiary shall direct in writing. In addition, the Trustee shall refund to the Grantor such amounts as the Commissioner specifies in writing. Upon refund, such funds shall no longer constitute part of the Fund as defined herein.

#### Section 5. Payments Comprising the Fund.

Payments made to the Trustee for the Fund shall consist of cash or securities acceptable to the Trustee.

## Section 6. Trustee Management.

The Trustee shall invest and reinvest the principal and income of the Fund and keep the Fund invested as a single fund, without distinction between principal and income, in accordance with general investment policies and guidelines which the Grantor may communicate in writing to the Trustee from time to time, subject, however, to the provisions of this section. In investing, reinvesting, exchanging, selling, and managing the Fund, the Trustee shall discharge his duties with respect to the trust fund solely in the interest of the beneficiary and with the care, skill, prudence, and diligence under the circumstances then prevailing which persons of prudence, acting in a like capacity and familiar with such matters, would use in the conduct of an enterprise of a like character and with like aims; except that:

- (i) Securities or other obligations of the Grantor, or any other owner or operator of the facilities, or any of their affiliates as defined in the Investment Company Act of 1940, as amended, 15 U.S.C. 80a-2.(a), shall not be acquired or held, unless they are securities or other obligations of the Federal or a state government;
- (ii) The Trustee is authorized to invest the Fund in time or demand deposits of the Trustee, to the extent insured by an agency of the Federal or a state government; and
- (iii) The Trustee is authorized to hold cash awaiting investment or distribution uninvested for a reasonable time and without liability for the payment of interest thereon.

## Section 7. Commingling and Investment.

The Trustee is expressly authorized in its discretion:

- (a) To transfer from time to time any or all of the assets of the Fund to any common, commingled, or collective trust fund created by the Trustee in which the Fund is eligible to participate, subject to all of the provisions thereof, to be commingled with the assets of other trusts participating therein; and
- (b) To purchase shares in any investment company registered under the Investment Company Act of 1940, 15 U.S.C. 80a-1 et seq., including one which may be created, managed, underwritten, or to which investment advice is rendered or the shares of which are sold by the Trustee. The Trustee may vote such shares in its discretion.

## Section 8. Express Powers of Trustee.

Without in any way limiting the powers and discretions conferred upon the Trustee by the other provisions of this Agreement or by law, the Trustee is expressly authorized and empowered:

- (a) To sell, exchange, convey, transfer, or otherwise dispose of any property held by it, by public or private sale. No person dealing with the Trustee shall be bound to see to the application of the purchase money or to inquire into the validity or expediency of any such sale or other disposition;
- (b) To make, execute, acknowledge, and deliver any and all documents of transfer and conveyance and any and all other instruments that may be necessary or appropriate to carry out the powers herein granted;
- (c) To register any securities held in the Fund in its own name or in the name of a nominee and to hold any security in bearer form or in book entry, or to combine certificates representing such securities with certificates of the same issue held by the Trustee in other fiduciary capacities, or to deposit or arrange for the deposit of such securities in a qualified central depository even though, when so deposited, such securities may be merged and held in bulk in the name of the nominee of such depository with other securities deposited therein by another person, or to deposit or arrange for the deposit of any securities issued by the United States Government, or any agency or instrumentality thereof, with a Federal Reserve bank, but the books and records of the Trustee shall at all times show that all such securities are part of the Fund;
- (d) To deposit any cash in the Fund in interest-bearing accounts maintained or savings certificates issued by the Trustee, in its separate corporate capacity, or in any other banking institution affiliated with the Trustee, to the extent insured by an agency of the Federal or a state government; and
- (e) To compromise or otherwise adjust all claims in favor of or against the Fund.

#### Section 9. Taxes and Expenses.

All taxes of any kind that may be assessed or levied against or in respect of the Fund and all brokerage commissions incurred by the Fund shall be paid from the Fund. All other expenses incurred by the Trustee in connection with the administration of this Trust, including fees for legal services rendered to the Trustee, the compensation of the Trustee to the extent not paid directly by the Grantor, and all other proper charges and disbursements of the Trustee shall be paid from the Fund.

#### Section 10. Annual Valuation.

The Trustee shall annually, at least 30 days prior to the anniversary date of establishment of the Fund, furnish to the Grantor and to the Commissioner a statement confirming the value of the Trust. Any securities in the Fund shall be valued at market value as of no more than 60 days prior to the anniversary date of establishment of the Fund. The failure of the Grantor to object in writing to the Trustee within 90 days after the statement has been furnished to the Grantor and the Commissioner shall constitute a conclusively binding assent by the Grantor, barring the Grantor from asserting any claim or liability against the Trustee with respect to matters disclosed in the statement.

#### Section 11. Advice of Counsel.

The Trustee may from time to time consult with counsel, who may be counsel to the Grantor, with respect to any question arising as to the construction of this Agreement or any action to be taken hereunder. The Trustee shall be fully protected, to the extent permitted by law, in acting upon the advice of counsel.

#### Section 12. Trustee Compensation.

The Trustee shall be entitled to reasonable compensation for its services as agreed upon in writing from time to time with the Grantor.

#### Section 13. Successor Trustee.

The Trustee may resign or the Grantor may replace the Trustee, but such resignation or replacement shall not be effective until the Grantor has appointed a successor trustee and this successor accepts the appointment. The successor trustee shall have the same powers and duties as those conferred upon the Trustee hereunder. Upon the successor trustee's acceptance of the appointment, the Trustee shall assign, transfer, and pay over to the successor trustee the funds and properties then constituting the Fund. If for any reason the Grantor cannot or does not act in the event of the resignation of the Trustee, the Trustee may apply to a court of competent jurisdiction for the appointment of a successor trustee or for instructions. The successor trustee shall specify the date on which it assumes administration of the trust in a writing sent to the Grantor, the Commissioner, and the present Trustee by certified mail 10 days before such change becomes effective. Any expenses incurred by the Trustee as a result of any of the acts contemplated by this Section shall be paid as provided in Section 9.

#### Section 14. Instructions to the Trustee.

All orders, requests, and instructions by the Grantor to the Trustee shall be in writing, signed by such persons as are designated in the attached Exhibit A or such other designees as the Grantor may designate by amendment to Exhibit A. The Trustee shall be fully protected in acting without inquiry in accordance with the Grantor's orders, requests, and instructions. All orders, requests, and instructions by the Commissioner to the Trustee shall be in writing, signed by the Commissioner or their designee, and the Trustee shall act and shall be fully protected in acting in accordance with such orders, requests, and instructions. The Trustee shall have the right to assume, in the absence of written notice to the contrary, that no event constituting a change or a termination of the authority of any person to act on behalf of the Grantor or the Commissioner hereunder has occurred. The Trustee shall have no duty to act in the absence of such orders, requests, and instructions from the Grantor and/or the Commissioner, except as provided for herein.

#### Section 15. Amendment of Agreement.

This Agreement may be amended by an instrument in writing executed by the Grantor, the Trustee, and the Commissioner, or by the Trustee and the Commissioner if the Grantor ceases to exist.

Section 16. Irrevocability and Termination.

Subject to the right of the parties to amend this Agreement as provided in Section 16, this Trust shall be irrevocable and shall continue until terminated at the written agreement of the Grantor, the Trustee, and the Commissioner, or by the Trustee and the Commissioner, if the Grantor ceases to exist. Upon termination of the Trust, all remaining trust property, less final trust administration expenses, shall be delivered to the Grantor.

Section 17. Immunity and Indemnification.

The Trustee shall not incur personal liability of any nature in connection with any act or omission, made in good faith, in the administration of this Trust, or in carrying out any directions by the Grantor or the Commissioner issued in accordance with this Agreement. The Trustee shall be indemnified and saved harmless by the Grantor or from the Trust Fund, or both, from and against any personal liability to which the Trustee may be subjected by reason of any act or conduct in its official capacity, including all expenses reasonably incurred in its defense in the event the Grantor fails to provide such defense.

Section 18. Choice of Law.

This Agreement shall be administered, construed, and enforced according to the laws of the state of [insert name of state].

Section 19. Interpretation.

As used in this Agreement, words in the singular include the plural and words in the plural include the singular. The descriptive headings for each Section of this Agreement shall not affect the interpretation or the legal efficacy of this Agreement.

In Witness Whereof the parties have caused this Agreement to be executed by their respective officers duly authorized and their corporate seals to be hereunto affixed and attested as of the date first above written: The parties below certify that the wording of this Agreement is identical to the wording specified in subpart (8)(l)1(i) of Rule 0400-12-01-.02 as such rules were constituted on the date first above written.

[Signature of Grantor]  
[Title]  
Attest:  
[Title]  
[Seal]  
[Signature of Trustee]  
Attest:  
[Title]  
[Seal]

- (ii) The following is an example of the certification of acknowledgment which must accompany the trust agreement for a trust fund as specified in part (d)1 of this paragraph.

State of \_\_\_\_\_ County of \_\_\_\_\_

On this [date], before me personally came [owner or operator] to me known, who, being by me duly sworn, did depose and say that she/he resides at [address], that she/he is [title] of [corporation], the corporation described in and which executed the above instrument; that she/he knows the seal of said corporation; that the seal affixed to such instrument is such corporate seal; that it was so affixed by order of the Board of Directors of said corporation, and that she/he signed her/his name thereto by like order.

[Signature of Notary Public]

2. A surety bond, as specified in part (d)2 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Financial Guarantee Bond

Date bond executed:

Effective date:

Principal: [legal name and business address of owner or operator]

Type of Organization: [insert "individual," "joint venture," "partnership," or "corporation"]

State of incorporation: \_\_\_\_\_

Surety(ies): [name(s) and business address(es)]

EPA Identification Number, name, address and amount(s) for each facility guaranteed by this bond:

Total penal sum of bond: \$ \_\_\_\_\_ Surety's bond number: \_\_\_\_\_

Know All Persons By These Presents, That we, the Principal and Surety(ies) are firmly bound to the Tennessee Department of Environment and Conservation in the event that the hazardous secondary materials at the reclamation or intermediate facility listed below no longer meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, in the above penal sum for the payment of which we bind ourselves, our heirs, executors, administrators, successors, and assigns jointly and severally; provided that, where the Surety(ies) are corporations acting as co-sureties, we, the Sureties, bind ourselves in such sum "jointly and severally" only for the purpose of allowing a joint action or actions against any or all of us, and for all other purposes each Surety binds itself, jointly and severally with the Principal, for the payment of such sum only as is set forth opposite the name of such Surety, but if no limit of liability is indicated, the limit of liability shall be the full amount of the penal sum.

Whereas said Principal is required, under the Tennessee Hazardous Waste Management Act, to have a permit or interim status in order to own or operate each facility identified above, or to meet conditions under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02; and

Whereas said Principal is required to provide financial assurance as a condition of permit or interim status or as a condition of an exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02;

Now, Therefore, the conditions of the obligation are such that if the Principal shall faithfully satisfy all the conditions established for exclusion of hazardous secondary materials from coverage as solid waste under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02,

Or, if the Principal shall provide alternate financial assurance, as specified in paragraph (8) of Rule 0400-12-01-.02, as applicable, and obtain the Commissioner's written approval of such assurance, within 90 days after the date notice of cancellation is received by both the Principal and the Commissioner from the Surety(ies), then this obligation shall be null and void; otherwise it is to remain in full force and effect.

The Surety(ies) shall become liable on this bond obligation only when the Principal has failed to fulfill the conditions described above. Upon notification by the Commissioner that the Principal has failed to perform as guaranteed by this bond, the Surety(ies) shall forfeit all or a portion of the penal sum of this bond to the Department.

Upon notification by the Commissioner that the Principal has failed to provide alternate financial assurance as specified in paragraph (8) of rule 0400-12-01-.02, and obtain written approval of such assurance from the Commissioner during the 90 days following receipt by both the Principal and the Commissioner of a notice of cancellation of the bond, the Surety(ies) shall forfeit the penal sum of this bond to the Department.

The liability of the Surety(ies) shall not be discharged by any payment or succession of payments hereunder, unless and until such payment or payments shall amount in the aggregate to the penal sum of the bond, but in no event shall the obligation of the Surety(ies) hereunder exceed the amount of said penal sum.

The Surety(ies) may cancel the bond by sending notice of cancellation by certified mail to the Principal and to the Commissioner, provided, however, that cancellation shall not occur during the 120 days beginning on the date of



receipt of the notice of cancellation by both the Principal and the Commissioner, as evidenced by the return receipts.

The Principal may terminate this bond by sending written notice to the Surety(ies), provided, however, that no such notice shall become effective until the Surety(ies) receive(s) written authorization for termination of the bond by the Commissioner.

[The following paragraph is an optional rider that may be included but is not required.]

Principal and Surety(ies) hereby agree to adjust the penal sum of the bond yearly so that it guarantees a new amount, provided that the penal sum does not increase by more than 20 percent in any one year, and no decrease in the penal sum takes place without the written permission of the Commissioner.

In Witness Whereof, the Principal and Surety(ies) have executed this Financial Guarantee Bond and have affixed their seals on the date set forth above.

The persons whose signatures appear below hereby certify that they are authorized to execute this surety bond on behalf of the Principal and Surety(ies) and that the wording of this surety bond is identical to the wording specified in part (8)(l)2 of Rule 0400-12-01-.02 as such rules were constituted on the date this bond was executed.

Principal

[Signature(s)]

\_\_\_\_\_

[Name(s)]

\_\_\_\_\_

[Title(s)]

\_\_\_\_\_

[Corporate seal] \_\_\_\_\_

Corporate Surety(ies)

[Name and address]

State of incorporation: \_\_\_\_\_

Liability limit:

\$ \_\_\_\_\_

[Signature(s)]

[Name(s) and title(s)]

[Corporate seal]

[For every co-surety, provide signature(s), corporate seal, and other information in the same manner as for Surety above.]

Bond premium: \$ \_\_\_\_\_

3. A letter of credit, as specified in part (d)3 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

#### Irrevocable Standby Letter of Credit

Commissioner

Tennessee Department of Environment and Conservation

Dear Sir or Madam: We hereby establish our Irrevocable Standby Letter of Credit No. \_\_\_\_\_ in your favor, in the event that the hazardous secondary materials at the covered reclamation or intermediary facility(ies) no longer meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, at the request and for the account of [owner's or operator's name and address] up to the aggregate amount of [in words] U.S. dollars \$ \_\_\_\_\_, available upon presentation of

- (1) your sight draft, bearing reference to this letter of credit No. \_\_\_\_\_, and
- (2) your signed statement reading as follows: "I certify that the amount of the draft is payable pursuant to rules issued under authority of T.C.A §§ 68-212-101 et seq."

This letter of credit is effective as of [date] and shall expire on [date at least 1 year later], but such expiration date shall be automatically extended for a period of [at least 1 year] on [date] and on each successive expiration date, unless, at least 120 days before the current expiration date, we notify both you and [owner's or operator's name] by certified mail that we have decided not to extend this letter of credit beyond the current expiration date. In the event you are so notified, any unused portion of the credit shall be available upon presentation of your sight draft for 120 days after the date of receipt by both you and [owner's or operator's name], as shown on the signed return receipts.

Whenever this letter of credit is drawn on under and in compliance with the terms of this credit, we shall duly honor such draft upon presentation to us, and we shall pay the amount of the draft to the State of Tennessee in accordance with your instructions.

We certify that the wording of this letter of credit is identical to the wording specified in part (8)(l)3 of Rule 0400-12-01-.02 as such rules were constituted on the date shown immediately below.

[Signature(s) and title(s) of official(s) of issuing institution] [Date]

This credit is subject to [insert "the most recent edition of the Uniform Customs and Practice for Documentary Credits, published and copyrighted by the International Chamber of Commerce," or "the Uniform Commercial Code"].

4. A hazardous secondary material reclamation/intermediate facility endorsement, as specified in part (d)5 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

#### Hazardous Secondary Material Reclamation/Intermediate Facility Endorsement

This endorsement certifies that the policy to which the endorsement is attached provides insurance to provide financial assurance so that in accordance with applicable rules all hazardous secondary materials can be removed from the facility or any unit at the facility and the facility or any unit at the facility can be decontaminated at the facilities identified above. The Insurer further warrants that such policy conforms in all respects with the requirements of part (8)(d)4 of Rule 0400-12-01-.02 as applicable and as such rules were constituted on the effective date of this endorsement. It is agreed that any provision of the policy inconsistent with such rules is hereby amended to eliminate such inconsistency. The coverage applies at [list EPA Identification Number (if any issued), name, and address for each facility]. The limits of liability are [insert the dollar amount], exclusive of legal defense costs.

Whenever requested by the Commissioner of the Tennessee Department of Environment and Conservation, the Insurer agrees to furnish to the Commissioner a duplicate original of the policy listed above, including all endorsements thereon.

I hereby certify that the wording of this endorsement is identical to the wording specified in part (8)(l)4 of Rule 0400-12-01-.02 as such rules were constituted on the date shown immediately below.

[Authorized signature for Insurer]

[Name of person signing]

[Title of person signing]

Signature of witness or notary: \_\_\_\_\_

[Date]

5. A letter from the chief financial officer, as specified in part (d)5 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Letter From Chief Financial Officer

[Address to the Commissioner of the Tennessee Department of Environment and Conservation].

I am the chief financial officer of [name and address of firm]. This letter is in support of this firm's use of the financial test to demonstrate financial assurance, as specified in paragraph (8) of Rule 0400-12-01-.02.

[Fill out the following nine paragraphs regarding facilities and associated cost estimates. If your firm has no facilities that belong in a particular paragraph, write "None" in the space indicated. For each facility, include its EPA Identification Number (if any issued), name, address, and current cost estimates.]

1. This firm is the owner or operator of the following facilities for which financial assurance is demonstrated through the financial test specified in paragraph (8) of Rule 0400-12-01-.02. The current cost estimates covered by the test are shown for each facility: \_\_\_\_\_.
2. This firm guarantees, through the guarantee specified in paragraph (8) of Rule 0400-12-01-.02, the following facilities owned or operated by the guaranteed party. The current cost estimates so guaranteed are shown for each facility: \_\_\_\_\_. The firm identified above is [insert one or more: (1) The direct or higher-tier parent corporation of the owner or operator; (2) owned by the same parent corporation as the parent corporation of the owner or operator, and receiving the following value in consideration of this guarantee \_\_\_\_\_, or (3) engaged in the following substantial business relationship with the owner or operator \_\_\_\_\_], and receiving the following value in consideration of this guarantee \_\_\_\_\_. [Attach a written description of the business relationship or a copy of the contract establishing such relationship to this letter].
3. In states other than Tennessee, this firm, as owner or operator or guarantor, is demonstrating financial assurance for the following facilities through the use of a test equivalent or substantially equivalent to the financial test specified in paragraph (8) of Rule 0400-12-01-.02. The current cost estimates covered by such a test are shown for each facility: \_\_\_\_\_.
4. This firm is the owner or operator of the following hazardous secondary materials management facilities for which financial assurance is required but has not been demonstrated either to EPA or a state through the financial test or any other financial assurance mechanism specified in paragraph (8) of Rule 0400-12-01-.02 or equivalent or substantially equivalent state mechanisms. The current cost estimates not covered by such financial assurance are shown for each facility: \_\_\_\_\_.
5. In states other than Tennessee, this firm, as owner and/or operator or guarantor, is demonstrating financial assurance to the EPA or other federal agency under federal statute or rules, or to a state under substantially equivalent state rules, for the following facilities through the use of a test equivalent or substantially equivalent

to the financial test specified herein, including but not limited to hazardous waste Treatment, Storage and Disposal Facilities ("TSDF") under 40 CFR Part 265, Solid Waste Landfill ("SWLF") facilities under 40 CFR Part 264, Underground Storage Tank ("UST") facilities under 40 CFR Part 280, Underground Injection Control ("UIC") sites under 40 CFR Part 144, the decommissioning of materials facilities licensed by the Nuclear Regulatory Commission under 10 CFR Parts 30, 40, 70, and 72 ("NRC"), and CERCLA settlements under CERCLA § 108(b). The total dollar amount of such financial assurance covered by a financial test is equal, in the aggregate, to [\$ \_\_\_\_\_], and is shown for each facility as follows: \_\_\_\_\_.

6. This firm is the owner or operator of the following facilities for which financial assurance for closure or post-closure care is demonstrated through the financial test specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06. The current closure and/or post-closure cost estimates covered by the test are shown for each facility: \_\_\_\_\_.
7. This firm guarantees, through the guarantee specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06, the closure or post-closure care of the following facilities owned or operated by the guaranteed party. The current cost estimates for the closure or post-closure care so guaranteed are shown for each facility: \_\_\_\_\_. The firm identified above is [insert one or more: (1) The direct or higher-tier parent corporation of the owner or operator; (2) owned by the same parent corporation as the parent corporation of the owner or operator, and receiving the following value in consideration of this guarantee \_\_\_\_\_; or (3) engaged in the following substantial business relationship with the owner or operator \_\_\_\_\_, and receiving the following value in consideration of this guarantee \_\_\_\_\_]. [Attach a written description of the business relationship or a copy of the contract establishing such relationship to this letter].
8. In states other than Tennessee, this firm, as owner or operator or guarantor, is demonstrating financial assurance for the closure or post-closure care of the following facilities through the use of a test equivalent or substantially equivalent to the financial test specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06. The current closure and/or post-closure cost estimates covered by such a test are shown for each facility: \_\_\_\_\_.
9. This firm is the owner or operator of the following SWLF, TSDF, UST, UIC, CERCLA, or NRC facilities for which financial assurance is required but has not been demonstrated either to the EPA or other federal agency or to a state through the financial test or any other financial assurance mechanism. The total dollar amount not covered by such financial assurance is shown for each facility: \_\_\_\_\_.

This firm [insert "is required" or "is not required"] to file a Form 10-K with the Securities and Exchange Commission (SEC) for the latest fiscal year.

The fiscal year of this firm ends on [month, day]. The figures for the following items marked with an asterisk are derived from this firm's independently audited, year-end financial statements for the latest completed fiscal year, ended [date].

[Fill in Alternative I if the criteria of item (d)5(i)(I) of Rule 0400-12-01-.02 are used. Fill in Alternative II if the criteria of item (d)5(i)(II) of Rule 0400-12-01-.02 are used.]

Alternative I

1. Sum of current cost estimates [total of all cost estimates shown in the nine paragraphs above] \$ \_\_\_\_\_
- \*2. Total liabilities [if any portion of the cost estimates is included in total liabilities, you may deduct the amount of that portion from this line and add that amount to lines 3 and 4] \$ \_\_\_\_\_
- \*3. Tangible net worth \$ \_\_\_\_\_
- \*4. Net worth \$ \_\_\_\_\_
- \*5. Current assets \$ \_\_\_\_\_
- \*6. Current liabilities \$ \_\_\_\_\_
7. Net working capital [line 5 minus line 6] \$ \_\_\_\_\_

- \*8. The sum of net income plus depreciation, depletion, and amortization \$ \_\_\_\_\_
- \*9. Total assets in U.S. (required only if less than 90% of firm's assets are located in the U.S.) \$ \_\_\_\_\_
- 10. Is line 3 at least \$10 million? (Yes/No) \_\_\_\_\_
- 11. Is line 3 at least 6 times line 1? (Yes/No) \_\_\_\_\_
- 12. Is line 7 at least 6 times line 1? (Yes/No) \_\_\_\_\_
- \*13. Are at least 90% of firm's assets located in the U.S.? If not, complete line 14 (Yes/No) \_\_\_\_\_
- 14. Is line 9 at least 6 times line 1? (Yes/No) \_\_\_\_\_
- 15. Is line 2 divided by line 4 less than 2.0? (Yes/No) \_\_\_\_\_
- 16. Is line 8 divided by line 2 greater than 0.1? (Yes/No) \_\_\_\_\_
- 17. Is line 5 divided by line 6 greater than 1.5? (Yes/No) \_\_\_\_\_

Alternative II

- 1. Sum of current cost estimates [total of all cost estimates shown in the eight paragraphs above] \$ \_\_\_\_\_
- 2. Current bond rating of most recent issuance of this firm and name of rating service \_\_\_\_\_
- 3. Date of issuance of bond \_\_\_\_\_
- 4. Date of maturity of bond \_\_\_\_\_
- \*5. Tangible net worth [if any portion of the cost estimates is included in "total liabilities" on your firm's financial statements, you may add the amount of that portion to this line] \$ \_\_\_\_\_
- \*6. Total assets in U.S. (required only if less than 90% of firm's assets are located in the U.S.) \$ \_\_\_\_\_
- 7. Is line 5 at least \$10 million? (Yes/No) \_\_\_\_\_
- 8. Is line 5 at least 6 times line 1? (Yes/No) \_\_\_\_\_
- \*9. Are at least 90% of firm's assets located in the U.S.? If not, complete line 10 (Yes/No) \_\_\_\_\_
- 10. Is line 6 at least 6 times line 1? (Yes/No) \_\_\_\_\_

I hereby certify that the wording of this letter is identical to the wording specified in part (8)(l)5 of Rule 0400-12-01-.02 as such rules were constituted on the date shown immediately below.

[Signature] \_\_\_\_\_  
 [Name] \_\_\_\_\_  
 [Title] \_\_\_\_\_  
 [Date] \_\_\_\_\_

6. A letter from the chief financial officer, as specified in part (h)6 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted.

Letter from Chief Financial Officer

[Address to the Commissioner of the Tennessee Department of Environment and Conservation].

I am the chief financial officer of [firm's name and address]. This letter is in support of the use of the financial test to demonstrate financial responsibility for liability coverage under subparagraph (h) [insert "and costs assured under part (d)5" if applicable] as specified in paragraph (8) of Rule 0400-12-01-.02.

[Fill out the following paragraphs regarding facilities and liability coverage. If there are no facilities that belong in a particular paragraph, write "None" in the space indicated. For each facility, include its EPA Identification Number (if any issued), name, and address].

The firm identified above is the owner or operator of the following facilities for which liability coverage for [insert "sudden" or "nonsudden" or "both sudden and nonsudden"] accidental occurrences is being demonstrated through the financial test specified in paragraph (8) of Rule 0400-12-01-.02: \_\_\_\_\_

The firm identified above guarantees, through the guarantee specified in paragraph (8) of Rule 0400-12-01-.02, liability coverage for [insert "sudden" or "nonsudden" or "both sudden and nonsudden"] accidental occurrences at the following facilities owned or operated by the following: \_\_\_\_\_. The firm identified above is [insert one or more: (1) The direct or higher-tier parent corporation of the owner or operator; (2) owned by the same parent corporation as the parent corporation of the owner or operator, and receiving the following value in consideration of this guarantee \_\_\_\_\_; or (3) engaged in the following substantial business relationship with the owner or operator \_\_\_\_\_, and receiving the following value in consideration of this guarantee \_\_\_\_\_]. [Attach a written description of the business relationship or a copy of the contract establishing such relationship to this letter.]

The firm identified above is the owner or operator of the following facilities for which liability coverage for [insert "sudden" or "nonsudden" or "both sudden and nonsudden"] accidental occurrences is being demonstrated through the financial test specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06: \_\_\_\_\_

The firm identified above guarantees, through the guarantee specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06, liability coverage for [insert "sudden" or "nonsudden" or "both sudden and nonsudden"] accidental occurrences at the following facilities owned or operated by the following: \_\_\_\_\_. The firm identified above is [insert one or more: (1) The direct or higher-tier parent corporation of the owner or operator; (2) owned by the same parent corporation as the parent corporation of the owner or operator, and receiving the following value in consideration of this guarantee \_\_\_\_\_; or (3) engaged in the following substantial business relationship with the owner or operator \_\_\_\_\_, and receiving the following value in consideration of this guarantee \_\_\_\_\_]. [Attach a written description of the business relationship or a copy of the contract establishing such relationship to this letter.]

[If you are using the financial test to demonstrate coverage of both liability and costs assured under part (8)(d)5 of Rule 0400-12-01-.02 or closure or post-closure care costs under subparagraph (8)(g) of Rule 0400-12-01-.05 or 0400-12-01-.06, fill in the following nine paragraphs regarding facilities and associated cost estimates. If there are no facilities that belong in a particular paragraph, write "None" in the space indicated. For each facility, include its EPA identification number (if any issued), name, address, and current cost estimates.]

1. This firm is the owner or operator of the following facilities for which financial assurance is demonstrated through the financial test specified in paragraph (8) of Rule 0400-12-01-.02. The current cost estimates covered by the test are shown for each facility: \_\_\_\_\_.
2. This firm guarantees, through the guarantee specified in paragraph (8) of Rule 0400-12-01-.02, the following facilities owned or operated by the guaranteed party. The current cost estimates so guaranteed are shown for each facility: \_\_\_\_\_. The firm identified above is [insert one or more: (1) The direct or higher-tier parent corporation of the owner or operator; (2) owned by the same parent corporation as the parent corporation of the owner or operator, and receiving the following value in consideration of this guarantee \_\_\_\_\_, or (3) engaged in the following substantial business relationship with the owner or operator \_\_\_\_\_, and receiving the following value in consideration of this guarantee \_\_\_\_\_]. [Attach a written description of the business relationship or a copy of the contract establishing such relationship to this letter].

3. In states other than Tennessee, this firm, as owner or operator or guarantor, is demonstrating financial assurance for the following facilities through the use of a test equivalent or substantially equivalent to the financial test specified in paragraph (8) of Rule 0400-12-01-.02. The current cost estimates covered by such a test are shown for each facility: \_\_\_\_\_.
4. This firm is the owner or operator of the following hazardous secondary materials management facilities for which financial assurance is required but has not been demonstrated either to EPA or a state through the financial test or any other financial assurance mechanism specified in paragraph (8) of Rule 0400-12-01-.02 or equivalent or substantially equivalent State mechanisms. The current cost estimates not covered by such financial assurance are shown for each facility: \_\_\_\_\_.
5. In states other than Tennessee, this firm, as owner and/or operator or guarantor, is demonstrating financial assurance to the EPA or other federal agency under federal statute or rules, or to a state under substantially equivalent state rules, for the following facilities through the use of a test equivalent or substantially equivalent to the financial test specified herein, including but not limited to hazardous waste Treatment, Storage and Disposal Facilities ("TSDF") under 40 CFR Part 265, Solid Waste Landfill ("SWLF") facilities under 40 CFR Part 264, Underground Storage Tank ("UST") facilities under 40 CFR Part 280, Underground Injection Control ("UIC") sites under 40 CFR Part 144, the decommissioning of materials facilities licensed by the Nuclear Regulatory Commission under 10 CFR Parts 30, 40, 70, and 72 ("NRC"), and CERCLA settlements under CERCLA § 108(b). The total dollar amount of such financial assurance covered by a financial test is equal, in the aggregate, to [\$\_\_\_\_\_], and is shown for each facility as follows: \_\_\_\_\_.
6. This firm is the owner or operator of the following facilities for which financial assurance for closure or post-closure care is demonstrated through the financial test specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06. The current closure and/or post-closure cost estimates covered by the test are shown for each facility: \_\_\_\_\_.
7. This firm guarantees, through the guarantee specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06, the closure or post-closure care of the following facilities owned or operated by the guaranteed party. The current cost estimates for the closure or post-closure care so guaranteed are shown for each facility: \_\_\_\_\_. The firm identified above is [insert one or more: (1) The direct or higher-tier parent corporation of the owner or operator; (2) owned by the same parent corporation as the parent corporation of the owner or operator, and receiving the following value in consideration of this guarantee \_\_\_\_\_; or (3) engaged in the following substantial business relationship with the owner or operator \_\_\_\_\_, and receiving the following value in consideration of this guarantee \_\_\_\_\_].

[Attach a written description of the business relationship or a copy of the contract establishing such relationship to this letter].

8. In states other than Tennessee, this firm, as owner or operator or guarantor, is demonstrating financial assurance for the closure or post-closure care of the following facilities through the use of a test equivalent or substantially equivalent to the financial test specified in paragraph (8) of Rules 0400-12-01-.05 and 0400-12-01-.06. The current closure and/or post-closure cost estimates covered by such a test are shown for each facility: \_\_\_\_\_.
9. This firm is the owner or operator of the following SWLF, TSDF, UST, UIC, CERCLA, or NRC facilities for which financial assurance is required but has not been demonstrated either to the EPA or other federal agency or to a state through the financial test or any other financial assurance mechanism. The total dollar amount not covered by such financial assurance is shown for each facility: \_\_\_\_\_.

This firm [insert "is required" or "is not required"] to file a Form 10-K with the Securities and Exchange Commission (SEC) for the latest fiscal year.

The fiscal year of this firm ends on [month, day]. The figures for the following items marked with an asterisk are derived from this firm's independently audited, year-end financial statements for the latest completed fiscal year, ended [date].

#### Part A. Liability Coverage for Accidental Occurrences

[Fill in Alternative I if the criteria of item (h)6(i)(I) of Rule 0400-12-01-.02 are used. Fill in Alternative II if the criteria of item (h)6(i)(II) of Rule 0400-12-01-.02 are used.]

Alternative I

1. Amount of annual aggregate liability coverage to be demonstrated \$ \_\_\_\_\_.
- \*2. Current assets \$ \_\_\_\_\_.
- \*3. Current liabilities \$ \_\_\_\_\_.
4. Net working capital (line 2 minus line 3) \$ \_\_\_\_\_.
- \*5. Tangible net worth \$ \_\_\_\_\_.
- \*6. If less than 90% of assets are located in the U.S., give total U.S. assets \$ \_\_\_\_\_.
7. Is line 5 at least \$10 million? (Yes/No) \_\_\_\_\_.
8. Is line 4 at least 6 times line 1? (Yes/No) \_\_\_\_\_.
9. Is line 5 at least 6 times line 1? (Yes/No) \_\_\_\_\_.
- \*10. Are at least 90% of assets located in the U.S.? (Yes/No) \_\_\_\_\_. If not, complete line 11.
11. Is line 6 at least 6 times line 1? (Yes/No) \_\_\_\_\_.

Alternative II

1. Amount of annual aggregate liability coverage to be demonstrated \$ \_\_\_\_\_.
2. Current bond rating of most recent issuance and name of rating service \_\_\_\_\_.
3. Date of issuance of bond \_\_\_\_\_.
4. Date of maturity of bond \_\_\_\_\_.
- \*5. Tangible net worth \$ \_\_\_\_\_.
- \*6. Total assets in U.S. (required only if less than 90% of assets are located in the U.S.) \$ \_\_\_\_\_.
7. Is line 5 at least \$10 million? (Yes/No) \_\_\_\_\_.
8. Is line 5 at least 6 times line 1? \_\_\_\_\_.
9. Are at least 90% of assets located in the U.S.? If not, complete line 10. (Yes/No) \_\_\_\_\_.
10. Is line 6 at least 6 times line 1? \_\_\_\_\_.

[Fill in part B if you are using the financial test to demonstrate assurance of both liability coverage and costs assured under part (8)(d)5 of Rule 0400-12-01-.02 or closure or post-closure care costs under subparagraph (g) of Rule 0400-12-01-.05 or 0400-12-01-.06.]

Part B. Facility Care and Liability Coverage

[Fill in Alternative I if the criteria of item (8)(d)5(i)(I) and item (8)(h)6(i)(I) of Rule 0400-12-01-.02 are used. Fill in Alternative II if the criteria of item (8)(d)5(i)(II) and item (8)(h)6(i)(II) of Rule 0400-12-01-.02 are used.]

Alternative I



1. Sum of current cost estimates (total of all cost estimates listed above) \$ \_\_\_\_\_
2. Amount of annual aggregate liability coverage to be demonstrated \$ \_\_\_\_\_
3. Sum of lines 1 and 2 \$ \_\_\_\_\_
- \*4. Total liabilities (if any portion of your cost estimates is included in your total liabilities, you may deduct that portion from this line and add that amount to lines 5 and 6) \$ \_\_\_\_\_
- \*5. Tangible net worth \$ \_\_\_\_\_
- \*6. Net worth \$ \_\_\_\_\_
- \*7. Current assets \$ \_\_\_\_\_
- \*8. Current liabilities \$ \_\_\_\_\_
9. Net working capital (line 7 minus line 8) \$ \_\_\_\_\_
- \*10. The sum of net income plus depreciation, depletion, and amortization \$ \_\_\_\_\_
- \*11. Total assets in U.S. (required only if less than 90% of assets are located in the U.S.) \$ \_\_\_\_\_
12. Is line 5 at least \$10 million? (Yes/No) \_\_\_\_\_
13. Is line 5 at least 6 times line 3? (Yes/No) \_\_\_\_\_
14. Is line 9 at least 6 times line 3? (Yes/No) \_\_\_\_\_
- \*15. Are at least 90% of assets located in the U.S.? (Yes/No) If not, complete line 16. \_\_\_\_\_
16. Is line 11 at least 6 times line 3? (Yes/No) \_\_\_\_\_
17. Is line 4 divided by line 6 less than 2.0? (Yes/No) \_\_\_\_\_
18. Is line 10 divided by line 4 greater than 0.1? (Yes/No) \_\_\_\_\_
19. Is line 7 divided by line 8 greater than 1.5? (Yes/No) \_\_\_\_\_

Alternative II

1. Sum of current cost estimates (total of all cost estimates listed above) \$ \_\_\_\_\_
2. Amount of annual aggregate liability coverage to be demonstrated \$ \_\_\_\_\_
3. Sum of lines 1 and 2 \$ \_\_\_\_\_
4. Current bond rating of most recent issuance and name of rating service \_\_\_\_\_
5. Date of issuance of bond \_\_\_\_\_
6. Date of maturity of bond \_\_\_\_\_
- \*7. Tangible net worth (if any portion of the cost estimates is included in "total liabilities" on your financial statements you may add that portion to this line) \$ \_\_\_\_\_
- \*8. Total assets in the U.S. (required only if less than 90% of assets are located in the U.S.) \$ \_\_\_\_\_
9. Is line 7 at least \$10 million? (Yes/No) \_\_\_\_\_

10. Is line 7 at least 6 times line 3? (Yes/No) \_\_\_\_\_  
\*11. Are at least 90% of assets located in the U.S.? (Yes/No) If not complete line 12. \_\_\_\_\_

12. Is line 8 at least 6 times line 3? (Yes/No) \_\_\_\_\_

I hereby certify that the wording of this letter is identical to the wording specified in part (8)(l)6 of Rule 0400-12-01-.02 as such rules were constituted on the date shown immediately below.

[Signature] \_\_\_\_\_

[Name] \_\_\_\_\_

[Title] \_\_\_\_\_

[Date] \_\_\_\_\_

7. (i) A corporate guarantee, as specified in part (d)5 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

#### Corporate Guarantee for Facility Care

Guarantee made this [date] by [name of guaranteeing entity], a business corporation organized under the laws of the state of Tennessee, herein referred to as guarantor. This guarantee is made on behalf of the [owner or operator] of [business address], which is [one of the following: "our subsidiary"; "a subsidiary of [name and address of common parent corporation], of which guarantor is a subsidiary"; or "an entity with which guarantor has a substantial business relationship, as defined in part (8)(b)9 of Rules 0400-12-01-.05 and 0400-12-01-.06" to the Tennessee Department of Environment and Conservation.

#### Recitals

1. Guarantor meets or exceeds the financial test criteria and agrees to comply with the reporting requirements for guarantors as specified in part (8)(d)5 of Rule 0400-12-01-.02.
2. [Owner or operator] owns or operates the following facility(ies) covered by this guarantee: [List for each facility: EPA Identification Number (if any issued), name, and address].
3. "Closure plans" as used below refer to the plans maintained as required by paragraph (8) of Rule 0400-12-01-.02 for the care of facilities as identified above.
4. For value received from [owner or operator], guarantor guarantees that in the event of a determination by the Commissioner that the hazardous secondary materials at the owner or operator's facility covered by this guarantee do not meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, the guarantor will dispose of any hazardous secondary material as hazardous waste, and close the facility in accordance with closure requirements found in Rule 0400-12-01-.05 or 0400-12-01-.06, as applicable, or establish a trust fund as specified in part (8)(d)1 of Rule 0400-12-01-.02 in the name of the owner or operator in the amount of the current cost estimate.
5. Guarantor agrees that if, at the end of any fiscal year before termination of this guarantee, the guarantor fails to meet the financial test criteria, guarantor shall send within 90 days, by certified mail, notice to the Commissioner and to [owner or operator] that he intends to provide alternate financial assurance as specified in paragraph (8) of Rule 0400-12-01-.02, as applicable, in the name of [owner or operator]. Within 120 days after the end of such fiscal year, the guarantor shall establish such financial assurance unless [owner or operator] has done so.
6. The guarantor agrees to notify the Commissioner by certified mail, of a voluntary or involuntary proceeding under Title 11 (Bankruptcy), U.S. Code, naming guarantor as debtor, within 10 days after commencement of the proceeding.

7. Guarantor agrees that within 30 days after being notified by the Commissioner of a determination that guarantor no longer meets the financial test criteria or that he is disallowed from continuing as a guarantor, he shall establish alternate financial assurance as specified in Rule 0400-12-01-.05, Rule 0400-12-01-.06, or paragraph (8) of Rule 0400-12-01-.02, as applicable, in the name of [owner or operator] unless [owner or operator] has done so.
8. Guarantor agrees to remain bound under this guarantee notwithstanding any or all of the following: amendment or modification of the closure plan, the extension or reduction of the time of performance, or any other modification or alteration of an obligation of the owner or operator pursuant to Rule 0400-12-01-.05, Rule 0400-12-01-.06, or paragraph (8) of Rule 0400-12-01-.02.
9. Guarantor agrees to remain bound under this guarantee for as long as [owner or operator] must comply with the applicable financial assurance requirements of Rules 0400-12-01-.05 and 0400-12-01-.06 or the financial assurance condition of subitem (1)(d)1(xxiv)(IV)IV of Rule 0400-12-01-.02 for the above-listed facilities, except as provided in paragraph 10 of this agreement.
10. [Insert the following language if the guarantor is (a) a direct or higher-tier corporate parent, or (b) a firm whose parent corporation is also the parent corporation of the owner or operator]:

Guarantor may terminate this guarantee by sending notice by certified mail to the Commissioner and to [owner or operator], provided that this guarantee may not be terminated unless and until [the owner or operator] obtains, and the Commissioner approves, alternate coverage complying with subparagraph (8)(d) of Rule 0400-12-01-.02.

[Insert the following language if the guarantor is a firm qualifying as a guarantor due to its “substantial business relationship” with the owner or operator]

Guarantor may terminate this guarantee 120 days following the receipt of notification, through certified mail, by the Commissioner and by [the owner or operator].

11. Guarantor agrees that if [owner or operator] fails to provide alternate financial assurance as specified in Rule 0400-12-01-.05, 0400-12-01-.06, or paragraph (8) of Rule 0400-12-01-.02, as applicable, and obtain written approval of such assurance from the Commissioner within 90 days after a notice of cancellation by the guarantor is received by Commissioner from guarantor, guarantor shall provide such alternate financial assurance in the name of [owner or operator].
12. Guarantor expressly waives notice of acceptance of this guarantee by the Commissioner or by [owner or operator]. Guarantor also expressly waives notice of amendments or modifications of the closure plan and of amendments or modifications of the applicable requirements of Rule 0400-12-01-.05, 0400-12-01-.06, or paragraph (8) of Rule 0400-12-01-.02.

I hereby certify that the wording of this guarantee is identical to the wording specified in subpart (8)(l)7(i) of Rule 0400-12-01-.02 as such rules were constituted on the date first above written.

Effective date: \_\_\_\_\_

[Name of guarantor] \_\_\_\_\_

[Authorized signature for guarantor] \_\_\_\_\_

[Name of person signing] \_\_\_\_\_

[Title of person signing] \_\_\_\_\_

Signature of witness or notary: \_\_\_\_\_

- (ii) A guarantee, as specified in part (8)(h)7 of Rule 0400-12-01-.02, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

## Guarantee for Liability Coverage

Guarantee made this [date] by [name of guaranteeing entity], a business corporation organized under the laws of [if incorporated within the United States insert "the state of \_\_\_\_\_" and insert name of state; if incorporated outside the United States insert the name of the country in which incorporated, the principal place of business within the United States, and the name and address of the registered agent in the state of the principal place of business], herein referred to as guarantor. This guarantee is made on behalf of [owner or operator] of [business address], which is one of the following: "our subsidiary;" "a subsidiary of [name and address of common parent corporation], of which guarantor is a subsidiary;" or "an entity with which guarantor has a substantial business relationship, as defined in [either part (8)(b)9 of Rule 0400-12-01-.05 or part (8)(b)9 of Rule 0400-12-01-.06], to any and all third parties who have sustained or may sustain bodily injury or property damage caused by [sudden and/or nonsudden] accidental occurrences arising from operation of the facility(ies) covered by this guarantee.

### Recitals

1. Guarantor meets or exceeds the financial test criteria and agrees to comply with the reporting requirements for guarantors as specified in part (8)(h)7 of Rule 0400-12-01-.02.

2. [Owner or operator] owns or operates the following facility(ies) covered by this guarantee: [List for each facility:

EPA identification number (if any issued), name, and address; and if guarantor is incorporated outside the United States list the name and address of the guarantor's registered agent in each state.] This corporate guarantee satisfies the paragraph (8) of Rule 0400-12-01-.02 third-party liability requirements for [insert "sudden" or "nonsudden" or "both sudden and nonsudden"] accidental occurrences in above-named owner or operator facilities for overage in the amount of [insert dollar amount] for each occurrence and [insert dollar amount] annual aggregate.

3. For value received from [owner or operator], guarantor guarantees to any and all third parties who have sustained or may sustain bodily injury or property damage caused by [sudden and/or nonsudden] accidental occurrences arising from operations of the facility(ies) covered by this guarantee that in the event that [owner or operator] fails to satisfy a judgment or award based on a determination of liability for bodily injury or property damage to third parties caused by [sudden and/or nonsudden] accidental occurrences, arising from the operation of the above-named facilities, or fails to pay an amount agreed to in settlement of a claim arising from or alleged to arise from such injury or damage, the guarantor will satisfy such judgment(s), award(s) or settlement agreement(s) up to the limits of coverage identified above.

4. Such obligation does not apply to any of the following:

(a) Bodily injury or property damage for which [insert owner or operator] is obligated to pay damages by reason of the assumption of liability in a contract or agreement. This exclusion does not apply to liability for damages that [insert owner or operator] would be obligated to pay in the absence of the contract or agreement.

(b) Any obligation of [insert owner or operator] under a workers' compensation, disability benefits, or unemployment compensation law or any similar law.

(c) Bodily injury to:

(1) An employee of [insert owner or operator] arising from, and in the course of, employment by [insert owner or operator]; or

(2) The spouse, child, parent, brother, or sister of that employee as a consequence of, or arising from, and in the course of employment by [insert owner or operator]. This exclusion applies:

(A) Whether [insert owner or operator] may be liable as an employer or in any other capacity; and

(B) To any obligation to share damages with or repay another person who must pay damages because of the injury to persons identified in paragraphs (1) and (2).

(d) Bodily injury or property damage arising out of the ownership, maintenance, use, or entrustment to others of any aircraft, motor vehicle or watercraft.

(e) Property damage to:

(1) Any property owned, rented, or occupied by [insert owner or operator];

(2) Premises that are sold, given away or abandoned by [insert owner or operator] if the property damage arises out of any part of those premises;

(3) Property loaned to [insert owner or operator];

(4) Personal property in the care, custody or control of [insert owner or operator];

(5) That particular part of real property on which [insert owner or operator] or any contractors or subcontractors working directly or indirectly on behalf of [insert owner or operator] are performing operations, if the property damage arises out of these operations.

5. Guarantor agrees that if, at the end of any fiscal year before termination of this guarantee, the guarantor fails to meet the financial test criteria, guarantor shall send within 90 days, by certified mail, notice to the Commissioner and to [owner or operator] that he intends to provide alternate liability coverage as specified in subparagraph (8)(h) of Rule 0400-12-01-.02, as applicable, in the name of [owner or operator]. Within 120 days after the end of such fiscal year, the guarantor shall establish such liability coverage unless [owner or operator] has done so.

6. The guarantor agrees to notify the Commissioner by certified mail of a voluntary or involuntary proceeding under title 11 (Bankruptcy), U.S. Code, naming guarantor as debtor, within 10 days after commencement of the proceeding. Guarantor agrees that within 30 days after being notified by the Commissioner of a determination that guarantor no longer meets the financial test criteria or that he is disallowed from continuing as a guarantor, he shall establish alternate liability coverage as specified in subparagraph (8)(h) of Rule 0400-12-01-.02 in the name of [owner or operator], unless [owner or operator] has done so.

7. Guarantor reserves the right to modify this agreement to take into account amendment or modification of the liability requirements set by subparagraph (8)(h) of Rule 0400-12-01-.02, provided that such modification shall become effective only if the Commissioner does not disapprove the modification within 30 days of receipt of notification of the modification.

8. Guarantor agrees to remain bound under this guarantee for so long as [owner or operator] must comply with the applicable requirements of subparagraph (8)(h) of Rule 0400-12-01-.02 for the above-listed facility(ies), except as provided in paragraph 10 of this agreement.

9. [Insert the following language if the guarantor is (a) a direct or higher-tier corporate parent, or (b) a firm whose parent corporation is also the parent corporation of the owner or operator]:

10. Guarantor may terminate this guarantee by sending notice by certified mail to the Commissioner and to [owner or operator], provided that this guarantee may not be terminated unless and until [the owner or operator] obtains, and the Commissioner approves, alternate liability coverage complying with subparagraph (8)(h) of Rule 0400-12-01-.02.

[Insert the following language if the guarantor is a firm qualifying as a guarantor due to its "substantial business relationship" with the owner or operator]:

Guarantor may terminate this guarantee 120 days following receipt of notification, through certified mail, by the Commissioner and by [the owner or operator].

11. Guarantor hereby expressly waives notice of acceptance of this guarantee by any party.

12. Guarantor agrees that this guarantee is in addition to and does not affect any other responsibility or liability of the guarantor with respect to the covered facilities.

13. The Guarantor shall satisfy a third-party liability claim only on receipt of one of the following documents:

- (a) Certification from the Principal and the third-party claimant(s) that the liability claim should be paid. The certification must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Certification of Valid Claim

The undersigned, as parties [insert Principal] and [insert name and address of third-party claimant(s)], hereby certify that the claim of bodily injury and/or property damage caused by a [sudden or nonsudden] accidental occurrence arising from operating [Principal's] facility should be paid in the amount of \$ \_\_\_\_.

[Signatures] \_\_\_\_\_

Principal \_\_\_\_\_

(Notary) Date \_\_\_\_\_

[Signatures] \_\_\_\_\_

Claimant(s) \_\_\_\_\_

(Notary) Date \_\_\_\_\_

- (b) A valid final court order establishing a judgment against the Principal for bodily injury or property damage caused by sudden or nonsudden accidental occurrences arising from the operation of the Principal's facility or group of facilities.

14. In the event of combination of this guarantee with another mechanism to meet liability requirements, this guarantee will be considered [insert "primary" or "excess"] coverage.

I hereby certify that the wording of the guarantee is identical to the wording specified in subpart (8)(l)7(ii) of Rule 0400-12-01-.02 as such rules were constituted on the date shown immediately below.

Effective date: \_\_\_\_\_

[Name of guarantor] \_\_\_\_\_

[Authorized signature for guarantor] \_\_\_\_\_

[Name of person signing] \_\_\_\_\_

[Title of person signing] \_\_\_\_\_

Signature of witness or notary: \_\_\_\_\_

- 8. A hazardous waste facility liability endorsement as required in subparagraph (h) of this paragraph must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Hazardous Secondary Material Reclamation/Intermediate Facility Liability Endorsement

- 1. This endorsement certifies that the policy to which the endorsement is attached provides liability insurance covering bodily injury and property damage in connection with the insured's obligation to demonstrate financial responsibility under subparagraph (8)(h) of Rule 0400-12-01-.02. The coverage applies at [list EPA Identification Number (if any issued), name, and address for each facility] for [insert "sudden accidental occurrences," "nonsudden accidental occurrences," or "sudden and nonsudden accidental occurrences"; if coverage is for multiple facilities and the coverage is different for different facilities, indicate which facilities are insured for sudden accidental occurrences, which are insured for nonsudden accidental occurrences, and

which are insured for both]. The limits of liability are [insert the dollar amount of the "each occurrence" and "annual aggregate" limits of the Insurer's liability], exclusive of legal defense costs.

2. The insurance afforded with respect to such occurrences is subject to all of the terms and conditions of the policy; provided, however, that any provisions of the policy inconsistent with subsections (a) through (e) of this Paragraph 2 are hereby amended to conform with subsections (a) through (e):
  - (a) Bankruptcy or insolvency of the insured shall not relieve the Insurer of its obligations under the policy to which this endorsement is attached.
  - (b) The Insurer is liable for the payment of amounts within any deductible applicable to the policy, with a right of reimbursement by the insured for any such payment made by the Insurer. This provision does not apply with respect to that amount of any deductible for which coverage is demonstrated as specified in part (8)(h)6 of Rule 0400-12-01-.02.
  - (c) Whenever requested by the Commissioner of the Tennessee Department of Environment and Conservation, the Insurer agrees to furnish to the Commissioner a signed duplicate original of the policy and all endorsements.
  - (d) Cancellation of this endorsement or the policy, whether by the Insurer, the insured, a parent corporation providing insurance coverage for its subsidiary, or by a firm having an insurable interest in and obtaining liability insurance on behalf of the owner or operator of the facility, will be effective only upon written notice and only after the expiration of 60 days after a copy of such written notice is received by the Commissioner.
  - (e) Any other termination of this endorsement or the policy will be effective only upon written notice and only after the expiration of 30 days after a copy of such written notice is received by the Commissioner.

Attached to and forming part of policy No. \_\_\_\_\_ issued by [name of Insurer], herein called the Insurer, of [address of Insurer] to [name of insured] of [address] this \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_. The effective date of said policy is \_\_\_\_\_ day of \_\_\_\_\_, \_\_\_\_\_.

I hereby certify that the wording of this endorsement is identical to the wording specified in part (8)(l)8 of Rule 0400-12-01-.02 as such rule was constituted on the date first above written, and that the Insurer is licensed to transact the business of insurance, or eligible to provide insurance as an excess or surplus lines insurer in Tennessee.

[Signature of Authorized Representative of Insurer] \_\_\_\_\_

[Type name] \_\_\_\_\_

[Title], Authorized Representative of [name of Insurer] \_\_\_\_\_

[Address of Representative] \_\_\_\_\_

9. A letter of credit, as specified in part (h)8 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Irrevocable Standby Letter of Credit

Name and Address of Issuing Institution \_\_\_\_\_

Commissioner \_\_\_\_\_

Tennessee Department of Environment and Conservation

Dear Sir or Madam: We hereby establish our Irrevocable Standby Letter of Credit No. \_\_\_\_\_ in the favor of ["any and all third-party liability claimants"], at the request and for the account of [owner or operator's name and address] for third-party liability awards or settlements up to [in words] U.S. dollars \$ \_\_\_\_\_ per

occurrence and the annual aggregate amount of [in words] U.S. dollars \$ \_\_\_\_\_, for sudden accidental occurrences and/or for third-party liability awards or settlements up to the amount of [in words] U.S. dollars \$ \_\_\_\_\_ per occurrence, and the annual aggregate amount of [in words] U.S. dollars \$ \_\_\_\_\_, for nonsudden accidental occurrences available upon presentation of a sight draft bearing reference to this letter of credit No. \_\_\_\_\_, and (1) a signed certificate reading as follows:

Certificate of Valid Claim

The undersigned, as parties [insert principal] and [insert name and address of third party claimant(s)], hereby certify that the claim of bodily injury and/or property damage caused by a [sudden or nonsudden] accidental occurrence arising from operations of [principal's] facility should be paid in the amount of \$[ ]. We hereby certify that the claim does not apply to any of the following:

- (a) Bodily injury or property damage for which [insert principal] is obligated to pay damages by reason of the assumption of liability in a contract or agreement. This exclusion does not apply to liability for damages that [insert principal] would be obligated to pay in the absence of the contract or agreement.
- (b) Any obligation of [insert principal] under a workers' compensation, disability benefits, or unemployment compensation law or any similar law.
- (c) Bodily injury to:
  - (1) An employee of [insert principal] arising from, and in the course of, employment by [insert principal]; or
  - (2) The spouse, child, parent, brother or sister of that employee as a consequence of, or arising from, and in the course of employment by [insert principal]. This exclusion applies:
    - (A) Whether [insert principal] may be liable as an employer or in any other capacity; and
    - (B) To any obligation to share damages with or repay another person who must pay damages because of the injury to persons identified in paragraphs (1) and (2).
- (d) Bodily injury or property damage arising out of the ownership, maintenance, use, or entrustment to others of any aircraft, motor vehicle or watercraft.
- (e) Property damage to:
  - (1) Any property owned, rented, or occupied by [insert principal];
  - (2) Premises that are sold, given away or abandoned by [insert principal] if the property damage arises out of any part of those premises;
  - (3) Property loaned to [insert principal];
  - (4) Personal property in the care, custody or control of [insert principal];
  - (5) That particular part of real property on which [insert principal] or any contractors or subcontractors working directly or indirectly on behalf of [insert principal] are performing operations, if the property damage arises out of these operations.

[Signatures] \_\_\_\_\_

Grantor \_\_\_\_\_

[Signatures] \_\_\_\_\_

Claimant(s) \_\_\_\_\_



or (2) a valid final court order establishing a judgment against the Grantor for bodily injury or property damage caused by sudden or nonsudden accidental occurrences arising from the operation of the Grantor's facility or group of facilities.

This letter of credit is effective as of [date] and shall expire on [date at least one year later], but such expiration date shall be automatically extended for a period of [at least one year] on [date and on each successive expiration date, unless, at least 120 days before the current expiration date, we notify you, the Commissioner of the Tennessee Department of Environment and Conservation, and [owner's or operator's name] by certified mail that we have decided not to extend this letter of credit beyond the current expiration date.

Whenever this letter of credit is drawn on under and in compliance with the terms of this credit, we shall duly honor such draft upon presentation to us.

In the event that this letter of credit is used in combination with another mechanism for liability coverage, this letter of credit shall be considered [insert "primary" or "excess" coverage].

We certify that the wording of this letter of credit is identical to the wording specified in part (8)(l)9 of Rule 0400-12-01-.02 as such rules were constituted on the date shown immediately below.

[Signature(s) and title(s) of official(s) of issuing institution]

[Date].

This credit is subject to [insert "the most recent edition of the Uniform Customs and Practice for Documentary Credits, published and copyrighted by the International Chamber of Commerce," or "the Uniform Commercial Code"].

10. A surety bond, as specified in part (h)9 of this paragraph, must be worded as follows: except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

#### Payment Bond

Surety Bond No. [Insert number]

Parties [Insert name and address of owner or operator],

Principal, incorporated in [Insert State of incorporation] of [Insert city and State of principal place of business] and [Insert name and address of surety company(ies)], Surety Company(ies), of [Insert surety(ies) place of business].

EPA Identification Number (if any issued), name, and address for each facility guaranteed by this bond: \_\_\_\_\_

	Nonsudden accidental occurrence	Sudden accidental occurrences
Penal Sum Per Occurrence	[Insert amount]	[Insert amount]
Annual Aggregate	[Insert amount]	[Insert amount]

Purpose: This is an agreement between the Surety(ies) and the Principal under which the Surety(ies), its(their) successors and assignees, agree to be responsible for the payment of claims against the Principal for bodily injury and/or property damage to third parties caused by ["sudden" and/or "nonsudden"] accidental occurrences arising from operations of the facility or group of facilities in the sums prescribed herein; subject to the governing provisions and the following conditions.

Governing Provisions:

- (1) Tennessee Hazardous Waste Management Act, as amended.
- (2) Rule Chapter 0400-12-01, particularly Rule 0400-12-01-.05, Rule 0400-12-01-.06, and paragraph (8) of Rule 0400-12-01-.02 (if applicable).

Conditions:

- (1) The Principal is subject to the applicable governing provisions that require the Principal to have and maintain liability coverage for bodily injury and property damage to third parties caused by ["sudden" and/or "nonsudden"] accidental occurrences arising from operations of the facility or group of facilities. Such obligation does not apply to any of the following:
  - (a) Bodily injury or property damage for which [insert Principal] is obligated to pay damages by reason of the assumption of liability in a contract or agreement. This exclusion does not apply to liability for damages that [insert Principal] would be obligated to pay in the absence of the contract or agreement.
  - (b) Any obligation of [insert Principal] under a workers' compensation, disability benefits, or unemployment compensation law or similar law.
  - (c) Bodily injury to:
    - (1) An employee of [insert Principal] arising from, and in the course of, employment by [insert principal]; or
    - (2) The spouse, child, parent, brother or sister of that employee as a consequence of, or arising from, and in the course of employment by [insert Principal]. This exclusion applies:
      - (A) Whether [insert Principal] may be liable as an employer or in any other capacity; and
      - (B) To any obligation to share damages with or repay another person who must pay damages because of the injury to persons identified in paragraphs (1) and (2).
  - (d) Bodily injury or property damage arising out of the ownership, maintenance, use, or entrustment to others of any aircraft, motor vehicle or watercraft.
  - (e) Property damage to:
    - (1) Any property owned, rented, or occupied by [insert Principal];
    - (2) Premises that are sold, given away or abandoned by [insert Principal] if the property damage arises out of any part of those premises;
    - (3) Property loaned to [insert Principal];
    - (4) Personal property in the care, custody or control of [insert Principal];
    - (5) That particular part of real property on which [insert Principal] or any contractors or subcontractors working directly or indirectly on behalf of [insert Principal] are performing operations, if the property damage arises out of these operations.
- (2) This bond assures that the Principal will satisfy valid third party liability claims, as described in condition (1).
- (3) If the Principal fails to satisfy a valid third party liability claim, as described above, the Surety(ies) becomes liable on this bond obligation.
- (4) The Surety(ies) shall satisfy a third party liability claim only upon the receipt of one of the following documents:
  - (a) Certification from the Principal and the third party claimant(s) that the liability claim should be paid. The certification must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Certification of Valid Claim

The undersigned, as parties [insert name of Principal] and [insert name and address of third party claimant(s)], hereby certify that the claim of bodily injury and/or property damage caused by a [sudden or nonsudden] accidental occurrence arising from operating [Principal's] facility should be paid in the amount of \$[ ].

[Signature] \_\_\_\_\_

Principal \_\_\_\_\_

[Notary] Date \_\_\_\_\_

[Signature(s)] \_\_\_\_\_

Claimant(s) \_\_\_\_\_

[Notary] Date \_\_\_\_\_

or

- (b) A valid final court order establishing a judgment against the Principal for bodily injury or property damage caused by sudden or nonsudden accidental occurrences arising from the operation of the Principal's facility or group of facilities.
- (5) In the event of combination of this bond with another mechanism for liability coverage, this bond will be considered [insert "primary" or "excess"] coverage.
- (6) The liability of the Surety(ies) shall not be discharged by any payment or succession of payments hereunder, unless and until such payment or payments shall amount in the aggregate to the penal sum of the bond. In no event shall the obligation of the Surety(ies) hereunder exceed the amount of said annual aggregate penal sum, provided that the Surety(ies) furnish(es) notice to the Commissioner of the Tennessee Department of Environment and Conservation forthwith of all claims filed and payments made by the Surety(ies) under this bond.
- (7) The Surety(ies) may cancel the bond by sending notice of cancellation by certified mail to the Principal and the Commissioner of the Tennessee Department of Environment and Conservation, provided, however, that cancellation shall not occur during the 120 days beginning on the date of receipt of the notice of cancellation by the Principal and the Commissioner, as evidenced by the return receipt.
- (8) The Principal may terminate this bond by sending written notice to the Surety(ies) and to the Commissioner.
- (9) The Surety(ies) hereby waive(s) notification of amendments to applicable laws, statutes, rules and regulations and agree(s) that no such amendment shall in any way alleviate its (their) obligation on this bond.
- (10) This bond is effective from [insert date] (12:01 a.m., standard time, at the address of the Principal as stated herein) and shall continue in force until terminated as described above.

In Witness Whereof, the Principal and Surety(ies) have executed this Bond and have affixed their seals on the date set forth above.

The persons whose signatures appear below hereby certify that they are authorized to execute this surety bond on behalf of the Principal and Surety(ies) and that the wording of this surety bond is identical to the wording specified in part (8)(l)10 of Rule 0400-12-01-.02, as such rules were constituted on the date this bond was executed.

PRINCIPAL

[Signature(s)]

[Name(s)]

[Title(s)]

[Corporate Seal]

CORPORATE SURETY[IES]

[Name and address]

State of incorporation: \_\_\_\_\_

Liability Limit: \$ \_\_\_\_\_

[Signature(s)]

[Name(s) and title(s)]

[Corporate seal]

[For every co-surety, provide signature(s), corporate seal, and other information in the same manner as for Surety above.]

Bond premium: \$ \_\_\_\_\_

11. (i) A trust agreement, as specified in part (h)10 of this paragraph, must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

#### Trust Agreement

Trust Agreement, the "Agreement," entered into as of [date] by and between [name of the owner or operator] a [name of state] [insert "corporation," "partnership," "association," or "proprietorship"], the "Grantor," and [name of corporate trustee], [insert, "incorporated in the state of \_\_\_\_\_" or "a national bank"], the "Trustee."

Whereas, the Underground Storage Tanks and Solid Waste Disposal Control Board, an agency of the State of Tennessee, has established certain regulations applicable to the Grantor, requiring that an owner or operator must demonstrate financial responsibility for bodily injury and property damage to third parties caused by sudden accidental and/or nonsudden accidental occurrences arising from operations of the facility or group of facilities.

Whereas, the Grantor has elected to establish a trust to assure all or part of such financial responsibility for the facilities identified herein.

Whereas, the Grantor, acting through its duly authorized officers, has selected the Trustee to be the trustee under this agreement, and the Trustee is willing to act as trustee.

Now, therefore, the Grantor and the Trustee agree as follows:

#### Section 1. Definitions.

As used in this Agreement:

- (a) The term "Grantor" means the owner or operator who enters into this Agreement and any successors or assigns of the Grantor.
- (b) The term "Trustee" means the Trustee who enters into this Agreement and any successor Trustee.

#### Section 2. Identification of Facilities.

This agreement pertains to the facilities identified on attached schedule A [on schedule A, for each facility list the EPA Identification Number (if any issued), name, and address of the facility(ies) and the amount of liability

coverage, or portions thereof, if more than one instrument affords combined coverage as demonstrated by this Agreement].

### Section 3. Establishment of Fund.

The Grantor and the Trustee hereby establish a trust fund, hereinafter the "Fund," for the benefit of any and all third parties injured or damaged by [sudden and/or nonsudden] accidental occurrences arising from operation of the facility(ies) covered by this guarantee, in the amounts of \_\_\_\_\_ [up to \$1 million] per occurrence and [up to \$2 million] annual aggregate for sudden accidental occurrences and \_\_\_\_\_ [up to \$3 million] per occurrence and \_\_\_\_\_ [up to \$6 million] annual aggregate for nonsudden occurrences, except that the Fund is not established for the benefit of third parties for the following:

- (a) Bodily injury or property damage for which [insert Grantor] is obligated to pay damages by reason of the assumption of liability in a contract or agreement. This exclusion does not apply to liability for damages that [insert Grantor] would be obligated to pay in the absence of the contract or agreement.
- (b) Any obligation of [insert Grantor] under a workers' compensation, disability benefits, or unemployment compensation law or any similar law.
- (c) Bodily injury to:
  - (1) An employee of [insert Grantor] arising from, and in the course of, employment by [insert Grantor]; or
  - (2) The spouse, child, parent, brother or sister of that employee as a consequence of, or arising from, and in the course of employment by [insert Grantor]. This exclusion applies:
    - (A) Whether [insert Grantor] may be liable as an employer or in any other capacity; and
    - (B) To any obligation to share damages with or repay another person who must pay damages because of the injury to persons identified in paragraphs (1) and (2).
- (d) Bodily injury or property damage arising out of the ownership, maintenance, use, or entrustment to others of any aircraft, motor vehicle or watercraft.
- (e) Property damage to:
  - (1) Any property owned, rented, or occupied by [insert Grantor];
  - (2) Premises that are sold, given away or abandoned by [insert Grantor] if the property damage arises out of any part of those premises;
  - (3) Property loaned to [insert Grantor];
  - (4) Personal property in the care, custody or control of [insert Grantor];
  - (5) That particular part of real property on which [insert Grantor] or any contractors or subcontractors working directly or indirectly on behalf of [insert Grantor] are performing operations, if the property damage arises out of these operations.

In the event of combination with another mechanism for liability coverage, the Fund shall be considered [insert "primary" or "excess"] coverage.

The Fund is established initially as consisting of the property, which is acceptable to the Trustee, described in Schedule B attached hereto. Such property and any other property subsequently transferred to the Trustee is referred to as the Fund, together with all earnings and profits thereon, less any payments or distributions made by the Trustee pursuant to this Agreement. The Fund shall be held by the Trustee, IN TRUST, as hereinafter provided. The Trustee shall not be responsible nor shall it undertake any responsibility for the amount or adequacy of, nor any duty to collect from the Grantor, any payments necessary to discharge any liabilities of the Grantor established by the Department.

#### Section 4. Payment for Bodily Injury or Property Damage.

The Trustee shall satisfy a third party liability claim by making payments from the Fund only upon receipt of one of the following documents;

- (a) Certification from the Grantor and the third party claimant(s) that the liability claim should be paid. The certification must be worded as follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

##### Certification of Valid Claim

The undersigned, as parties [insert Grantor] and [insert name and address of third party claimant(s)], hereby certify that the claim of bodily injury and/or property damage caused by a [sudden or nonsudden] accidental occurrence arising from operating [Grantor's] facility or group of facilities should be paid in the amount of \$[ ].

[Signatures]

Grantor

[Signatures]

Claimant(s)

- (b) A valid final court order establishing a judgment against the Grantor for bodily injury or property damage caused by sudden or nonsudden accidental occurrences arising from the operation of the Grantor's facility or group of facilities.

#### Section 5. Payments Comprising the Fund.

Payments made to the Trustee for the Fund shall consist of cash or securities acceptable to the Trustee.

#### Section 6. Trustee Management.

The Trustee shall invest and reinvest the principal and income, in accordance with general investment policies and guidelines which the Grantor may communicate in writing to the Trustee from time to time, subject, however, to the provisions of this section. In investing, reinvesting, exchanging, selling, and managing the Fund, the Trustee shall discharge his duties with respect to the trust fund solely in the interest of the beneficiary and with the care, skill, prudence, and diligence under the circumstance then prevailing which persons of prudence, acting in a like capacity and familiar with such matters, would use in the conduct of an enterprise of a like character and with like aims; except that:

- (i) Securities or other obligations of the Grantor, or any other owner or operator of the facilities, or any of their affiliates as defined in the Investment Company Act of 1940, as amended, 15 U.S.C. 80a-2.(a), shall not be acquired or held unless they are securities or other obligations of the Federal or a state government;
- (ii) The Trustee is authorized to invest the Fund in time or demand deposits of the Trustee, to the extent insured by an agency of the Federal or a state government; and
- (iii) The Trustee is authorized to hold cash awaiting investment or distribution uninvested for a reasonable time and without liability for the payment of interest thereon.

#### Section 7. Commingling and Investment.

The Trustee is expressly authorized in its discretion:

- (a) To transfer from time to time any or all of the assets of the Fund to any common commingled, or collective trust fund created by the Trustee in which the fund is eligible to participate, subject to all of the provisions thereof, to be commingled with the assets of other trusts participating therein; and

- (b) To purchase shares in any investment company registered under the Investment Company Act of 1940, 15 U.S.C. 81a-1 et seq., including one which may be created, managed, underwritten, or to which investment advice is rendered or the shares of which are sold by the Trustee. The Trustee may vote such shares in its discretion.

#### Section 8. Express Powers of Trustee.

Without in any way limiting the powers and discretions conferred upon the Trustee by the other provisions of this Agreement or by law, the Trustee is expressly authorized and empowered:

- (a) To sell, exchange, convey, transfer, or otherwise dispose of any property held by it, by public or private sale. No person dealing with the Trustee shall be bound to see to the application of the purchase money or to inquire into the validity or expediency of any such sale or other disposition;
- (b) To make, execute, acknowledge, and deliver any and all documents of transfer and conveyance and any and all other instruments that may be necessary or appropriate to carry out the powers herein granted;
- (c) To register any securities held in the Fund in its own name or in the name of a nominee and to hold any security in bearer form or in book entry, or to combine certificates representing such securities with certificates of the same issue held by the Trustee in other fiduciary capacities, or to deposit or arrange for the deposit of such securities in a qualified central depository even though, when so deposited, such securities may be merged and held in bulk in the name of the nominee of such depository with other securities deposited therein by another person, or to deposit or arrange for the deposit of any securities issued by the United States Government, or any agency or instrumentality thereof, with a Federal Reserve bank, but the books and records of the Trustee shall at all times show that all such securities are part of the Fund;
- (d) To deposit any cash in the Fund in interest-bearing accounts maintained or savings certificates issued by the Trustee, in its separate corporate capacity, or in any other banking institution affiliated with the Trustee, to the extent insured by an agency of the Federal or a state government; and
- (e) To compromise or otherwise adjust all claims in favor of or against the Fund.

#### Section 9. Taxes and Expenses.

All taxes of any kind that may be assessed or levied against or in respect of the Fund and all brokerage commissions incurred by the Fund shall be paid from the Fund. All other expenses incurred by the Trustee in connection with the administration of this Trust, including fees for legal services rendered to the Trustee, the compensation of the Trustee to the extent not paid directly by the Grantor, and all other proper charges and disbursements of the Trustee shall be paid from the Fund.

#### Section 10. Annual Valuations.

The Trustee shall annually, at least 30 days prior to the anniversary date of establishment of the Fund, furnish to the Grantor and to the Commissioner of the Tennessee Department of Environment and Conservation a statement confirming the value of the Trust. Any securities in the Fund shall be valued at market value as of no more than 60 days prior to the anniversary date of establishment of the Fund. The failure of the Grantor to object in writing to the Trustee within 90 days after the statement has been furnished to the Grantor and the Commissioner shall constitute a conclusively binding assent by the Grantor barring the Grantor from asserting any claim or liability against the Trustee with respect to matters disclosed in the statement.

#### Section 11. Advice of Counsel.

The Trustee may from time to time consult with counsel, who may be counsel to the Grantor with respect to any question arising as to the construction of this Agreement or any action to be taken hereunder. The Trustee shall be fully protected, to the extent permitted by law, in acting upon the advice of counsel.

#### Section 12. Trustee Compensation.

The Trustee shall be entitled to reasonable compensation for its services as agreed upon in writing from time to time with the Grantor.

#### Section 13. Successor Trustee.

The Trustee may resign or the Grantor may replace the Trustee, but such resignation or replacement shall not be effective until the Grantor has appointed a successor trustee and this successor accepts the appointment. The successor trustee shall have the same powers and duties as those conferred upon the Trustee hereunder. Upon the successor trustee's acceptance of the appointment, the Trustee shall assign, transfer, and pay over to the successor trustee the funds and properties then constituting the Fund. If for any reason the Grantor cannot or does not act in the event of the resignation of the Trustee, the Trustee may apply to a court of competent jurisdiction for the appointment of a successor trustee or for instructions. The successor trustee shall specify the date on which it assumes administration of the trust in a writing sent to the Grantor, the Commissioner of the Tennessee Department of Environment and Conservation, and the present Trustee by certified mail 10 days before such change becomes effective. Any expenses incurred by the Trustee as a result of any of the acts contemplated by this section shall be paid as provided in Section 9.

#### Section 14. Instructions to the Trustee.

All orders, requests, and instructions by the Grantor to the Trustee shall be in writing, signed by such persons as are designated in the attached Exhibit A or such other designees as the Grantor may designate by amendments to Exhibit A. The Trustee shall be fully protected in acting without inquiry in accordance with the Grantor's orders, requests, and instructions. All orders, requests, and instructions by the Commissioner of the Tennessee Department of Environment and Conservation to the Trustee shall be in writing, signed by the Commissioner, or designee, and the Trustee shall act and shall be fully protected in acting in accordance with such orders, requests, and instructions. The Trustee shall have the right to assume, in the absence of written notice to the contrary, that no event constituting a change or a termination of the authority of any person to act on behalf of the Grantor or the Tennessee Department of Environment and Conservation hereunder has occurred. The Trustee shall have no duty to act in the absence of such orders, requests, and instructions from the Grantor and/or the Commissioner of the Tennessee Department of Environment and Conservation, except as provided for herein.

#### Section 15. Notice of Nonpayment.

If a payment for bodily injury or property damage is made under Section 4 of this trust, the Trustee shall notify the Grantor of such payment and the amount(s) thereof within 5 working days. The Grantor shall, on or before the anniversary date of the establishment of the Fund following such notice, either make payments to the Trustee in amounts sufficient to cause the trust to return to its value immediately prior to the payment of claims under Section 4, or shall provide written proof to the Trustee that other financial assurance for liability coverage has been obtained equaling the amount necessary to return the trust to its value prior to the payment of claims. If the Grantor does not either make payments to the Trustee or provide the Trustee with such proof, the Trustee shall within 10 working days after the anniversary date of the establishment of the Fund provide a written notice of nonpayment to the Commissioner.

#### Section 16. Amendment of Agreement.

This Agreement may be amended by an instrument in writing executed by the Grantor, the Trustee, and the Commissioner of the Tennessee Department of Environment and Conservation, or by the Trustee and the Commissioner if the Grantor ceases to exist.

#### Section 17. Irrevocability and Termination.

Subject to the right of the parties to amend this Agreement as provided in Section 16, this Trust shall be irrevocable and shall continue until terminated at the written agreement of the Grantor, the Trustee, and the Commissioner of the Tennessee Department of Environment and Conservation, or by the Trustee and the Commissioner, if the Grantor ceases to exist. Upon termination of the Trust, all remaining trust property, less final trust administration expenses, shall be delivered to the Grantor.

The Commissioner of the Tennessee Department of Environment and Conservation will agree to termination of the Trust when the owner or operator substitutes alternate financial assurance as specified in this section.

#### Section 18. Immunity and Indemnification.



The Trustee shall not incur personal liability of any nature in connection with any act or omission, made in good faith, in the administration of this Trust, or in carrying out any directions by the Grantor or the Commissioner of the Tennessee Department of Environment and Conservation issued in accordance with this Agreement. The Trustee shall be indemnified and saved harmless by the Grantor or from the Trust Fund, or both, from and against any personal liability to which the Trustee may be subjected by reason of any act or conduct in its official capacity, including all expenses reasonably incurred in its defense in the event the Grantor fails to provide such defense.

Section 19. Choice of Law.

This Agreement shall be administered, construed, and enforced according to the laws of the state of [enter name of state].

Section 20. Interpretation.

As used in this Agreement, words in the singular include the plural and words in the plural include the singular. The descriptive headings for each section of this Agreement shall not affect the interpretation or the legal efficacy of this Agreement.

In Witness Whereof the parties have caused this Agreement to be executed by their respective officers duly authorized and their corporate seals to be hereunto affixed and attested as of the date first above written. The parties below certify that the wording of this Agreement is identical to the wording specified in part (8)(l)11 of Rule 0400-12-01-.02 as such regulations were constituted on the date first above written.

[Signature of Grantor]

[Title]

Attest:

[Title]

[Seal]

[Signature of Trustee]

Attest:

[Title]

[Seal]

- (ii) The following is an example of the certification of acknowledgement which must accompany the trust agreement for a trust fund as specified in part (h)10 of this paragraph.

State of \_\_\_\_\_ County of \_\_\_\_\_

On this [date], before me personally came [owner or operator] to me known, who, being by me duly sworn, did depose and say that she/he resides at [address], that she/he is [title] of [corporation], the corporation described in and which executed the above instrument; that she/he knows the seal of said corporation; that the seal affixed to such instrument is such corporate seal; that it was so affixed by order of the Board of Directors of said corporation, and that she/he signed her/ his name thereto by like order.

[Signature of Notary Public]

12. Reserved

13. (i) A personal bond supported by certificate of deposit, as specified in part 6 of this paragraph, shall include the following information and use the language provided in subpart (ii) of this part:
- (I) Effective date;
  - (II) Principal (legal name and address of owner/operator);
  - (III) Type of organization (insert "individual," "joint venture," "partnership" or "corporation");
  - (IV) State of incorporation;
  - (V) Permit number;
  - (VI) Name and address of facility;
  - (VII) Total penal sum of the bond;
  - (VIII) Name and address of the financial institution issuing the certificate of deposit; and
  - (IX) Serial number(s) of certificate of deposit.
- (ii) The personal bond must use the language that follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

#### Personal Bond

Know All Persons By These Presents, That I, the Principal am firmly bound to the Tennessee Department of Environment and Conservation in the event that the hazardous secondary materials at the reclamation or intermediate facility listed below no longer meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, in the above penal sum for the payment of which I bind myself, my heirs, executors, administrators, successors, and assigns jointly and severally for the payment of the full amount of the penal sum.

Whereas said Principal is required, under the Tennessee Hazardous Waste Management Act, to have a permit or interim status in order to own or operate each facility identified above, or to meet conditions under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02; and

Whereas said Principal is required to provide financial assurance as a condition of permit or interim status or as a condition of an exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02;

Now, Therefore, the conditions of the obligation are such that if the Principal shall faithfully satisfy all the conditions established for exclusion of hazardous secondary materials from coverage as solid waste under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02,

Or, if the Principal shall provide alternate financial assurance, as specified in paragraph (8) of Rule 0400-12-01-.02, as applicable, and obtain the Commissioner's written approval of such assurance, then this obligation shall be null and void; otherwise it is to remain in full force and effect.

The Principal shall become liable on this bond obligation only when the Principal has failed to fulfill the conditions described above. Upon notification by the Commissioner that the Principal has failed to perform as guaranteed by this bond, the Principal shall forfeit all or a portion of the penal sum of this bond to the Department.

The liability of the Surety(ies) shall not be discharged by any payment or succession of payments hereunder, unless and until such payment or payments shall amount in the aggregate to the penal sum of the bond, but in no event shall the obligation of the Surety(ies) hereunder exceed the amount of said penal sum.

The Principal has this day irrevocably assigned the deposit to the Department and has submitted to the Department the original of Certificate of Deposit # \_\_\_\_\_ or an original safekeeping receipt of the deposit.

The person whose signature appears below hereby certifies that he/she is authorized to execute this surety bond on behalf of the Principal and that the wording of this surety bond is identical to the wording specified in Rule 0400-12-01-.02(8)(I)13(ii) as such rules were constituted on the date this bond was executed.

Principal

[Signature(s)]

\_\_\_\_\_

[Name(s)]

\_\_\_\_\_

[Title(s)]

\_\_\_\_\_

Subscribed and sworn to before me this the \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_\_.

\_\_\_\_\_  
Notary Public

My commission expires on the \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_\_.

14. (i) A personal bond supported by cash, as specified in part 7 of this paragraph, shall include the following information and use the language provided in subpart (ii) of this part:
- (I) Effective date;
  - (II) Principal (legal name and address of owner/operator);
  - (III) Type of organization (insert "individual," "joint venture," "partnership" or "corporation");
  - (IV) State of incorporation;
  - (V) Permit number;
  - (VI) Name and address of facility;
  - (VII) Total penal sum of the bond;
- (ii) The personal bond must use the language that follows, except that instructions in brackets are to be replaced with the relevant information and the brackets deleted:

Personal Bond

Know All Persons By These Presents, That I, the Principal am firmly bound to the Tennessee Department of Environment and Conservation in the event that the hazardous secondary materials at the reclamation or intermediate facility listed below no longer meet the conditions of the exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, in the above penal sum for the payment of which I bind myself, my heirs, executors, administrators, successors, and assigns jointly and severally for the payment of the full amount of the penal sum.

Whereas said Principal is required, under the Tennessee Hazardous Waste Management Act, to have a permit or interim status in order to own or operate each facility identified above, or to meet conditions under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02, and

Whereas said Principal is required to provide financial assurance as a condition of permit or interim status or as a condition of an exclusion under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02;

Now, Therefore, the conditions of the obligation are such that if the Principal shall faithfully satisfy all the conditions established for exclusion of hazardous secondary materials from coverage as solid waste under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02,

Or, if the Principal shall provide alternate financial assurance, as specified in paragraph (8) of Rule 0400-12-01-.02, as applicable, and obtain the Commissioner's written approval of such assurance, then this obligation shall be null and void; otherwise it is to remain in full force and effect.

The Principal shall become liable on this bond obligation only when the Principal has failed to fulfill the conditions described above. Upon notification by the Commissioner that the Principal has failed to perform as guaranteed by this bond, the Principal shall forfeit all or a portion of the penal sum of this bond to the Department.

The liability of the Surety(ies) shall not be discharged by any payment or succession of payments hereunder, unless and until such payment or payments shall amount in the aggregate to the penal sum of the bond, but in no event shall the obligation of the Surety(ies) hereunder exceed the amount of said penal sum.

The Principal has this day deposited funds equal to the penal sum of the bond with the treasurer of the state of Tennessee in support of this personal bond.

The person whose signature appears below hereby certifies that he/she is authorized to execute this surety bond on behalf of the Principal and that the wording of this surety bond is identical to the wording specified in Rule 0400-12-01-.02(8)(l)14(ii) as such rules were constituted on the date this bond was executed.

Principal

[Signature(s)]

\_\_\_\_\_

[Name(s)]

\_\_\_\_\_

[Title(s)]

\_\_\_\_\_

Subscribed and sworn to before me this the \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_\_.

\_\_\_\_\_  
Notary Public

My commission expires on the \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_\_\_\_.

(9) Use and Management of Containers [40 CFR 261 Subpart I]

(a) Applicability [40 CFR 261.170]

This paragraph applies to hazardous secondary materials excluded under the remanufacturing exclusion at subpart (1)(d)1(xxvii) of this rule and stored in containers.

(b) Condition of containers [40 CFR 261.171]

If a container holding hazardous secondary material is not in good condition (e.g., severe rusting, apparent structural defects) or if it begins to leak, the hazardous secondary material must be transferred from this container to a container that is in good condition or managed in some other way that complies with the requirements of this rule.

(c) Compatibility of hazardous secondary materials with containers [40 CFR 261.172]

The container must be made of or lined with materials which will not react with, and are otherwise compatible with, the hazardous secondary material to be stored, so that the ability of the container to contain the material is not impaired.

(d) Management of containers [40 CFR 261.173]

1. A container holding hazardous secondary material must always be closed during storage, except when it is necessary to add or remove the hazardous secondary material.
2. A container holding hazardous secondary material must not be opened, handled, or stored in a manner which may rupture the container or cause it to leak.

(e) Reserved

(f) Containment [40 CFR 261.175]

1. Container storage areas must have a containment system that is designed and operated in accordance with part 2 of this subparagraph.
2. A containment system must be designed and operated as follows:
  - (i) A base must underlie the containers which is free of cracks or gaps and is sufficiently impervious to contain leaks, spills, and accumulated precipitation until the collected material is detected and removed;
  - (ii) The base must be sloped or the containment system must be otherwise designed and operated to drain and remove liquids resulting from leaks, spills, or precipitation, unless the containers are elevated or are otherwise protected from contact with accumulated liquids;
  - (iii) The containment system must have sufficient capacity to contain 10% of the volume of containers or the volume of the largest container, whichever is greater.
  - (iv) Run-on into the containment system must be prevented unless the collection system has sufficient excess capacity in addition to that required in subpart (iii) of part to contain any run-on which might enter the system; and
  - (v) Spilled or leaked material and accumulated precipitation must be removed from the sump or collection area in as timely a manner as is necessary to prevent overflow of the collection system.

(g) Special requirements for ignitable or reactive hazardous secondary material [40 CFR 261.176]

Containers holding ignitable or reactive hazardous secondary material must be located at least 15 meters (50 feet) from the facility's property line.

(h) Special requirements for incompatible materials [40 CFR 261.177]

1. Incompatible materials must not be placed in the same container.
2. Hazardous secondary material must not be placed in an unwashed container that previously held an incompatible material.
3. A storage container holding a hazardous secondary material that is incompatible with any other materials stored nearby must be separated from the other materials or protected from them by means of a dike, berm, wall, or other device.

(i) Reserved

(j) Air emission standards [40 CFR 261.179]

The remanufacturer or other person that stores or treats the hazardous secondary material shall manage all hazardous secondary material placed in a container in accordance with the applicable requirements of paragraphs (27), (28) and (29) of this rule.

(10) Tank Systems [40 CFR 261 Subpart J]

(a) Applicability [40 CFR 261.190]

1. The requirements of this paragraph apply to tank systems for storing or treating hazardous secondary material excluded under the remanufacturing exclusion at subpart (1)(d)1(xxvii) of this rule.
2. Tank systems, including sumps, as defined in subparagraph (2)(a) of Rule 0400-12-01-.01, that serve as part of a secondary containment system to collect or contain releases of hazardous secondary materials are exempted from the requirements in part (d)1 of this paragraph.

(b) Assessment of existing tank system's integrity [40 CFR 261.191]

1. Tank systems must meet the secondary containment requirements of subparagraph (d) of this paragraph, or the remanufacturer or other person that handles the hazardous secondary material must determine that the tank system is not leaking and is fit for use. Except as provided in part 3 of the subparagraph, a written assessment reviewed and certified by a qualified Professional Engineer must be kept on file at the remanufacturer's facility or other facility that stores or treats the hazardous secondary material that attests to the tank system's integrity.
2. This assessment must determine that the tank system is adequately designed and has sufficient structural strength and compatibility with the material(s) to be stored or treated, to ensure that it will not collapse, rupture, or fail. At a minimum, this assessment must consider the following:
  - (i) Design standard(s), if available, according to which the tank and ancillary equipment were constructed;
  - (ii) Hazardous characteristics of the material(s) that have been and will be handled;
  - (iii) Existing corrosion protection measures;
  - (iv) Documented age of the tank system, if available (otherwise, an estimate of the age); and

- (v) Results of a leak test, internal inspection, or other tank integrity examination such that:
  - (I) For non-enterable underground tanks, the assessment must include a leak test that is capable of taking into account the effects of temperature variations, tank end deflection, vapor pockets, and high water table effects; and
  - (II) For other than non-enterable underground tanks and for ancillary equipment, this assessment must include either a leak test, as described in item (I) of this subpart, or other integrity examination that is certified by a qualified Professional Engineer that addresses cracks, leaks, corrosion, and erosion.

(Note: The practices described in the American Petroleum Institute (API) Publication, Guide for Inspection of Refinery Equipment, Chapter XIII, "Atmospheric and Low-Pressure Storage Tanks," 4th edition, 1981, may be used, where applicable, as guidelines in conducting other than a leak test.)

- 3. If, as a result of the assessment conducted in accordance with part 1 of this subparagraph, a tank system is found to be leaking or unfit for use, the remanufacturer or other person that stores or treats the hazardous secondary material must comply with the requirements of subparagraph (g) of this paragraph.

(c) Reserved [ 40 CFR 261.192]

(d) Containment and detection of releases [40 CFR 261.193]

- 1. Secondary containment systems must be:
  - (i) Designed, installed, and operated to prevent any migration of materials or accumulated liquid out of the system to the soil, ground water, or surface water at any time during the use of the tank system; and
  - (ii) Capable of detecting and collecting releases and accumulated liquids until the collected material is removed.

(Note: If the collected material is a hazardous waste under this rule, it is subject to management as a hazardous waste in accordance with all applicable requirements of Rule 0400-12-01-.03 through Rule 0400-12-01-.10. If the collected material is discharged through a point source to waters of the United States, it is subject to the requirements of Tennessee Water Quality Control Act, as amended. If discharged to a Publicly Owned Treatment Works (POTW), it is subject to the requirements of the Tennessee Water Quality Control Act, as amended. If the collected material is released to the environment, it may be subject to the reporting requirements of 40 CFR part 302.)

- 2. To meet the requirements of part 1 of this subparagraph, secondary containment systems must be at a minimum:
  - (i) Constructed of or lined with materials that are compatible with the materials(s) to be placed in the tank system and must have sufficient strength and thickness to prevent failure owing to pressure gradients (including static head and external hydrological forces), physical contact with the material to which it is exposed, climatic conditions, and the stress of daily operation (including stresses from nearby vehicular traffic);
  - (ii) Placed on a foundation or base capable of providing support to the secondary

containment system, resistance to pressure gradients above and below the system, and capable of preventing failure due to settlement, compression, or uplift;

- (iii) Provided with a leak-detection system that is designed and operated so that it will detect the failure of either the primary or secondary containment structure or the presence of any release of hazardous secondary material or accumulated liquid in the secondary containment system at the earliest practicable time; and
- (iv) Sloped or otherwise designed or operated to drain and remove liquids resulting from leaks, spills, or precipitation. Spilled or leaked material and accumulated precipitation must be removed from the secondary containment system within 24 hours, or in as timely a manner as is possible to prevent harm to human health and the environment.

3. Secondary containment for tanks must include one or more of the following devices:

- (i) A liner (external to the tank);
- (ii) A vault; or
- (iii) A double-walled tank.

4. In addition to the requirements of parts 1, 2 and 3 of this subparagraph, secondary containment systems must satisfy the following requirements:

- (i) External liner systems must be:
  - (I) Designed or operated to contain 100 percent of the capacity of the largest tank within its boundary;
  - (II) Designed or operated to prevent run-on or infiltration of precipitation into the secondary containment system unless the collection system has sufficient excess capacity to contain run-on or infiltration. Such additional capacity must be sufficient to contain precipitation from a 25-year, 24-hour rainfall event.
  - (III) Free of cracks or gaps; and
  - (IV) Designed and installed to surround the tank completely and to cover all surrounding earth likely to come into contact with the material if the material is released from the tank(s) (i.e., capable of preventing lateral as well as vertical migration of the material).
- (ii) Vault systems must be:
  - (I) Designed or operated to contain 100 percent of the capacity of the largest tank within its boundary;
  - (II) Designed or operated to prevent run-on or infiltration of precipitation into the secondary containment system unless the collection system has sufficient excess capacity to contain run-on or infiltration. Such additional capacity must be sufficient to contain precipitation from a 25-year, 24-hour rainfall event;
  - (III) Constructed with chemical-resistant water stops in place at all joints (if any);
  - (IV) Provided with an impermeable interior coating or lining that is compatible with the stored material and that will prevent migration of material into



the concrete;

(V) Provided with a means to protect against the formation of and ignition of vapors within the vault, if the material being stored or treated is ignitable or reactive; and

(VI) Provided with an exterior moisture barrier or be otherwise designed or operated to prevent migration of moisture into the vault if the vault is subject to hydraulic pressure.

(iii) Double-walled tanks must be:

(I) Designed as an integral structure (i.e., an inner tank completely enveloped within an outer shell) so that any release from the inner tank is contained by the outer shell;

(II) Protected, if constructed of metal, from both corrosion of the primary tank interior and of the external surface of the outer shell; and

(III) Provided with a built-in continuous leak detection system capable of detecting a release within 24 hours, or at the earliest practicable time.

(Note: The provisions outlined in the Steel Tank Institute's (STI) "Standard for Dual Wall Underground Steel Storage Tanks" may be used as guidelines for aspects of the design of underground steel double-walled tanks.)

5. Reserved

6. Ancillary equipment must be provided with secondary containment (e.g., trench, jacketing, double-walled piping) that meets the requirements of parts 1 and 2 of this subparagraph except for:

(i) Aboveground piping (exclusive of flanges, joints, valves, and other connections) that are visually inspected for leaks on a daily basis;

(ii) Welded flanges, welded joints, and welded connections that are visually inspected for leaks on a daily basis;

(iii) Sealless or magnetic coupling pumps and sealless valves that are visually inspected for leaks on a daily basis; and

(iv) Pressurized aboveground piping systems with automatic shut-off devices (e.g., excess flow check valves, flow metering shutdown devices, loss of pressure actuated shut-off devices) that are visually inspected for leaks on a daily basis.

(e) General operating requirements [40 CFR 261.194]

1. Hazardous secondary materials or treatment reagents must not be placed in a tank system if they could cause the tank, its ancillary equipment, or the containment system to rupture, leak, corrode, or otherwise fail.

2. The remanufacturer or other person that stores or treats the hazardous secondary material must use appropriate controls and practices to prevent spills and overflows from tank or containment systems. These include at a minimum:

(i) Spill prevention controls (e.g., check valves, dry disconnect couplings);

(ii) Overfill prevention controls (e.g., level sensing devices, high level alarms, automatic feed cutoff, or bypass to a standby tank); and

- (iii) Maintenance of sufficient freeboard in uncovered tanks to prevent overtopping by wave or wind action or by precipitation.
3. The remanufacturer or other person that stores or treats the hazardous secondary material must comply with the requirements of subparagraph (g) of this paragraph if a leak or spill occurs in the tank system.
- (f) Reserved [40 CFR 261.195]
  - (g) Response to leaks or spills and disposition of leaking or unfit-for-use tank systems [40 CFR 261.196]

A tank system or secondary containment system from which there has been a leak or spill, or which is unfit for use, must be removed from service immediately, and the remanufacturer or other person that stores or treats the hazardous secondary material must satisfy the following requirements:

1. Cessation of use; prevent flow or addition of materials. The remanufacturer or other person that stores or treats the hazardous secondary material must immediately stop the flow of hazardous secondary material into the tank system or secondary containment system and inspect the system to determine the cause of the release.
2. Removal of material from tank system or secondary containment system
  - (i) If the release was from the tank system, the remanufacturer or other person that stores or treats the hazardous secondary material must, within 24 hours after detection of the leak or, if the remanufacturer or other person that stores or treats the hazardous secondary material demonstrates that it is not possible, at the earliest practicable time, remove as much of the material as is necessary to prevent further release of hazardous secondary material to the environment and to allow inspection and repair of the tank system to be performed.
  - (ii) If the material released was to a secondary containment system, all released materials must be removed within 24 hours or in as timely a manner as is possible to prevent harm to human health and the environment.
3. Containment of visible releases to the environment. The remanufacturer or other person that stores or treats the hazardous secondary material must immediately conduct a visual inspection of the release and, based upon that inspection:
  - (i) Prevent further migration of the leak or spill to soils or surface water; and
  - (ii) Remove, and properly dispose of, any visible contamination of the soil or surface water.
4. Notifications, reports
  - (i) Any release to the environment, except as provided in subpart (ii) of this part, must be reported to the Commissioner within 24 hours of its detection. If the release has been reported pursuant to 40 CFR part 302, that report will satisfy this requirement.
  - (ii) A leak or spill of hazardous secondary material is exempted from the requirements of this paragraph if it is:
    - (I) Less than or equal to a quantity of 1 pound; and
    - (II) Immediately contained and cleaned up.
  - (iii) Within 30 days of detection of a release to the environment, a report containing

the following information must be submitted to the Commissioner:

- (I) Likely route of migration of the release;
- (II) Characteristics of the surrounding soil (soil composition, geology, hydrogeology, climate);
- (III) Results of any monitoring or sampling conducted in connection with the release (if available). If sampling or monitoring data relating to the release are not available within 30 days, these data must be submitted to the Commissioner as soon as they become available;
- (IV) Proximity to downgradient drinking water, surface water, and populated areas; and
- (V) Description of response actions taken or planned.

5. Provision of secondary containment, repair, or closure

- (i) Unless the remanufacturer or other person that stores or treats the hazardous secondary material satisfies the requirements of subparts (ii) through (iv) of this part, the tank system must cease to operate under the remanufacturing exclusion at subpart (1)(d)1(xxvii) of the rule.
- (ii) If the cause of the release was a spill that has not damaged the integrity of the system, the remanufacturer or other person that stores or treats the hazardous secondary material may return the system to service as soon as the released material is removed and repairs, if necessary, are made.
- (iii) If the cause of the release was a leak from the primary tank system into the secondary containment system, the system must be repaired prior to returning the tank system to service.
- (iv) If the source of the release was a leak to the environment from a component of a tank system without secondary containment, the remanufacturer or other person that stores or treats the hazardous secondary material must provide the component of the system from which the leak occurred with secondary containment that satisfies the requirements of subparagraph (d) of this paragraph before it can be returned to service, unless the source of the leak is an aboveground portion of a tank system that can be inspected visually. If the source is an aboveground component that can be inspected visually, the component must be repaired and may be returned to service without secondary containment as long as the requirements of part 6 of this subparagraph are satisfied. Additionally, if a leak has occurred in any portion of a tank system component that is not readily accessible for visual inspection (e.g., the bottom of an inground or onground tank), the entire component must be provided with secondary containment in accordance with subparagraph (d) of this paragraph prior to being returned to use.

6. Certification of major repairs

If the remanufacturer or other person that stores or treats the hazardous secondary material has repaired a tank system in accordance with part 5 of this subparagraph, and the repair has been extensive (e.g., installation of an internal liner; repair of a ruptured primary containment or secondary containment vessel), the tank system must not be returned to service unless the remanufacturer or other person that stores or treats the hazardous secondary material has obtained a certification by a qualified Professional Engineer that the repaired system is capable of handling hazardous secondary materials without release for the intended life of the system. This certification must be kept on file at the facility and maintained until closure of the facility.

(Note: The Commissioner may, on the basis of any information received that there is or has been a release of hazardous secondary material or hazardous constituents into the environment, issue an order under the Act (T.C.A. §§ 68-212-101 et seq.) requiring corrective action or such other response as deemed necessary to protect human health or the environment.)

(Note: The Tennessee Water Quality Control Act may require the owner or operator to notify the National Response Center of certain releases.)

(h) Termination of remanufacturing exclusion [40 CFR 261.197]

Hazardous secondary material stored in units more than 90 days after the unit ceases to operate under the remanufacturing exclusion at subpart (1)(d)1(xxvii) of this rule or otherwise ceases to be operated for manufacturing, or for storage of a product or a raw material, then becomes subject to regulation as hazardous waste under Rules 0400-12-01-.02 through 0400-12-01-.10, as applicable.

(i) Special requirements for ignitable or reactive materials [40 CFR 261.198]

1. Ignitable or reactive material must not be placed in tank systems, unless the material is stored or treated in such a way that it is protected from any material or conditions that may cause the material to ignite or react.
2. The remanufacturer or other person that stores or treats hazardous secondary material which is ignitable or reactive must store or treat the hazardous secondary material in a tank that is in compliance with the requirements for the maintenance of protective distances between the material management area and any public ways, streets, alleys, or an adjoining property line that can be built upon as required in Tables 2-1 through 2-6 of the National Fire Protection Association's "Flammable and Combustible Liquids Code," (1977 or 1981), (incorporated by reference, see 40 CFR 260.11).

(j) Special requirements for incompatible materials [40 CFR 261.199]

1. Incompatible materials must not be placed in the same tank system.
2. Hazardous secondary material must not be placed in a tank system that has not been decontaminated and that previously held an incompatible material.

(k) Air emission standards [40 CFR 261.200]

The remanufacturer or other person that stores or treats the hazardous secondary material shall manage all hazardous secondary material placed in a tank in accordance with the applicable requirements of paragraphs (27), (28) and (29) of this rule.

(11) – (12) Reserved

(13) Emergency Preparedness and Response for Management of Excluded Hazardous Secondary Materials [40 CFR 261 Subpart M]

(a) Applicability [40 CFR 261.400]

The requirements of this paragraph apply to those areas of an entity managing hazardous secondary materials excluded under subpart (1)(d)1(xxiii) and/or (xxiv) of this rule where hazardous secondary materials are generated or accumulated on site.

1. A generator of hazardous secondary material, or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01, that accumulates 6000 kg or less of hazardous secondary material at any time must comply with subparagraphs (b) and (c) of this paragraph.

2. A generator of hazardous secondary material, or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 that accumulates more than 6000 kg of hazardous secondary material at any time must comply with subparagraphs (b) and (d) of this paragraph.

(b) Preparedness and prevention [40 CFR 261.410]

1. Maintenance and operation of facility

Facilities generating or accumulating hazardous secondary material must be maintained and operated to minimize the possibility of a fire, explosion, or any unplanned sudden or non-sudden release of hazardous secondary materials or hazardous secondary material constituents to air, soil, or surface water which could threaten human health or the environment.

2. Required equipment

All facilities generating or accumulating hazardous secondary material must be equipped with the following, unless none of the hazards posed by hazardous secondary material handled at the facility could require a particular kind of equipment specified below:

- (i) An internal communications or alarm system capable of providing immediate emergency instruction (voice or signal) to facility personnel;
- (ii) A device, such as a telephone (immediately available at the scene of operations) or a hand-held two-way radio, capable of summoning emergency assistance from local police departments, fire departments, or state or local emergency response teams;
- (iii) Portable fire extinguishers, fire control equipment (including special extinguishing equipment, such as that using foam, inert gas, or dry chemicals), spill control equipment, and decontamination equipment; and
- (iv) Water at adequate volume and pressure to supply water hose streams, or foam producing equipment, or automatic sprinklers, or water spray systems.

3. Testing and maintenance of equipment

All facility communications or alarm systems, fire protection equipment, spill control equipment, and decontamination equipment, where required, must be tested and maintained as necessary to assure its proper operation in time of emergency.

4. Access to communications or alarm system

- (i) Whenever hazardous secondary material is being poured, mixed, spread, or otherwise handled, all personnel involved in the operation must have immediate access to an internal alarm or emergency communication device, either directly or through visual or voice contact with another employee, unless such a device is not required under part 2 of this subparagraph.
- (ii) If there is ever just one employee on the premises while the facility is operating, he must have immediate access to a device, such as a telephone (immediately available at the scene of operation) or a hand-held two-way radio, capable of summoning external emergency assistance, unless such a device is not required under part 2 of this subparagraph.

5. Required aisle space

The hazardous secondary material generator or intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 must

maintain aisle space to allow the unobstructed movement of personnel, fire protection equipment, spill control equipment, and decontamination equipment to any area of facility operation in an emergency, unless aisle space is not needed for any of these purposes.

6. Arrangements with local authorities

- (i) The hazardous secondary material generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 must attempt to make the following arrangements, as appropriate for the type of waste handled at his facility and the potential need for the services of these organizations:
  - (I) Arrangements to familiarize police, fire departments, and emergency response teams with the layout of the facility, properties of hazardous secondary material handled at the facility and associated hazards, places where facility personnel would normally be working, entrances to roads inside the facility, and possible evacuation routes;
  - (II) Where more than one police and fire department might respond to an emergency, agreements designating primary emergency authority to a specific police and a specific fire department, and agreements with any others to provide support to the primary emergency authority;
  - (III) Agreements with state emergency response teams, emergency response contractors, and equipment suppliers; and
  - (IV) Arrangements to familiarize local hospitals with the properties of hazardous waste handled at the facility and the types of injuries or illnesses which could result from fires, explosions, or releases at the facility.
- (ii) Where state or local authorities decline to enter into such arrangements, the hazardous secondary material generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 must document the refusal in the operating record.
- (c) Emergency procedures for facilities generating or accumulating 6000 kg or less of hazardous secondary material [40 CFR 261.411]

A generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 that generates or accumulates 6000 kg or less of hazardous secondary material must comply with the following requirements:

- 1. At all times there must be at least one employee either on the premises or on call (i.e., available to respond to an emergency by reaching the facility within a short period of time) with the responsibility for coordinating all emergency response measures specified in part 4 of this subparagraph. This employee is the emergency coordinator.
- 2. The generator or intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 must post the following information next to the telephone:
  - (i) The name and telephone number of the emergency coordinator;
  - (ii) Location of fire extinguishers and spill control material, and, if present, fire alarm; and
  - (iii) The telephone number of the fire department, unless the facility has a direct alarm.

3. The generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 must ensure that all employees are thoroughly familiar with proper waste handling and emergency procedures, relevant to their responsibilities during normal facility operations and emergencies.
4. The emergency coordinator or his designee must respond to any emergencies that arise. The applicable responses are as follows:
  - (i) In the event of a fire, call the fire department or attempt to extinguish it using a fire extinguisher;
  - (ii) In the event of a spill, contain the flow of hazardous waste to the extent possible, and as soon as is practicable, clean up the hazardous waste and any contaminated materials or soil;
  - (iii) In the event of a fire, explosion, or other release which could threaten human health outside the facility or when the generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 has knowledge that a spill has reached surface water, the generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 must immediately notify the National Response Center (using their 24-hour toll free number 800/424-8802). The report must include the following information:
    - (I) The name, address, and U.S. EPA Identification Number of the facility;
    - (II) Date, time, and type of incident (e.g., spill or fire);
    - (III) Quantity and type of hazardous waste involved in the incident;
    - (IV) Extent of injuries, if any; and
    - (V) Estimated quantity and disposition of recovered materials, if any.
- (d) Contingency planning and emergency procedures for facilities generating or accumulating more than 6000 kg of hazardous secondary material [40 CFR 261.420]

A generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 that generates or accumulates more than 6000 kg of hazardous secondary material must comply with the following requirements:

1. Purpose and implementation of contingency plan
  - (i) Each generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 that accumulates more than 6000 kg of hazardous secondary material must have a contingency plan for his facility. The contingency plan must be designed to minimize hazards to human health or the environment from fires, explosions, or any unplanned sudden or non-sudden release of hazardous secondary material or hazardous secondary material constituents to air, soil, or surface water.
  - (ii) The provisions of the plan must be carried out immediately whenever there is a fire, explosion, or release of hazardous secondary material or hazardous secondary material constituents which could threaten human health or the environment.
2. Content of contingency plan
  - (i) The contingency plan must describe the actions facility personnel must take to comply with parts 1 and 6 of this subparagraph in response to fires, explosions,

or any unplanned sudden or non-sudden release of hazardous secondary material or hazardous secondary material constituents to air, soil, or surface water at the facility.

- (ii) If the generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 accumulating more than 6000 kg of hazardous secondary material has already prepared a Spill Prevention, Control, and Countermeasures (SPCC) Plan in accordance with 40 CFR part 112, or some other emergency or contingency plan, he need only amend that plan to incorporate hazardous waste management provisions that are sufficient to comply with the requirements of this rule. The hazardous secondary material generator or an intermediate or reclamation facility operating under a Certificate to Operate under part (4)(b)2 of Rule 0400-12-01-.01 may develop one contingency plan which meets all regulatory requirements. The Department recommends that the plan be based on the National Response Team's Integrated Contingency Plan Guidance ("One Plan"). When modifications are made to non-Rule Chapter 0400-12-01 provisions in an integrated contingency plan, the changes do not trigger the need for a permit modification under Rule 0400-12-01-.07.
- (iii) The plan must describe arrangements agreed to by local police departments, fire departments, hospitals, contractors, and state and local emergency response teams to coordinate emergency services, pursuant to part (b)6 of this paragraph.
- (iv) The plan must list names, addresses, and phone numbers (office and home) of all persons qualified to act as emergency coordinator (see part 5 of this subparagraph), and this list must be kept up-to-date. Where more than one person is listed, one must be named as primary emergency coordinator and others must be listed in the order in which they will assume responsibility as alternates.
- (v) The plan must include a list of all emergency equipment at the facility (such as fire extinguishing systems, spill control equipment, communications and alarm systems (internal and external), and decontamination equipment), where this equipment is required. This list must be kept up to date. In addition, the plan must include the location and a physical description of each item on the list, and a brief outline of its capabilities.
- (vi) The plan must include an evacuation plan for facility personnel where there is a possibility that evacuation could be necessary. This plan must describe signal(s) to be used to begin evacuation, evacuation routes, and alternate evacuation routes (in cases where the primary routes could be blocked by releases of hazardous waste or fires).

### 3. Copies of contingency plan

A copy of the contingency plan and all revisions to the plan must be:

- (i) Maintained at the facility; and
- (ii) Submitted to all local police departments, fire departments, hospitals, and state and local emergency response teams that may be called upon to provide emergency services.

### 4. Amendment of contingency plan

The contingency plan must be reviewed, and immediately amended, if necessary, whenever:

- (i) Applicable rules are revised;



- (ii) The plan fails in an emergency;
- (iii) The facility changes--in its design, construction, operation, maintenance, or other circumstances--in a way that materially increases the potential for fires, explosions, or releases of hazardous secondary material or hazardous secondary material constituents, or changes the response necessary in an emergency;
- (iv) The list of emergency coordinators changes; or
- (v) The list of emergency equipment changes.

5. Emergency coordinator

At all times, there must be at least one employee either on the facility premises or on call (i.e., available to respond to an emergency by reaching the facility within a short period of time) with the responsibility for coordinating all emergency response measures. This emergency coordinator must be thoroughly familiar with all aspects of the facility's contingency plan, all operations and activities at the facility, the location and characteristics of waste handled, the location of all records within the facility, and the facility layout. In addition, this person must have the authority to commit the resources needed to carry out the contingency plan. The emergency coordinator's responsibilities are more fully spelled out in part 6 of this subparagraph. Applicable responsibilities for the emergency coordinator vary, depending on factors such as type and variety of hazardous secondary material(s) handled by the facility, and type and complexity of the facility.

6. Emergency procedures

- (i) Whenever there is an imminent or actual emergency situation, the emergency coordinator (or his designee when the emergency coordinator is on call) must immediately:
  - (I) Activate internal facility alarms or communication systems, where applicable, to notify all facility personnel; and
  - (II) Notify appropriate state or local agencies with designated response roles if their help is needed.
- (ii) Whenever there is a release, fire, or explosion, the emergency coordinator must immediately identify the character, exact source, amount, and areal extent of any released materials. He may do this by observation or review of facility records or manifests and, if necessary, by chemical analysis.
- (iii) Concurrently, the emergency coordinator must assess possible hazards to human health or the environment that may result from the release, fire, or explosion. This assessment must consider both direct and indirect effects of the release, fire, or explosion (e.g., the effects of any toxic, irritating, or asphyxiating gases that are generated, or the effects of any hazardous surface water run-offs from water or chemical agents used to control fire and heat-induced explosions).
- (iv) If the emergency coordinator determines that the facility has had a release, fire, or explosion which could threaten human health, or the environment, outside the facility, he must report his findings as follows:
  - (I) If his assessment indicates that evacuation of local areas may be advisable, he must immediately notify appropriate local authorities. He must be available to help appropriate officials decide whether local areas should be evacuated; and

- (II) He must immediately notify either the government official designated as the on-scene coordinator for that geographical area, or the National Response Center (using their 24-hour toll free number 800/424-8802). The report must include:
  - I. Name and telephone number of reporter;
  - II. Name and address of facility;
  - III. Time and type of incident (e.g., release, fire);
  - IV. Name and quantity of material(s) involved, to the extent known;
  - V. The extent of injuries, if any; and
  - VI. The possible hazards to human health, or the environment, outside the facility.
  
- (v) During an emergency, the emergency coordinator must take all reasonable measures necessary to ensure that fires, explosions, and releases do not occur, recur, or spread to other hazardous secondary material at the facility. These measures must include, where applicable, stopping processes and operations, collecting and containing released material, and removing or isolating containers.
  
- (vi) If the facility stops operations in response to a fire, explosion or release, the emergency coordinator must monitor for leaks, pressure buildup, gas generation, or ruptures in valves, pipes, or other equipment, wherever this is appropriate.
  
- (vii) Immediately after an emergency, the emergency coordinator must provide for treating, storing, or disposing of recovered secondary material, contaminated soil or surface water, or any other material that results from a release, fire, or explosion at the facility. Unless the hazardous secondary material generator can demonstrate, in accordance with part (1)(c)3 or part (1)(c)4 of this rule, that the recovered material is not a hazardous waste, the owner or operator becomes a generator of hazardous waste and must manage it in accordance with all applicable requirements of Rules 0400-12-01-.03, 0400-12-01-.04 and 0400-12-01-.05.
  
- (viii) The emergency coordinator must ensure that, in the affected area(s) of the facility:
  - (I) No secondary material that may be incompatible with the released material is treated, stored, or disposed of until cleanup procedures are completed; and
  - (ii) All emergency equipment listed in the contingency plan is cleaned and fit for its intended use before operations are resumed.
  
- (ix) The hazardous secondary material generator must note in the operating record the time, date, and details of any incident that requires implementing the contingency plan. Within 15 days after the incident, he must submit a written report on the incident to the Commissioner. The report must include:
  - (I) Name, address, and telephone number of the hazardous secondary material generator;
  - (II) Name, address, and telephone number of the facility;
  - (III) Date, time, and type of incident (e.g., fire, explosion);

- (IV) Name and quantity of material(s) involved;
- (V) The extent of injuries, if any;
- (VI) An assessment of actual or potential hazards to human health or the environment, where this is applicable; and
- (VII) Estimated quantity and disposition of recovered material that resulted from the incident.

(14) – (26) Reserved

(27) Air Emission Standards for Process Vents [40 CFR 261 Subpart AA]

(a) Applicability [40 CFR 261.1030]

This paragraph applies to process vents associated with distillation, fractionation, thin-film evaporation, solvent extraction, or air or stream stripping operations that manage hazardous secondary materials excluded under the remanufacturing exclusion at (1)(d)1(xxvii) of this rule with concentrations of at least 10 ppmw, unless the process vents are equipped with operating air emission controls in accordance with the requirements of an applicable rule under the Tennessee Air Quality Act and Rule Division 1200-03 or Rule Division 0400-30.

(b) Definitions [40 CFR 261.1031]

As used in this paragraph, all terms not defined herein shall have the meaning given them in the Tennessee Hazardous Waste Management Act and subparagraph (2)(a) of Rule 0400-12-01-.01.

“Air stripping operation” is a desorption operation employed to transfer one or more volatile components from a liquid mixture into a gas (air) either with or without the application of heat to the liquid. Packed towers, spray towers, and bubble-cap, sieve, or valve-type plate towers are among the process configurations used for contacting the air and a liquid.

“Bottoms receiver” means a container or tank used to receive and collect the heavier bottoms fractions of the distillation feed stream that remain in the liquid phase.

“Closed-vent system” means a system that is not open to the atmosphere and that is composed of piping, connections, and, if necessary, flow-inducing devices that transport gas or vapor from a piece or pieces of equipment to a control device.

“Condenser” means a heat-transfer device that reduces a thermodynamic fluid from its vapor phase to its liquid phase.

“Connector” means flanged, screwed, welded, or other joined fittings used to connect two pipelines or a pipeline and a piece of equipment. For the purposes of reporting and recordkeeping, connector means flanged fittings that are not covered by insulation or other materials that prevent location of the fittings.

“Continuous recorder” means a data-recording device recording an instantaneous data value at least once every 15 minutes.

“Control device” means an enclosed combustion device, vapor recovery system, or flare. Any device the primary function of which is the recovery or capture of solvents or other organics for use, reuse, or sale (e.g., a primary condenser on a solvent recovery unit) is not a control device.

“Control device shutdown” means the cessation of operation of a control device for any purpose.

“Distillate receiver” means a container or tank used to receive and collect liquid material (condensed) from the overhead condenser of a distillation unit and from which the condensed liquid is pumped to larger storage tanks or other process units.

“Distillation operation” means an operation, either batch or continuous, separating one or more feed stream(s) into two or more exit streams, each exit stream having component concentrations different from those in the feed stream(s). The separation is achieved by the redistribution of the components between the liquid and vapor phase as they approach equilibrium within the distillation unit.

“Double block and bleed system” means two block valves connected in series with a bleed valve or line that can vent the line between the two block valves.

“Equipment” means each valve, pump, compressor, pressure relief device, sampling connection system, open-ended valve or line, or flange or other connector, and any control devices or systems required by this paragraph.

“Flame zone” means the portion of the combustion chamber in a boiler occupied by the flame envelope.

“Flow indicator” means a device that indicates whether gas flow is present in a vent stream.

“First attempt at repair” means to take rapid action for the purpose of stopping or reducing leakage of organic material to the atmosphere using best practices.

“Fractionation operation” means a distillation operation or method used to separate a mixture of several volatile components of different boiling points in successive stages, each stage removing from the mixture some proportion of one of the components.

“Hazardous secondary material management unit shutdown” means a work practice or operational procedure that stops operation of a hazardous secondary material management unit or part of a hazardous secondary material management unit. An unscheduled work practice or operational procedure that stops operation of a hazardous secondary material management unit or part of a hazardous secondary material management unit for less than 24 hours is not a hazardous secondary material management unit shutdown. The use of spare equipment and technically feasible bypassing of equipment without stopping operation are not hazardous secondary material management unit shutdowns.

“Hot well” means a container for collecting condensate as in a steam condenser serving a vacuum-jet or steam-jet ejector.

“In gas/vapor service” means that the piece of equipment contains or contacts a hazardous secondary material stream that is in the gaseous state at operating conditions.

“In heavy liquid service” means that the piece of equipment is not in gas/vapor service or in light liquid service.

“In light liquid service” means that the piece of equipment contains or contacts a material stream where the vapor pressure of one or more of the organic components in the stream is greater than 0.3 kilopascals (kPa) at 20°C, the total concentration of the pure organic components having a vapor pressure greater than 0.3 kilopascals (kPa) at 20°C is equal to or greater than 20 percent by weight, and the fluid is a liquid at operating conditions.

“In situ sampling systems” means nonextractive samplers or in-line samplers.

“In vacuum service” means that equipment is operating at an internal pressure that is at least 5 kPa below ambient pressure.

“Malfunction” means any sudden failure of a control device or a hazardous secondary material management unit or failure of a hazardous secondary material management unit to operate in a normal or usual manner, so that organic emissions are increased.

“Open-ended valve or line” means any valve, except pressure relief valves, having one side of the

valve seat in contact with hazardous secondary material and one side open to the atmosphere, either directly or through open piping.

“Pressure release” means the emission of materials resulting from the system pressure being greater than the set pressure of the pressure relief device.

“Process heater” means a device that transfers heat liberated by burning fuel to fluids contained in tubes, including all fluids except water that are heated to produce steam.

“Process vent” means any open-ended pipe or stack that is vented to the atmosphere either directly, through a vacuum-producing system, or through a tank (e.g., distillate receiver, condenser, bottoms receiver, surge control tank, separator tank, or hot well) associated with hazardous secondary material distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operations.

“Repaired” means that equipment is adjusted, or otherwise altered, to eliminate a leak.

“Sampling connection system” means an assembly of equipment within a process or material management unit used during periods of representative operation to take samples of the process or material fluid. Equipment used to take non-routine grab samples is not considered a sampling connection system.

“Sensor” means a device that measures a physical quantity or the change in a physical quantity, such as temperature, pressure, flow rate, pH, or liquid level.

“Separator tank” means a device used for separation of two immiscible liquids.

“Solvent extraction operation” means an operation or method of separation in which a solid or solution is contacted with a liquid solvent (the two being mutually insoluble) to preferentially dissolve and transfer one or more components into the solvent.

“Startup” means the setting in operation of a hazardous secondary material management unit or control device for any purpose.

“Steam stripping operation” means a distillation operation in which vaporization of the volatile constituents of a liquid mixture takes place by the introduction of steam directly into the charge.

“Surge control tank” means a large-sized pipe or storage reservoir sufficient to contain the surging liquid discharge of the process tank to which it is connected.

“Thin-film evaporation operation” means a distillation operation that employs a heating surface consisting of a large diameter tube that may be either straight or tapered, horizontal or vertical. Liquid is spread on the tube wall by a rotating assembly of blades that maintain a close clearance from the wall or actually ride on the film of liquid on the wall.

“Vapor incinerator” means any enclosed combustion device that is used for destroying organic compounds and does not extract energy in the form of steam or process heat.

“Vented” means discharged through an opening, typically an open-ended pipe or stack, allowing the passage of a stream of liquids, gases, or fumes into the atmosphere. The passage of liquids, gases, or fumes is caused by mechanical means such as compressors or vacuum-producing systems or by process-related means such as evaporation produced by heating and not caused by tank loading and unloading (working losses) or by natural means such as diurnal temperature changes.

(c) Standards: Process vents [40 CFR 261.1032]

1. The remanufacturer or other person that stores or treats hazardous secondary materials in hazardous secondary material management units with process vents associated with distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping

operations managing hazardous secondary material with organic concentrations of at least 10 ppmw shall either:

- (i) Reduce total organic emissions from all affected process vents at the facility below 1.4 kg/h (3 lb/h) and 2.8 Mg/yr (3.1 tons/yr); or
  - (ii) Reduce, by use of a control device, total organic emissions from all affected process vents at the facility by 95 weight percent.
2. If the remanufacturer or other person that stores or treats the hazardous secondary material installs a closed-vent system and control device to comply with the provisions of part 1 of this subparagraph the closed-vent system and control device must meet the requirements of subparagraph (d) of this paragraph.
  3. Determinations of vent emissions and emission reductions or total organic compound concentrations achieved by add-on control devices may be based on engineering calculations or performance tests. If performance tests are used to determine vent emissions, emission reductions, or total organic compound concentrations achieved by add-on control devices, the performance tests must conform with the requirements of part (e)3 of this paragraph.
  4. When a remanufacturer or other person that stores or treats the hazardous secondary material and the Commissioner do not agree on determinations of vent emissions and/or emission reductions or total organic compound concentrations achieved by add-on control devices based on engineering calculations, the procedures in part (e)3 of this paragraph shall be used to resolve the disagreement.

(d) Standards: Closed-vent systems and control devices [40 CFR 261.1033]

1. (i) The remanufacturer or other person that stores or treats the hazardous secondary materials in hazardous secondary material management units using closed-vent systems and control devices used to comply with provisions of this rule shall comply with the provisions of this subparagraph.  
  
(ii) Reserved
2. A control device involving vapor recovery (e.g., a condenser or adsorber) shall be designed and operated to recover the organic vapors vented to it with an efficiency of 95 weight percent or greater unless the total organic emission limits of subpart (c)1(i) of this paragraph for all affected process vents can be attained at an efficiency less than 95 weight percent.
3. An enclosed combustion device (e.g., a vapor incinerator, boiler, or process heater) shall be designed and operated to reduce the organic emissions vented to it by 95 weight percent or greater; to achieve a total organic compound concentration of 20 ppmv, expressed as the sum of the actual compounds, not carbon equivalents, on a dry basis corrected to 3 percent oxygen; or to provide a minimum residence time of 0.50 seconds at a minimum temperature of 760°C. If a boiler or process heater is used as the control device, then the vent stream shall be introduced into the flame zone of the boiler or process heater.
4. (i) A flare shall be designed for and operated with no visible emissions as determined by the methods specified in subpart 5(i) of this subparagraph, except for periods not to exceed a total of 5 minutes during any 2 consecutive hours.  
  
(ii) A flare shall be operated with a flame present at all times, as determined by the methods specified in item 6(ii)(III) of this subparagraph.  
  
(iii) A flare shall be used only if the net heating value of the gas being combusted is 11.2 MJ/scm (300 Btu/scf) or greater if the flare is steam-assisted or air-assisted;

or if the net heating value of the gas being combusted is 7.45 MJ/scm (200 Btu/scf) or greater if the flare is nonassisted. The net heating value of the gas being combusted shall be determined by the methods specified in subpart 5(ii) of this subparagraph.

- (iv) (I) A steam-assisted or nonassisted flare shall be designed for and operated with an exit velocity, as determined by the methods specified in subpart 5(iii) of this subparagraph, less than 18.3 m/s (60 ft/s), except as provided in items (II) and (III) of this subpart.
  - (II) A steam-assisted or nonassisted flare designed for and operated with an exit velocity, as determined by the methods specified in subpart 5(iii) of this subparagraph, equal to or greater than 18.3 m/s (60 ft/s) but less than 122 m/s (400 ft/s) is allowed if the net heating value of the gas being combusted is greater than 37.3 MJ/scm (1,000 Btu/scf).
  - (III) A steam-assisted or nonassisted flare designed for and operated with an exit velocity, as determined by the methods specified in subpart 5(iii) of this subparagraph, less than the velocity,  $V_{max}$ , as determined by the method specified in subpart 5(iv) of this subparagraph and less than 122 m/s (400 ft/s) is allowed.
  - (v) An air-assisted flare shall be designed and operated with an exit velocity less than the velocity,  $V_{max}$ , as determined by the method specified in subpart 5(v) of this subparagraph.
  - (vi) A flare used to comply with this section shall be steam-assisted, air-assisted, or nonassisted.
5. (i) Reference Method 22 in 40 CFR part 60 shall be used to determine the compliance of a flare with the visible emission provisions of this subpart. The observation period is 2 hours and shall be used according to Method 22.
- (ii) The net heating value of the gas being combusted in a flare shall be calculated using the following equation:

$$H_t = K \left[ \sum_{i=1}^n C_i H_i \right]$$

where:

- $H_t$  = Net heating value of the sample, MJ/scm; where the net enthalpy per mole of offgas is based on combustion at 25 °C and 760 mm Hg, but the standard temperature for determining the volume corresponding to 1 mol is 20 °C;
- $K$  = Constant,  $1.74 \times 10^{-7}$  (1/ppm) (g mol/scm) (MJ/kcal) where standard temperature for (g mol/scm) is 20 °C;
- $C_i$  = Concentration of sample component i in ppm on a wet basis, as measured for organics by Reference Method 18 in 40 CFR part 60 and measured for hydrogen and carbon monoxide by ASTM D 1946-82 (listed in Rule 0400-12-01-.01(2)(b)); and
- $H_i$  = Net heat of combustion of sample component i, kcal/g mol at

25°C and 760 mm Hg. The heats of combustion may be determined using ASTM D 2382-83 (listed in Rule 0400-12-01-.01(2)(b)) if published values are not available or cannot be calculated.

(iii) The actual exit velocity of a flare shall be determined by dividing the volumetric flow rate (in units of standard temperature and pressure), as determined by Reference Methods 2, 2A, 2C, or 2D in 40 CFR part 60 as appropriate, by the unobstructed (free) cross-sectional area of the flare tip.

(iv) The maximum allowed velocity in m/s,  $V_{max}$ , for a flare complying with item 4(iv)(III) of this subparagraph shall be determined by the following equation:

$$\text{Log}_{10}(V_{max}) = (HT + 28.8) \div 31.7$$

Where:

28.8 = Constant,

31.7 = Constant,

HT = The net heating value as determined in subpart (ii) of this part.

(v) The maximum allowed velocity in m/s,  $V_{max}$ , for an air-assisted flare shall be determined by the following equation:

$$V_{max} = 8.706 + 0.7084 (HT)$$

Where:

8.706 = Constant,

0.7084 = Constant,

HT = The net heating value as determined in subpart (ii) of this part.

6. The remanufacturer or other person that stores or treats the hazardous secondary material shall monitor and inspect each control device required to comply with this subparagraph to ensure proper operation and maintenance of the control device by implementing the following requirements:

(i) Install, calibrate, maintain, and operate according to the manufacturer's specifications a flow indicator that provides a record of vent stream flow from each affected process vent to the control device at least once every hour. The flow indicator sensor shall be installed in the vent stream at the nearest feasible point to the control device inlet but before the point at which the vent streams are combined.

(ii) Install, calibrate, maintain, and operate according to the manufacturer's specifications a device to continuously monitor control device operation as specified below:

(I) For a thermal vapor incinerator, a temperature monitoring device equipped with a continuous recorder. The device shall have an accuracy of  $\pm 1$  percent of the temperature being monitored in °C or  $\pm 0.5$  °C, whichever is greater. The temperature sensor shall be installed at a location in the combustion chamber downstream of the combustion zone.

(II) For a catalytic vapor incinerator, a temperature monitoring device equipped with a continuous recorder. The device shall be capable of



monitoring temperature at two locations and have an accuracy of  $\pm 1$  percent of the temperature being monitored in  $^{\circ}\text{C}$  or  $\pm 0.5$   $^{\circ}\text{C}$ , whichever is greater. One temperature sensor shall be installed in the vent stream at the nearest feasible point to the catalyst bed inlet and a second temperature sensor shall be installed in the vent stream at the nearest feasible point to the catalyst bed outlet.

- (III) For a flare, a heat sensing monitoring device equipped with a continuous recorder that indicates the continuous ignition of the pilot flame.
  - (IV) For a boiler or process heater having a design heat input capacity less than 44 MW, a temperature monitoring device equipped with a continuous recorder. The device shall have an accuracy of  $\pm 1$  percent of the temperature being monitored in  $^{\circ}\text{C}$  or  $\pm 0.5$   $^{\circ}\text{C}$ , whichever is greater. The temperature sensor shall be installed at a location in the furnace downstream of the combustion zone.
  - (V) For a boiler or process heater having a design heat input capacity greater than or equal to 44 MW, a monitoring device equipped with a continuous recorder to measure a parameter(s) that indicates good combustion operating practices are being used.
  - (VI) For a condenser, either:
    - I. A monitoring device equipped with a continuous recorder to measure the concentration level of the organic compounds in the exhaust vent stream from the condenser; or
    - II. A temperature monitoring device equipped with a continuous recorder. The device shall be capable of monitoring temperature with an accuracy of  $\pm 1$  percent of the temperature being monitored in degrees Celsius ( $^{\circ}\text{C}$ ) or  $\pm 0.5$   $^{\circ}\text{C}$ , whichever is greater. The temperature sensor shall be installed at a location in the exhaust vent stream from the condenser exit (i.e., product side).
  - (VII) For a carbon adsorption system that regenerates the carbon bed directly in the control device such as a fixed-bed carbon adsorber, either:
    - I. A monitoring device equipped with a continuous recorder to measure the concentration level of the organic compounds in the exhaust vent stream from the carbon bed; or
    - II. A monitoring device equipped with a continuous recorder to measure a parameter that indicates the carbon bed is regenerated on a regular, predetermined time cycle.
  - (iii) Inspect the readings from each monitoring device required by subparts (i) and (ii) of this part at least once each operating day to check control device operation and, if necessary, immediately implement the corrective measures necessary to ensure the control device operates in compliance with the requirements of this subparagraph.
7. A remanufacturer or other person that stores or treats hazardous secondary material in a hazardous secondary material management unit using a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly onsite in the control device shall replace the existing carbon in the control device with fresh carbon at a regular, predetermined time interval that is no longer than the carbon service life established as a requirement of subitem (f)2(iv)(III)VI of this paragraph.

8. A remanufacturer or other person that stores or treats hazardous secondary material in a hazardous secondary material management unit using a carbon adsorption system such as a carbon canister that does not regenerate the carbon bed directly onsite in the control device shall replace the existing carbon in the control device with fresh carbon on a regular basis by using one of the following procedures:
  - (i) Monitor the concentration level of the organic compounds in the exhaust vent stream from the carbon adsorption system on a regular schedule, and replace the existing carbon with fresh carbon immediately when carbon breakthrough is indicated. The monitoring frequency shall be daily or at an interval no greater than 20 percent of the time required to consume the total carbon working capacity established as a requirement of subitem (f)2(iv)(III)VII of this paragraph, whichever is longer.
  - (ii) Replace the existing carbon with fresh carbon at a regular, predetermined time interval that is less than the design carbon replacement interval established as a requirement of subitem (f)2(iv)(III)VII of this paragraph.
9. An alternative operational or process parameter may be monitored if it can be demonstrated that another parameter will ensure that the control device is operated in conformance with these standards and the control device's design specifications.
10. A remanufacturer or other person that stores or treats hazardous secondary material at an affected facility seeking to comply with the provisions of this rule by using a control device other than a thermal vapor incinerator, catalytic vapor incinerator, flare, boiler, process heater, condenser, or carbon adsorption system is required to develop documentation including sufficient information to describe the control device operation and identify the process parameter or parameters that indicate proper operation and maintenance of the control device.
11. A closed-vent system shall meet either of the following design requirements:
  - (i) A closed-vent system shall be designed to operate with no detectable emissions, as indicated by an instrument reading of less than 500 ppmv above background as determined by the procedure in part (e)2 of this paragraph, and by visual inspections; or
  - (ii) A closed-vent system shall be designed to operate at a pressure below atmospheric pressure. The system shall be equipped with at least one pressure gauge or other pressure measurement device that can be read from a readily accessible location to verify that negative pressure is being maintained in the closed-vent system when the control device is operating.
12. The remanufacturer or other person that stores or treats the hazardous secondary material shall monitor and inspect each closed-vent system required to comply with this subparagraph to ensure proper operation and maintenance of the closed-vent system by implementing the following requirements:
  - (i) Each closed-vent system that is used to comply with subpart 11(i) of this subparagraph shall be inspected and monitored in accordance with the following requirements:
    - (I) An initial leak detection monitoring of the closed-vent system shall be conducted by the remanufacturer or other person that stores or treats the hazardous secondary material on or before the date that the system becomes subject to this subparagraph. The remanufacturer or other person that stores or treats the hazardous secondary material shall monitor the closed-vent system components and connections using the procedures specified in part (e)2 of this paragraph to demonstrate that the closed-vent system operates with no detectable emissions, as

indicated by an instrument reading of less than 500 ppmv above background.

- (II) After initial leak detection monitoring required in item (I) of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material shall inspect and monitor the closed-vent system as follows:
    - I. Closed-vent system joints, seams, or other connections that are permanently or semi-permanently sealed (e.g., a welded joint between two sections of hard piping or a bolted and gasketed ducting flange) shall be visually inspected at least once per year to check for defects that could result in air pollutant emissions. The remanufacturer or other person that stores or treats the hazardous secondary material shall monitor a component or connection using the procedures specified in part (e)2 of this paragraph to demonstrate that it operates with no detectable emissions following any time the component is repaired or replaced (e.g., a section of damaged hard piping is replaced with new hard piping) or the connection is unsealed (e.g., a flange is unbolted).
    - II. Closed-vent system components or connections other than those specified in subitem I of this item shall be monitored annually and at other times as requested by the Commissioner, except as provided for in part 15 of this subparagraph, using the procedures specified in part (e)2 of this paragraph to demonstrate that the components or connections operate with no detectable emissions.
  - (III) In the event that a defect or leak is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect or leak in accordance with the requirements of subpart (iii) of part.
  - (IV) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection and monitoring in accordance with the requirements specified in subparagraph (f) of this paragraph.
- (ii) Each closed-vent system that is used to comply with subpart 11(ii) of this subparagraph shall be inspected and monitored in accordance with the following requirements:
- (I) The closed-vent system shall be visually inspected by the remanufacturer or other person that stores or treats the hazardous secondary material to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes, or gaps in ductwork or piping or loose connections.
  - (II) The remanufacturer or other person that stores or treats the hazardous secondary material shall perform an initial inspection of the closed-vent system on or before the date that the system becomes subject to this subparagraph. Thereafter, the remanufacturer or other person that stores or treats the hazardous secondary material shall perform the inspections at least once every year.
  - (III) In the event that a defect or leak is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of subpart (iii) of

this part.

- (IV) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection and monitoring in accordance with the requirements specified in subparagraph (f) of this paragraph.
- (iii) The remanufacturer or other person that stores or treats the hazardous secondary material shall repair all detected defects as follows:
  - (I) Detectable emissions, as indicated by visual inspection, or by an instrument reading greater than 500 ppmv above background, shall be controlled as soon as practicable, but not later than 15 calendar days after the emission is detected, except as provided for in item (III) of this subpart.
  - (II) A first attempt at repair shall be made no later than 5 calendar days after the emission is detected.
  - (III) Delay of repair of a closed-vent system for which leaks have been detected is allowed if the repair is technically infeasible without a process unit shutdown, or if the remanufacturer or other person that stores or treats the hazardous secondary material determines that emissions resulting from immediate repair would be greater than the fugitive emissions likely to result from delay of repair. Repair of such equipment shall be completed by the end of the next process unit shutdown.
  - (IV) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the defect repair in accordance with the requirements specified in subparagraph (f) of this paragraph.
- 13. Closed-vent systems and control devices used to comply with provisions of this paragraph shall be operated at all times when emissions may be vented to them.
- 14. The owner or operator using a carbon adsorption system to control air pollutant emissions shall document that all carbon that is a hazardous waste and that is removed from the control device is managed in one of the following manners, regardless of the average volatile organic concentration of the carbon:
  - (i) Regenerated or reactivated in a thermal treatment unit that meets one of the following:
    - (I) The owner or operator of the unit has been issued a final permit under Rule 0400-12-01-.07 which implements the requirements of paragraph (27) of Rule 0400-12-01-.06;
    - (II) The unit is equipped with and operating air emission controls in accordance with the applicable requirements of either paragraphs (27) and (29) of Rule 0400-12-01-.05 or paragraphs (30) and (32) of Rule 0400-12-01-.06; or
    - (III) The unit is equipped with and operating air emission controls in accordance with a national emission standard for hazardous air pollutants under 40 CFR part 61 or 40 CFR part 63.
  - (ii) Incinerated in a hazardous waste incinerator for which the owner or operator either:
    - (I) Has been issued a final permit under Rule 0400-12-01-.07 which

implements the requirements of paragraph (15) of Rule 0400-12-01-.06;  
or

- (II) Has designed and operates the incinerator in accordance with the interim status requirements of paragraph (15) of Rule 0400-12-01-.05.
  - (iii) Burned in a boiler or industrial furnace for which the owner or operator either:
    - (i) Has been issued a final permit under Rule 0400-12-01-.07 which implements the requirements of paragraph (8) of Rule 0400-12-01-.09; or
    - (II) Has designed and operates the boiler or industrial furnace in accordance with the interim status requirements of paragraph (8) of Rule 0400-12-01-.09,
15. Any components of a closed-vent system that are designated, as described in subpart (f)3(ix) of this paragraph, as unsafe to monitor are exempt from the requirements of subitem 12(i)(II) of this subparagraph if:
- (i) The remanufacturer or other person that stores or treats the hazardous secondary material in a hazardous secondary material management unit using a closed-vent system determines that the components of the closed-vent system are unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with subitem 12(i)(II) of this subparagraph; and
  - (ii) The remanufacturer or other person that stores or treats the hazardous secondary material in a hazardous secondary material management unit using a closed-vent system adheres to a written plan that requires monitoring the closed-vent system components using the procedure specified in subitem 12(i)(II) of this subparagraph as frequently as practicable during safe-to-monitor times.
- (e) Test methods and procedures [40 CFR 261.1034]
- 1. Each remanufacturer or other person that stores or treats the hazardous secondary material subject to the provisions of this paragraph shall comply with the test methods and procedural requirements provided in this subparagraph.
  - 2. When a closed-vent system is tested for compliance with no detectable emissions, as required in part (d)12 of this paragraph, the test shall comply with the following requirements:
    - (i) Monitoring shall comply with Reference Method 21 in 40 CFR part 60.
    - (ii) The detection instrument shall meet the performance criteria of Reference Method 21.
    - (iii) The instrument shall be calibrated before use on each day of its use by the procedures specified in Reference Method 21.
    - (iv) Calibration gases shall be:
      - (I) Zero air (less than 10 ppm of hydrocarbon in air).
      - (II) A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppm methane or n-hexane.
    - (v) The background level shall be determined as set forth in Reference Method 21.
    - (iv) The instrument probe shall be traversed around all potential leak interfaces as

close to the interface as possible as described in Reference Method 21.

- (vii) The arithmetic difference between the maximum concentration indicated by the instrument and the background level is compared with 500 ppm for determining compliance.
3. Performance tests to determine compliance with part (c)1 of this paragraph and with the total organic compound concentration limit of part (d)3 of this paragraph shall comply with the following:
- (i) Performance tests to determine total organic compound concentrations and mass flow rates entering and exiting control devices shall be conducted and data reduced in accordance with the following reference methods and calculation procedures:
    - (I) Method 2 in 40 CFR part 60 for velocity and volumetric flow rate.
    - (II) Method 18 or Method 25A in 40 CFR part 60, appendix A, for organic content. If Method 25A is used, the organic HAP used as the calibration gas must be the single organic HAP representing the largest percent by volume of the emissions. The use of Method 25A is acceptable if the response from the high-level calibration gas is at least 20 times the standard deviation of the response from the zero calibration gas when the instrument is zeroed on the most sensitive scale.
    - (III) Each performance test shall consist of three separate runs; each run conducted for at least 1 hour under the conditions that exist when the hazardous secondary material management unit is operating at the highest load or capacity level reasonably expected to occur. For the purpose of determining total organic compound concentrations and mass flow rates, the average of results of all runs shall apply. The average shall be computed on a time-weighted basis.
    - (IV) Total organic mass flow rates shall be determined by the following equation:
      - I. For sources utilizing Method 18.

$$E_h = Q_{2sd} \left[ \sum_{i=1}^n C_i MW_i \right] (0.0416) (10^{-6})$$

where:

$E_h$  = Total organic mass flow rate, kg/h;

$Q_{2sd}$  = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm/h;

$n$  = Number of organic compounds in the vent gas;

$C_i$  = Organic concentration in ppm, dry basis, of compound  $i$  in the vent gas, as determined by Method 18;

$MW_i$  = Molecular weight of organic compound  $i$  in the vent gas, kg/kg-mol;

0.0416 = Conversion factor for molar volume, kg-mol/m<sup>3</sup> (@ 293 K and 760 mm Hg);

10<sup>-6</sup> = Conversion from ppm.

II. For sources utilizing Method 25A.

$$E_h = (Q)(C)(MW)(0.0416)(10^{-6})$$

where:

$E_h$  = Total organic mass flow rate, kg/h;

$Q$  = Volumetric flow rate of gases entering or exiting control device, as determined by Method 2, dscm/h;

$C$  = Organic concentration in ppm, dry basis, as determined by Method 25A;

$MW$  = Molecular weight of propane, 44;

0.0416 = Conversion factor for molar volume, kg-mol/m<sup>3</sup> (@ 293 K and 760 mm Hg);

10<sup>-6</sup> = Conversion from ppm.

(V) The annual total organic emission rate shall be determined by the following equation:

$$E_A = (E_h)(H)$$

where:

$E_A$  = Total organic mass emission rate, kg/y;

$E_h$  = Total organic mass flow rate for the process vent, kg/h;

$H$  = Total annual hours of operations for the affected unit, h.

(VI) Total organic emissions from all affected process vents at the facility shall be determined by summing the hourly total organic mass emission rates ( $E_h$ , as determined in item (IV) of this subpart) and by summing the annual total organic mass emission rates ( $E_A$ , as determined in item (V) of this subpart) for all affected process vents at the facility.

(ii) The remanufacturer or other person that stores or treats the hazardous secondary material shall record such process information as may be necessary to determine the conditions of the performance tests. Operations during periods of startup, shutdown, and malfunction shall not constitute representative conditions for the purpose of a performance test.

(iii) The remanufacturer or other person that stores or treats the hazardous secondary material at an affected facility shall provide, or cause to be provided, performance testing facilities as follows:

(I) Sampling ports adequate for the test methods specified in subpart (i) of this part.

- (II) Safe sampling platform(s).
  - (III) Safe access to sampling platform(s).
  - (IV) Utilities for sampling and testing equipment.
- (iv) For the purpose of making compliance determinations, the time-weighted average of the results of the three runs shall apply. In the event that a sample is accidentally lost or conditions occur in which one of the three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sample train, extreme meteorological conditions, or other circumstances beyond the remanufacturer's or other person's that stores or treats the hazardous secondary material control, compliance may, upon the Commissioner's approval, be determined using the average of the results of the two other runs.
4. To show that a process vent associated with a hazardous secondary material distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operation is not subject to the requirements of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material must make an initial determination that the time-weighted, annual average total organic concentration of the material managed by the hazardous secondary material management unit is less than 10 ppmw using one of the following two methods:
- (i) Direct measurement of the organic concentration of the material using the following procedures:
    - (I) The remanufacturer or other person that stores or treats the hazardous secondary material must take a minimum of four grab samples of material for each material stream managed in the affected unit under process conditions expected to cause the maximum material organic concentration.
    - (II) For material generated onsite, the grab samples must be collected at a point before the material is exposed to the atmosphere such as in an enclosed pipe or other closed system that is used to transfer the material after generation to the first affected distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operation. For material generated offsite, the grab samples must be collected at the inlet to the first material management unit that receives the material provided the material has been transferred to the facility in a closed system such as a tank truck and the material is not diluted or mixed with other material.
    - (III) Each sample shall be analyzed and the total organic concentration of the sample shall be computed using Method 9060A (incorporated by reference under subparagraph (2)(b) of Rule 0400-12-01-.01) of "Test Methods for Evaluating Solid Waste, Physical/Chemical Methods," EPA Publication SW-846, or analyzed for its individual organic constituents.
    - (IV) The arithmetic mean of the results of the analyses of the four samples shall apply for each material stream managed in the unit in determining the time-weighted, annual average total organic concentration of the material. The time-weighted average is to be calculated using the annual quantity of each material stream processed and the mean organic concentration of each material stream managed in the unit.
  - (ii) Using knowledge of the material to determine that its total organic concentration is less than 10 ppmw. Documentation of the material determination is required. Examples of documentation that shall be used to support a determination under this provision include production process information documenting that no



organic compounds are used, information that the material is generated by a process that is identical to a process at the same or another facility that has previously been demonstrated by direct measurement to generate a material stream having a total organic content less than 10 ppmw, or prior speciation analysis results on the same material stream where it can also be documented that no process changes have occurred since that analysis that could affect the material total organic concentration.

5. The determination that distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operations manage hazardous secondary materials with time-weighted, annual average total organic concentrations less than 10 ppmw shall be made as follows:
    - (i) By the effective date that the facility becomes subject to the provisions of this paragraph or by the date when the material is first managed in a hazardous secondary material management unit, whichever is later, and
    - (ii) For continuously generated material, annually, or
    - (iii) Whenever there is a change in the material being managed or a change in the process that generates or treats the material.
  6. When a remanufacturer or other person that stores or treats the hazardous secondary material and the Commissioner do not agree on whether a distillation, fractionation, thin-film evaporation, solvent extraction, or air or steam stripping operation manages a hazardous secondary material with organic concentrations of at least 10 ppmw based on knowledge of the material, the dispute may be resolved by using direct measurement as specified at subpart 4(i) of this subparagraph.
- (f) Recordkeeping requirements [40 CFR 261.1035]
1.
    - (i) Each remanufacturer or other person that stores or treats the hazardous secondary material subject to the provisions of this paragraph shall comply with the recordkeeping requirements of this subparagraph.
    - (ii) A remanufacturer or other person that stores or treats the hazardous secondary material of more than one hazardous secondary material management unit subject to the provisions of this subpart may comply with the recordkeeping requirements for these hazardous secondary material management units in one recordkeeping system if the system identifies each record by each hazardous secondary material management unit.
  2. The remanufacturer or other person that stores or treats the hazardous secondary material must keep the following records on-site:
    - (i) For facilities that comply with the provisions of subpart (d)1(ii) of this paragraph, an implementation schedule that includes dates by which the closed-vent system and control device will be installed and in operation. The schedule must also include a rationale of why the installation cannot be completed at an earlier date. The implementation schedule must be kept on-site at the facility by the effective date that the facility becomes subject to the provisions of this paragraph.
    - (ii) Up-to-date documentation of compliance with the process vent standards in subparagraph (c) of this paragraph, including:
      - (I) Information and data identifying all affected process vents, annual throughput and operating hours of each affected unit, estimated emission rates for each affected vent and for the overall facility (i.e., the total emissions for all affected vents at the facility), and the approximate location within the facility of each affected unit (e.g., identify the

hazardous secondary material management units on a facility plot plan).

- (II) Information and data supporting determinations of vent emissions and emission reductions achieved by add-on control devices based on engineering calculations or source tests. For the purpose of determining compliance, determinations of vent emissions and emission reductions must be made using operating parameter values (e.g., temperatures, flow rates, or vent stream organic compounds and concentrations) that represent the conditions that result in maximum organic emissions, such as when the hazardous secondary material management unit is operating at the highest load or capacity level reasonably expected to occur. If the remanufacturer or other person that stores or treats the hazardous secondary material takes any action (e.g., managing a material of different composition or increasing operating hours of affected hazardous secondary material management units) that would result in an increase in total organic emissions from affected process vents at the facility, then a new determination is required.
- (iii) Where a remanufacturer or other person that stores or treats the hazardous secondary material chooses to use test data to determine the organic removal efficiency or total organic compound concentration achieved by the control device, a performance test plan must be developed and include:
  - (I) A description of how it is determined that the planned test is going to be conducted when the hazardous secondary material management unit is operating at the highest load or capacity level reasonably expected to occur. This shall include the estimated or design flow rate and organic content of each vent stream and define the acceptable operating ranges of key process and control device parameters during the test program.
  - (II) A detailed engineering description of the closed-vent system and control device including:
    - I. Manufacturer's name and model number of control device.
    - II. Type of control device.
    - III. Dimensions of the control device.
    - IV. Capacity.
    - V. Construction materials.
  - (III) A detailed description of sampling and monitoring procedures, including sampling and monitoring locations in the system, the equipment to be used, sampling and monitoring frequency, and planned analytical procedures for sample analysis.
- (iv) Documentation of compliance with subparagraph (d) of this paragraph shall include the following information:
  - (I) A list of all information references and sources used in preparing the documentation.
  - (II) Records, including the dates, of each compliance test required by part (d)11 of this paragraph.
  - (III) If engineering calculations are used, a design analysis, specifications, drawings, schematics, and piping and instrumentation diagrams based on the appropriate sections of "APTI Course 415: Control of Gaseous

Emissions” (incorporated by reference as specified in subparagraph (2)(b) of Rule 0400-12-01-.01) or other engineering texts acceptable to the Commissioner that present basic control device design information. Documentation provided by the control device manufacturer or vendor that describes the control device design in accordance with subitems I through VII of this item may be used to comply with this requirement. The design analysis shall address the vent stream characteristics and control device operation parameters as specified below.

- I. For a thermal vapor incinerator, the design analysis shall consider the vent stream composition, constituent concentrations, and flow rate. The design analysis shall also establish the design minimum and average temperature in the combustion zone and the combustion zone residence time.
- II. For a catalytic vapor incinerator, the design analysis shall consider the vent stream composition, constituent concentrations, and flow rate. The design analysis shall also establish the design minimum and average temperatures across the catalyst bed inlet and outlet.
- III. For a boiler or process heater, the design analysis shall consider the vent stream composition, constituent concentrations, and flow rate. The design analysis shall also establish the design minimum and average flame zone temperatures, combustion zone residence time, and description of method and location where the vent stream is introduced into the combustion zone.
- IV. For a flare, the design analysis shall consider the vent stream composition, constituent concentrations, and flow rate. The design analysis shall also consider the requirements specified in part (d)4 of this paragraph.
- V. For a condenser, the design analysis shall consider the vent stream composition, constituent concentrations, flow rate, relative humidity, and temperature. The design analysis shall also establish the design outlet organic compound concentration level, design average temperature of the condenser exhaust vent stream, and design average temperatures of the coolant fluid at the condenser inlet and outlet.
- VI. For a carbon adsorption system such as a fixed-bed adsorber that regenerates the carbon bed directly onsite in the control device, the design analysis shall consider the vent stream composition, constituent concentrations, flow rate, relative humidity, and temperature. The design analysis shall also establish the design exhaust vent stream organic compound concentration level, number and capacity of carbon beds, type and working capacity of activated carbon used for carbon beds, design total steam flow over the period of each complete carbon bed regeneration cycle, duration of the carbon bed steaming and cooling/drying cycles, design carbon bed temperature after regeneration, design carbon bed regeneration time, and design service life of carbon.
- VII. For a carbon adsorption system such as a carbon canister that does not regenerate the carbon bed directly onsite in the control device, the design analysis shall consider the vent stream composition, constituent concentrations, flow rate, relative humidity, and temperature. The design analysis shall also

establish the design outlet organic concentration level, capacity of carbon bed, type and working capacity of activated carbon used for carbon bed, and design carbon replacement interval based on the total carbon working capacity of the control device and source operating schedule.

- (IV) A statement signed and dated by the remanufacturer or other person that stores or treats the hazardous secondary material certifying that the operating parameters used in the design analysis reasonably represent the conditions that exist when the hazardous secondary material management unit is or would be operating at the highest load or capacity level reasonably expected to occur.
  - (V) A statement signed and dated by the remanufacturer or other person that stores or treats the hazardous secondary material certifying that the control device is designed to operate at an efficiency of 95 percent or greater unless the total organic concentration limit of part (c)1 of this paragraph is achieved at an efficiency less than 95 weight percent or the total organic emission limits of part (c)1 of this paragraph for affected process vents at the facility can be attained by a control device involving vapor recovery at an efficiency less than 95 weight percent. A statement provided by the control device manufacturer or vendor certifying that the control equipment meets the design specifications may be used to comply with this requirement.
  - (VI) If performance tests are used to demonstrate compliance, all test results.
3. Design documentation and monitoring, operating, and inspection information for each closed-vent system and control device required to comply with the provisions of this rule shall be recorded and kept up-to-date at the facility. The information shall include:
- (i) Description and date of each modification that is made to the closed-vent system or control device design.
  - (ii) Identification of operating parameter, description of monitoring device, and diagram of monitoring sensor location or locations used to comply with subparts (d)6(i) and (ii) of this paragraph.
  - (iii) Monitoring, operating, and inspection information required by part (d)6 through 11 of this paragraph.
  - (iv) Date, time, and duration of each period that occurs while the control device is operating when any monitored parameter exceeds the value established in the control device design analysis as specified below:
    - (I) For a thermal vapor incinerator designed to operate with a minimum residence time of 0.50 second at a minimum temperature of 760°C, period when the combustion temperature is below 760°C.
    - (II) For a thermal vapor incinerator designed to operate with an organic emission reduction efficiency of 95 weight percent or greater, period when the combustion zone temperature is more than 28°C below the design average combustion zone temperature established as a requirement of subitem 2(iv)(III)I of this subparagraph.
    - (III) For a catalytic vapor incinerator, period when:
      - I. Temperature of the vent stream at the catalyst bed inlet is more than 28°C below the average temperature of the inlet vent stream established as a requirement of subitem 2(iv)(III)II of this

subparagraph; or

- II. Temperature difference across the catalyst bed is less than 80 percent of the design average temperature difference established as a requirement of subitem 2(iv)(III)II.

(IV) For a boiler or process heater, period when:

- I. Flame zone temperature is more than 28°C below the design average flame zone temperature established as a requirement of subitem 2(iv)(III)III of this subparagraph; or
- II. Position changes where the vent stream is introduced to the combustion zone from the location established as a requirement of subitem 2(iv)(III)III of this subparagraph.

(V) For a flare, period when the pilot flame is not ignited.

(VI) For a condenser that complies with subitem (d)6(ii)(VI)I of this paragraph, period when the organic compound concentration level or readings of organic compounds in the exhaust vent stream from the condenser are more than 20 percent greater than the design outlet organic compound concentration level established as a requirement of subitem 2(iv)(III)V of this subparagraph.

(VII) For a condenser that complies with subitem (d)6(ii)(VI)II of this paragraph, period when:

- I. Temperature of the exhaust vent stream from the condenser is more than 6°C above the design average exhaust vent stream temperature established as a requirement of subitem 2(iv)(III)V of this subparagraph; or
- II. Temperature of the coolant fluid exiting the condenser is more than 6°C above the design average coolant fluid temperature at the condenser outlet established as a requirement of subitem 2(iv)(III)V of this subparagraph.

(VIII) For a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly on-site in the control device and complies with subitem (d)6(ii)(VII)I of this paragraph, period when the organic compound concentration level or readings of organic compounds in the exhaust vent stream from the carbon bed are more than 20 percent greater than the design exhaust vent stream organic compound concentration level established as a requirement of subitem 2(iv)(III)VI of this subparagraph.

(IX) For a carbon adsorption system such as a fixed-bed carbon adsorber that regenerates the carbon bed directly on-site in the control device and complies with subitem (d)6(ii)(VII)II of this paragraph, period when the vent stream continues to flow through the control device beyond the predetermined carbon bed regeneration time established as a requirement of subitem 2(iv)(III)VI of this subparagraph.

(v) Explanation for each period recorded under subpart (iv) of this part of the cause for control device operating parameter exceeding the design value and the measures implemented to correct the control device operation.

(vi) For a carbon adsorption system operated subject to requirements specified in part (d)7 or subpart (d)8(ii) of this paragraph, date when existing carbon in the

control device is replaced with fresh carbon.

- (vii) For a carbon adsorption system operated subject to requirements specified in subpart (d)8(i) of this paragraph, a log that records:
    - (I) Date and time when control device is monitored for carbon breakthrough and the monitoring device reading.
    - (II) Date when existing carbon in the control device is replaced with fresh carbon.
  - (viii) Date of each control device startup and shutdown.
  - (ix) A remanufacturer or other person that stores or treats the hazardous secondary material designating any components of a closed-vent system as unsafe to monitor pursuant to part (d)15 of this paragraph shall record in a log that is kept at the facility the identification of closed-vent system components that are designated as unsafe to monitor in accordance with the requirements of part (d)15 of this paragraph, an explanation for each closed-vent system component stating why the closed-vent system component is unsafe to monitor, and the plan for monitoring each closed-vent system component.
  - (x) When each leak is detected as specified in part (d)12 of this paragraph, the following information shall be recorded:
    - (I) The instrument identification number, the closed-vent system component identification number, and the operator name, initials, or identification number.
    - (II) The date the leak was detected and the date of first attempt to repair the leak.
    - (III) The date of successful repair of the leak.
    - (IV) Maximum instrument reading measured by Method 21 of 40 CFR part 60, appendix A after it is successfully repaired or determined to be nonrepairable.
    - (V) "Repair delayed" and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.
      - I. The remanufacturer or other person that stores or treats the hazardous secondary material may develop a written procedure that identifies the conditions that justify a delay of repair. In such cases, reasons for delay of repair may be documented by citing the relevant sections of the written procedure.
      - II. If delay of repair was caused by depletion of stocked parts, there must be documentation that the spare parts were sufficiently stocked on-site before depletion and the reason for depletion.
4. Records of the monitoring, operating, and inspection information required by subparts 3(iii) through (x) of this subparagraph shall be maintained by the owner or operator for at least 3 years following the date of each occurrence, measurement, maintenance, corrective action, or record.
5. For a control device other than a thermal vapor incinerator, catalytic vapor incinerator, flare, boiler, process heater, condenser, or carbon adsorption system, the Commissioner will specify the appropriate recordkeeping requirements.

6. Up-to-date information and data used to determine whether or not a process vent is subject to the requirements in subparagraph (c) of this paragraph including supporting documentation as required by subpart (e)4(ii) of this paragraph when application of the knowledge of the nature of the hazardous secondary material stream or the process by which it was produced is used, shall be recorded in a log that is kept at the facility.

(g) through (t) Reserved [40 CFR 261.1036-261.1049]

(28) Air Emission Standards for Equipment Leaks [40 CFR 261 -- Subpart BB]

(a) Applicability. [40 CFR 261.1050]

1. This paragraph applies to equipment that contains hazardous secondary materials excluded under the remanufacturing exclusion at subpart (1)(d)1(xxvii) of this rule, unless the equipment operations are subject to the requirements of an applicable Clean Air Act regulation codified under 40 CFR part 60, part 61, or part 63.
2. Reserved

(b) Definitions [40 CFR 261.1051]

As used in this paragraph, all terms shall have the meaning given them in subparagraph (27)(b) of this rule, the Tennessee Hazardous Waste Management Act and subparagraph (2)(a) of Rule 0400-12-01-.01.

(c) Standards: Pumps in light liquid service [40 CFR 261.1052]

1.
  - (i) Each pump in light liquid service shall be monitored monthly to detect leaks by the methods specified in part (n)2 of this paragraph, except as provided in parts 4, 5 and 6 of this subparagraph.
  - (ii) Each pump in light liquid service shall be checked by visual inspection each calendar week for indications of liquids dripping from the pump seal.
2.
  - (i) If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
  - (ii) If there are indications of liquids dripping from the pump seal, a leak is detected.
3.
  - (i) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in subparagraph (j) of this paragraph.
  - (ii) A first attempt at repair (e.g., tightening the packing gland) shall be made no later than 5 calendar days after each leak is detected.
4. Each pump equipped with a dual mechanical seal system that includes a barrier fluid system is exempt from the requirements of part 1 of this subparagraph, provided the following requirements are met:
  - (i) Each dual mechanical seal system must be:
    - (I) Operated with the barrier fluid at a pressure that is at all times greater than the pump stuffing box pressure;
    - (II) Equipped with a barrier fluid degassing reservoir that is connected by a closed-vent system to a control device that complies with the requirements of subparagraph (k) of this paragraph; or
    - (III) Equipped with a system that purges the barrier fluid into a hazardous

secondary material stream with no detectable emissions to the atmosphere.

- (ii) The barrier fluid system must not be a hazardous secondary material with organic concentrations 10 percent or greater by weight.
- (iii) Each barrier fluid system must be equipped with a sensor that will detect failure of the seal system, the barrier fluid system, or both.
- (iv) Each pump must be checked by visual inspection, each calendar week, for indications of liquids dripping from the pump seals.
- (v)
  - (I) Each sensor as described in subpart (iii) of this part must be checked daily or be equipped with an audible alarm that must be checked monthly to ensure that it is functioning properly.
  - (II) The remanufacturer or other person that stores or treats the hazardous secondary material must determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both.
- (vi)
  - (I) If there are indications of liquids dripping from the pump seal or the sensor indicates failure of the seal system, the barrier fluid system, or both based on the criterion determined in item (v)(II) of this part, a leak is detected.
  - (II) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in subparagraph (j) of this paragraph.
  - (III) A first attempt at repair (e.g., relapping the seal) shall be made no later than 5 calendar days after each leak is detected.

5. Any pump that is designated, as described in subpart (o)7(ii) of this paragraph, for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of parts 1, 3 and 4 of this subparagraph if the pump meets the following requirements:

- (i) Must have no externally actuated shaft penetrating the pump housing.
- (ii) Must operate with no detectable emissions as indicated by an instrument reading of less than 500 ppm above background as measured by the methods specified in part (n)3 of this paragraph.
- (iii) Must be tested for compliance with subpart (ii) of this part initially upon designation, annually, and at other times as requested by the Commissioner.

6. If any pump is equipped with a closed-vent system capable of capturing and transporting any leakage from the seal or seals to a control device that complies with the requirements of subparagraph (k) of this paragraph, it is exempt from the requirements of parts 1 through 5 of this subparagraph.

(d) Standards: Compressors [40 CFR 261.1053]

- 1. Each compressor shall be equipped with a seal system that includes a barrier fluid system and that prevents leakage of total organic emissions to the atmosphere, except as provided in parts 8 and 9 of this subparagraph.
- 2. Each compressor seal system as required in part 1 of this subparagraph shall be:



- (i) Operated with the barrier fluid at a pressure that is at all times greater than the compressor stuffing box pressure;
  - (ii) Equipped with a barrier fluid system that is connected by a closed-vent system to a control device that complies with the requirements of subparagraph (k) of this paragraph; or
  - (iii) Equipped with a system that purges the barrier fluid into a hazardous secondary material stream with no detectable emissions to atmosphere.
3. The barrier fluid must not be a hazardous secondary material with organic concentrations 10 percent or greater by weight.
  4. Each barrier fluid system as described in parts 1 through 3 of this subparagraph shall be equipped with a sensor that will detect failure of the seal system, barrier fluid system, or both.
  5.
    - (i) Each sensor as required in part 4 of this subparagraph shall be checked daily or shall be equipped with an audible alarm that must be checked monthly to ensure that it is functioning properly unless the compressor is located within the boundary of an unmanned plant site, in which case the sensor must be checked daily.
    - (ii) The remanufacturer or other person that stores or treats the hazardous secondary material shall determine, based on design considerations and operating experience, a criterion that indicates failure of the seal system, the barrier fluid system, or both.
  6. If the sensor indicates failure of the seal system, the barrier fluid system, or both based on the criterion determined under subpart 5(ii) of this subparagraph, a leak is detected.
  7.
    - (i) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in subparagraph (j) of this paragraph.
    - (ii) A first attempt at repair (e.g., tightening the packing gland) shall be made no later than 5 calendar days after each leak is detected.
  8. A compressor is exempt from the requirements of parts 1 and 2 of this subparagraph if it is equipped with a closed-vent system capable of capturing and transporting any leakage from the seal to a control device that complies with the requirements of subparagraph (k) of this paragraph, except as provided in part 9 of this subparagraph.
  9. Any compressor that is designated, as described in subpart (o)7(ii) of this paragraph, for no detectable emissions as indicated by an instrument reading of less than 500 ppm above background is exempt from the requirements of parts 1 through 8 of this subparagraph if the compressor:
    - (i) Is determined to be operating with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified part (n)3 of this paragraph.
    - (ii) Is tested for compliance with subpart (i) of this part initially upon designation, annually, and at other times as requested by the Commissioner.
- (e) Standards: Pressure relief devices in gas/vapor service [40 CFR 261.1054]
1. Except during pressure releases, each pressure relief device in gas/vapor service shall be operated with no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified in part (n)3 of

this paragraph.

2. (i) After each pressure release, the pressure relief device shall be returned to a condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as soon as practicable, but no later than 5 calendar days after each pressure release, except as provided in subparagraph (j) of this paragraph.
- (ii) No later than 5 calendar days after the pressure release, the pressure relief device shall be monitored to confirm the condition of no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, as measured by the method specified in part (n)3 of this paragraph.
3. Any pressure relief device that is equipped with a closed-vent system capable of capturing and transporting leakage from the pressure relief device to a control device as described in subparagraph (k) of this paragraph is exempt from the requirements of parts 1 and 2 of this subparagraph.

(f) Standards: Sampling connection systems [40 CFR 261.1055]

1. Each sampling connection system shall be equipped with a closed-purge, closed-loop, or closed-vent system. This system shall collect the sample purge for return to the process or for routing to the appropriate treatment system. Gases displaced during filling of the sample container are not required to be collected or captured.
2. Each closed-purge, closed-loop, or closed-vent system as required in part 1 of this subparagraph shall meet one of the following requirements:
  - (i) Return the purged process fluid directly to the process line;
  - (ii) Collect and recycle the purged process fluid; or
  - (iii) Be designed and operated to capture and transport all the purged process fluid to a material management unit that complies with the applicable requirements of subparagraphs (29)(e) through (g) of this rule or a control device that complies with the requirements of subparagraph (k) of this paragraph.
3. In-situ sampling systems and sampling systems without purges are exempt from the requirements of parts 1 and 2 of this subparagraph.

(g) Standards: Open-ended valves or lines [40 CFR 261.1056]

1. (i) Each open-ended valve or line shall be equipped with a cap, blind flange, plug, or a second valve.
- (ii) The cap, blind flange, plug, or second valve shall seal the open end at all times except during operations requiring hazardous secondary material stream flow through the open-ended valve or line.
2. Each open-ended valve or line equipped with a second valve shall be operated in a manner such that the valve on the hazardous secondary material stream end is closed before the second valve is closed.
3. When a double block and bleed system is being used, the bleed valve or line may remain open during operations that require venting the line between the block valves but shall comply with part 1 of this subparagraph at all other times.

(h) Standards: Valves in gas/vapor service or in light liquid service [40 CFR 261.1057]

1. Each valve in gas/vapor or light liquid service shall be monitored monthly to detect leaks

by the methods specified in part (n)2 of this paragraph and shall comply with parts 2 through 5 of this subparagraph, except as provided in parts 6, 7 and 8 of this subparagraph and subparagraphs (l) and (m) of this paragraph.

2. If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
3.
  - (i) Any valve for which a leak is not detected for two successive months may be monitored the first month of every succeeding quarter, beginning with the next quarter, until a leak is detected.
  - (ii) If a leak is detected, the valve shall be monitored monthly until a leak is not detected for two successive months,
4.
  - (i) When a leak is detected, it shall be repaired as soon as practicable, but no later than 15 calendar days after the leak is detected, except as provided in subparagraph (j) of this paragraph.
  - (ii) A first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
5. First attempts at repair include, but are not limited to, the following best practices where practicable:
  - (i) Tightening of bonnet bolts.
  - (ii) Replacement of bonnet bolts.
  - (iii) Tightening of packing gland nuts.
  - (iv) Injection of lubricant into lubricated packing.
6. Any valve that is designated, as described in subpart (o)7(ii) of this paragraph, for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, is exempt from the requirements of part 1 of this subparagraph if the valve:
  - (i) Has no external actuating mechanism in contact with the hazardous secondary material stream.
  - (ii) Is operated with emissions less than 500 ppm above background as determined by the method specified in part (n)3 of this paragraph.
  - (iii) Is tested for compliance with subpart 6(ii) of this subparagraph initially upon designation, annually, and at other times as requested by the Commissioner.
7. Any valve that is designated, as described in subpart (o)8(i) of this paragraph, as an unsafe-to-monitor valve is exempt from the requirements of part 1 of this subparagraph if:
  - (i) The remanufacturer or other person that stores or treats the hazardous secondary material determines that the valve is unsafe to monitor because monitoring personnel would be exposed to an immediate danger as a consequence of complying with part 1 of this subparagraph.
  - (ii) The remanufacturer or other person that stores or treats the hazardous secondary material adheres to a written plan that requires monitoring of the valve as frequently as practicable during safe-to-monitor times.
8. Any valve that is designated, as described in subpart (o)8(ii) of this paragraph, as a difficult-to-monitor valve is exempt from the requirements of part 1 of this subparagraph if:
  - (i) The remanufacturer or other person that stores or treats the hazardous

secondary material determines that the valve cannot be monitored without elevating the monitoring personnel more than 2 meters above a support surface.

- (ii) The hazardous secondary material management unit within which the valve is located was in operation before January 13, 2015.
  - (iii) The owner or operator of the valve follows a written plan that requires monitoring of the valve at least once per calendar year.
- (i) Standards: Pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service, and flanges and other connectors [40 CFR 261.1058]
- 1. Pumps and valves in heavy liquid service, pressure relief devices in light liquid or heavy liquid service, and flanges and other connectors shall be monitored within 5 days by the method specified in part (n)2 of this paragraph if evidence of a potential leak is found by visual, audible, olfactory, or any other detection method.
  - 2. If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
  - 3. (i) When a leak is detected, it shall be repaired as soon as practicable, but not later than 15 calendar days after it is detected, except as provided in subparagraph (j) of this paragraph.  
(ii) The first attempt at repair shall be made no later than 5 calendar days after each leak is detected.
  - 4. First attempts at repair include, but are not limited to, the best practices described under part (h)5 of this paragraph.
  - 5. Any connector that is inaccessible or is ceramic or ceramic-lined (e.g., porcelain, glass, or glass-lined) is exempt from the monitoring requirements of part 1 of this subparagraph and from the recordkeeping requirements of subparagraph (o) of this paragraph.
- (j) Standards: Delay of repair [40 CFR 261.1059]
- 1. Delay of repair of equipment for which leaks have been detected will be allowed if the repair is technically infeasible without a hazardous secondary material management unit shutdown. In such a case, repair of this equipment shall occur before the end of the next hazardous secondary material management unit shutdown.
  - 2. Delay of repair of equipment for which leaks have been detected will be allowed for equipment that is isolated from the hazardous secondary material management unit and that does not continue to contain or contact hazardous secondary material with organic concentrations at least 10 percent by weight.
  - 3. Delay of repair for valves will be allowed if:
    - (i) The remanufacturer or other person that stores or treats the hazardous secondary material determines that emissions of purged material resulting from immediate repair are greater than the emissions likely to result from delay of repair.
    - (ii) When repair procedures are effected, the purged material is collected and destroyed or recovered in a control device complying with subparagraph (k) of this paragraph.
  - 4. Delay of repair for pumps will be allowed if:
    - (i) Repair requires the use of a dual mechanical seal system that includes a barrier fluid system.

- (ii) Repair is completed as soon as practicable, but not later than 6 months after the leak was detected.
- 5. Delay of repair beyond a hazardous secondary material management unit shutdown will be allowed for a valve if valve assembly replacement is necessary during the hazardous secondary material management unit shutdown, valve assembly supplies have been depleted, and valve assembly supplies had been sufficiently stocked before the supplies were depleted. Delay of repair beyond the next hazardous secondary material management unit shutdown will not be allowed unless the next hazardous secondary material management unit shutdown occurs sooner than 6 months after the first hazardous secondary material management unit shutdown.
- (k) Standards: Closed-vent systems and control devices [40 CFR 261.1060]
  - 1. The remanufacturer or other person that stores or treats the hazardous secondary material in a hazardous secondary material management units using closed-vent systems and control devices subject to this paragraph shall comply with the provisions of subparagraph (27)(d) of this rule.
  - 2.
    - (i) The remanufacturer or other person that stores or treats the hazardous secondary material at an existing facility who cannot install a closed-vent system and control device to comply with the provisions of this paragraph on the effective date that the facility becomes subject to the provisions of this paragraph must prepare an implementation schedule that includes dates by which the closed-vent system and control device will be installed and in operation. The controls must be installed as soon as possible, but the implementation schedule may allow up to 30 months after the effective date that the facility becomes subject to this paragraph for installation and startup.
    - (ii) Any unit that begins operation after July 13, 2015 and is subject to the provisions of this paragraph when operation begins, must comply with the rules immediately (i.e., must have control devices installed and operating on startup of the affected unit); the 30-month implementation schedule does not apply.
    - (iii) The remanufacturer or other person that stores or treats the hazardous secondary material at any facility in existence on the effective date of a statutory or regulatory amendment that renders the facility subject to this paragraph shall comply with all requirements of this paragraph as soon as practicable but no later than 30 months after the amendment's effective date. When control equipment required by this paragraph cannot be installed and begin operation by the effective date of the amendment, the facility owner or operator shall prepare an implementation schedule that includes the following information: Specific calendar dates for award of contracts or issuance of purchase orders for the control equipment, initiation of on-site installation of the control equipment, completion of the control equipment installation, and performance of any testing to demonstrate that the installed equipment meets the applicable standards of this paragraph. The remanufacturer or other person that stores or treats the hazardous secondary material shall keep a copy of the implementation schedule at the facility.
    - (iv) Remanufacturers or other persons that store or treat the hazardous secondary materials at facilities and units already subject to federal law, due to an action other than those described in subpart 2(ii) of this subparagraph must comply with all applicable requirements immediately (i.e., must have control devices installed and operating on the date the facility or unit becomes subject to this subpart; the 30-month implementation schedule does not apply).
- (l) Alternative standards for valves in gas/vapor service or in light liquid service: percentage of valves allowed to leak [40 CFR 261.1061]

1. A remanufacturer or other person that stores or treats the hazardous secondary material subject to the requirements of subparagraph (h) of this paragraph may elect to have all valves within a hazardous secondary material management unit comply with an alternative standard that allows no greater than 2 percent of the valves to leak.
  2. The following requirements shall be met if a remanufacturer or other person that stores or treats the hazardous secondary material decides to comply with the alternative standard of allowing 2 percent of valves to leak:
    - (i) A performance test as specified in part 3 of this subparagraph shall be conducted initially upon designation, annually, and at other times requested by the Commissioner.
    - (ii) If a valve leak is detected, it shall be repaired in accordance with parts (h)4 and 5 of this paragraph.
  3. Performance tests shall be conducted in the following manner:
    - (i) All valves subject to the requirements in subparagraph (h) of this paragraph within the hazardous secondary material management unit shall be monitored within 1 week by the methods specified in part (n)2 of this paragraph.
    - (ii) If an instrument reading of 10,000 ppm or greater is measured, a leak is detected.
    - (iii) The leak percentage shall be determined by dividing the number of valves subject to the requirements in subparagraph (h) of this paragraph for which leaks are detected by the total number of valves subject to the requirements in subparagraph (h) of this paragraph within the hazardous secondary material management unit.
- (m) Alternative standards for valves in gas/vapor service or in light liquid service: skip period leak detection and repair [40 CFR 261.1062]
1. A remanufacturer or other person that stores or treats the hazardous secondary material subject to the requirements of subparagraph (h) of this paragraph may elect for all valves within a hazardous secondary material management unit to comply with one of the alternative work practices specified in subparts 2(ii) and (iii) of this subparagraph.
  2.
    - (i) A remanufacturer or other person that stores or treats the hazardous secondary material shall comply with the requirements for valves, as described in subparagraph (h) of this paragraph, except as described in subparts (ii) and (iii) of this part.
    - (ii) After two consecutive quarterly leak detection periods with the percentage of valves leaking equal to or less than 2 percent, a remanufacturer or other person that stores or treats the hazardous secondary material may begin to skip one of the quarterly leak detection periods (i.e., monitor for leaks once every 6 months) for the valves subject to the requirements in subparagraph (h) of this paragraph.
    - (iii) After 5 consecutive quarterly leak detection periods with the percentage of valves leaking equal to or less than 2 percent, a remanufacturer or other person that stores or treats the hazardous secondary material may begin to skip 3 of the quarterly leak detection periods (i.e., monitor for leaks once every year) for the valves subject to the requirements in subparagraph (h) of this paragraph.
    - (iv) If the percentage of valves leaking is greater than 2 percent, the remanufacturer or other person that stores or treats the hazardous secondary material shall monitor monthly in compliance with the requirements in subparagraph (h) of this

paragraph, but may again elect to use this subparagraph after meeting the requirements of subpart (h)3(i) of this paragraph.

- (n) Test methods and procedures [40 CFR 261.1063]
1. Each remanufacturer or other person that stores or treats the hazardous secondary material subject to the provisions of this paragraph shall comply with the test methods and procedures requirements provided in this subparagraph.
  2. Leak detection monitoring, as required in subparagraph (c) through (m) of this paragraph, shall comply with the following requirements:
    - (i) Monitoring shall comply with Reference Method 21 in 40 CFR part 60.
    - (ii) The detection instrument shall meet the performance criteria of Reference Method 21.
    - (iii) The instrument shall be calibrated before use on each day of its use by the procedures specified in Reference Method 21.
    - (iv) Calibration gases shall be:
      - (I) Zero air (less than 10 ppm of hydrocarbon in air).
      - (II) A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppm methane or n-hexane.
    - (v) The instrument probe shall be traversed around all potential leak interfaces as close to the interface as possible as described in Reference Method 21.
  3. When equipment is tested for compliance with no detectable emissions, as required in (c)5, part (d)9, subparagraph (e) and part (h)6 of this paragraph, the test shall comply with the following requirements:
    - (i) The requirements of subparts 2(i) through (iv) of this subparagraph shall apply.
    - (ii) The background level shall be determined as set forth in Reference Method 21.
    - (iii) The instrument probe shall be traversed around all potential leak interfaces as close to the interface as possible as described in Reference Method 21.
    - (iv) The arithmetic difference between the maximum concentration indicated by the instrument and the background level is compared with 500 ppm for determining compliance.
  4. A remanufacturer or other person that stores or treats the hazardous secondary material must determine, for each piece of equipment, whether the equipment contains or contacts a hazardous secondary material with organic concentration that equals or exceeds 10 percent by weight using the following:
    - (i) Methods described in ASTM Methods D 2267-88, E 169-87, E 168-88, E 260-85 (incorporated by reference under subparagraph (2)(b) of Rule 0400-12-01-.01);
    - (ii) Method 9060A (incorporated by reference under subparagraph (2)(b) of Rule 0400-12-01-.01) of "Test Methods for Evaluating Solid Waste," EPA Publication SW-846, for computing total organic concentration of the sample, or analyzed for its individual organic constituents; or
    - (iii) Application of the knowledge of the nature of the hazardous secondary material stream or the process by which it was produced. Documentation of a material

determination by knowledge is required. Examples of documentation that shall be used to support a determination under this provision include production process information documenting that no organic compounds are used, information that the material is generated by a process that is identical to a process at the same or another facility that has previously been demonstrated by direct measurement to have a total organic content less than 10 percent, or prior speciation analysis results on the same material stream where it can also be documented that no process changes have occurred since that analysis that could affect the material total organic concentration.

5. If a remanufacturer or other person that stores or treats the hazardous secondary material determines that a piece of equipment contains or contacts a hazardous secondary material with organic concentrations at least 10 percent by weight, the determination can be revised only after following the procedures in subparts 4(i) or (ii) of this subparagraph.
  6. When a remanufacturer or other person that stores or treats the hazardous secondary material and the Commissioner do not agree on whether a piece of equipment contains or contacts a hazardous secondary material with organic concentrations at least 10 percent by weight, the procedures in subparts 4(i) or (ii) of this subparagraph can be used to resolve the dispute.
  7. Samples used in determining the percent organic content shall be representative of the highest total organic content hazardous secondary material that is expected to be contained in or contact the equipment.
  8. To determine if pumps or valves are in light liquid service, the vapor pressures of constituents may be obtained from standard reference texts or may be determined by ASTM D-2879-86 (incorporated by reference under subparagraph (2)(b) of Rule 0400-12-01-.01).
  9. Performance tests to determine if a control device achieves 95 weight percent organic emission reduction shall comply with the procedures of subparts (27)(e)3(i) through (iv) of this rule.
- (o) Recordkeeping requirements [40 CFR 261.1064]
1.
    - (i) Each remanufacturer or other person that stores or treats the hazardous secondary material subject to the provisions of this paragraph shall comply with the recordkeeping requirements of this subparagraph.
    - (ii) A remanufacturer or other person that stores or treats the hazardous secondary material in more than one hazardous secondary material management unit subject to the provisions of this subpart may comply with the recordkeeping requirements for these hazardous secondary material management units in one recordkeeping system if the system identifies each record by each hazardous secondary material management unit.
  2. Remanufacturers and other persons that store or treat the hazardous secondary material must record and keep the following information at the facility:
    - (i) For each piece of equipment to which this paragraph applies:
      - (I) Equipment identification number and hazardous secondary material management unit identification.
      - (II) Approximate locations within the facility (e.g., identify the hazardous secondary material management unit on a facility plot plan).
      - (III) Type of equipment (e.g., a pump or pipeline valve).



- (IV) Percent-by-weight total organics in the hazardous secondary material stream at the equipment.
  - (V) Hazardous secondary material state at the equipment (e.g., gas/vapor or liquid).
  - (VI) Method of compliance with the standard (e.g., “monthly leak detection and repair” or “equipped with dual mechanical seals”).
- (ii) For facilities that comply with the provisions of subpart (27)(d)1(ii) of this rule, an implementation schedule as specified in subpart (27)(d)1(ii) of this rule.
  - (iii) Where a remanufacturer or other person that stores or treats the hazardous secondary material chooses to use test data to demonstrate the organic removal efficiency or total organic compound concentration achieved by the control device, a performance test plan as specified in subpart (27)(f)2(iii) of this rule.
  - (iv) Documentation of compliance with subparagraph (k) of this paragraph, including the detailed design documentation or performance test results specified in subpart (27)(f)2(iv) of this rule.
3. When each leak is detected as specified in subparagraphs (c), (d), (h) and (i) of this paragraph, the following requirements apply:
- (i) A weatherproof and readily visible identification, marked with the equipment identification number, the date evidence of a potential leak was found in accordance with part (i)1 of this paragraph, and the date the leak was detected, shall be attached to the leaking equipment.
  - (ii) The identification on equipment, except on a valve, may be removed after it has been repaired.
  - (iii) The identification on a valve may be removed after it has been monitored for 2 successive months as specified in part (h)3 of this paragraph and no leak has been detected during those two months.
4. When each leak is detected as specified in subparagraphs (c), (d), (h) and (i) of this paragraph, the following information shall be recorded in an inspection log and shall be kept at the facility:
- (i) The instrument and operator identification numbers and the equipment identification number.
  - (ii) The date evidence of a potential leak was found in accordance with part (i)1 of this paragraph.
  - (iii) The date the leak was detected and the dates of each attempt to repair the leak.
  - (iv) Repair methods applied in each attempt to repair the leak.
  - (v) “Above 10,000” if the maximum instrument reading measured by the methods specified in part (n)2 of this paragraph after each repair attempt is equal to or greater than 10,000 ppm.
  - (vi) “Repair delayed” and the reason for the delay if a leak is not repaired within 15 calendar days after discovery of the leak.
  - (vii) Documentation supporting the delay of repair of a valve in compliance with part (j)3 of this paragraph.

- (viii) The signature of the remanufacturer or other person that stores or treats the hazardous secondary material (or designate) whose decision it was that repair could not be effected without a hazardous secondary material management unit shutdown.
  - (ix) The expected date of successful repair of the leak if a leak is not repaired within 15 calendar days.
  - (x) The date of successful repair of the leak.
5. Design documentation and monitoring, operating, and inspection information for each closed-vent system and control device required to comply with the provisions of subparagraph (k) of this paragraph shall be recorded and kept up-to-date at the facility as specified in part (27)(f)3 of this rule. Design documentation is specified in subparts (27)(f)3(i) and (ii) of this rule and monitoring, operating, and inspection information in subparts (27)(f)3(iii) through (viii) of this rule.
  6. For a control device other than a thermal vapor incinerator, catalytic vapor incinerator, flare, boiler, process heater, condenser, or carbon adsorption system, the Commissioner will specify the appropriate recordkeeping requirements.
  7. The following information pertaining to all equipment subject to the requirements in subparagraphs (c) through (k) of this paragraph shall be recorded in a log that is kept at the facility:
    - (i) A list of identification numbers for equipment (except welded fittings) subject to the requirements of this paragraph.
    - (ii)
      - (I) A list of identification numbers for equipment that the remanufacturer or other person that stores or treats the hazardous secondary material elects to designate for no detectable emissions, as indicated by an instrument reading of less than 500 ppm above background, under the provisions of parts (c)5, (d)9 and (h)6 of this paragraph.
      - (II) The designation of this equipment as subject to the requirements of parts (c)5, (d)9 and (h)6 of this paragraph shall be signed by the remanufacturer or other person that stores or treats the hazardous secondary material.
    - (iii) A list of equipment identification numbers for pressure relief devices required to comply with part (e)1 of this paragraph.
    - (iv)
      - (I) The dates of each compliance test required in part (c)5, part (d)9, subparagraph (e) and part (h)6 of this paragraph.
      - (II) The background level measured during each compliance test.
      - (III) The maximum instrument reading measured at the equipment during each compliance test.
    - (v) A list of identification numbers for equipment in vacuum service.
    - (vi) Identification, either by list or location (area or group) of equipment that contains or contacts hazardous secondary material with an organic concentration of at least 10 percent by weight for less than 300 hours per calendar year.
  8. The following information pertaining to all valves subject to the requirements of parts (h)7 and 8 of this paragraph shall be recorded in a log that is kept at the facility:

- (i) A list of identification numbers for valves that are designated as unsafe to monitor, an explanation for each valve stating why the valve is unsafe to monitor, and the plan for monitoring each valve.
  - (ii) A list of identification numbers for valves that are designated as difficult to monitor, an explanation for each valve stating why the valve is difficult to monitor, and the planned schedule for monitoring each valve.
- 9. The following information shall be recorded in a log that is kept at the facility for valves complying with subparagraph (m) of this paragraph:
  - (i) A schedule of monitoring.
  - (ii) The percent of valves found leaking during each monitoring period.
- 10. The following information shall be recorded in a log that is kept at in the facility:
  - (i) Criteria required in item (c)4(v)(II) and subpart (d)5(ii) of this paragraph and an explanation of the design criteria.
  - (ii) Any changes to these criteria and the reasons for the changes.
- 11. The following information shall be recorded in a log that is kept at the facility for use in determining exemptions as provided in the applicability subparagraph of this paragraph and other specific paragraphs:
  - (i) An analysis determining the design capacity of the hazardous secondary material management unit.
  - (ii) A statement listing the hazardous secondary material influent to and effluent from each hazardous secondary material management unit subject to the requirements in subparagraphs (c) through (k) of this paragraph and an analysis determining whether these hazardous secondary materials are heavy liquids.
  - (iii) An up-to-date analysis and the supporting information and data used to determine whether or not equipment is subject to the requirements in subparagraphs (c) through (k) of this paragraph. The record shall include supporting documentation as required by subpart (n)4(iii) of this paragraph when application of the knowledge of the nature of the hazardous secondary material stream or the process by which it was produced is used. If the remanufacturer or other person that stores or treats the hazardous secondary material takes any action (e.g., changing the process that produced the material) that could result in an increase in the total organic content of the material contained in or contacted by equipment determined not to be subject to the requirements in subparagraphs (c) through (k) of this paragraph, then a new determination is required.
- 12. Records of the equipment leak information required by part 4 of this subparagraph and the operating information required by part 5 of this subparagraph need be kept only three years.
- 13. The remanufacturer or other person that stores or treats the hazardous secondary material at a facility with equipment that is subject to this paragraph and to regulations at 40 CFR part 60, part 61, or part 63 may elect to determine compliance with this paragraph either by documentation pursuant to this paragraph, or by documentation of compliance with the regulations at 40 CFR part 60, part 61, or part 63 pursuant to the relevant provisions of the regulations at 40 part 60, part 61, or part 63. The documentation of compliance under regulations at 40 CFR part 60, part 61, or part 63 shall be kept with or made readily available at the facility.

(p) through (dd) Reserved [40 CFR 261.1065-261.1079]

(29) Air Emission Standards for Tanks and Containers [40 CFR 261 -- Subpart CC]

(a) Applicability [40 CFR 261.1080]

1. This paragraph applies to tanks and containers that contain hazardous secondary materials excluded under the remanufacturing exclusion at subpart (1)(d)1(xxvii) of this rule, unless the tanks and containers are equipped with and operating air emission controls in accordance with the requirements of an applicable Clean Air Act regulations codified under 40 CFR part 60, part 61, or part 63.
2. Reserved

(b) Definitions [40 CFR 261.1081]

As used in this subpart, all terms not defined herein shall have the meaning given to them in the Act and Rules 0400-12-01-.01 through 0400-12-01-.06 and 0400-12-01-.09.

“Average volatile organic concentration” or “average VO concentration” means the mass-weighted average volatile organic concentration of a hazardous secondary material as determined in accordance with the requirements of subparagraph (e) of this paragraph.

“Closure device” means a cap, hatch, lid, plug, seal, valve, or other type of fitting that blocks an opening in a cover such that when the device is secured in the closed position it prevents or reduces air pollutant emissions to the atmosphere. Closure devices include devices that are detachable from the cover (e.g., a sampling port cap), manually operated (e.g., a hinged access lid or hatch), or automatically operated (e.g., a spring-loaded pressure relief valve).

“Continuous seal” means a seal that forms a continuous closure that completely covers the space between the edge of the floating roof and the wall of a tank. A continuous seal may be a vapor-mounted seal, liquid-mounted seal, or metallic shoe seal. A continuous seal may be constructed of fastened segments so as to form a continuous seal.

“Cover” means a device that provides a continuous barrier over the hazardous secondary material managed in a unit to prevent or reduce air pollutant emissions to the atmosphere. A cover may have openings (such as access hatches, sampling ports, gauge wells) that are necessary for operation, inspection, maintenance, and repair of the unit on which the cover is used. A cover may be a separate piece of equipment which can be detached and removed from the unit or a cover may be formed by structural features permanently integrated into the design of the unit.

“Empty hazardous secondary material container” means:

1. A container from which all hazardous secondary materials have been removed that can be removed using the practices commonly employed to remove materials from that type of container, e.g., pouring, pumping, and aspirating, and no more than 2.5 centimeters (one inch) of residue remain on the bottom of the container or inner liner;
2. A container that is less than or equal to 119 gallons in size and no more than 3 percent by weight of the total capacity of the container remains in the container or inner liner; or
3. A container that is greater than 119 gallons in size and no more than 0.3 percent by weight of the total capacity of the container remains in the container or inner liner.

“Enclosure” means a structure that surrounds a tank or container, captures organic vapors emitted from the tank or container, and vents the captured vapors through a closed-vent system to a control device.

“External floating roof” means a pontoon-type or double-deck type cover that rests on the surface of the material managed in a tank with no fixed roof.

“Fixed roof” means a cover that is mounted on a unit in a stationary position and does not move with fluctuations in the level of the material managed in the unit.

“Floating membrane cover” means a cover consisting of a synthetic flexible membrane material that rests upon and is supported by the hazardous secondary material being managed in a surface impoundment.

“Floating roof” means a cover consisting of a double deck, pontoon single deck, or internal floating cover which rests upon and is supported by the material being contained, and is equipped with a continuous seal.

“Hard-piping” means pipe or tubing that is manufactured and properly installed in accordance with relevant standards and good engineering practices.

“In light material service” means the container is used to manage a material for which both of the following conditions apply: The vapor pressure of one or more of the organic constituents in the material is greater than 0.3 kilopascals (kPa) at 20 °C; and the total concentration of the pure organic constituents having a vapor pressure greater than 0.3 kPa at 20 °C is equal to or greater than 20 percent by weight.

“Internal floating roof” means a cover that rests or floats on the material surface (but not necessarily in complete contact with it) inside a tank that has a fixed roof.

“Liquid-mounted seal” means a foam or liquid-filled primary seal mounted in contact with the hazardous secondary material between the tank wall and the floating roof continuously around the circumference of the tank.

“Malfunction” means any sudden, infrequent, and not reasonably preventable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner. Failures that are caused in part by poor maintenance or careless operation are not malfunctions.

“Material determination” means performing all applicable procedures in accordance with the requirements of subparagraph (e) of this paragraph to determine whether a hazardous secondary material meets standards specified in this paragraph. Examples of a material determination include performing the procedures in accordance with the requirements of subparagraph (e) of this paragraph to determine the average VO concentration of a hazardous secondary material at the point of material origination; the average VO concentration of a hazardous secondary material at the point of material treatment and comparing the results to the exit concentration limit specified for the process used to treat the hazardous secondary material; the organic reduction efficiency and the organic biodegradation efficiency for a biological process used to treat a hazardous secondary material and comparing the results to the applicable standards; or the maximum volatile organic vapor pressure for a hazardous secondary material in a tank and comparing the results to the applicable standards.

“Maximum organic vapor pressure” means the sum of the individual organic constituent partial pressures exerted by the material contained in a tank, at the maximum vapor pressure-causing conditions (i.e., temperature, agitation, pH effects of combining materials, etc.) reasonably expected to occur in the tank. For the purpose of this paragraph, maximum organic vapor pressure is determined using the procedures specified in part (e)3 of this paragraph.

“Metallic shoe seal” means a continuous seal that is constructed of metal sheets which are held vertically against the wall of the tank by springs, weighted levers, or other mechanisms and is connected to the floating roof by braces or other means. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.

“No detectable organic emissions” means no escape of organics to the atmosphere as determined using the procedure specified in part (e)4 of this paragraph.

“Point of material origination” means as follows:

1. When the remanufacturer or other person that stores or treats the hazardous secondary material is the generator of the hazardous secondary material, the point of material origination means the point where a material produced by a system, process, or material management unit is determined to be a hazardous secondary material excluded under subpart (1)(d)1(xxvii) of this rule.

(Note: This term is being used in a manner similar to the use of the term “point of generation” in air standards established under authority of the Clean Air Act in 40 CFR parts 60, 61, and 63.)

2. When the remanufacturer or other person that stores or treats the hazardous secondary material is not the generator of the hazardous secondary material, point of material origination means the point where the remanufacturer or other person that stores or treats the hazardous secondary material accepts delivery or takes possession of the hazardous secondary material.

“Safety device” means a closure device such as a pressure relief valve, frangible disc, fusible plug, or any other type of device which functions exclusively to prevent physical damage or permanent deformation to a unit or its air emission control equipment by venting gases or vapors directly to the atmosphere during unsafe conditions resulting from an unplanned, accidental, or emergency event. For the purpose of this paragraph, a safety device is not used for routine venting of gases or vapors from the vapor headspace underneath a cover such as during filling of the unit or to adjust the pressure in this vapor headspace in response to normal daily diurnal ambient temperature fluctuations. A safety device is designed to remain in a closed position during normal operations and open only when the internal pressure, or another relevant parameter, exceeds the device threshold setting applicable to the air emission control equipment as determined by the remanufacturer or other person that stores or treats the hazardous secondary material based on manufacturer recommendations, applicable regulations, fire protection and prevention codes, standard engineering codes and practices, or other requirements for the safe handling of flammable, ignitable, explosive, reactive, or hazardous materials.

“Single-seal system” means a floating roof having one continuous seal. This seal may be vapor-mounted, liquid-mounted, or a metallic shoe seal.

“Vapor-mounted seal” means a continuous seal that is mounted such that there is a vapor space between the hazardous secondary material in the unit and the bottom of the seal.

“Volatile organic concentration” or “VO concentration” means the fraction by weight of the volatile organic compounds contained in a hazardous secondary material expressed in terms of parts per million (ppmw) as determined by direct measurement or by knowledge of the material in accordance with the requirements of subparagraph (e) of this paragraph. For the purpose of determining the VO concentration of a hazardous secondary material, organic compounds with a Henry's law constant value of at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in the liquid-phase (0.1 Y/X) (which can also be expressed as  $1.8 \times 10^{-6}$  atmospheres/gram-mole/m<sup>3</sup>) at 25°C must be included.

(c) Standards: General [40 CFR 261.1082]

1. This subparagraph applies to the management of hazardous secondary material in tanks and containers subject to this paragraph.
2. The remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from each hazardous secondary material management unit in accordance with standards specified in subparagraphs (e) through (h) of this paragraph, as applicable to the hazardous secondary material management unit, except as provided for in part 3 of this subparagraph.

3. A tank or container is exempt from standards specified in subparagraphs (e) through (h) of this paragraph, as applicable, provided that the hazardous secondary material management unit is a tank or container for which all hazardous secondary material entering the unit has an average VO concentration at the point of material origination of less than 500 parts per million by weight (ppmw). The average VO concentration shall be determined using the procedures specified in part (d)1 of this paragraph. The remanufacturer or other person that stores or treats the hazardous secondary material shall review and update, as necessary, this determination at least once every 12 months following the date of the initial determination for the hazardous secondary material streams entering the unit.

(d) Material determination procedures [40 CFR 261.1083]

1. Material determination procedure to determine average volatile organic (VO) concentration of a hazardous secondary material at the point of material origination
  - (i) Determining average VO concentration at the point of material origination. A remanufacturer or other person that stores or treats the hazardous secondary material shall determine the average VO concentration at the point of material origination for each hazardous secondary material placed in a hazardous secondary material management unit exempted under the provisions of part (c)3 of this paragraph from using air emission controls in accordance with standards specified in subparagraphs (e) through (h) of this paragraph, as applicable to the hazardous secondary material management unit.
    - (I) An initial determination of the average VO concentration of the material stream shall be made before the first time any portion of the material in the hazardous secondary material stream is placed in a hazardous secondary material management unit exempted under the provisions of part (c)3 of this paragraph from using air emission controls, and thereafter an initial determination of the average VO concentration of the material stream shall be made for each averaging period that a hazardous secondary material is managed in the unit; and
    - (II) Perform a new material determination whenever changes to the source generating the material stream are reasonably likely to cause the average VO concentration of the hazardous secondary material to increase to a level that is equal to or greater than the applicable VO concentration limits specified in subparagraph (c) of this paragraph.
  - (ii) Determination of average VO concentration using direct measurement or knowledge. For a material determination that is required by subpart (i) of this part, the average VO concentration of a hazardous secondary material at the point of material origination shall be determined using either direct measurement as specified in subpart (iii) of this part or by knowledge as specified in subpart (iv) of this part.
  - (iii) Direct measurement to determine average VO concentration of a hazardous secondary material at the point of material origination
    - (I) Identification. The remanufacturer or other person that stores or treats the hazardous secondary material shall identify and record in a log that is kept at the facility the point of material origination for the hazardous secondary material.
    - (II) Sampling. Samples of the hazardous secondary material stream shall be collected at the point of material origination in a manner such that volatilization of organics contained in the material and in the subsequent sample is minimized and an adequately representative sample is collected and maintained for analysis by the selected method.

- I. The averaging period to be used for determining the average VO concentration for the hazardous secondary material stream on a mass-weighted average basis shall be designated and recorded. The averaging period can represent any time interval that the remanufacturer or other person that stores or treats the hazardous secondary material determines is appropriate for the hazardous secondary material stream but shall not exceed 1 year.
  - II. A sufficient number of samples, but no less than 4 samples, shall be collected and analyzed for a hazardous secondary material determination. All of the samples for a given material determination shall be collected within a one-hour period. The average of the 4 or more sample results constitutes a material determination for the material stream. One or more material determinations may be required to represent the complete range of material compositions and quantities that occur during the entire averaging period due to normal variations in the operating conditions for the source or process generating the hazardous secondary material stream. Examples of such normal variations are seasonal variations in material quantity or fluctuations in ambient temperature.
  - III. All samples shall be collected and handled in accordance with written procedures prepared by the remanufacturer or other person that stores or treats the hazardous secondary material and documented in a site sampling plan. This plan shall describe the procedure by which representative samples of the hazardous secondary material stream are collected such that a minimum loss of organics occurs throughout the sample collection and handling process, and by which sample integrity is maintained. A copy of the written sampling plan shall be maintained at the facility. An example of acceptable sample collection and handling procedures for a total volatile organic constituent concentration may be found in Method 25D in 40 CFR part 60, appendix A.
  - IV. Sufficient information, as specified in the "site sampling plan" required under subitem III of this item, shall be prepared and recorded to document the material quantity represented by the samples and, as applicable, the operating conditions for the source or process generating the hazardous secondary material represented by the samples.
- (III) Analysis. Each collected sample shall be prepared and analyzed in accordance with Method 25D in 40 CFR part 60, appendix A for the total concentration of volatile organic constituents, or using one or more methods when the individual organic compound concentrations are identified and summed and the summed material concentration accounts for and reflects all organic compounds in the material with Henry's law constant values at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase (0.1 Y/X) [which can also be expressed as  $1.8 \times 10^{-6}$  atmospheres/gram-mole/m<sup>3</sup>] at 25°C. At the discretion of the remanufacturer or other person that stores or treats the hazardous secondary material, the test data obtained may be adjusted by any appropriate method to discount any contribution to the total volatile organic concentration that is a result of including a compound with a Henry's law constant value of less than 0.1 Y/X at 25°C. To adjust these data, the measured concentration of each individual chemical constituent contained in the material is multiplied by the appropriate constituent-



specific adjustment factor ( $f_{m25D}$ ). If the remanufacturer or other person that stores or treats the hazardous secondary material elects to adjust the test data, the adjustment must be made to all individual chemical constituents with a Henry's law constant value greater than or equal to 0.1 Y/X at 25 degrees Celsius contained in the material. Constituent-specific adjustment factors ( $f_{m25D}$ ) can be obtained by contacting the Waste and Chemical Processes Group, Office of Air Quality Planning and Standards, Research Triangle Park, NC 27711. Other test methods may be used if they meet the requirements in subitem I or II of this item and provided the requirement to reflect all organic compounds in the material with Henry's law constant values greater than or equal to 0.1 Y/X [which can also be expressed as  $1.8 \times 10^{-6}$  atmospheres/gram-mole/ $m^3$ ] at 25°C, is met.

- I. Any EPA standard method that has been validated in accordance with "Alternative Validation Procedure for EPA Waste and Wastewater Methods," 40 CFR part 63, appendix D.
- II. Any other analysis method that has been validated in accordance with the procedures specified in Section 5.1 or Section 5.3, and the corresponding calculations in Section 6.1 or Section 6.3, of Method 301 in 40 CFR part 63, appendix A. The data are acceptable if they meet the criteria specified in Section 6.1.5 or Section 6.3.3 of Method 301. If correction is required under section 6.3.3 of Method 301, the data are acceptable if the correction factor is within the range 0.7 to 1.30. Other sections of Method 301 are not required.

(IV) Calculations

- I. The average VO concentration (C) on a mass-weighted basis shall be calculated by using the results for all material determinations conducted in accordance with paragraphs items (II) and (III) of this subpart and the following equation:

$$\bar{C} = \frac{1}{Q_T} \times \sum_{i=1}^n (Q_i \times C_i)$$

Where:

- |           |   |  |
|-----------|---|--|
| $\bar{C}$ | = | Average VO concentration of the hazardous secondary material at the point of material origination on a mass-weighted basis, ppmw.      |
| i         | = | Individual waste determination "i" of the hazardous secondary material.  |
| n         | = | Total number of material determinations of the hazardous secondary material conducted for the averaging period (not to exceed 1 year). |
| $Q_i$     | = | Mass quantity of hazardous secondary material stream represented by $C_i$ , kg/hr.   |
| $Q_T$     | = | Total mass quantity of hazardous secondary material during the averaging period, kg/hr.  |
| $C_i$     | = | Measured VO concentration of material determination "i" as determined in accordance  |

with the requirements of item (III) of this subpart (i.e. the average of the four or more samples specified in subitem (II)II of this subpart), ppmw.

- II. For the purpose of determining  $C_i$ , for individual material samples analyzed in accordance with item III of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material shall account for VO concentrations determined to be below the limit of detection of the analytical method by using the following VO concentration:
  - A. If Method 25D in 40 CFR part 60, appendix A is used for the analysis, one-half the blank value determined in the method at section 4.4 of Method 25D in 40 CFR part 60, appendix A.
  - B. If any other analytical method is used, one-half the sum of the limits of detection established for each organic constituent in the material that has a Henry's law constant values at least 0.1 mole-fraction-in-the-gas-phase/mole-fraction-in-the-liquid-phase (0.1 Y/X) [which can also be expressed as  $1.8 \times 10^{-6}$  atmospheres/gram-mole/ $m^3$ ] at 25°C.
- (iv) Use of knowledge by the remanufacturer or other person that stores or treats the hazardous secondary material to determine average VO concentration of a hazardous secondary material at the point of material origination
  - (I) Documentation shall be prepared that presents the information used as the basis for the knowledge by the remanufacturer or other person that stores or treats the hazardous secondary material of the hazardous secondary material stream's average VO concentration. Examples of information that may be used as the basis for knowledge include: Material balances for the source or process generating the hazardous secondary material stream; constituent-specific chemical test data for the hazardous secondary material stream from previous testing that are still applicable to the current material stream; previous test data for other locations managing the same type of material stream; or other knowledge based on information included in shipping papers or material certification notices.
  - (II) If test data are used as the basis for knowledge, then the remanufacturer or other person that stores or treats the hazardous secondary material shall document the test method, sampling protocol, and the means by which sampling variability and analytical variability are accounted for in the determination of the average VO concentration. For example, a remanufacturer or other person that stores or treats the hazardous secondary material may use organic concentration test data for the hazardous secondary material stream that are validated in accordance with Method 301 in 40 CFR part 63, appendix A as the basis for knowledge of the material.
  - (III) A remanufacturer or other person that stores or treats the hazardous secondary material using chemical constituent-specific concentration test data as the basis for knowledge of the hazardous secondary material may adjust the test data to the corresponding average VO concentration value which would have been obtained had the material samples been analyzed using Method 25D in 40 CFR part 60, appendix A. To adjust these data, the measured concentration for each individual chemical constituent contained in the material is multiplied by the appropriate

constituent-specific adjustment factor ( $f_{m25D}$ ).

- (IV) In the event that the Commissioner and the remanufacturer or other person that stores or treats the hazardous secondary material disagree on a determination of the average VO concentration for a hazardous secondary material stream using knowledge, then the results from a determination of average VO concentration using direct measurement as specified in subpart (iii) of this part shall be used to establish compliance with the applicable requirements of this paragraph. The Commissioner may perform or request that the remanufacturer or other person that stores or treats the hazardous secondary material perform this determination using direct measurement. The remanufacturer or other person that stores or treats the hazardous secondary material may choose one or more appropriate methods to analyze each collected sample in accordance with the requirements of item (iii)(III) of this part.

2. Reserved

3. Procedure to determine the maximum organic vapor pressure of a hazardous secondary material in a tank

(i) A remanufacturer or other person that stores or treats the hazardous secondary material shall determine the maximum organic vapor pressure for each hazardous secondary material placed in a tank using Tank Level 1 controls in accordance with standards specified in part (e)3 of this paragraph.

(ii) A remanufacturer or other person that stores or treats the hazardous secondary material shall use either direct measurement as specified in subpart (iii) of this part or knowledge of the waste as specified by subpart (iv) of this part to determine the maximum organic vapor pressure which is representative of the hazardous secondary material composition stored or treated in the tank.

(iii) Direct measurement to determine the maximum organic vapor pressure of a hazardous secondary material.

(I) Sampling. A sufficient number of samples shall be collected to be representative of the hazardous secondary material contained in the tank. All samples shall be collected and handled in accordance with written procedures prepared by the remanufacturer or other person that stores or treats the hazardous secondary material and documented in a site sampling plan. This plan shall describe the procedure by which representative samples of the hazardous secondary material are collected such that a minimum loss of organics occurs throughout the sample collection and handling process and by which sample integrity is maintained. A copy of the written sampling plan shall be maintained at the facility. An example of acceptable sample collection and handling procedures may be found in Method 25D in 40 CFR part 60, appendix A.

(II) Analysis. Any appropriate one of the following methods may be used to analyze the samples and compute the maximum organic vapor pressure of the hazardous secondary material:

I. Method 25E in 40 CFR part 60 appendix A;

II. Methods described in American Petroleum Institute Publication 2517, Third Edition, February 1989, "Evaporative Loss from External Floating-Roof Tanks," (incorporated by reference--refer to subparagraph (2)(b) of Rule 0400-12-01-.01);

III. Methods obtained from standard reference texts;

- IV. ASTM Method 2879-92 (incorporated by reference--refer to subparagraph (2)(b) of Rule 0400-12-01-.01); and
  - V. Any other method approved by the Commissioner.
- (iv) Use of knowledge to determine the maximum organic vapor pressure of the hazardous secondary material. Documentation shall be prepared and recorded that presents the information used as the basis for the knowledge by the remanufacturer or other person that stores or treats the hazardous secondary material that the maximum organic vapor pressure of the hazardous secondary material is less than the maximum vapor pressure limit listed in item (e)2(i)(I) of this paragraph for the applicable tank design capacity category. An example of information that may be used is documentation that the hazardous secondary material is generated by a process for which at other locations it previously has been determined by direct measurement that the hazardous secondary material's waste maximum organic vapor pressure is less than the maximum vapor pressure limit for the appropriate tank design capacity category.
4. Procedure for determining no detectable organic emissions for the purpose of complying with this paragraph:
- (i) The test shall be conducted in accordance with the procedures specified in Method 21 of 40 CFR part 60, appendix A. Each potential leak interface (i.e., a location where organic vapor leakage could occur) on the cover and associated closure devices shall be checked. Potential leak interfaces that are associated with covers and closure devices include, but are not limited to: the interface of the cover and its foundation mounting; the periphery of any opening on the cover and its associated closure device; and the sealing seat interface on a spring-loaded pressure relief valve.
  - (ii) The test shall be performed when the unit contains a hazardous secondary material having an organic concentration representative of the range of concentrations for the hazardous secondary material expected to be managed in the unit. During the test, the cover and closure devices shall be secured in the closed position.
  - (iii) The detection instrument shall meet the performance criteria of Method 21 of 40 CFR part 60, appendix A, except the instrument response factor criteria in section 3.1.2(a) of Method 21 shall be for the average composition of the organic constituents in the hazardous secondary material placed in the hazardous secondary management unit, not for each individual organic constituent.
  - (iv) The detection instrument shall be calibrated before use on each day of its use by the procedures specified in Method 21 of 40 CFR part 60, appendix A.
  - (v) Calibration gases shall be as follows:
    - (I) Zero air (less than 10 ppmv hydrocarbon in air); and
    - (II) A mixture of methane or n-hexane and air at a concentration of approximately, but less than, 10,000 ppmv methane or n-hexane.
  - (vi) The background level shall be determined according to the procedures in Method 21 of 40 CFR part 60, appendix A.
  - (vii) Each potential leak interface shall be checked by traversing the instrument probe around the potential leak interface as close to the interface as possible, as described in Method 21 of 40 CFR part 60, appendix A. In the case when the configuration of the cover or closure device prevents a complete traverse of the

interface, all accessible portions of the interface shall be sampled. In the case when the configuration of the closure device prevents any sampling at the interface and the device is equipped with an enclosed extension or horn (e.g., some pressure relief devices), the instrument probe inlet shall be placed at approximately the center of the exhaust area to the atmosphere.

- (viii) The arithmetic difference between the maximum organic concentration indicated by the instrument and the background level shall be compared with the value of 500 ppmv except when monitoring a seal around a rotating shaft that passes through a cover opening, in which case the comparison shall be as specified in subpart (ix) of this part. If the difference is less than 500 ppmv, then the potential leak interface is determined to operate with no detectable organic emissions.
- (ix) For the seals around a rotating shaft that passes through a cover opening, the arithmetic difference between the maximum organic concentration indicated by the instrument and the background level shall be compared with the value of 10,000 ppmw. If the difference is less than 10,000 ppmw, then the potential leak interface is determined to operate with no detectable organic emissions.

(e) Standards: tanks [40 CFR 261.1084]

1. The provisions of this section apply to the control of air pollutant emissions from tanks for which part (d)2 of this paragraph references the use of this subparagraph for such air emission control.
2. The remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from each tank subject to this subparagraph in accordance with the following requirements as applicable:
  - (i) For a tank that manages hazardous secondary material that meets all of the conditions specified in items (I) through (III) of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from the tank in accordance with the Tank Level 1 controls specified in part 3 of this subparagraph or the Tank Level 2 controls specified in part 4 of this subparagraph.
    - (I) The hazardous secondary material in the tank has a maximum organic vapor pressure which is less than the maximum organic vapor pressure limit for the tank's design capacity category as follows:
      - I. For a tank design capacity equal to or greater than 151 m<sup>3</sup>, the maximum organic vapor pressure limit for the tank is 5.2 kPa.
      - II. For a tank design capacity equal to or greater than 75 m<sup>3</sup> but less than 151 m<sup>3</sup>, the maximum organic vapor pressure limit for the tank is 27.6 kPa.
      - III. For a tank design capacity less than 75 m<sup>3</sup>, the maximum organic vapor pressure limit for the tank is 76.6 kPa.
    - (II) The hazardous secondary material in the tank is not heated by the remanufacturer or other person that stores or treats the hazardous secondary material to a temperature that is greater than the temperature at which the maximum organic vapor pressure of the hazardous secondary material is determined for the purpose of complying with item (I) of this subpart.
  - (ii) For a tank that manages hazardous secondary material that does not meet all of the conditions specified in items (i)(I) and (II) of this part, the remanufacturer or other person that stores or treats the hazardous secondary material shall control

air pollutant emissions from the tank by using Tank Level 2 controls in accordance with the requirements of part 4 of this subparagraph. An example of tanks required to use Tank Level 2 controls is a tank for which the hazardous secondary material in the tank has a maximum organic vapor pressure that is equal to or greater than the maximum organic vapor pressure limit for the tank's design capacity category as specified in item (i)(I) of this part.

3. Remanufacturers or other persons that store or treat the hazardous secondary material controlling air pollutant emissions from a tank using Tank Level 1 controls shall meet the requirements specified in subparts (i) through (iv) of this part:

(i) The remanufacturer or other person that stores or treats that hazardous secondary material shall determine the maximum organic vapor pressure for a hazardous secondary material to be managed in the tank using Tank Level 1 controls before the first time the hazardous secondary material is placed in the tank. The maximum organic vapor pressure shall be determined using the procedures specified in part (d)3 of this paragraph. Thereafter, the remanufacturer or other person that stores or treats the hazardous secondary material shall perform a new determination whenever changes to the hazardous secondary material managed in the tank could potentially cause the maximum organic vapor pressure to increase to a level that is equal to or greater than the maximum organic vapor pressure limit for the tank design capacity category specified in item 2(i)(I) of this subparagraph, as applicable to the tank.

(ii) The tank shall be equipped with a fixed roof designed to meet the following specifications:

(I) The fixed roof and its closure devices shall be designed to form a continuous barrier over the entire surface area of the hazardous secondary material in the tank. The fixed roof may be a separate cover installed on the tank (e.g., a removable cover mounted on an open-top tank) or may be an integral part of the tank structural design (e.g., a horizontal cylindrical tank equipped with a hatch).

(II) The fixed roof shall be installed in a manner such that there are no visible cracks, holes, gaps, or other open spaces between roof section joints or between the interface of the roof edge and the tank wall.

(III) Each opening in the fixed roof, and any manifold system associated with the fixed roof, shall be either:

I. Equipped with a closure device designed to operate such that when the closure device is secured in the closed position there are no visible cracks, holes, gaps, or other open spaces in the closure device or between the perimeter of the opening and the closure device; or

II. Connected by a closed-vent system that is vented to a control device. The control device shall remove or destroy organics in the vent stream, and shall be operating whenever hazardous secondary material is managed in the tank, except as provided for in sections A and B of this subitem.

A. During periods when it is necessary to provide access to the tank for performing the activities of section B of this subitem, venting of the vapor headspace underneath the fixed roof to the control device is not required, opening of closure devices is allowed, and removal of the fixed roof is allowed. Following completion of the activity, the remanufacturer or other person that stores or treats the

hazardous secondary material shall promptly secure the closure device in the closed position or reinstall the cover, as applicable, and resume operation of the control device.

- B. During periods of routine inspection, maintenance, or other activities needed for normal operations, and for removal of accumulated sludge or other residues from the bottom of the tank.
- (IV) The fixed roof and its closure devices shall be made of suitable materials that will minimize exposure of the hazardous secondary material to the atmosphere, to the extent practical, and will maintain the integrity of the fixed roof and closure devices throughout their intended service life. Factors to be considered when selecting the materials for and designing the fixed roof and closure devices shall include: organic vapor permeability, the effects of any contact with the hazardous secondary material or its vapors managed in the tank; the effects of outdoor exposure to wind, moisture, and sunlight; and the operating practices used for the tank on which the fixed roof is installed.
- (iii) Whenever a hazardous secondary material is in the tank, the fixed roof shall be installed with each closure device secured in the closed position except as follows:
- (I) Opening of closure devices or removal of the fixed roof is allowed at the following times:
    - I. To provide access to the tank for performing routine inspection, maintenance, or other activities needed for normal operations. Examples of such activities include those times when a worker needs to open a port to sample the liquid in the tank, or when a worker needs to open a hatch to maintain or repair equipment. Following completion of the activity, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure device in the closed position or reinstall the cover, as applicable, to the tank.
    - II. To remove accumulated sludge or other residues from the bottom of tank.
  - (II) Opening of a spring-loaded pressure-vacuum relief valve, conservation vent, or similar type of pressure relief device which vents to the atmosphere is allowed during normal operations for the purpose of maintaining the tank internal pressure in accordance with the tank design specifications. The device shall be designed to operate with no detectable organic emissions when the device is secured in the closed position. The settings at which the device opens shall be established such that the device remains in the closed position whenever the tank internal pressure is within the internal pressure operating range determined by the remanufacturer or other person that stores or treats the hazardous secondary material based on the tank manufacturer recommendations, applicable regulations, fire protection and prevention codes, standard engineering codes and practices, or other requirements for the safe handling of flammable, ignitable, explosive, reactive, or hazardous materials. Examples of normal operating conditions that may require these devices to open are during those times when the tank internal pressure exceeds the internal pressure operating range for the tank as a result of loading operations or diurnal ambient temperature fluctuations.

- (III) Opening of a safety device, as defined in subparagraph (b) of this paragraph, is allowed at any time conditions require doing so to avoid an unsafe condition.
- (iv) The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect the air emission control equipment in accordance with the following requirements.
  - (I) The fixed roof and its closure devices shall be visually inspected by the remanufacturer or other person that stores or treats the hazardous secondary material to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes, or gaps in the roof sections or between the roof and the tank wall; broken, cracked, or otherwise damaged seals or gaskets on closure devices; and broken or missing hatches, access covers, caps, or other closure devices.
  - (II) The remanufacturer or other person that stores or treats the hazardous secondary material shall perform an initial inspection of the fixed roof and its closure devices on or before the date that the tank becomes subject to this section. Thereafter, the remanufacturer or other person that stores or treats the hazardous secondary material shall perform the inspections at least once every year except under the special conditions provided for in part 12 of this subparagraph.
  - (III) In the event that a defect is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of part 11 of this subparagraph.
  - (IV) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection in accordance with the requirements specified in part (j)2 of this paragraph.
- 4. Remanufacturers or other persons that store or treat the hazardous secondary material controlling air pollutant emissions from a tank using Tank Level 2 controls shall use one of the following tanks:
  - (i) A fixed-roof tank equipped with an internal floating roof in accordance with the requirements specified in part 5 of this subparagraph;
  - (ii) A tank equipped with an external floating roof in accordance with the requirements specified in part 6 of this subparagraph;
  - (iii) A tank vented through a closed-vent system to a control device in accordance with the requirements specified in part 7 of this subparagraph;
  - (iv) A pressure tank designed and operated in accordance with the requirements specified in part 8 of this subparagraph; or
  - (v) A tank located inside an enclosure that is vented through a closed-vent system to an enclosed combustion control device in accordance with the requirements specified in part 9 of this subparagraph.
- 5. The remanufacturer or other person that stores or treats the hazardous secondary material who controls air pollutant emissions from a tank using a fixed roof with an internal floating roof shall meet the requirements specified in subparts 5(i) through (iii) of this subparagraph.



- (i) The tank shall be equipped with a fixed roof and an internal floating roof in accordance with the following requirements:
  - (I) The internal floating roof shall be designed to float on the liquid surface except when the floating roof must be supported by the leg supports.
  - (II) The internal floating roof shall be equipped with a continuous seal between the wall of the tank and the floating roof edge that meets either of the following requirements:
    - I. A single continuous seal that is either a liquid-mounted seal or a metallic shoe seal, as defined in subparagraph (b) of this paragraph; or
    - II. Two continuous seals mounted one above the other. The lower seal may be a vapor-mounted seal.
  - (III) The internal floating roof shall meet the following specifications:
    - I. Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
    - II. Each opening in the internal floating roof shall be equipped with a gasketed cover or a gasketed lid except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains.
    - III. Each penetration of the internal floating roof for the purpose of sampling shall have a slit fabric cover that covers at least 90 percent of the opening.
    - IV. Each automatic bleeder vent and rim space vent shall be gasketed.
    - V. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.
    - VI. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- (ii) The remanufacturer or other person that stores or treats the hazardous secondary material shall operate the tank in accordance with the following requirements:
  - (I) When the floating roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be completed as soon as practical.
  - (II) Automatic bleeder vents are to be set closed at all times when the roof is floating, except when the roof is being floated off or is being landed on the leg supports.
  - (III) Prior to filling the tank, each cover, access hatch, gauge float well or lid on any opening in the internal floating roof shall be bolted or fastened closed (i.e., no visible gaps). Rim space vents are to be set to open only when the internal floating roof is not floating or when the pressure beneath the rim exceeds the manufacturer's recommended setting.

- (iii) The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect the internal floating roof in accordance with the procedures specified as follows:
  - (I) The floating roof and its closure devices shall be visually inspected by the remanufacture or other person that stores or treats the hazardous secondary material to check for defects that could result in air pollutant emissions. Defects include, but are not limited to: the internal floating roof is not floating on the surface of the liquid inside the tank; liquid has accumulated on top of the internal floating roof; any portion of the roof seals have detached from the roof rim; holes, tears, or other openings are visible in the seal fabric; the gaskets no longer close off the hazardous secondary material surface from the atmosphere; or the slotted membrane has more than 10 percent open area.
  - (II) The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect the internal floating roof components as follows except as provided in item (III) of this subpart:
    - I. Visually inspect the internal floating roof components through openings on the fixed-roof (e.g., manholes and roof hatches) at least once every 12 months after initial fill, and
    - II. Visually inspect the internal floating roof, primary seal, secondary seal (if one is in service), gaskets, slotted membranes, and sleeve seals (if any) each time the tank is emptied and degassed and at least every 10 years.
  - (III) As an alternative to performing the inspections specified in item (II) of this subpart for an internal floating roof equipped with two continuous seals mounted one above the other, the remanufacturer or other person that stores or treats the hazardous secondary material may visually inspect the internal floating roof, primary and secondary seals, gaskets, slotted membranes, and sleeve seals (if any) each time the tank is emptied and degassed and at least every 5 years.
  - (IV) Prior to each inspection required by item (II) or (III) of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material shall notify the Commissioner in advance of each inspection to provide the Commissioner with the opportunity to have an observer present during the inspection. The remanufacturer or other person that stores or treats the hazardous secondary material shall notify the Commissioner of the date and location of the inspection as follows:
    - I. Prior to each visual inspection of an internal floating roof in a tank that has been emptied and degassed, written notification shall be prepared and sent by the remanufacturer or other person that stores or treats the hazardous secondary material so that it is received by the Commissioner at least 30 calendar days before refilling the tank except when an inspection is not planned as provided for in subitem II of this item.
    - II. When a visual inspection is not planned and the remanufacturer or other person that stores or treats the hazardous secondary material could not have known about the inspection 30 calendar days before refilling the tank, the remanufacturer or other person that stores or treats the hazardous secondary material shall notify the Commissioner as soon as possible, but no later than 7 calendar days before refilling of the tank. This notification may be made by telephone and immediately followed by a written

explanation for why the inspection is unplanned. Alternatively, written notification, including the explanation for the unplanned inspection, may be sent so that it is received by the Commissioner at least seven calendar days before refilling the tank.

- (V) In the event that a defect is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of part 11 of this subparagraph.
  - (VI) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection in accordance with the requirements specified in part (j)2 of this paragraph.
  - (iv) Safety devices, as defined in subparagraph (b) of this paragraph, may be installed and operated as necessary on any tank complying with the requirements of this part.
6. The remanufacturer or other person that stores or treats the hazardous secondary material who controls air pollutant emissions from a tank using an external floating roof shall meet the requirements specified in subpart (i) through (iii) of this part.
- (i) The remanufacturer or other person that stores or treats the hazardous secondary material shall design the external floating roof in accordance with the following requirements:
    - (I) The external floating roof shall be designed to float on the liquid surface except when the floating roof must be supported by the leg supports.
    - (II) The floating roof shall be equipped with two continuous seals, one above the other, between the wall of the tank and the roof edge. The lower seal is referred to as the primary seal, and the upper seal is referred to as the secondary seal.
      - I. The primary seal shall be a liquid-mounted seal or a metallic shoe seal, as defined in subparagraph (b) of this paragraph. The total area of the gaps between the tank wall and the primary seal shall not exceed 212 square centimeters (cm<sup>2</sup>) per meter of tank diameter, and the width of any portion of these gaps shall not exceed 3.8 centimeters (cm). If a metallic shoe seal is used for the primary seal, the metallic shoe seal shall be designed so that one end extends into the liquid in the tank and the other end extends a vertical distance of at least 61 centimeters (cm) above the liquid surface.
      - II. The secondary seal shall be mounted above the primary seal and cover the annular space between the floating roof and the wall of the tank. The total area of the gaps between the tank wall and the secondary seal shall not exceed 21.2 square centimeters (cm<sup>2</sup>) per meter of tank diameter, and the width of any portion of these gaps shall not exceed 1.3 centimeters (cm).
    - (III) The external floating roof shall meet the following specifications:
      - I. Except for automatic bleeder vents (vacuum breaker vents) and rim space vents, each opening in a noncontact external floating roof shall provide a projection below the liquid surface.
      - II. Except for automatic bleeder vents, rim space vents, roof drains,

and leg sleeves, each opening in the roof shall be equipped with a gasketed cover, seal, or lid.

- III. Each access hatch and each gauge float well shall be equipped with a cover designed to be bolted or fastened when the cover is secured in the closed position.
- IV. Each automatic bleeder vent and each rim space vent shall be equipped with a gasket.
- V. Each roof drain that empties into the liquid managed in the tank shall be equipped with a slotted membrane fabric cover that covers at least 90 percent of the area of the opening.
- VI. Each unslotted and slotted guide pole well shall be equipped with a gasketed sliding cover or a flexible fabric sleeve seal.
- VII. Each unslotted guide pole shall be equipped with a gasketed cap on the end of the pole.
- VIII. Each slotted guide pole shall be equipped with a gasketed float or other device which closes off the liquid surface from the atmosphere.
- IX. Each gauge hatch and each sample well shall be equipped with a gasketed cover.

(ii) The remanufacturer or other person that stores or treats the hazardous secondary material shall operate the tank in accordance with the following requirements:

- (I) When the floating roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be completed as soon as practical.
- (II) Except for automatic bleeder vents, rim space vents, roof drains, and leg sleeves, each opening in the roof shall be secured and maintained in a closed position at all times except when the closure device must be open for access.
- (III) Covers on each access hatch and each gauge float well shall be bolted or fastened when secured in the closed position.
- (IV) Automatic bleeder vents shall be set closed at all times when the roof is floating, except when the roof is being floated off or is being landed on the leg supports.
- (V) Rim space vents shall be set to open only at those times that the roof is being floated off the roof leg supports or when the pressure beneath the rim seal exceeds the manufacturer's recommended setting.
- (VI) The cap on the end of each unslotted guide pole shall be secured in the closed position at all times except when measuring the level or collecting samples of the liquid in the tank.
- (VII) The cover on each gauge hatch or sample well shall be secured in the closed position at all times except when the hatch or well must be opened for access.
- (VIII) Both the primary seal and the secondary seal shall completely cover the

annular space between the external floating roof and the wall of the tank in a continuous fashion except during inspections.

- (iii) The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect the external floating roof in accordance with the procedures specified as follows:
  - (I) The remanufacturer or other person that stores or treats the hazardous secondary material shall measure the external floating roof seal gaps in accordance with the following requirements:
    - I. The remanufacturer or other person that stores or treats the hazardous secondary material shall perform measurements of gaps between the tank wall and the primary seal within 60 calendar days after initial operation of the tank following installation of the floating roof and, thereafter, at least once every 5 years.
    - II. The remanufacturer or other person that stores or treats the hazardous secondary material shall perform measurements of gaps between the tank wall and the secondary seal within 60 calendar days after initial operation of the tank following installation of the floating roof and, thereafter, at least once every year.
    - III. If a tank ceases to hold hazardous secondary material for a period of 1 year or more, subsequent introduction of hazardous secondary material into the tank shall be considered an initial operation for the purposes of subitems I and II of this item.
    - IV. The remanufacturer or other person that stores or treats the hazardous secondary material shall determine the total surface area of gaps in the primary seal and in the secondary seal individually using the following procedure:
      - A. The seal gap measurements shall be performed at one or more floating roof levels when the roof is floating off the roof supports.
      - B. Seal gaps, if any, shall be measured around the entire perimeter of the floating roof in each place where a 0.32-centimeter (cm) diameter uniform probe passes freely (without forcing or binding against the seal) between the seal and the wall of the tank and measure the circumferential distance of each such location.
      - C. For a seal gap measured under this subpart, the gap surface area shall be determined by using probes of various widths to measure accurately the actual distance from the tank wall to the seal and multiplying each such width by its respective circumferential distance.
      - D. The total gap area shall be calculated by adding the gap surface areas determined for each identified gap location for the primary seal and the secondary seal individually, and then dividing the sum for each seal type by the nominal diameter of the tank. These total gap areas for the primary seal and secondary seal are then compared to the respective standards for the seal type as specified in item (i)(II) of this part.

- V. In the event that the seal gap measurements do not conform to the specifications in item (i)(II) of this part, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of part 11 of this subparagraph.
  - VI. The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection in accordance with the requirements specified in part (j)2 of this paragraph.
- (II) The remanufacturer or other person that stores or treats the hazardous secondary material shall visually inspect the external floating roof in accordance with the following requirements:
- I. The floating roof and its closure devices shall be visually inspected by the remanufacturer or other person that stores or treats the hazardous secondary material to check for defects that could result in air pollutant emissions. Defects include, but are not limited to: holes, tears, or other openings in the rim seal or seal fabric of the floating roof; a rim seal detached from the floating roof; all or a portion of the floating roof deck being submerged below the surface of the liquid in the tank; broken, cracked, or otherwise damaged seals or gaskets on closure devices; and broken or missing hatches, access covers, caps, or other closure devices.
  - II. The remanufacturer or other person that stores or treats the hazardous secondary material shall perform an initial inspection of the external floating roof and its closure devices on or before the date that the tank becomes subject to this subparagraph. Thereafter, the remanufacturer or other person that stores or treats the hazardous secondary material shall perform the inspections at least once every year except for the special conditions provided for in part 12 of this subparagraph.
  - III. In the event that a defect is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of part 11 of this subparagraph.
  - IV. The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection in accordance with the requirements specified in part (j)2 of this paragraph.
- (III) Prior to each inspection required by item (I) or (II) of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material shall notify the Commissioner in advance of each inspection to provide the Commissioner with the opportunity to have an observer present during the inspection. The remanufacturer or other person that stores or treats the hazardous secondary material shall notify the Commissioner of the date and location of the inspection as follows:
- I. Prior to each inspection to measure external floating roof seal gaps as required under item (I) of this subpart, written notification shall be prepared and sent by the remanufacturer or other person that stores or treats the hazardous secondary material so that it is received by the Commissioner at least 30 calendar days

before the date the measurements are scheduled to be performed.

- II. Prior to each visual inspection of an external floating roof in a tank that has been emptied and degassed, written notification shall be prepared and sent by the remanufacturer or other person that stores or treats the hazardous secondary material so that it is received by the Commissioner at least 30 calendar days before refilling the tank except when an inspection is not planned as provided for in subitem III of this item.
  - III. When a visual inspection is not planned and the remanufacturer or other person that stores or treats the hazardous secondary material could not have known about the inspection 30 calendar days before refilling the tank, the owner or operator shall notify the Commissioner as soon as possible, but no later than 7 calendar days before refilling of the tank. This notification may be made by telephone and immediately followed by a written explanation for why the inspection is unplanned. Alternatively, written notification, including the explanation for the unplanned inspection, may be sent so that it is received by the Commissioner at least 7 calendar days before refilling the tank.
- (iv) Safety devices, as defined in subparagraph (b) of this paragraph, may be installed and operated as necessary on any tank complying with the requirements of this part.
7. The remanufacturer or other person that stores or treats the hazardous secondary material who controls air pollutant emissions from a tank by venting the tank to a control device shall meet the requirements specified in subparts (i) through (iii) of this part.
- (i) The tank shall be covered by a fixed roof and vented directly through a closed-vent system to a control device in accordance with the following requirements:
    - (I) The fixed roof and its closure devices shall be designed to form a continuous barrier over the entire surface area of the liquid in the tank.
    - (II) Each opening in the fixed roof not vented to the control device shall be equipped with a closure device. If the pressure in the vapor headspace underneath the fixed roof is less than atmospheric pressure when the control device is operating, the closure devices shall be designed to operate such that when the closure device is secured in the closed position there are no visible cracks, holes, gaps, or other open spaces in the closure device or between the perimeter of the cover opening and the closure device. If the pressure in the vapor headspace underneath the fixed roof is equal to or greater than atmospheric pressure when the control device is operating, the closure device shall be designed to operate with no detectable organic emissions.
    - (III) The fixed roof and its closure devices shall be made of suitable materials that will minimize exposure of the hazardous secondary material to the atmosphere, to the extent practical, and will maintain the integrity of the fixed roof and closure devices throughout their intended service life. Factors to be considered when selecting the materials for and designing the fixed roof and closure devices shall include: organic vapor permeability, the effects of any contact with the liquid and its vapor managed in the tank; the effects of outdoor exposure to wind, moisture, and sunlight; and the operating practices used for the tank on which the fixed roof is installed.

- (IV) The closed-vent system and control device shall be designed and operated in accordance with the requirements of subparagraph (h) of this paragraph.
- (ii) Whenever a hazardous secondary material is in the tank, the fixed roof shall be installed with each closure device secured in the closed position and the vapor headspace underneath the fixed roof vented to the control device except as follows:
  - (I) Venting to the control device is not required, and opening of closure devices or removal of the fixed roof is allowed at the following times:
    - I. To provide access to the tank for performing routine inspection, maintenance, or other activities needed for normal operations. Examples of such activities include those times when a worker needs to open a port to sample liquid in the tank, or when a worker needs to open a hatch to maintain or repair equipment. Following completion of the activity, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure device in the closed position or reinstall the cover, as applicable, to the tank.
    - II. To remove accumulated sludge or other residues from the bottom of a tank.
  - (II) Opening of a safety device, as defined in subparagraph (b) of this paragraph, is allowed at any time conditions require doing so to avoid an unsafe condition.
- (iii) The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect and monitor the air emission control equipment in accordance with the following procedures:
  - (I) The fixed roof and its closure devices shall be visually inspected by the remanufacturer or other person that stores or treats the hazardous secondary material to check for defects that could result in air pollutant emissions. Defects include, but are not limited to, visible cracks, holes, or gaps in the roof sections or between the roof and the tank wall; broken, cracked, or otherwise damaged seals or gaskets on closure devices; and broken or missing hatches, access covers, caps, or other closure devices.
  - (II) The closed-vent system and control device shall be inspected and monitored by the remanufacturer or other person that stores or treats the hazardous secondary material in accordance with the procedures specified in subparagraph (h) of this paragraph.
  - (III) The remanufacturer or other person that stores or treats the hazardous secondary material shall perform an initial inspection of the air emission control equipment on or before the date that the tank becomes subject to this subparagraph. Thereafter, the remanufacturer or other person that stores or treats the hazardous secondary material shall perform the inspections at least once every year except for the special conditions provided for in part 12 of this subparagraph.
  - (IV) In the event that a defect is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of part 11 of this subparagraph.



- (V) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain a record of the inspection in accordance with the requirements specified in part (j)2 of this paragraph.
8. The remanufacturer or other person that stores or treats the hazardous secondary material who controls air pollutant emissions by using a pressure tank shall meet the following requirements.
- (i) The tank shall be designed not to vent to the atmosphere as a result of compression of the vapor headspace in the tank during filling of the tank to its design capacity.
  - (ii) All tank openings shall be equipped with closure devices designed to operate with no detectable organic emissions as determined using the procedure specified in part (e)4 of this paragraph.
  - (iii) Whenever a hazardous secondary material is in the tank, the tank shall be operated as a closed system that does not vent to the atmosphere except under either or the following conditions as specified in item (I) or (II) of this subpart.
    - (I) At those times when opening of a safety device, as defined in subparagraph (b) of this paragraph, is required to avoid an unsafe condition.
    - (II) At those times when purging of inerts from the tank is required and the purge stream is routed to a closed-vent system and control device designed and operated in accordance with the requirements of subparagraph (h) of this paragraph.
9. The remanufacturer or other person that stores or treats the hazardous secondary material who controls air pollutant emissions by using an enclosure vented through a closed-vent system to an enclosed combustion control device shall meet the requirements specified in subparts (i) through (iv) of this part.
- (i) The tank shall be located inside an enclosure. The enclosure shall be designed and operated in accordance with the criteria for a permanent total enclosure as specified in "Procedure T--Criteria for and Verification of a Permanent or Temporary Total Enclosure" under 40 CFR 52.741, appendix B. The enclosure may have permanent or temporary openings to allow worker access; passage of material into or out of the enclosure by conveyor, vehicles, or other mechanical means; entry of permanent mechanical or electrical equipment; or direct airflow into the enclosure. The remanufacturer or other person that stores or treats the hazardous secondary material shall perform the verification procedure for the enclosure as specified in Section 5.0 to "Procedure T--Criteria for and Verification of a Permanent or Temporary Total Enclosure" initially when the enclosure is first installed and, thereafter, annually.
  - (ii) The enclosure shall be vented through a closed-vent system to an enclosed combustion control device that is designed and operated in accordance with the standards for either a vapor incinerator, boiler, or process heater specified in subparagraph (h) of this paragraph.
  - (iii) Safety devices, as defined in subparagraph (b) of this paragraph, may be installed and operated as necessary on any enclosure, closed-vent system, or control device used to comply with the requirements of subparts (i) and (ii) of this part.
  - (iv) The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect and monitor the closed-vent system and control device as specified in subparagraph (h) of this paragraph.

10. The remanufacturer or other person that stores or treats the hazardous secondary material shall transfer hazardous secondary material to a tank subject to this subparagraph in accordance with the following requirements:
  - (i) Transfer of hazardous secondary material, except as provided in subpart (ii) of this part, to the tank from another tank subject to this subparagraph shall be conducted using continuous hard-piping or another closed system that does not allow exposure of the hazardous secondary material to the atmosphere. For the purpose of complying with this provision, an individual drain system is considered to be a closed system when it meets the requirements of 40 CFR part 63, subpart RR--National Emission Standards for Individual Drain Systems.
  - (ii) The requirements of subpart (i) of this part do not apply when transferring a hazardous secondary material to the tank under any of the following conditions:
    - (I) The hazardous secondary material meets the average VO concentration conditions specified in part (c)3 of this paragraph at the point of material origination.
    - (II) The hazardous secondary material has been treated by an organic destruction or removal process to meet the requirements in subpart (c)3(ii) of this paragraph.
    - (III) The hazardous secondary material meets the requirements of subpart (c)3(iv) of this paragraph.
11. The remanufacturer or other person that stores or treats the hazardous secondary material shall repair each defect detected during an inspection performed in accordance with the requirements of subparts 3(iv), 5(iii), 6(iii), or 7(iii) of this subparagraph as follows:
  - (i) The remanufacturer or other person that stores or treats the hazardous secondary material shall make first efforts at repair of the defect no later than 5 calendar days after detection, and repair shall be completed as soon as possible but no later than 45 calendar days after detection except as provided in subpart (ii) of this part.
  - (ii) Repair of a defect may be delayed beyond 45 calendar days if the remanufacturer or other person that stores or treats the hazardous secondary material determines that repair of the defect requires emptying or temporary removal from service of the tank and no alternative tank capacity is available at the site to accept the hazardous secondary material normally managed in the tank. In this case, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect the next time the process or unit that is generating the hazardous secondary material managed in the tank stops operation. Repair of the defect shall be completed before the process or unit resumes operation.
12. Following the initial inspection and monitoring of the cover as required by the applicable provisions of this paragraph, subsequent inspection and monitoring may be performed at intervals longer than 1 year under the following special conditions:
  - (i) In the case when inspecting or monitoring the cover would expose a worker to dangerous, hazardous, or other unsafe conditions, then the remanufacturer or other person that stores or treats the hazardous secondary material may designate a cover as an "unsafe to inspect and monitor cover" and comply with all of the following requirements:
    - (I) Prepare a written explanation for the cover stating the reasons why the

cover is unsafe to visually inspect or to monitor, if required.

(II) Develop and implement a written plan and schedule to inspect and monitor the cover, using the procedures specified in the applicable subparagraph of this paragraph, as frequently as practicable during those times when a worker can safely access the cover.

(ii) In the case when a tank is buried partially or entirely underground, a remanufacturer or other person that stores or treats the hazardous secondary material is required to inspect and monitor, as required by the applicable provisions of this section, only those portions of the tank cover and those connections to the tank (e.g., fill ports, access hatches, gauge wells, etc.) that are located on or above the ground surface.

(f) Reserved [40 CFR 261.1085]

(g) Standards: containers [40 CFR 261.1086]

1. Applicability

The provisions of this subparagraph apply to the control of air pollutant emissions from containers for which part (c)2 of this paragraph references the use of this subparagraph for such air emission control.

2. General requirements

(i) The remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from each container subject to this subparagraph in accordance with the following requirements, as applicable to the container.

(I) For a container having a design capacity greater than 0.1 m<sup>3</sup> and less than or equal to 0.46 m<sup>3</sup>, the remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from the container in accordance with the Container Level 1 standards specified in part 3 of this subparagraph.

(II) For a container having a design capacity greater than 0.46 m<sup>3</sup> that is not in light material service, the remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from the container in accordance with the Container Level 1 standards specified in part 3 of this subparagraph.

(III) For a container having a design capacity greater than 0.46 m<sup>3</sup> that is in light material service, the remanufacturer or other person that stores or treats the hazardous secondary material shall control air pollutant emissions from the container in accordance with the Container Level 2 standards specified in part 4 of this subparagraph.

(ii) Reserved

3. Container Level 1 standards

(i) A container using Container Level 1 controls is one of the following:

(I) A container that meets the applicable U.S. Department of Transportation (DOT) regulations on packaging hazardous materials for transportation as specified in part 6 of this subparagraph.

(II) A container equipped with a cover and closure devices that form a

continuous barrier over the container openings such that when the cover and closure devices are secured in the closed position there are no visible holes, gaps, or other open spaces into the interior of the container. The cover may be a separate cover installed on the container (e.g., a lid on a drum or a suitably secured tarp on a roll-off box) or may be an integral part of the container structural design (e.g., a "portable tank" or bulk cargo container equipped with a screw-type cap).

- (III) An open-top container in which an organic-vapor suppressing barrier is placed on or over the hazardous secondary material in the container such that no hazardous secondary material is exposed to the atmosphere. One example of such a barrier is application of a suitable organic-vapor suppressing foam.
- (ii) A container used to meet the requirements of item (i)(II) or (III) of this part shall be equipped with covers and closure devices, as applicable to the container, that are composed of suitable materials to minimize exposure of the hazardous secondary material to the atmosphere and to maintain the equipment integrity, for as long as the container is in service. Factors to be considered in selecting the materials of construction and designing the cover and closure devices shall include: organic vapor permeability; the effects of contact with the hazardous secondary material or its vapor managed in the container; the effects of outdoor exposure of the closure device or cover material to wind, moisture, and sunlight; and the operating practices for which the container is intended to be used.
- (iii) Whenever a hazardous secondary material is in a container using Container Level 1 controls, the remanufacturer or other person that stores or treats the hazardous secondary material shall install all covers and closure devices for the container, as applicable to the container, and secure and maintain each closure device in the closed position except as follows:
  - (I) Opening of a closure device or cover is allowed for the purpose of adding hazardous secondary material or other material to the container as follows:
    - I. In the case when the container is filled to the intended final level in one continuous operation, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure devices in the closed position and install the covers, as applicable to the container, upon conclusion of the filling operation.
    - II. In the case when discrete quantities or batches of material intermittently are added to the container over a period of time, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon either the container being filled to the intended final level; the completion of a batch loading after which no additional material will be added to the container within 15 minutes; the person performing the loading operation leaving the immediate vicinity of the container; or the shutdown of the process generating the hazardous secondary material being added to the container, whichever condition occurs first.
  - (II) Opening of a closure device or cover is allowed for the purpose of removing hazardous secondary material from the container as follows:
    - I. For the purpose of meeting the requirements of this subparagraph, an empty hazardous secondary material

container may be open to the atmosphere at any time (i.e., covers and closure devices on such a container are not required to be secured in the closed position).

- II. In the case when discrete quantities or batches of material are removed from the container, but the container is not an empty hazardous secondary material container, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon the completion of a batch removal after which no additional material will be removed from the container within 15 minutes or the person performing the unloading operation leaves the immediate vicinity of the container, whichever condition occurs first.
- (III) Opening of a closure device or cover is allowed when access inside the container is needed to perform routine activities other than transfer of hazardous secondary material. Examples of such activities include those times when a worker needs to open a port to measure the depth of or sample the material in the container, or when a worker needs to open a manhole hatch to access equipment inside the container. Following completion of the activity, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure device in the closed position or reinstall the cover, as applicable to the container.
  - (IV) Opening of a spring-loaded pressure-vacuum relief valve, conservation vent, or similar type of pressure relief device which vents to the atmosphere is allowed during normal operations for the purpose of maintaining the internal pressure of the container in accordance with the container design specifications. The device shall be designed to operate with no detectable organic emissions when the device is secured in the closed position. The settings at which the device opens shall be established such that the device remains in the closed position whenever the internal pressure of the container is within the internal pressure operating range determined by the remanufacturer or other persons that stores or treats the hazardous secondary material based on container manufacturer recommendations, applicable regulations, fire protection and prevention codes, standard engineering codes and practices, or other requirements for the safe handling of flammable, ignitable, explosive, reactive, or hazardous materials. Examples of normal operating conditions that may require these devices to open are during those times when the internal pressure of the container exceeds the internal pressure operating range for the container as a result of loading operations or diurnal ambient temperature fluctuations.
  - (V) Opening of a safety device, as defined in subparagraph (b) of this paragraph, is allowed at any time conditions require doing so to avoid an unsafe condition.
- (iv) The remanufacturer or other person that stores or treats the hazardous secondary material using containers with Container Level 1 controls shall inspect the containers and their covers and closure devices as follows:
    - (I) In the case when a hazardous secondary material already is in the container at the time the remanufacturer or other person that stores or treats the hazardous secondary material first accepts possession of the container at the facility and the container is not emptied within 24 hours after the container is accepted at the facility (i.e., is not an empty

hazardous secondary material container) the remanufacturer or other person that stores or treats the hazardous secondary material shall visually inspect the container and its cover and closure devices to check for visible cracks, holes, gaps, or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. The container visual inspection shall be conducted on or before the date that the container is accepted at the facility (i.e., the date the container becomes subject to the standards of this paragraph).

- (II) In the case when a container used for managing hazardous secondary material remains at the facility for a period of 1 year or more, the remanufacturer or other person that stores or treats the hazardous secondary material shall visually inspect the container and its cover and closure devices initially and thereafter, at least once every 12 months, to check for visible cracks, holes, gaps, or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. If a defect is detected, the remanufacturer or other person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of item (III) of this subpart.
- (III) When a defect is detected for the container, cover, or closure devices, the remanufacturer or other person that stores or treats the hazardous secondary material shall make first efforts at repair of the defect no later than 24 hours after detection and repair shall be completed as soon as possible but no later than 5 calendar days after detection. If repair of a defect cannot be completed within 5 calendar days, then the hazardous secondary material shall be removed from the container and the container shall not be used to manage hazardous secondary material until the defect is repaired.
- (v) The remanufacturer or other person that stores or treats the hazardous secondary material shall maintain at the facility a copy of the procedure used to determine that containers with capacity of 0.46 m<sup>3</sup> or greater, which do not meet applicable DOT regulations as specified in part 6 of this subparagraph, are not managing hazardous secondary material in light material service.

#### 4. Container Level 2 standards

- (i) A container using Container Level 2 controls is one of the following:
  - (I) A container that meets the applicable U.S. Department of Transportation (DOT) regulations on packaging hazardous materials for transportation as specified in part 6 of this subparagraph.
  - (II) A container that operates with no detectable organic emissions as defined in subparagraph (b) of this paragraph and determined in accordance with the procedure specified in part 7 of this subparagraph.
  - (III) A container that has been demonstrated within the preceding 12 months to be vapor-tight by using 40 CFR part 60, appendix A, Method 27 in accordance with the procedure specified in part 8 of this subparagraph.
- (ii) Transfer of hazardous secondary material in or out of a container using Container Level 2 controls shall be conducted in such a manner as to minimize exposure of the hazardous secondary material to the atmosphere, to the extent practical, considering the physical properties of the hazardous secondary material and good engineering and safety practices for handling flammable, ignitable, explosive, reactive, or other hazardous materials. Examples of container loading procedures that the EPA considers to meet the requirements of

this subpart include using any one of the following: a submerged-fill pipe or other submerged-fill method to load liquids into the container; a vapor-balancing system or a vapor-recovery system to collect and control the vapors displaced from the container during filling operations; or a fitted opening in the top of a container through which the hazardous secondary material is filled and subsequently purging the transfer line before removing it from the container opening.

(iii) Whenever a hazardous secondary material is in a container using Container Level 2 controls, the remanufacturer or other person that stores or treats the hazardous secondary material shall install all covers and closure devices for the container, and secure and maintain each closure device in the closed position except as follows:

(I) Opening of a closure device or cover is allowed for the purpose of adding hazardous secondary material or other material to the container as follows:

I. In the case when the container is filled to the intended final level in one continuous operation, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure devices in the closed position and install the covers, as applicable to the container, upon conclusion of the filling operation.

II. In the case when discrete quantities or batches of material intermittently are added to the container over a period of time, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon either the container being filled to the intended final level; the completion of a batch loading after which no additional material will be added to the container within 15 minutes; the person performing the loading operation leaving the immediate vicinity of the container; or the shutdown of the process generating the material being added to the container, whichever condition occurs first.

(II) Opening of a closure device or cover is allowed for the purpose of removing hazardous secondary material from the container as follows:

I. For the purpose of meeting the requirements of this subparagraph, an empty hazardous secondary material container may be open to the atmosphere at any time (i.e., covers and closure devices are not required to be secured in the closed position on an empty container).

II. In the case when discrete quantities or batches of material are removed from the container, but the container is not an empty hazardous secondary materials container, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure devices in the closed position and install covers, as applicable to the container, upon the completion of a batch removal after which no additional material will be removed from the container within 15 minutes or the person performing the unloading operation leaves the immediate vicinity of the container, whichever condition occurs first.

(III) Opening of a closure device or cover is allowed when access inside the

container is needed to perform routine activities other than transfer of hazardous secondary material. Examples of such activities include those times when a worker needs to open a port to measure the depth of or sample the material in the container, or when a worker needs to open a manhole hatch to access equipment inside the container. Following completion of the activity, the remanufacturer or other person that stores or treats the hazardous secondary material shall promptly secure the closure device in the closed position or reinstall the cover, as applicable to the container.

- (IV) Opening of a spring-loaded, pressure-vacuum relief valve, conservation vent, or similar type of pressure relief device which vents to the atmosphere is allowed during normal operations for the purpose of maintaining the internal pressure of the container in accordance with the container design specifications. The device shall be designed to operate with no detectable organic emission when the device is secured in the closed position. The settings at which the device opens shall be established such that the device remains in the closed position whenever the internal pressure of the container is within the internal pressure operating range determined by the remanufacturer or other person that stores or treats the hazardous secondary material based on container manufacturer recommendations, applicable regulations, fire protection and prevention codes, standard engineering codes and practices, or other requirements for the safe handling of flammable, ignitable, explosive, reactive, or hazardous materials. Examples of normal operating conditions that may require these devices to open are during those times when the internal pressure of the container exceeds the internal pressure operating range for the container as a result of loading operations or diurnal ambient temperature fluctuations.
  - (V) Opening of a safety device, as defined in subparagraph (b) of this paragraph, is allowed at any time conditions require doing so to avoid an unsafe condition.
- (iv) The remanufacture or other person that stores or treats the hazardous secondary material using containers with Container Level 2 controls shall inspect the containers and their covers and closure devices as follows:
- (I) In the case when a hazardous secondary material already is in the container at the time the remanufacturer or other person that stores or treats the hazardous secondary material first accepts possession of the container at the facility and the container is not emptied within 24 hours after the container is accepted at the facility (i.e., is not an empty hazardous secondary material container), the remanufacturer or other person that stores or treats the hazardous secondary material shall visually inspect the container and its cover and closure devices to check for visible cracks, holes, gaps, or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. The container visual inspection shall be conducted on or before the date that the container is accepted at the facility (i.e., the date the container becomes subject to the standards of this paragraph).
  - (II) In the case when a container used for managing hazardous secondary material remains at the facility for a period of 1 year or more, the remanufacturer or other person that stores or treats the hazardous secondary material shall visually inspect the container and its cover and closure devices initially and thereafter, at least once every 12 months, to check for visible cracks, holes, gaps, or other open spaces into the interior of the container when the cover and closure devices are secured in the closed position. If a defect is detected, the remanufacturer or other



person that stores or treats the hazardous secondary material shall repair the defect in accordance with the requirements of item (III) of this subpart.

- (III) When a defect is detected for the container, cover, or closure devices, the remanufacturer or other person that stores or treats the hazardous secondary material shall make first efforts at repair of the defect no later than 24 hours after detection, and repair shall be completed as soon as possible but no later than 5 calendar days after detection. If repair of a defect cannot be completed within 5 calendar days, then the hazardous secondary material shall be removed from the container and the container shall not be used to manage hazardous secondary material until the defect is repaired.

5. Container Level 3 standards

- (i) A container using Container Level 3 controls is one of the following:
  - (I) A container that is vented directly through a closed-vent system to a control device in accordance with the requirements of item (ii)(II) of this part.
  - (II) A container that is vented inside an enclosure which is exhausted through a closed-vent system to a control device in accordance with the requirements of items (ii)(I) and (II) of this part.
- (ii) The remanufacturer or other person that stores or treats the hazardous secondary material shall meet the following requirements, as applicable to the type of air emission control equipment selected by the remanufacturer or other person that stores or treats the hazardous secondary material:
  - (I) The container enclosure shall be designed and operated in accordance with the criteria for a permanent total enclosure as specified in "Procedure T--Criteria for and Verification of a Permanent or Temporary Total Enclosure" under 40 CFR 52.741, appendix B. The enclosure may have permanent or temporary openings to allow worker access; passage of containers through the enclosure by conveyor or other mechanical means; entry of permanent mechanical or electrical equipment; or direct airflow into the enclosure. The remanufacturer or other person that stores or treats the hazardous secondary material shall perform the verification procedure for the enclosure as specified in Section 5.0 to "Procedure T--Criteria for and Verification of a Permanent or Temporary Total Enclosure" initially when the enclosure is first installed and, thereafter, annually.
  - (II) The closed-vent system and control device shall be designed and operated in accordance with the requirements of subparagraph (h) of this paragraph.
- (iii) Safety devices, as defined in subparagraph (b) of this paragraph, may be installed and operated as necessary on any container, enclosure, closed-vent system, or control device used to comply with the requirements of subpart (i) of this part.
- (iv) Remanufacturers or other persons that store or treat the hazardous secondary material using Container Level 3 controls in accordance with the provisions of this paragraph shall inspect and monitor the closed-vent systems and control devices as specified in subparagraph (h) of this paragraph.
- (v) Remanufacturers or other persons that store or treat the hazardous secondary

material that use Container Level 3 controls in accordance with the provisions of this paragraph shall prepare and maintain the records specified in part (j)4 of this paragraph.

- (vi) Transfer of hazardous secondary material in or out of a container using Container Level 3 controls shall be conducted in such a manner as to minimize exposure of the hazardous secondary material to the atmosphere, to the extent practical, considering the physical properties of the hazardous secondary material and good engineering and safety practices for handling flammable, ignitable, explosive, reactive, or other hazardous materials. Examples of container loading procedures that the EPA considers to meet the requirements of this subpart include using any one of the following: a submerged-fill pipe or other submerged-fill method to load liquids into the container; a vapor-balancing system or a vapor-recovery system to collect and control the vapors displaced from the container during filling operations; or a fitted opening in the top of a container through which the hazardous secondary material is filled and subsequently purging the transfer line before removing it from the container opening.
6. For the purpose of compliance with item 3(i)(I) or 4(i)(I) of this subparagraph, containers shall be used that meet the applicable U.S. Department of Transportation (DOT) regulations on packaging hazardous materials for transportation as follows:
- (i) The container meets the applicable requirements specified in 49 CFR part 178 or part 179.
  - (ii) Hazardous secondary material is managed in the container in accordance with the applicable requirements specified in 49 CFR part 107, subpart B and 49 CFR parts 172, 173, and 180.
  - (iii) For the purpose of complying with this paragraph, no exceptions to the 49 CFR part 178 or part 179 regulations are allowed.
7. To determine compliance with the no detectable organic emissions requirement of item 4(i)(II) of this subparagraph, the procedure specified in part (d)4 of this paragraph shall be used.
- (i) Each potential leak interface (i.e., a location where organic vapor leakage could occur) on the container, its cover, and associated closure devices, as applicable to the container, shall be checked. Potential leak interfaces that are associated with containers include, but are not limited to: the interface of the cover rim and the container wall; the periphery of any opening on the container or container cover and its associated closure device; and the sealing seat interface on a spring-loaded pressure-relief valve.
  - (ii) The test shall be performed when the container is filled with a material having a volatile organic concentration representative of the range of volatile organic concentrations for the hazardous secondary materials expected to be managed in this type of container. During the test, the container cover and closure devices shall be secured in the closed position.
8. Procedure for determining a container to be vapor-tight using Method 27 of 40 CFR part 60, appendix A for the purpose of complying with item 4(i)(II) of this subparagraph.
- (i) The test shall be performed in accordance with Method 27 of 40 CFR part 60, appendix A of this chapter.
  - (ii) A pressure measurement device shall be used that has a precision of 2.5 mm water and that is capable of measuring above the pressure at which the container is to be tested for vapor tightness.

- (iii) If the test results determined by Method 27 indicate that the container sustains a pressure change less than or equal to 750 Pascals within 5 minutes after it is pressurized to a minimum of 4,500 Pascals, then the container is determined to be vapor-tight.
- (h) Standards: Closed-vent systems and control devices [40 CFR 261.1087]
1. This subparagraph applies to each closed-vent system and control device installed and operated by the remanufacturer or other person who stores or treats the hazardous secondary material to control air emissions in accordance with standards of this paragraph.
  2. The closed-vent system shall meet the following requirements:
    - (i) The closed-vent system shall route the gases, vapors, and fumes emitted from the hazardous secondary material in the hazardous secondary material management unit to a control device that meets the requirements specified in part 3 of this subparagraph.
    - (ii) The closed-vent system shall be designed and operated in accordance with the requirements specified in part (27)(d)11 of this rule.
    - (iii) In the case when the closed-vent system includes bypass devices that could be used to divert the gas or vapor stream to the atmosphere before entering the control device, each bypass device shall be equipped with either a flow indicator as specified in item (I) of this subpart or a seal or locking device as specified in item (II) of this subpart. For the purpose of complying with this subpart, low leg drains, high point bleeds, analyzer vents, open-ended valves or lines, spring loaded pressure relief valves, and other fittings used for safety purposes are not considered to be bypass devices.
      - (I) If a flow indicator is used to comply with this subpart, the indicator shall be installed at the inlet to the bypass line used to divert gases and vapors from the closed-vent system to the atmosphere at a point upstream of the control device inlet. For this item, a flow indicator means a device which indicates the presence of either gas or vapor flow in the bypass line.
      - (II) If a seal or locking device is used to comply with this subpart, the device shall be placed on the mechanism by which the bypass device position is controlled (e.g., valve handle, damper lever) when the bypass device is in the closed position such that the bypass device cannot be opened without breaking the seal or removing the lock. Examples of such devices include, but are not limited to, a car-seal or a lock-and-key configuration valve. The remanufacturer or other person that stores or treats the hazardous secondary material shall visually inspect the seal or closure mechanism at least once every month to verify that the bypass mechanism is maintained in the closed position.
    - (iv) The closed-vent system shall be inspected and monitored by the remanufacturer or other person that stores or treats the hazardous secondary material in accordance with the procedure specified in part (27)(d)12 of this rule.
  3. The control device shall meet the following requirements:
    - (i) The control device shall be one of the following devices:
      - (I) A control device designed and operated to reduce the total organic content of the inlet vapor stream vented to the control device by at least

95 percent by weight;

- (II) An enclosed combustion device designed and operated in accordance with the requirements of part (27)(d)3 of this rule; or
  - (III) A flare designed and operated in accordance with the requirements of part (27)(d)4 of this rule.
- (ii) The remanufacturer or other person that stores or treats the hazardous secondary material who elects to use a closed-vent system and control device to comply with the requirements of this subparagraph shall comply with the requirements specified in items (I) through (VI) of this subpart.
- (I) Periods of planned routine maintenance of the control device, during which the control device does not meet the specifications of items (i)(I), (II), or (III) of this part, as applicable, shall not exceed 240 hours per year.
  - (II) The specifications and requirements in items (i)(I) through (III) of this part for control devices do not apply during periods of planned routine maintenance.
  - (III) The specifications and requirements in items (i)(I) through (III) of this part for control devices do not apply during a control device system malfunction.
  - (IV) The remanufacturer or other person that stores or treats the hazardous secondary material shall demonstrate compliance with the requirements of item (I) of this subpart (i.e., planned routine maintenance of a control device, during which the control device does not meet the specifications of items (i)(I) through (III) of this part, as applicable, shall not exceed 240 hours per year) by recording the information specified in item (j)5(i)(V) of this paragraph.
  - (V) The remanufacturer or other person that stores or treats the hazardous secondary material shall correct control device system malfunctions as soon as practicable after their occurrence in order to minimize excess emissions of air pollutants.
  - (VI) The remanufacturer or other person that stores or treats the hazardous secondary material shall operate the closed-vent system such that gases, vapors, or fumes are not actively vented to the control device during periods of planned maintenance or control device system malfunction (i.e., periods when the control device is not operating or not operating normally) except in cases when it is necessary to vent the gases, vapors, and/or fumes to avoid an unsafe condition or to implement malfunction corrective actions or planned maintenance actions.
- (iii) The remanufacturer or other person that stores or treats the hazardous secondary material using a carbon adsorption system to comply with subpart (i) of this part shall operate and maintain the control device in accordance with the following requirements:
- (I) Following the initial startup of the control device, all activated carbon in the control device shall be replaced with fresh carbon on a regular basis in accordance with the requirements of part (27)(d)7 or part (27)(d)8 of this rule.
  - (II) All carbon that is hazardous waste and that is removed from the control

device shall be managed in accordance with the requirements of part (27)(d)14 of this rule, regardless of the average volatile organic concentration of the carbon.

- (iv) A remanufacturer or other person that stores or treats the hazardous secondary material using a control device other than a thermal vapor incinerator, flare, boiler, process heater, condenser, or carbon adsorption system to comply with subpart (i) of this part shall operate and maintain the control device in accordance with the requirements of part (27)(d)10 of this rule.
- (v) The remanufacturer or other person that stores or treats the hazardous secondary material shall demonstrate that a control device achieves the performance requirements of subpart (i) of this part as follows:
  - (I) A remanufacturer or other person that stores or treats the hazardous secondary material shall demonstrate using either a performance test as specified in item (III) of this subpart or a design analysis as specified in item (IV) of this subpart the performance of each control device except for the following:
    - I. A flare;
    - II. A boiler or process heater with a design heat input capacity of 44 megawatts or greater;
    - III. A boiler or process heater into which the vent stream is introduced with the primary fuel;
  - (II) A remanufacturer or other person that stores or treats the hazardous secondary material shall demonstrate the performance of each flare in accordance with the requirements specified in part (27)(d)5 of this rule.
  - (III) For a performance test conducted to meet the requirements of item (I) of this subpart, the remanufacturer or other person that stores or treats the hazardous secondary material shall use the test methods and procedures specified in subparts (27)(e)3(i) through (iv) of this rule.
  - (IV) For a design analysis conducted to meet the requirements of item (I) of this subpart, the design analysis shall meet the requirements specified in item (27)(f)2(iv)(III) of this rule.
  - (V) The remanufacturer or other person that stores or treats the hazardous secondary material shall demonstrate that a carbon adsorption system achieves the performance requirements of subpart (i) of this part based on the total quantity of organics vented to the atmosphere from all carbon adsorption system equipment that is used for organic adsorption, organic desorption or carbon regeneration, organic recovery, and carbon disposal.
- (vi) If the remanufacturer or other person that stores or treats the hazardous secondary material and the Commissioner do not agree on a demonstration of control device performance using a design analysis then the disagreement shall be resolved using the results of a performance test performed by the remanufacturer or other person that stores or treats the hazardous secondary material in accordance with the requirements of item (v)(III) of this part. The Commissioner may choose to have an authorized representative observe the performance test.
- (vii) The closed-vent system and control device shall be inspected and monitored by the remanufacture or other person that stores or treats the hazardous secondary

material in accordance with the procedures specified in subpart (27)(d)6(ii) and part (27)(d)12 of this rule. The readings from each monitoring device required by subpart (27)(d)6(ii) of this rule shall be inspected at least once each operating day to check control device operation. Any necessary corrective measures shall be immediately implemented to ensure the control device is operated in compliance with the requirements of this subparagraph.

(i) Inspection and monitoring requirements [40 CFR 261.1088]

1. The remanufacturer or other person that stores or treats the hazardous secondary material shall inspect and monitor air emission control equipment used to comply with this paragraph in accordance with the applicable requirements specified in subparagraphs (e) through (h) of this paragraph.
2. The remanufacturer or other person that stores or treats the hazardous secondary material shall develop and implement a written plan and schedule to perform the inspections and monitoring required by part 1 of this subparagraph. The remanufacturer or other person that stores or treats the hazardous secondary material shall keep the plan and schedule at the facility.

(j) Recordkeeping requirements. [40 CFR 261.1089]

1. Each remanufacturer or other person that stores or treats the hazardous secondary material subject to requirements of this paragraph shall record and maintain the information specified in parts 2 through 8 of this subparagraph, as applicable to the facility. Except for air emission control equipment design documentation, records required by this subparagraph shall be maintained at the facility for a minimum of 3 years. Air emission control equipment design documentation shall be maintained at the facility until the air emission control equipment is replaced or otherwise no longer in service.
2. The remanufacturer or other person that stores or treats the hazardous secondary material using a tank with air emission controls in accordance with the requirements of subparagraph (e) of this paragraph shall prepare and maintain records for the tank that include the following information:
  - (i) For each tank using air emission controls in accordance with the requirements of subparagraph (e) of this paragraph, the remanufacturer or other person that stores or treats the hazardous secondary material shall record:
    - (I) A tank identification number (or other unique identification description as selected by the remanufacturer or other person that stores or treats the hazardous secondary material).
    - (II) A record for each inspection required by subparagraph (e) of this paragraph that includes the following information:
      - I. Date inspection was conducted.
      - II. For each defect detected during the inspection: The location of the defect, a description of the defect, the date of detection, and corrective action taken to repair the defect. In the event that repair of the defect is delayed in accordance with the requirements of subparagraph (e) of this paragraph, the remanufacturer or other person that stores or treats the hazardous secondary material shall also record the reason for the delay and the date that completion of repair of the defect is expected.
  - (ii) In addition to the information required by subpart (i) of this part, the remanufacturer or other person that stores or treats the hazardous secondary

material shall record the following information, as applicable to the tank:

- (I) The remanufacturer or other person that stores or treats the hazardous secondary material using a fixed roof to comply with the Tank Level 1 control requirements specified in part (e)3 of this paragraph shall prepare and maintain records for each determination for the maximum organic vapor pressure of the hazardous secondary material in the tank performed in accordance with the requirements of part (e)3 of this paragraph. The records shall include the date and time the samples were collected, the analysis method used, and the analysis results.
  - (II) The remanufacturer or other person that stores or treats the hazardous secondary material using an internal floating roof to comply with the Tank Level 2 control requirements specified in part (e)5 of this paragraph shall prepare and maintain documentation describing the floating roof design.
  - (III) Remanufacturer or other persons that store or treat the hazardous secondary material using an external floating roof to comply with the Tank Level 2 control requirements specified in part (e)6 of this paragraph shall prepare and maintain the following records:
    - I. Documentation describing the floating roof design and the dimensions of the tank.
    - II. Records for each seal gap inspection required by subpart (e)6(iii) of this paragraph describing the results of the seal gap measurements. The records shall include the date that the measurements were performed, the raw data obtained for the measurements, and the calculations of the total gap surface area. In the event that the seal gap measurements do not conform to the specifications in subpart (e)6(i) of this paragraph, the records shall include a description of the repairs that were made, the date the repairs were made, and the date the tank was emptied, if necessary.
  - (IV) Each remanufacturer or other person that stores or treats the hazardous secondary material using an enclosure to comply with the Tank Level 2 control requirements specified in part (e)9 of this paragraph shall prepare and maintain the following records:
    - I. Records for the most recent set of calculations and measurements performed by the remanufacturer or other person that stores or treats the hazardous secondary material to verify that the enclosure meets the criteria of a permanent total enclosure as specified in "Procedure T--Criteria for and Verification of a Permanent or Temporary Total Enclosure" under 40 CFR 52.741, appendix B.
    - II. Records required for the closed-vent system and control device in accordance with the requirements of part 5 of this subparagraph.
3. Reserved
  4. The remanufacturer or other person that stores or treats the hazardous secondary material using containers with Container Level 3 air emission controls in accordance with the requirements of subparagraph (g) of this paragraph shall prepare and maintain records that include the following information:
    - (i) Records for the most recent set of calculations and measurements performed by

the remanufacturer or other person that stores or treats the hazardous secondary material to verify that the enclosure meets the criteria of a permanent total enclosure as specified in "Procedure T--Criteria for and Verification of a Permanent or Temporary Total Enclosure" under 40 CFR 52.741, appendix B.

- (ii) Records required for the closed-vent system and control device in accordance with the requirements of part 5 of this subparagraph.
5. The remanufacturer or other person that stores or treats the hazardous secondary material using a closed-vent system and control device in accordance with the requirements of subparagraph (h) of this paragraph shall prepare and maintain records that include the following information:
- (i) Documentation for the closed-vent system and control device that includes:
    - (I) Certification that is signed and dated by the remanufacturer or other person that stores or treats the hazardous secondary material stating that the control device is designed to operate at the performance level documented by a design analysis as specified in item (II) of this subpart or by performance tests as specified in item (III) of this subpart when the tank or container is or would be operating at capacity or the highest level reasonably expected to occur.
    - (II) If a design analysis is used, then design documentation as specified in subpart (27)(f)2(iv) of this rule. The documentation shall include information prepared by the remanufacturer or other person that stores or treats the hazardous secondary material or provided by the control device manufacturer or vendor that describes the control device design in accordance with item (27)(f)2(iv)(III) of this rule and certification by the remanufacturer or other person that stores or treats the hazardous secondary material that the control equipment meets the applicable specifications.
    - (III) If performance tests are used, then a performance test plan as specified in subpart (27)(f)2(iii) of this rule and all test results.
    - (IV) Information as required by subparts (27)(f)3(i) and (ii) of this rule, as applicable.
    - (V) A remanufacturer or other person that stores or treats the hazardous secondary material shall record, on a semiannual basis, the information specified in subitems I and II of this item for those planned routine maintenance operations that would require the control device not to meet the requirements of item (h)3(i)(I), (II) or (III) of this paragraph, as applicable.
      - I. A description of the planned routine maintenance that is anticipated to be performed for the control device during the next 6-month period. This description shall include the type of maintenance necessary, planned frequency of maintenance, and lengths of maintenance periods.
      - II. A description of the planned routine maintenance that was performed for the control device during the previous 6-month period. This description shall include the type of maintenance performed and the total number of hours during those 6 months that the control device did not meet the requirements of item (h)3(i)(I), (II) or (III) of this paragraph, as applicable, due to planned routine maintenance.



(VI) A remanufacturer or other person that stores or treats the hazardous secondary material shall record the information specified in subitems I through III of this item for those unexpected control device system malfunctions that would require the control device not to meet the requirements of item (h)3(i)(I), (II) or (III) of this paragraph, as applicable.

I. The occurrence and duration of each malfunction of the control device system.

II. The duration of each period during a malfunction when gases, vapors, or fumes are vented from the hazardous secondary material management unit through the closed-vent system to the control device while the control device is not properly functioning.

III. Actions taken during periods of malfunction to restore a malfunctioning control device to its normal or usual manner of operation.

(VII) Records of the management of carbon removed from a carbon adsorption system conducted in accordance with item (h)3(iii)(II) of this paragraph.

6. The remanufacturer or other person that stores or treats the hazardous secondary material using a tank or container exempted under the hazardous secondary material organic concentration conditions specified in subpart (c)3(i) of this paragraph or items (c)3(ii)(I) through (IV) of this paragraph, shall prepare and maintain at the facility records documenting the information used for each material determination (e.g., test results, measurements, calculations, and other documentation). If analysis results for material samples are used for the material determination, then the remanufacturer or other person that stores or treats the hazardous secondary material shall record the date, time, and location that each material sample is collected in accordance with applicable requirements of subparagraph (d) of this paragraph.

7. A remanufacturer or other person that stores or treats the hazardous secondary material designating a cover as “unsafe to inspect and monitor” pursuant to part (e)12 or (f)7 of this paragraph shall record and keep at facility the following information: the identification numbers for hazardous secondary material management units with covers that are designated as “unsafe to inspect and monitor,” the explanation for each cover stating why the cover is unsafe to inspect and monitor, and the plan and schedule for inspecting and monitoring each cover.

8. The remanufacturer or other person that stores or treats the hazardous secondary material that is subject to this paragraph and to the control device standards in 40 CFR part 60, subpart VV, or 40 CFR part 61, subpart V, may elect to demonstrate compliance with the applicable subparagraphs of this paragraph by documentation either pursuant to this paragraph, or pursuant to the provisions of 40 CFR part 60, subpart VV or 40 CFR part 61, subpart V, to the extent that the documentation required by 40 CFR parts 60 or 61 duplicates the documentation required by this subparagraph.

(k) Reserved [40 CFR 261.1090]

(30) Appendices to Rule 0400-12-01-.02 [Appendices to 40 CFR 261]

#### Appendix I -- Representative Sampling Methods

The methods and equipment used for sampling waste materials will vary with the form and consistency of the waste materials to be sampled. Samples collected using the sampling protocols listed below, for sampling waste with properties similar to the indicated materials, will be considered by the Department to be representative of the waste.

Extremely viscous liquid -- ASTM Standard D140-70 Crushed or powdered material -- ASTM Standard D346-75  
Soil or rock-like material -- ASTM Standard D420-69 Soil-like material -- ASTM Standard D1452-65

Fly Ash-like material -- ASTM Standard D2234-76 (ASTM Standards are available from ASTM, 1916 Race St., Philadelphia, PA 19103)

Containerized liquid waste -- "COLIWASA"

Liquid waste in pits, ponds, lagoons, and similar reservoirs -- "Pond Sampler"

SW-846 also contains additional information on the application of these protocols.

Appendix II -- (RESERVED)

Appendix III -- (RESERVED)

Appendix IV -- (RESERVED) - Radioactive Waste Test Methods

Appendix V -- (RESERVED) - Infectious Waste Treatment Specifications

Appendix VI -- (RESERVED) - Etiologic Agents

Appendix VII -- Basis for Listing Hazardous Waste

Hazardous Waste Code	Hazardous Constituents for Which Listed
F001	Tetrachloroethylene, methylene chloride trichloroethylene, 1,1,1-trichloroethane, carbon tetrachloride, chlorinated fluorocarbons.
F002	Tetrachloroethylene, methylene chloride, trichloroethylene, 1,1,1-trichloroethane, 1,1,2-trichloroethane, chlorobenzene, 1,1,2-trichloro-1,2,2-trifluoroethane, ortho-dichlorobenzene, trichlorofluoromethane.
F003	N.A.
F004	Cresols and cresylic acid, nitrobenzene.
F005	Toluene, methyl ethyl ketone, carbon disulfide, isobutanol, pyridine, 2-ethoxyethanol, benzene, 2-nitropropane.
F006	Cadmium, hexavalent chromium, nickel, cyanide (complexed).
F007	Cyanide (salts).
F008	Cyanide (salts).
F009	Cyanide (salts).
F010	Cyanide (salts).
F011	Cyanide (salts).
F012	Cyanide (complexed).
F019	Hexavalent chromium, cyanide (complexed).
F020	Tetra- and pentachlorodibenzo-p-dioxins; tetra and pentachlorodi-benzofurans; tri- and tetrachlorophenols and their chlorophenoxy derivative acids, esters, ethers, amine and other salts.
F021	Penta- and hexachlorodibenzo-p-dioxins; penta- and hexachlorodibenzofurans; pentachlorophenol and its derivatives.
F022	Tetra-, penta-, and hexachlorodibenzo-p-dioxins; tetra-, penta-, and hexachlorodibenzofurans.

F023	Tetra-, and pentachlorodibenzo-p-dioxins; tetra- and pentachlorodibenzofurans; tri- and tetrachlorophenols and their chlorophenoxy derivative acids, esters, ethers, amine and other salts.
F024	Chloromethane, dichloromethane, trichloromethane, carbon tetrachloride, chloroethylene, 1,1-dichloroethane, 1,2-dichloroethane, trans-1,2-dichloroethylene, 1,1-dichloroethylene, 1,1,1-trichloroethane, 1,1,2-trichloroethane, trichloroethylene, 1,1,1,2-tetra-chloroethane, 1,1,2,2-tetrachloroethane, tetrachloroethylene, pentachloroethane, hexachloroethane, allyl chloride (3-chloropropene), dichloropropane, dichloropropene, 2-chloro-1,3-butadiene, hexachloro-1,3-butadiene, hexachlorocyclopentadiene, hexachlorocyclohexane, benzene, chlorobenzene, dichlorobenzenes, 1,2,4-trichlorobenzene, tetrachlorobenzene, pentachlorobenzene, hexachlorobenzene, toluene, naphthalene.
F025	Chloromethane; Dichloromethane; Trichloromethane; Carbon tetrachloride; Chloroethylene; 1,1-Dichloroethane; 1,2-Dichloroethane; trans-1,2-Dichloroethylene; 1,1-Dichloroethylene; 1,1,1-Trichloroethane; 1,1,2-Trichloroethane; Trichloroethylene; 1,1,1,2-Tetrachloroethane; 1,1,2,2-Tetrachloroethane; Tetrachloroethylene; Pentachloroethane; Hexachloroethane; Allyl chloride (3-Chloropropene); Dichloropropane; Dichloropropene; 2-Chloro-1,3-butadiene; Hexachloro-1,3-butadiene; Hexachlorocyclopentadiene; Benzene; Chlorobenzene; Dichlorobenzene; 1,2,4-Trichlorobenzene; Tetrachlorobenzene; Pentachlorobenzene; Hexachlorobenzene; Toluene; Naphthalene.
F026	Tetra-, penta-, and hexachlorodibenzo-p-dioxins; tetra-, penta-, and hexachlorodibenzofurans.
F027	Tetra-, penta-, and hexachlorodibenzo-p-dioxins; tetra-, penta-, and hexachlorodibenzofurans; tri-, tetra-, and pentachlorophenols and their chlorophenoxy derivative acids, esters, ethers, amine and other salts.
F028	Tetra-, penta-, and hexachlorodibenzo-p-dioxins; tetra-, penta-, and hexachlorodibenzofurans; tri-, tetra-, and pentachlorophenols and their chlorophenoxy derivative acids, esters, ethers, amine and other salts.
F032	Benz(a)anthracene, benzo(a)pyrene, dibenz(a,h)-anthracene, indeno(1,2,3-cd)pyrene, pentachlorophenol, arsenic, chromium, tetra-, penta-, hexa-, heptachlorodibenzo-p-dioxins, tetra-, penta-, hexa-, heptachlorodibenzofurans.
F034	Benz(a)anthracene, benzo(k)fluoranthene, benzo(a)pyrene, dibenz(a,h)anthracene, indeno(1,2,3-cd)pyrene, naphthalene, arsenic, chromium.
F035	Arsenic, chromium, lead.
F037	Benzene, benzo(a)pyrene, chrysene, lead, chromium.
F038	Benzene, benzo(a)pyrene, chrysene, lead, chromium.
F039	All constituents for which treatment standards are specified for multi-source leachate (wastewaters and nonwastewaters) under 40 CFR 268.43, Table CCW.
K001	Pentachlorophenol, phenol, 2-chlorophenol, p-chloro-m-cresol, 2,4-dimethylphenyl, 2,4-dinitrophenol, trichlorophenols, tetrachlorophenols, 2,4-dinitrophenol, creosote, chrysene, naphthalene, fluoranthene, benzo(b)fluoranthene, benzo(a)pyrene, indeno(1,2,3-cd)pyrene, benz(a)anthracene, dibenz(a)anthracene, acenaphthalene.
K002	Hexavalent chromium, lead
K003	Hexavalent chromium, lead.
K004	Hexavalent chromium.
K005	Hexavalent chromium, lead.
K006	Hexavalent chromium.

K007	Cyanide (complexed), hexavalent chromium.
K008	Hexavalent chromium.
K009	Chloroform, formaldehyde, methylene chloride, methyl chloride, paraldehyde, formic acid.
K010	Chloroform, formaldehyde, methylene chloride, methyl chloride, paraldehyde, formic acid, chloroacetaldehyde.
K011	Acrylonitrile, acetonitrile, hydrocyanic acid.
K013	Hydrocyanic acid, acrylonitrile, acetonitrile.
K014	Acetonitrile, acrylamide.
K015	Benzyl chloride, chlorobenzene, toluene, benzotrichloride.
K016	Hexachlorobenzene, hexachlorobutadiene, carbon tetrachloride, hexachloroethane, perchloroethylene.
K017	Epichlorohydrin, chloroethers [bis(chloromethyl) ether and bis (2-chloroethyl) ethers], trichloropropane, dichloropropanols.
K018	1,2-dichloroethane, trichloroethylene, hexachlorobutadiene, hexachlorobenzene.
K019	Ethylene dichloride, 1,1,1-trichloroethane, 1,1,2-trichloroethane, tetrachloroethanes (1,1,2,2-tetrachloroethane and 1,1,1,2-tetrachloroethane), trichloroethylene, tetrachloroethylene, carbon tetrachloride, chloroform, vinyl chloride, vinylidene chloride.
K020	Ethylene dichloride, 1,1,1-trichloroethane, 1,1,2-trichloroethane, tetrachloroethanes (1,1,2,2-tetrachloroethane and 1,1,1,2-tetrachloroethane), trichloroethylene, tetrachloroethylene, carbon tetrachloride, chloroform, vinyl chloride, vinylidene chloride.
K021	Antimony, carbon tetrachloride, chloroform.
K022	Phenol, tars (polycyclic aromatic hydrocarbons).
K023	Phthalic anhydride, maleic anhydride.
K024	Phthalic anhydride, 1,4-naphthoquinone.
K025	Meta-dinitrobenzene, 2,4-dinitrotoluene.
K026	Paraldehyde, pyridines, 2-picoline.
K027	Toluene diisocyanate, toluene-2, 4-diamine.
K028	1,1,1-trichloroethane, vinyl chloride.
K029	1,2-dichloroethane, 1,1,1-trichloroethane, vinyl chloride, vinylidene chloride, chloroform.
K030	Hexachlorobenzene, hexachlorobutadiene, hexachloroethane, 1,1,1,2-tetrachloroethane, 1,1,2,2-tetrachloroethane, ethylene dichloride.
K031	Arsenic.
K032	Hexachlorocyclopentadiene.
K033	Hexachlorocyclopentadiene.
K034	Hexachlorocyclopentadiene.
K035	Creosote, chrysene, naphthalene, fluoranthene, benzo(b) fluoranthene, benzo(a)pyrene, indeno(1,2,3-cd) pyrene, benzo(a)anthracene, dibenzo(a)anthracene, acenaphthalene.

K036	Toluene, phosphorodithioic and phosphorothioic acid esters.
K037	Toluene, phosphorodithioic and phosphorothioic acid esters.
K038	Phorate, formaldehyde, phosphorodithioic and phosphorothioic acid esters.
K039	Phosphorodithioic and phosphorothioic acid esters.
K040	Phorate, formaldehyde, phosphorodithioic and phosphorothioic acid esters.
K041	Toxaphene.
K042	Hexachlorobenzene, ortho-dichlorobenzene.
K043	2,4-dichlorophenol, 2,6-dichlorophenol, 2,4,6-trichlorophenol.
K044	N.A.
K045	N.A.
K046	Lead.
K047	N.A.
K048	Hexavalent chromium, lead.
K049	Hexavalent chromium, lead.
K050	Hexavalent chromium.
K051	Hexavalent chromium, lead.
K052	Lead.
K060	Cyanide, naphthalene, phenolic compounds, arsenic.
K061	Hexavalent chromium, lead, cadmium.
K062	Hexavalent chromium, lead.
K069	Hexavalent chromium, lead, cadmium.
K071	Mercury.
K073	Chloroform, carbon tetrachloride, hexachloroethane, trichloroethane, tetrachloroethylene, dichloroethylene, 1,1,2,2-tetrachloroethane.
K083	Aniline, diphenylamine, nitrobenzene, phenylenediamine.
K084	Arsenic.
K085	Benzene, dichlorobenzenes, trichlorobenzenes, tetrachlorobenzenes, pentachlorobenzene, hexachlorobenzene, benzyl chloride.
K086	Lead, hexavalent chromium.
K087	Phenol, naphthalene.
K088	Cyanide (complexes).
K093	Phthalic anhydride, maleic anhydride.
K094	Phthalic anhydride.
K095	1,1,2-trichloroethane, 1,1,1,2-tetrachloroethane, 1,1,2,2-tetrachloroethane.
K096	1,2-dichloroethane, 1,1,1-trichloroethane, 1,1,2-trichloroethane.
K097	Chlordane, heptachlor.
K098	Toxaphene.
K099	2,4-dichlorophenol, 2,4,6-trichlorophenol.

K100	Hexavalent chromium, lead, cadmium.
K101	Arsenic.
K102	Arsenic.
K103	Aniline, nitrobenzene, phenylenediamine.
K104	Aniline, benzene, diphenylamine, nitrobenzene, phenylenediamine.
K105	Benzene, monochlorobenzene, dichlorobenzenes, 2,4,6-trichlorophenol.
K106	Mercury.
K107	1,1-Dimethylhydrazine (UDMH).
K108	1,1-Dimethylhydrazine (UDMH).
K109	1,1-Dimethylhydrazine (UDMH).
K110	1,1-Dimethylhydrazine (UDMH).
K111	2,4-Dinitrotoluene.
K112	2,4-Toluenediamine, o-toluidine, p-toluidine, aniline.
K113	2,4-Toluenediamine, o-toluidine, p-toluidine, aniline.
K114	2,4-Toluenediamine, o-toluidine, p-toluidine.
K115	2,4-Toluenediamine.
K116	Carbon tetrachloride, tetrachloroethylene, chloroform, phosgene.
K117	Ethylene dibromide.
K118	Ethylene dibromide.
K123	Ethylene thiourea.
K124	Ethylene thiourea.
K125	Ethylene thiourea.
K126	Ethylene thiourea.
K131	Dimethyl sulfate, methyl bromide.
K132	Methyl bromide.
K136	Ethylene dibromide.
K141	Benzene, benz(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, dibenz(a,h)anthracene, indeno(1,2,3-cd)pyrene.
K142	Benzene, benz(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, dibenz(a,h)anthracene, indeno(1,2,3-cd)pyrene.
K143	Benzene, benz(a)anthracene, benzo(b)fluoranthene, benzo(k)fluoranthene.
K144	Benzene, benz(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, dibenz(a,h)anthracene.
K145	Benzene, benz(a)anthracene, benzo(a)pyrene, dibenz(a,h)anthracene, naphthalene.
K147	Benzene, benz(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, dibenz(a,h)anthracene, indeno(1,2,3-cd)pyrene.
K148	Benz(a)anthracene, benzo(a)pyrene, benzo(b)fluoranthene, benzo(k)fluoranthene, dibenz(a,h)anthracene, indeno(1,2,3-cd)pyrene.

K149	Benzotrichloride, benzyl chloride, chloroform, chloromethane, chlorobenzene, 1,4-dichlorobenzene, hexachlorobenzene, pentachlorobenzene, 1,2,4,5-tetrachlorobenzene, toluene.
K150	Carbon tetrachloride, chloroform, chloromethane, 1,4-dichlorobenzene, hexachlorobenzene, pentachlorobenzene, 1,2,4,5-tetrachlorobenzene, 1,1,2,2-tetrachloroethane, tetrachloroethylene, 1,2,4-trichlorobenzene.
K151	Benzene, carbon tetrachloride, chloroform, hexachlorobenzene, pentachlorobenzene, toluene, 1,2,4,5-tetrachlorobenzene, tetrachloroethylene.
K156	Benomyl, carbaryl, carbendazim, carbofuran, carbosulfan, formaldehyde, methylene chloride, triethylamine.
K157	Carbon tetrachloride, formaldehyde, methyl chloride, methylene chloride, pyridine, triethylamine.
K158	Benomyl, carbendazim, carbofuran, carbosulfan, chloroform, methylene chloride.
K159	Benzene, butylate, eptc, molinate, pebulate, vernolate.
K161	Antimony, arsenic, metam-sodium, ziram.
K169	Benzene.
K170	Benzo(a)pyrene, dibenz(a,h)anthracene, benzo (a) anthracene, benzo (b)fluoranthene, benzo(k)fluoranthene, 3-methylcholanthrene, 7, 12-dimethylbenz(a)anthracene.
K171	Benzene, arsenic.
K172	Benzene, arsenic.
K174	1, 2, 3, 4, 6, 7, 8-Heptachlorodibenzo-p-dioxin (1, 2, 3, 4, 6, 7, 8-HpCDD), 1, 2, 3, 4, 6, 7, 8-Heptachlorodibenzofuran (1, 2, 3, 4, 6, 7, 8-HpCDF), 1, 2, 3, 4, 7, 8, 9-Heptachlorodibenzofuran (1, 2, 3, 6, 7, 8, 9-HpCDF), HxCDDs (All Hexachlorodibenzo-p-dioxins), HxCDFs (All Hexachlorodibenzofurans), PeCDDs (All Pentachlorodibenzo-p-dioxins), OCDD (1, 2, 3, 4, 6, 7, 8, 9-Octachlorodibenzo-p-dioxin, OCDF (1, 2, 3, 4, 6, 7, 8, 9-Octachlorodibenzofuran), PeCDFs (All Pentachlorodibenzofurans), TCDDs (All tetrachlorodi-benzo-p-dioxins), TCDFs (All tetrachlorodibenxofurans).
K175	Mercury
K176	Arsenic, Lead
K177	Antimony
K178	Thallium
K181	Aniline, o-anisidine, 4-chloroaniline, p-cresidine, 2, 4-dimethylaniline, 1, 2-phenylenediamine, 1, 3-phenylenediamine.

FOOTNOTE: N.A. -- Waste is hazardous because it fails the test for the characteristic of ignitability, corrosivity, or reactivity.

#### Appendix VIII -- Hazardous Constituents

Common Name	Chemical Abstracts Name	Chemical Abstracts No.	Hazardous Waste Code
A2213	Ethanimidothioic acid, 2- (dimethylamino) -N-hydroxy-2-oxo-, methyl ester	30558-43-1	U394
Acetonitrile	Same	75-05-8	U003
Acetophenone	Ethanone, 1-phenyl-	98-86-2	U004

2-Acetylaminefluorone	Acetamide, N-9H-fluoren-2-yl-	53-96-3	U005
Acetyl chloride	Same	75-36-5	U006
1-Acetyl-2-thiourea	Acetamide, N-(aminothioxomethyl)-	591-08-2	P002
Acrolein	2-Propenal	107-02-8	P003
Acrylamide	2-Propenamide	79-06-1	U007
Acrylonitrile	2-Propenenitrile	107-13-1	U009
Aflatoxins	Same	1402-68-2	
Aldicarb	Propanal, 2-methyl-2-(methylthio)-, O-[(methylamino)carbonyl]oxime	116-06-3	P070
Aldicarb sulfone	Propanal, 2-methyl-2-(methylsulfonyl) O-[(methylamino) carbonyl] oxime	1646-88-4	P203
Aldrin	1,4,5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro-, (1alpha,4alpha,4abeta,5alpha,8alpha, 8abeta)-	309-00-2	P004
Allyl alcohol	2-Propen-1-ol	107-18-6	P005
Allyl chloride	1-Propane, 3-chloro	107-05-1	
Aluminum phosphide	Same	20859-73-8	P006
4-Aminobiphenyl	[1,1'-Biphenyl]-4-amine	92-67-1	
5-(Aminomethyl)-3-isoxazolol	3(2H)-Isoxazolone, 5-(aminomethyl)-	2763-96-4	P007
4-Aminopyridine	4-Pyridinamine	504-24-5	P008
Amitrole	1H-1,2,4-Triazol-3-amine	61-82-5	U011
Ammonium vanadate	Vanadic acid, ammonium salt	7803-55-6	P119
Aniline	Benzenamine	62-53-3	U012
o-Anisidine (2-methoxyaniline)	Benzenamine, 2-Methoxy-	90-04-0	
Antimony	Benzenamine	7440-36-0	
Antimony compounds, N.O.S. <sup>1</sup>			
Aramite	Sulfurous acid, 2-chloroethyl 2-[4-(1,1-dimethylethyl)phenoxy]-1-methylethyl ester	140-57-8	
Arsenic	Same	7440-38-2	
Arsenic compounds, N.O.S. <sup>1</sup>			
Arsenic acid	Arsenic acid H <sub>3</sub> AsO <sub>4</sub>	7778-39-4	P010
Arsenic pentoxide	Arsenic oxide As <sub>2</sub> O <sub>5</sub>	1303-28-2	P011
Arsenic trioxide	Arsenic oxide As <sub>2</sub> O <sub>3</sub>	1327-53-3	P012
Auramine	Benzenamine, 4,4'-carbonimidoylbis[N,N-dimethyl	492-80-8	U014
Azaserine	L-Serine, diazoacetate (ester)	115-02-6	U015
Barban	Carbamic acid, (3-chlorophenyl) -, 4-chloro-2-butynyl ester	101-27-9	U280
Barium	Same	7440-39-3	



Barium compounds, N.O.S. <sup>1</sup>			
Barium cyanide	Same	542-62-1	P013
Bendiocarb	1,3-Benzodioxol-4-ol, 2,2-dimethyl-, methyl carbamate	22781-23-3	U278
Bendiocarb phenol	1,3-Benzodioxol-4-ol, 2,2-dimethyl-,	22961-82-6	U364
Benomyl	Carbamic acid, [1- [(butylamino) carbonyl]-1H-benzimidazol-2-yl] -, methyl ester	17804-35-2	U271
Benz[c]acridine	Same	225-51-4	U016
Benz[a]anthracene	Same	56-55-3	U018
Benzal chloride	Benzene, (dichloromethyl)-	98-87-3	U017
Benzene	Same	71-43-2	U019
Benzeneearsonic acid	Arsonic acid, phenyl-	98-05-5	
Benzidine	[1,1'-Biphenyl]-4,4'-diamine	92-87-5	U021
Benzo[b]fluoranthene	Benz[e]acephenanthrylene	205-99-2	
Benzo[j]fluoranthene	Same	205-82-3	
Benzo(k)fluoranthene	Same	207-08-9	
Benzo[a]pyrene	Same	50-32-8	U022
p-Benzoquinone	2,5-Cyclohexadiene-1,4-dione	106-51-4	U197
Benzotrichloride	Benzene, (trichloromethyl)-	98-07-7	U023
Benzyl chloride	Benzene, (chloromethyl)-	100-44-7	P028
Beryllium powder	Same	7440-41-7	P015
Beryllium compounds, N.O.S. <sup>1</sup>			
Bis(pentamethylene)-thiuram tetrasulfide	Piperidine, 1,1'-(tetrathiodicarbonothioyl)-bis-	120-54-7	
Bromoacetone	2-Propanone, 1-bromo-	598-31-2	P017
Bromoform	Methane, tribromo-	75-25-2	U225
4-Bromophenyl phenyl ether	Benzene, 1-bromo-4-phenoxy-	101-55-3	U030
Brucine	Strychnidin-10-one, 2,3-dimethoxy-	357-57-3	P018
Butylate	Carbamothioic acid, bis(2-methylpropyl)-, S-ethyl ester	2008-41-5	
Butyl benzyl phthalate	1,2-Benzenedicarboxylic acid, butyl phenylmethyl ester	85-68-7	
Cacodylic acid	Arsinic acid, dimethyl-	75-60-5	U136
Cadmium	Same	7440-43-9	
Cadmium compounds, N.O.S. <sup>1</sup>			
Calcium chromate	Chromic acid H <sub>2</sub> CrO <sub>4</sub> , calcium salt	13765-19-0	U032
Calcium cyanide	Calcium cyanide Ca(CN) <sub>2</sub>	592-01-8	P021
Carbaryl	1-Naphthalenol, methylcarbamate	63-25-2	U279
Carbendazim	Carbamic acid, 1H-benzimidazol-2-yl, methyl ester	10605-21-7	U372
Carbofuran	7-Benzofuranol, 2,3-dihydro-2,2-dimethyl-, methylcarbamate	1563-66-2	P127

Carbofuran phenol	7-Benzofuranol, 2,3-dihydro-2,2-dimethyl-	1563-38-8	U367
Carbon disulfide	Same	75-15-0	P022
Carbon oxyfluoride	Carbonic difluoride	353-50-4	U033
Carbon tetrachloride	Methane, tetrachloro-	56-23-5	U211
Carbosulfan	Carbamic acid, [(dibutylamino) thio] methyl-, 2,3-dihydro-2,2-dimethyl-7-benzofuranyl ester	55285-14-8	P189
Chloral	Acetaldehyde, trichloro-	75-87-6	U034
Chlorambucil	Benzenebutanoic acid, 4-[bis(2-chloroethyl)amino]-	305-03-3	U035
Chlordane	4,7-Methano-1H-indene, 1,2,4,5,6,7,8,8-octachloro-2,3,3a,4,7,7a-hexahydro-	57-74-9	U036
Chlordane (alpha and gamma isomers)			U036
Chlorinated benzenes, N.O.S. <sup>1</sup>			
Chlorinated ethane, N.O.S. <sup>1</sup>			
Chlorinated fluorocarbons, N.O.S. <sup>1</sup>			
Chlorinated naphthalene, N.O.S. <sup>1</sup>			
Chlorinated phenol, N.O.S. <sup>1</sup>			
Chlornaphazin	Naphthalenamine, N,N'-bis(2-chloroethyl)-	494-03-1	U026
Chloroacetaldehyde	Acetaldehyde, chloro-	107-20-0	P023
Chloroalkyl ethers, N.O.S. <sup>1</sup>			
p-Chloroaniline	Benzenamine, 4-chloro-	106-47-8	P024
Chlorobenzene	Benzene, chloro-	108-90-7	U037
Chlorobenzilate	Benzeneacetic acid, 4-chloro-alpha-(4-chlorophenyl)-alpha-hydroxy-, ethyl ester	510-15-6	U038
p-Chloro-m-cresol	Phenol, 4-chloro-3-methyl-	59-50-7	U039
2-Chloroethyl vinyl ether	Ethene, (2-chloroethoxy)-	110-75-8	U042
Chloroform	Methane, trichloro-	67-66-3	U044
Chloromethyl methyl ether	Methane, chloromethoxy-	107-30-2	U046
beta-Chloronaphthalene	Naphthalene, 2-chloro-	91-58-7	U047
o-Chlorophenol	Phenol, 2-chloro-	95-57-8	U048
1-(o-Chlorophenyl)thiourea	Thiourea, (2-chlorophenyl)-	5344-82-1	P026
Chloroprene	1,3-Butadiene, 2-chloro-	126-99-8	
3-Chloropropionitrile	Propanenitrile, 3-chloro-	542-76-7	P027
Chromium	Same	7440-47-3	
Chromium compounds, N.O.S. <sup>1</sup>			
Chrysene	Same	218-01-9	U050
Citrus red No. 2	2-Naphthalenol, 1-[(2,5-dimethoxyphenyl)azo]-	6358-53-8	

Coal tar creosote	Same	8007-45-2	
Copper cyanide	Copper cyanide CuCN	544-92-3	P029
Copper dimethyldithiocarbamate	Copper, bis(dimethylcarbamo-dithioato-S,S'),	137-29-1	
Creosote	Same		U051
p-Cresidine	2-Methoxy-5-methylbenzenamine	120-71-8	
Cresol (Cresylic acid)	Phenol, methyl-	1319-77-3	U052
Crotonaldehyde	2-Butenal	4170-30-3	U053
m-Cumenyl methylcarbamate	Phenol, 3-(methylethyl)-, methyl carbamate	64-00-6	P202
Cyanides (soluble salts and complexes) N.O.S. <sup>1</sup>			P030
Cyanogen	Ethanedinitrile	460-19-5	P031
Cyanogen bromide	Cyanogen bromide (CN)Br	506-68-3	U246
Cyanogen chloride	Cyanogen chloride (CN)Cl	506-77-4	P033
Cycasin	beta-D-Glucopyranoside, (methyl-ONN-azoxy)methyl	14901-08-7	
Cycolate	Carbamothioic acid, cyclohexylethyl-, S-ethyl ester	1134-23-2	
2-Cyclohexyl-4,6-dinitrophenol	Phenol, 2-cyclohexyl-4,6-dinitro-	131-89-5	P034
Cyclophosphamide	2H-1,3,2-Oxazaphosphorin-2-amine, N,N-bis(2-chloroethyl)tetrahydro-, 2-oxide	50-18-0	U058
2,4-D	Acetic acid, (2,4-dichlorophenoxy)-	94-75-7	U240
2,4-D, salts, esters			U240
Daunomycin	5,12-Naphthacenedione, 8-acetyl-10-[(3-amino-2,3,6-trideoxy-alpha-L-lyxo-hexopyranosyl)oxy]-7,8,9,10-tetrahydro-6,8,11-trihydroxy-1-methoxy-, (8S-cis)-	20830-81-3	U059
Dazomet	2H-1,3,5-thiadiazine-2-thione, tetrahydro-3,5-dimethyl	533-74-4	
DDD	Benzene, 1,1'-(2,2-dichloroethylidene)bis[4-chloro-	72-54-8	U060
DDE	Benzene, 1,1'-(dichloroethenylidene)bis[4-chloro-	72-55-9	
DDT	Benzene, 1,1'-(2,2,2-trichloroethylidene)bis[4-chloro-	50-29-3	U061
Diallate	Carbamothioic acid, bis(1-methylethyl)-, S-(2,3-dichloro-2-propenyl) ester	2303-16-4	U062
Dibenz[a,h]acridine	Same	226-36-8	
Dibenz[a,j]acridine	Same	224-42-0	
Dibenz[a,h]anthracene	Same	53-70-3	U063
7H-Dibenzo[c,g]carbazole	Same	194-59-2	
Dibenzo[a,e]pyrene	Naphtho[1,2,3,4-def]chrysene	192-65-4	
Dibenzo[a,h]pyrene	Dibenzo[b,def]chrysene	189-64-0	
Dibenzo[a,i]pyrene	Benzo[rs]t]pentaphene	189-55-9	U064
1,2-Dibromo-3-chloropropane	Propane, 1,2-dibromo-3-chloro-	96-12-8	U066
Dibutyl phthalate	1,2-Benzenedicarboxylic acid, dibutyl ester	84-74-2	U069

o-Dichlorobenzene	Benzene, 1,2-dichloro-	95-50-1	U070
m-Dichlorobenzene	Benzene, 1,3-dichloro-	541-73-1	U071
p-Dichlorobenzene	Benzene, 1,4-dichloro-	106-46-7	U072
Dichlorobenzene, N.O.S. <sup>1</sup>	Benzene, dichloro-	25321-22-6	
3,3'-Dichlorobenzidine	[1,1'-Biphenyl]-4,4'-diamine, 3,3'-dichloro-	91-94-1	U073
1,4-Dichloro-2-butene	2-Butene, 1,4-dichloro-	764-41-0	U074
Dichlorodifluoromethane	Methane, dichlorodifluoro-	75-71-8	U075
Dichloroethylene, N.O.S. <sup>1</sup>	Dichloroethylene	25323-30-2	
1,1-Dichloroethylene	Ethene, 1,1-dichloro-	75-35-4	U078
1,2-Dichloroethylene	Ethene, 1,2-dichloro-, (E)-	156-60-5	U079
Dichloroethyl ether	Ethane, 1,1'-oxybis[2-chloro-	111-44-4	U025
Dichloroisopropyl ether	Propane, 2,2'-oxybis[2-chloro-	108-60-1	U027
Dichloromethoxy ethane	Ethane, 1,1'-[methylenebis(oxy)]bis[2-chloro-	111-91-1	U024
Dichloromethyl ether	Methane, oxybis[chloro-	542-88-1	P016
2,4-Dichlorophenol	Phenol, 2,4-dichloro-	120-83-2	U081
2,6-Dichlorophenol	Phenol, 2,6-dichloro-	87-65-0	U082
Dichlorophenylarsine	Arsonous dichloride, phenyl-	696-28-6	P036
Dichloropropane, N.O.S. <sup>1</sup>	Propane, dichloro-	26638-19-7	
Dichloropropanol, N.O.S. <sup>1</sup>	Propanol, dichloro-	26545-73-3	
Dichloropropene, N.O.S. <sup>1</sup>	1-Propene, dichloro-	26952-23-8	
1,3-Dichloropropene	1-Propene, 1,3-dichloro-	542-75-6	U084
Dieldrin	2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-, (1aalpha,2beta,2aalpha,3beta,6beta,6aalpha,7beta,7aalpha)-	60-57-1	P037
1,2:3,4-Diepoxybutane	2,2'-Bioxirane	1464-53-5	U085
Diethylarsine	Arsine, diethyl-	692-42-2	P038
Diethylene glycol, dicarbamate	Ethanol, 2,2'-oxybis-, dicarbamate	5952-26-1	U395
1,4-Diethyleneoxide	1,4-Dioxane	123-91-1	U108
Diethylhexyl phthalate	1,2-Benzenedicarboxylic acid, bis(2-ethylhexyl) ester	117-81-7	U028
N,N'-Diethylhydrazine	Hydrazine, 1,2-diethyl-	1615-80-1	U086
O,O-Diethyl dithiophosphate S-methyl	Phosphorodithioic acid, O,O-diethyl S-methyl ester	3288-58-2	U087
Diethyl-p-nitrophenyl phosphate	Phosphoric acid, diethyl 4-nitrophenyl ester	311-45-5	P041
Diethyl phthalate	1,2-Benzenedicarboxylic acid, diethyl ester	84-66-2	U088
O,O-Diethyl phosphorothioate O-pyrazinyl	Phosphorothioic acid, O,O-diethyl O-pyrazinyl ester	297-97-2	P040
Diethylstilbesterol	Phenol, 4,4'-(1,2-diethyl-1,2-ethenediyl)bis-, (E)-	56-53-1	U089

Dihydrosafrole	1,3-Benzodioxole, 5-propyl-	94-58-6	U090
Diisopropylfluorophosphate (DFP)	Phosphorofluoridic acid, bis(1-methylethyl) ester	55-91-4	P043
Dimethoate	Phosphorodithioic acid, O,O-dimethyl S-[2-(methylamino)-2-oxoethyl] ester	60-51-5	P044
3,3'-Dimethoxybenzidine	[1,1'-Biphenyl]-4,4'-diamine, 3,3'-dimethoxy-	119-90-4	U091
p-Dimethylaminoazobenzene	Benzenamine, N,N-dimethyl-4-(phenylazo)-	60-11-7	U093
2, 4-Dimethylaniline (2, 4-xylylidine)	Benzenamine, 2, 4-dimethyl-	95-68-1	
7,12-Dimethylbenz[a]anthracene	Benz[a]anthracene, 7,12-dimethyl-	57-97-6	U094
3,3'-Dimethylbenzidine	[1,1'-Biphenyl]-4,4'-diamine, 3,3'-dimethyl-	119-93-7	U095
Dimethylcarbamoyl chloride	Carbamic chloride, dimethyl-	79-44-7	U097
1,1-Dimethylhydrazine	Hydrazine, 1,1-dimethyl-	57-14-7	U098
1,2-Dimethylhydrazine	Hydrazine, 1,2-dimethyl-	540-73-8	U099
alpha,alpha-Dimethylphenethylamine	Benzeneethanamine, alpha,alpha-dimethyl-	122-09-8	P046
2,4-Dimethylphenol	Phenol, 2,4-dimethyl-	105-67-9	U101
Dimethyl phthalate	1,2-Benzenedicarboxylic acid, dimethyl ester	131-11-3	U102
Dimethyl sulfate	Sulfuric acid, dimethyl ester	77-78-1	U103
Dimetilan	Carbamic acid, dimethyl-, 1- [(dimethylamino) carbonyl]-5-methyl-1H-pyrazol-3-yl ester	644-64-4	P191
Dinitrobenzene, N.O.S. <sup>1</sup>	Benzene, dinitro-	25154-54-5	
4,6-Dinitro-o-cresol	Phenol, 2-methyl-4,6-dinitro-	534-52-1	P047
4,6-Dinitro-o-cresol salts			P047
2,4-Dinitrophenol	Phenol, 2,4-dinitro-	51-28-5	P048
2,4-Dinitrotoluene	Benzene, 1-methyl-2,4-dinitro-	121-14-2	U105
2,6-Dinitrotoluene	Benzene, 2-methyl-1,3-dinitro-	606-20-2	U106
Dinoseb	Phenol, 2-(1-methylpropyl)-4,6-dinitro-	88-85-7	P020
Di-n-octylphthalate	1,2-Benzenedicarboxylic acid, dioctyl ester	117-84-0	U017
Diphenylamine	Benzenamine, N-phenyl-	122-39-4	
1,2-Diphenylhydrazine	Hydrazine, 1,2-diphenyl-	122-66-7	U109
Di-n-propylnitrosamine	1-Propanamine, N-nitroso-N-propyl-	621-64-7	U111
Disulfiram	Thioperoxydicarbonic diamide, tetraethyl	97-77-8	
Disulfoton	Phosphorodithioic acid, O,O-diethyl S-[2-(ethylthio)ethyl] ester	298-04-4	P039
Dithiobiuret	Thioimidodicarbonic diamide [(H <sub>2</sub> N)C(S)] <sub>2</sub> NH	541-53-7	P049
Endosulfan	6,9-Methano-2,4,3-benzodioxathiepin, 6,7,8,9,10,10-hexachloro-1,5,5a,6,9,9a-hexahydro-, 3-oxide	115-29-7	P050
Endothall	7-Oxabicyclo[2.2.1]heptane-2,3-dicarboxylic acid	145-73-3	P088

Endrin	2,7:3,6-Dimethanonaphth[2,3-b]oxirene, 3,4,5,6,9,9-hexachloro-1a,2,2a,3,6,6a,7,7a-octahydro-,(1aalpha,2beta,2abeta,3alpha,6alpha,6abeta,7beta,7aalpha)-	72-20-8	P051
Endrin metabolites			P051
Epichlorohydrin	Oxirane, (chloromethyl)-	106-89-8	U041
Epinephrine	1,2-Benzenediol, 4-[1-hydroxy-2-(methylamino)ethyl]-, (R)-	51-43-4	P042
EPTC	Carbamothioic acid, dipropyl-, S-ethyl ester	759-94-4	
Ethyl carbamate (urethane)	Carbamic acid, ethyl ester	51-79-6	U238
Ethyl cyanide	Propanenitrile	107-12-0	P101
Ethylenebisdithiocarbamic acid	Carbamodithioic acid, 1,2-ethanediybis-	111-54-6	U114
Ethylenebisdithiocarbamic acid, salts and esters			U114
Ethylene dibromide	Ethane, 1,2-dibromo-	106-93-4	U067
Ethylene dichloride	Ethane, 1,2-dichloro-	107-06-2	U077
Ethylene glycol monoethyl ether	Ethanol, 2-ethoxy-	110-80-5	U359
Ethyleneimine	Aziridine	151-56-4	P054
Ethylene oxide	Oxirane	75-21-8	U115
Ethylenethiourea	2-Imidazolidinethione	96-45-7	U116
Ethylidene dichloride	Ethane, 1,1-dichloro-	75-34-3	U076
Ethyl methacrylate	2-Propenoic acid, 2-methyl-, ethyl ester	97-63-2	U118
Ethyl methanesulfonate	Methanesulfonic acid, ethyl ester	62-50-0	U119
Ethyl Ziram	Zinc, bis(diethylcarbamodithioato-S,S')-	14324-55-1	
Famphur	Phosphorothioic acid, O-[4-[(dimethylamino)sulfonyl]phenyl] O,O-dimethyl ester	52-85-7	P097
Ferbam	Iron, tris(dimethylcarbamodithioato-S,S')-	14484-64-1	
Fluoranthene	Same	206-44-0	U120
Fluorine	Same	7782-41-4	P056
Fluoroacetamide	Acetamide, 2-fluoro-	640-19-7	P057
Fluoroacetic acid, sodium salt	Acetic acid, fluoro-, sodium salt	62-74-8	P058
Formaldehyde	Same	50-00-0	U122
Formetanate hydrochloride	Methanimidamide, N,N-dimethyl-N'-[3-[(methylamino)carbonyl]oxy]phenyl]-, monohydrochloride	23422-53-9	P198
Formic acid	Same	64-18-6	U123
Formparanate	Methanimidamide, N,N-dimethyl-N'-[2-methyl-4-[(methylamino)carbonyl]oxy]phenyl]-	17702-57-7	P197
Glycidylaldehyde	Oxiranecarboxyaldehyde	765-34-4	U126
Halomethanes, N.O.S. <sup>1</sup>			

Heptachlor	4,7-Methano-1H-indene, 1,4,5,6,7,8,8-heptachloro-3a,4,7,7a-tetrahydro-	76-44-8	P059
Heptachlor epoxide	2,5-Methano-2H-indeno[1,2-b]oxirene, 2,3,4,5,6,7,7-heptachloro-1a,1b,5,5a,6,6a-hexahydro-, (1aalpha,1bbeta,2alpha,5alpha, 5abeta,6beta,6aalpha)-	1024-57-3	
Heptachlor epoxide (alpha, beta, and gamma isomers)			
Heptachlorodibenzofurans.			
Heptachlorodibenzo-p-dioxins			
Hexachlorobenzene	Benzene, hexachloro-	118-74-1	U127
Hexachlorobutadiene	1,3-Butadiene, 1,1,2,3,4,4-hexachloro-	87-68-3	U128
Hexachlorocyclopentadiene	1,3-Cyclopentadiene, 1,2,3,4,5,5-hexachloro-	77-47-4	U130
Hexachlorodibenzo-p-dioxins			
Hexachlorodibenzofurans			
Hexachloroethane	Ethane, hexachloro-	67-72-1	U131
Hexachlorophene	Phenol, 2,2'-methylenebis[3,4,6-trichloro-	70-30-4	U132
Hexachloropropene	1-Propene, 1,1,2,3,3,3-hexachloro-	1888-71-7	U243
Hexaethyl tetraphosphate	Tetraphosphoric acid, hexaethyl ester	757-58-4	P062
Hydrazine	Same	302-01-2	U133
Hydrogen cyanide	Hydrocyanic acid	74-90-8	P063
Hydrogen fluoride	Hydrofluoric acid	7664-39-3	U134
Hydrogen sulfide	Hydrogen sulfide H <sub>2</sub> S	7783-06-4	U135
Indeno[1,2,3-cd]pyrene	Same	193-39-5	U137
3-Iodo-2-propynyl butylcarbamate	n- Carbamic acid, butyl-, 3-iodo-2-propynyl ester	55406-53-6	
Isobutyl alcohol	1-Propanol, 2-methyl-	78-83-1	U140
Isodrin	1,4,5,8-Dimethanonaphthalene, 1,2,3,4,10,10-hexachloro-1,4,4a,5,8,8a-hexahydro-, (1alpha,4alpha,4abeta,5beta,8beta,-8abeta) -	465-73-6	P060
Isolan	Carbamic acid, dimethyl-, 3-methyl-1-(1-methylethyl)-1H-pyrazol-5-yl ester	119-38-0	P192
Isosafrole	1,3-Benzodioxole, 5-(1-propenyl)-	120-58-1	U141
Kepon	1,3,4-Metheno-2H-cyclobuta[cd]pentalen-2-one, 1,1a,3,3a,4,5,5a,5b,6-decachlorooctahydro-	143-50-0	U142
Lasiocarpine	2-Butenoic acid, 2-methyl-, 7-[[2,3-dihydroxy-2-(1-methoxyethyl)-3-methyl-1-oxobutoxy]methyl]-2,3,5,7a-tetrahydro-1H-pyrrolizin-1-yl ester, [1S-[1alpha(Z),7(2S*,3R*),7aalpha]]-	303-34-4	U143
Lead	Same	7439-92-1	
Lead compounds, N.O.S. <sup>1</sup>			
Lead acetate	Acetic acid, lead(2+) salt	301-04-2	U144

Lead phosphate	Phosphoric acid, lead(2+) salt (2:3)	7446-27-7	U145
Lead subacetate	Lead, bis(acetato-O)tetrahydroxytri-	1335-32-6	U146
Lindane	Cyclohexane, 1,2,3,4,5,6-hexachloro-, (1alpha,2alpha,3beta,4alpha,5alpha,6beta)-	58-89-9	U129
Maleic anhydride	2,5-Furandione	108-31-6	U147
Maleic hydrazide	3,6-Pyridazinedione, 1,2-dihydro-	123-33-1	U148
Malononitrile	Propanedinitrile	109-77-3	U149
Manganese dimethyldithiocarbamate	Manganese, bis(dimethylcarbomodithioato-S,S')-,	15339-36-3	P196
Melphalan	L-Phenylalanine, 4-[bis(2-chloroethyl)amino]-	148-82-3	U150
Mercury	Same	7439-97-6	U151
Mercury compounds, N.O.S. <sup>1</sup>			
Mercury fulminate	Fulminic acid, mercury(2+) salt	628-86-4	P065
Metam Sodium	Carbamodithioic acid, methyl-, monosodium salt	137-42-8	
Methacrylonitrile	2-Propenenitrile, 2-methyl-	126-98-7	U152
Methapyrilene	1,2-Ethanediamine, N,N-dimethyl-N'-2-pyridinyl-N'-(2-thienylmethyl)-	91-80-5	U155
Methiocarb	Phenol, (3,5-dimethyl-4-(methylthio)-, methylcarbamate	2032-65-7	P199
Methomyl	Ethanimidothioic acid, N-[(methylamino)carbonyloxy]-, methyl ester	16752-77-5	P066
Methoxychlor	Benzene, 1,1'-(2,2,2-trichloroethylidene)bis[4-methoxy-	72-43-5	U247
Methyl bromide	Methane, bromo-	74-83-9	U029
Methyl chloride	Methane, chloro-	74-87-3	U045
Methyl chlorocarbonate	Carbonochloridic acid, methyl ester	79-22-1	U156
Methyl chloroform	Ethane, 1,1,1-trichloro-	71-55-6	U226
3-Methylcholanthrene	Benz[j]aceanthrylene, 1,2-dihydro-3-methyl-	56-49-5	U157
4,4'-Methylenebis chloroaniline) (2-	Benzenamine, 4,4'-methylenebis[2-chloro-	101-14-4	U158
Methylene bromide	Methane, dibromo-	74-95-3	U068
Methylene chloride	Methane, dichloro-	75-09-2	U080
Methyl ethyl ketone (MEK)	2-Butanone	78-93-3	U159
Methyl ethyl ketone peroxide	2-Butanone, peroxide	1338-23-4	U160
Methyl hydrazine	Hydrazine, methyl-	60-34-4	P068
Methyl iodide	Methane, iodo-	74-88-4	U138
Methyl isocyanate	Methane, isocyanato-	624-83-9	P064
2-Methylacetonitrile	Propanenitrile, 2-hydroxy-2-methyl-	75-86-5	P069
Methyl methacrylate	2-Propenoic acid, 2-methyl-, methyl ester	80-62-6	U162
Methyl methanesulfonate	Methanesulfonic acid, methyl ester	66-27-3	



Methyl parathion	Phosphorothioic acid, O,O-dimethyl O-(4-nitrophenyl) ester	298-00-0	P071
Methylthiouracil	4(1H)-Pyrimidinone, 2,3-dihydro-6-methyl-2-thioxo-	56-04-2	U164
Metolcarb	Carbamic acid, methyl-, 3-methylphenyl ester	1129-41-5	P190
Mexacarbate	Phenol, 4-(dimethylamino)-3,5-dimethyl-, methylcarbamate (ester)	315-18-4	P128
Mitomycin C	Azirino[2',3':3,4]pyrrolo[1,2-a]indole-4,7-dione, 6-amino-8-[[[(aminocarbonyloxy)methyl]-1,1a,2,8,8a,8b-hexahydro-8a-methoxy-5-methyl-, [1aS-(1aalpha,8beta,8aalpha,8balpha)]-	50-07-7	U010
MNNG	Guanidine, N-methyl-N'-nitro-N-nitroso-	70-25-7	U163
Molinate	1H-Azepine-1-carbothioic acid, hexahydro-, S-ethyl ester	2212-67-1	
Mustard gas	Ethane, 1,1'-thiobis[2-chloro-	505-60-2	
Naphthalene	Same	91-20-3	U165
1,4-Naphthoquinone	1,4-Naphthalenedione	130-15-4	U166
alpha-Naphthylamine	1-Naphthalenamine	134-32-7	U167
beta-Naphthylamine	2-Naphthalenamine	91-59-8	U168
alpha-Naphthylthiourea	Thiourea, 1-naphthalenyl-	86-88-4	P072
Nickel	Same	7440-02-0	
Nickel compounds, N.O.S. <sup>1</sup>			
Nickel carbonyl	Nickel carbonyl Ni(CO) <sub>4</sub> , (T-4)-	13463-39-3	P073
Nickel cyanide	Nickel cyanide Ni(CN) <sub>2</sub>	557-19-7	P074
Nicotine	Pyridine, 3-(1-methyl-2-pyrrolidinyl)-, (S)-	54-11-5	P075
Nicotine salts			P075
Nitric oxide	Nitrogen oxide NO	10102-43-9	P076
p-Nitroaniline	Benzenamine, 4-nitro-	100-01-6	P077
Nitrobenzene	Benzene, nitro-	98-95-3	U169
Nitrogen dioxide	Nitrogen oxide NO <sub>2</sub>	10102-44-0	P078
Nitrogen mustard	Ethanamine, 2-chloro-N-(2-chloroethyl)-N-methyl-	51-75-2	
Nitrogen mustard, hydrochloride salt			
Nitrogen mustard N-oxide	Ethanamine, 2-chloro-N-(2-chloroethyl)-N-methyl-, N-oxide	126-85-2	
Nitrogen mustard, N-oxide, hydrochloride salt			
Nitroglycerin	1,2,3-Propanetriol, trinitrate	55-63-0	P081
p-Nitrophenol	Phenol, 4-nitro-	100-02-7	U170
2-Nitropropane	Propane, 2-nitro-	79-46-9	U171
Nitrosamines, N.O.S. <sup>1</sup>		35576-91-1	
N-Nitrosodi-n-butylamine	1-Butanamine, N-butyl-N-nitroso-	924-16-3	U172

N-Nitrosodiethanolamine	Ethanol, 2,2'-(nitrosoimino)bis-	1116-54-7	U173
N-Nitrosodiethylamine	Ethanamine, N-ethyl-N-nitroso-	55-18-5	U174
N-Nitrosodimethylamine	Methanamine, N-methyl-N-nitroso-	62-75-9	P082
N-Nitroso-N-ethylurea	Urea, N-ethyl-N-nitroso-	759-73-9	U176
N-Nitrosomethylethylamine	Ethanamine, N-methyl-N-nitroso-	10595-95-6	
N-Nitroso-N-methylurea	Urea, N-methyl-N-nitroso-	684-93-5	U177
N-Nitroso-N-methylurethane	Carbamic acid, methylnitroso-, ethyl ester	615-53-2	U178
N-Nitrosomethylvinylamine	Vinylamine, N-methyl-N-nitroso-	4549-40-0	P084
N-Nitrosomorpholine	Morpholine, 4-nitroso-	59-89-2	
N-Nitrosornicotine	Pyridine, 3-(1-nitroso-2-pyrrolidinyl)-, (S)-	16543-55-8	
N-Nitrosopiperidine	Piperidine, 1-nitroso-	100-75-4	U179
N-Nitrosopyrrolidine	Pyrrolidine, 1-nitroso-	930-55-2	U180
N-Nitrososarcosine	Glycine, N-methyl-N-nitroso-	13256-22-9	
5-Nitro-o-toluidine	Benzenamine, 2-methyl-5-nitro-	99-55-8	U181
Octachlorodibenzo-p-dioxin (OCDD)	1, 2, 3, 4, 6, 7, 8, 9-Octachlorodibenzo-p-dioxin	3268-87-9	
Octachlorodibenzofuran (OCDF)	1, 2, 3, 4, 6, 7, 8, 9-Octachlorodibenzofuran	39001-02-0	
Octamethylpyrophosphoramide	Diphosphoramidate, octamethyl-	152-16-9	P085
Osmium tetroxide	Osmium oxide OsO <sub>4</sub> , (T-4)-	20816-12-0	P087
Oxamyl	Ethanimidothioic acid, 2-(dimethylamino)-N-[[[(methylamino)carbonyl]-oxy]-2-oxo-, methyl ester	23135-22-0	P194
Paraldehyde	1,3,5-Trioxane, 2,4,6-trimethyl-	123-63-7	U182
Parathion	Phosphorothioic acid, O,O-diethyl O-(4-nitrophenyl) ester	56-38-2	P089
Pebulate	Carbamothioic acid, butylethyl-, S-propyl ester	1114-71-2	
Pentachlorobenzene	Benzene, pentachloro-	608-93-5	U183
Pentachlorodibenzo-p-dioxins			
Pentachlorodibenzofurans			
Pentachloroethane	Ethane, pentachloro-	76-01-7	U184
Pentachloronitrobenzene (PCNB)	Benzene, pentachloronitro-	82-68-8	U185
Pentachlorophenol	Phenol, pentachloro-	87-86-5	See F027
Phenacetin	Acetamide, N-(4-ethoxyphenyl)-	62-44-2	U187
Phenol	Same	108-95-2	U188
Phenylenediamine	Benzenediamine	25265-76-3	
1, 2-Phenylenediamine	1, 2-Benzenediamine	95-54-5	
1, 3-Phenylenediamine	1, 3-Benzenediamine	108-45-2	

Phenylmercury acetate	Mercury, (acetato-O)phenyl-	62-38-4	P092
Phenylthiourea	Thiourea, phenyl-	103-85-5	P093
Phosgene	Carbonic dichloride	75-44-5	P095
Phosphine	Same	7803-51-2	P096
Phorate	Phosphorodithioic acid, O,O-diethyl S-[(ethylthio)methyl] ester	298-02-2	P094
Phthalic acid esters, N.O.S. <sup>1</sup>			
Phthalic anhydride	1,3-Isobenzofurandione	85-44-9	U190
Physostigmine	Pyrrolo[2,3-b]indol-5-01, 1,2,3,3a,8,8a-hexahydro-1,3a,8-trimethyl-, methylcarbamate (ester), (3aS-cis)-	57-47-6	P204
Physostigmine salicylate	Benzoic acid, 2-hydroxy-, compd. with (3aS-cis) -1,2,3,3a,8,8a-hexahydro-1,3a,8-trimethylpyrrolo [2,3-b]indol-5-yl methylcarbamate ester (1:1)	57-64-7	P188
2-Picoline	Pyridine, 2-methyl-	109-06-8	U191
Polychlorinated biphenyls, N.O.S. <sup>1</sup>			
Potassium cyanide	Potassium cyanide K(CN)	151-50-8	P098
Potassium dimethyldithiocarbamate	Carbamodithioic acid, dimethyl, potassium salt	128-03-0	
Potassium n-hydroxymethyl-n-methyl-dithiocarbamate	Carbamodithioic acid, (hydroxymethyl)methyl-, monopotassium salt	51026-28-9	
Potassium n-methyldithiocarbamate	Carbamodithioic acid, methyl-monopotassium salt	137-41-7	
Potassium pentachlorophenate	Pentachlorophenol, potassium salt	7778736	None
Potassium silver cyanide	Argentate(1-), bis(cyano-C)-, potassium	506-61-6	P099
Promecarb	Phenol, 3-methyl-5-(1-methylethyl)-, methyl carbamate	2631-37-0	P201
Pronamide	Benzamide, 3,5-dichloro-N-(1,1-dimethyl-2-propynyl)-	23950-58-5	U192
1,3-Propane sultone	1,2-Oxathiolane, 2,2-dioxide	1120-71-4	U193
Propham	Carbamic acid, phenyl-, 1-methylethyl ester	122-42-9	U373
Propoxur	Phenol, 2-(1-methylethoxy)-, methylcarbamate	114-26-1	U411
n-Propylamine	1-Propanamine	107-10-8	U194
Propargyl alcohol	2-Propyn-1-ol	107-19-7	P102
Propylene dichloride	Propane, 1,2-dichloro-	78-87-5	U083
1,2-Propylenimine	Aziridine, 2-methyl-	75-55-8	P067
Propylthiouracil	4(1H)-Pyrimidinone, 2,3-dihydro-6-propyl-2-thio-	51-52-5	
Prosulfocarb	Carbamothioic acid, dipropyl-, S-(phenylmethyl) ester	52888-80-9	U387
Pyridine	Same	110-86-1	U196

Reserpine	Yohimban-16-carboxylic acid, 11,17-dimethoxy-18- [(3,4,5-trimethoxybenzoyl)oxy]-smethyl ester, (3beta,16beta,17alpha,18beta,20alpha)-	50-55-5	U200
Resorcinol	1,3-Benzenediol	108-46-3	U201
Safrole	1,3-Benzodioxole, 5-(2-propenyl)-	94-59-7	U203
Selenium	Same	7782-49-2	
Selenium compounds, N.O.S. <sup>1</sup>			
Selenium dioxide	Selenious acid	7783-00-8	U204
Selenium sulfide	Selenium sulfide SeS <sub>2</sub>	7488-56-4	U205
Selenium, tetrakis(dimethyl- dithiocarbamate)	Carbamodithioic acid, dimethyl-, tetraanhydrosulfide with orthothioselenious acid	144-34-3	
Selenourea	Same	630-10-4	P103
Silver	Same	7440-22-4	
Silver compounds, N.O.S. <sup>1</sup>			
Silver cyanide	Silver cyanide Ag(CN)	506-64-9	P104
Silvex (2,4,5-TP)	Propanoic acid, 2-(2,4,5-trichlorophenoxy)-	93-72-1	See F027
Sodium cyanide	Sodium cyanide Na(CN)	143-33-9	P106
Sodium dibutyldithiocarbamate	Carbamodithioic acid, dibutyl, sodium salt	136-30-1	
Sodium diethyldithiocarbamate	Carbamodithioic acid, diethyl-, sodium salt	148-18-5	
Sodium dimethyldithiocarbamate	Carbamodithioic acid, dimethyl-, sodium salt	128-04-1	
Sodium pentachlorophenate	Pentachlorophenol, sodium salt	131522	None
Streptozotocin	D-Glucose, 2-deoxy-2- [[[(methylnitrosoamino)carbonyl]amino]-	18883-66-4	U206
Strychnine	Strychnidin-10-one	57-24-9	P108
Strychnine salts			P108
Sulfallate	Carbamodithioic acid, diethyl-, 2-chloro-2-propenyl ester	95-06-7	
TCDD	Dibenzo[b,e][1,4]dioxin, 2,3,7,8-tetrachloro-	1746-01-6	
Tetrabutylthiuram disulfide	Thioperoxydicarbonic diamide, tetrabutyl	1634-02-2	
1,2,4,5-Tetrachlorobenzene	Benzene, 1,2,4,5-tetrachloro-	95-94-3	U207
Tetrachlorodibenzo-p-dioxins			
Tetrachlorodibenzofurans			
Tetrachloroethane, N.O.S. <sup>1</sup>	Ethane, tetrachloro-, N.O.S.	25322-20-7	
1,1,1,2-Tetrachloroethane	Ethane, 1,1,1,2-tetrachloro-	630-20-6	U208
1,1,2,2-Tetrachloroethane	Ethane, 1,1,2,2-tetrachloro-	79-34-5	U209
Tetrachloroethylene	Ethene, tetrachloro-	127-18-4	U210
2,3,4,6-Tetrachlorophenol	Phenol, 2,3,4,6-tetrachloro-	58-90-2	See F027
***2,3,4,6-tetrachlorophenol, potassium salt	same	53535276	None

2,3,4,6-tetrachlorophenol, sodium salt	same	25567559	None
Tetraethyldithiopyrophosphate	Thiodiphosphoric acid, tetraethyl ester	3689-24-5	P109
Tetraethyl lead	Plumbane, tetraethyl-	78-00-2	P110
Tetraethyl pyrophosphate	Diphosphoric acid, tetraethyl ester	107-49-3	P111
Tetramethylthiuram monosulfide	Bis(dimethylthiocarbamoyl) sulfide	97-74-5	
Tetranitromethane	Methane, tetranitro-	509-14-8	P112
Thallium	Same	7440-28-0	
Thallium compounds, N.O.S. <sup>1</sup>			
Thallic oxide	Thallium oxide Tl <sub>2</sub> O <sub>3</sub>	1314-32-5	P113
Thallium(I) acetate	Acetic acid, thallium(1+) salt	563-68-8	U214
Thallium(I) carbonate	Carbonic acid, dithallium(1+) salt	6533-73-9	U215
Thallium(I) chloride	Thallium chloride TlCl	7791-12-0	U216
Thallium(I) nitrate	Nitric acid, thallium(1+) salt	10102-45-1	U217
Thallium selenite	Selenious acid, dithallium(1+) salt	12039-52-0	P114
Thallium(I) sulfate	Sulfuric acid, dithallium(1+) salt	7446-18-6	P115
Thioacetamide	Ethanethioamide	62-55-5	U218
Thiodicarb	Ethanimidothioic acid, N,N'-[[thiobis [(methylimino) carbonyloxy]] bis-, dimethyl ester.	59669-26-0	U410
Thiofanox	2-Butanone, 3,3-dimethyl-1-(methylthio)-, O-[[methylamino]carbonyl] oxime	39196-18-4	P045
Thiomethanol	Methanethiol	74-93-1	U153
Thiophanate-methyl	Carbamic acid, [1,2-phenylenebis (iminocarbonothioyl)] bis-, dimethyl ester	23564-05-8	U409
Thiophenol	Benzenethiol	108-98-5	P014
Thiosemicarbazide	Hydrazinecarbothioamide	79-19-6	P116
Thiourea	Same	62-56-6	U219
Thiram	Thioperoxydicarbonic diamide tetramethyl-	[(H <sub>2</sub> N)C(S)] <sub>2</sub> S <sub>2</sub> , 137-26-8	U244
Tirpate	1,3-Dithiolane-2-carboxaldehyde, O-[[methylamino] carbonyl] oxime	2,4-dimethyl-, 26419-73-8	P185
Toluene	Benzene, methyl-	108-88-3	U220
Toluenediamine	Benzenediamine, ar-methyl-	25376-45-8	U221
Toluene-2,4-diamine	1,3-Benzenediamine, 4-methyl-	95-80-7	
Toluene-2,6-diamine	1,3-Benzenediamine, 2-methyl-	823-40-5	
Toluene-3,4-diamine	1,2-Benzenediamine, 4-methyl-	496-72-0	
Toluene diisocyanate	Benzene, 1,3-diisocyanatomethyl-	26471-62-5	U223
o-Toluidine	Benzenamine, 2-methyl-	95-53-4	U328

o-Toluidine hydrochloride	Benzenamine, 2-methyl-, hydrochloride	636-21-5	U222
p-Toluidine	Benzenamine, 4-methyl-	106-49-0	U353
Toxaphene	Same	8001-35-2	P123
Triallate	Carbamothioic acid, bis(1-methylethyl)-, S-(2,3,3-trichloro-2-propenyl) ester	2303-17-5	U389
1,2,4-Trichlorobenzene	Benzene, 1,2,4-trichloro-	120-82-1	
1,1,2-Trichloroethane	Ethane, 1,1,2-trichloro-	79-00-5	U227
Trichloroethylene	Ethene, trichloro-	79-01-6	U228
Trichloromethanethiol	Methanethiol, trichloro-	75-70-7	P118
Trichloromonofluoro methane	Methane, trichlorofluoro-	75-69-4	U121
2,4,5-Trichlorophenol	Phenol, 2,4,5-trichloro-	95-95-4	See F027
2,4,6-Trichlorophenol	Phenol, 2,4,6-trichloro-	88-06-2	See F027
2,4,5-T	Acetic acid, (2,4,5-trichlorophenoxy)-	93-76-5	See F027
Trichloropropane, N.O.S. <sup>1</sup>		25735-29-9	
1,2,3-Trichloropropane	Propane, 1,2,3-trichloro-	96-18-4	
Triethylamine	Ethanamine, N,N-diethyl-	121-44-8	U404
O,O,O-Triethyl phosphorothioate	Phosphorothioic acid, O,O,O-triethyl ester	126-68-1	
1,3,5-Trinitrobenzene	Benzene, 1,3,5-trinitro-	99-35-4	U234
Tris(1-aziridinyl)phosphine sulfide	Aziridine, 1,1',1"-phosphinothioylidynetris-	52-24-4	
Tris(2,3-dibromopropyl) phosphate	1-Propanol, 2,3-dibromo-, phosphate (3:1)	126-72-7	U235
Trypan blue	2,7-Naphthalenedisulfonic acid, 3,3'-[(3,3'-dimethyl[1,1'-biphenyl]-4,4'-diyl)bis(azo)]- bis[5-amino-4-hydroxy-, tetrasodium salt	72-57-1	U236
Uracil mustard	2,4-(1H,3H)-Pyrimidinedione, 5-[bis(2-chloroethyl)amino]-	66-75-1	U237
Vanadium pentoxide	Vanadium oxide V <sub>2</sub> O <sub>5</sub>	1314-62-1	P120
Vernolate	Carbamothioic acid, dipropyl-,S-propyl ester	1929-77-7	
Vinyl chloride	Ethene, chloro-	75-01-4	U043
Warfarin	2H-1-Benzopyran-2-one, 4-hydroxy-3-(3-oxo-1-phenylbutyl)-, when present at concentrations less than 0.3%	81-81-2	U248
Warfarin	2H-1-Benzopyran-2-one, 4-hydroxy-3-(3-oxo-1-phenylbutyl)-, when present at concentrations greater than 0.3%	81-81-2	P001
Warfarin salts, when present at concentrations less than 0.3%			U248

Warfarin salts, when present at concentrations greater than 0.3%			P001
Zinc cyanide	Zinc cyanide Zn(CN) <sub>2</sub>	557-21-1	P121
Zinc phosphide	Zinc phosphide Zn <sub>3</sub> P <sub>2</sub> , when present at concentrations greater than 10%	1314-84-7	P122
Zinc phosphide	Zinc phosphide Zn <sub>3</sub> P <sub>2</sub> , when present at concentrations of 10% or less	1314-84-7	U249
Ziram	Zinc, bis(dimethylcarbomodithioato-S,S'), (T-4)-	137-30-4	P205

FOOTNOTE: <sup>1</sup>The abbreviation N.O.S. (not otherwise specified) signifies those members of the general class not specifically listed by name in this appendix.

Appendix IX - (Reserved) [40 CFR 261 Appendix IX]  
(Note: EPA maintains the listing in Appendix IX.)

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subpart (i) of part 5 of subparagraph (m) of paragraph (12) of Rule 0400-12-01-.03 Notification Requirements and Standards Applicable to Generators of Hazardous Waste is amended by deleting it in its entirety and substituting instead the following:

- (i) Write the words “hazardous waste” on the container label that is affixed or attached to the container within four (4) calendar days of arriving at the on-site interim status or permitted treatment, storage or disposal facility and before the hazardous waste may be removed from the on-site interim status or permitted treatment, storage or disposal facility; and

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subpart (xi) of part 2 of subparagraph (b) of paragraph (1) of Rule 1200-12-01-.05 Interim Status Standards for Owners and Operators of Existing Hazardous Waste Treatment, Storage, and Disposal Facilities is amended by deleting it in its entirety and substituting instead the following:

- (xi) A farmer disposing of waste pesticides from his own use in compliance with item (1)(d)2(ii)(II) of Rule 0400-12-01-.02.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subpart (ix) of part 2 of subparagraph (b) of paragraph (1) of Rule 0400-12-01-.06 Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities is amended by deleting it in its entirety and substituting instead the following:

- (ix) A farmer disposing of waste pesticides from his own use in compliance with item (1)(d)2(ii)(II) of Rule 0400-12-01-.02.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subparagraph (a) of paragraph (27) of Rule 0400-12-01-.06 Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities is amended by deleting it in its entirety and substituting instead the following:

- (a) Applicability [40 CFR 264.600]

The requirements in this paragraph apply to owners and operators of facilities that treat, store, or dispose of hazardous waste in miscellaneous units, except as paragraph (1) of this rule provides otherwise.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subparagraph (a) of paragraph (10) of Rule 0400-12-01-.07 Permitting of Hazardous Waste Treatment, Storage, and Disposal Facilities is amended by adding parts 9 and 10 to read as follows:

- |     |   |    |
|-----|---|----|
| 9.  | Changes to remove permit conditions applicable to a unit excluded under the provisions of subparagraph (1)(d) of Rule 0400-12-01-.02.                               | 11 |
| 10. | Changes in the expiration date of a permit issued to a facility at which all units are excluded under the provisions of subparagraph (1)(d) of Rule 0400-12-01-.02. | 11 |

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Paragraph (11) of Rule 0400-12-01-.08 Fee System for Transporters, Storer, Treater, Disposer, and Certain Generators of Hazardous Waste and For Certain Used Oil Facilities or Transporters is amended by deleting it in its entirety and substituting instead the following:

(11) Chromium Exclusion Review Fee

2,500 dollars for each chromium waste stream applicable to the exclusion in subpart (1)(d)2(vi) of Rule 0400-12-01-.02.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subpart (i) of part 4 of subparagraph (a) of paragraph (3) of Rule 0400-12-01-.09 Standards for the Management of Specific Hazardous Wastes and Specific Types of Hazardous Waste Management Facilities is amended by deleting it in its entirety and substituting instead the following:

- (i) They are zinc fertilizers excluded from the definition of solid waste according to subpart (1)(d)1(xxi) of Rule 0400-12-01-.02; or

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Part 4 of subparagraph (a) of paragraph (6) of Rule 0400-12-01-.09 Standards for the Management of Specific Hazardous Wastes and Specific Types of Hazardous Waste Management Facilities is amended by deleting it in its entirety and substituting instead the following:

4. Recyclable materials that are regulated under this paragraph that are accumulated speculatively (as defined in subpart (1)(a)3(viii) of Rule 0400-12-01-.02) are subject to all applicable provisions of Rules 0400-12-01-.03 through 0400-12-01-.07.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

Subparagraph (m) of paragraph (8) of Rule 0400-12-01-.09 Standards for the Management of Specific Hazardous Wastes and Specific Types of Hazardous Waste Management Facilities is amended by deleting it in its entirety and substituting instead the following:

(m) Regulation of Residues [40 CFR 266.112]

A residue derived from the burning or processing of hazardous waste in a boiler or industrial furnace is not excluded from the definition of a hazardous waste under subparts (1)(d)2(iv), (vii), or (viii) of Rule 0400-12-01-.02 unless the device and the owner or operator meet the following requirements:

1. The device meets the following criteria:

(i) Boilers

Boilers must burn at least 50% coal on a total heat input or mass input basis,



whichever results in the greater mass feed rate of coal;

(ii) Ore or Mineral Furnaces

Industrial furnaces subject to subpart (1)(d)2(vii) of Rule 0400-12-01-.02 must process at least 50% by weight normal, nonhazardous raw materials;

(iii) Cement Kilns

Cement kilns must process at least 50% by weight normal cement-production raw materials;

2. The owner or operator demonstrates that the hazardous waste does not significantly affect the residue by demonstrating conformance with either of the following criteria:

(i) Comparison of Waste-derived Residue With Normal Residue

The waste-derived residue must not contain Appendix VIII, paragraph (30) of Rule 0400-12-01-.02 constituents (toxic constituents) that could reasonably be attributable to the hazardous waste at concentrations significantly higher than in residue generated without burning or processing of hazardous waste, using the following procedure. Toxic compounds that could reasonably be attributable to burning or processing the hazardous waste (constituents of concern) include toxic constituents in the hazardous waste, and the organic compounds listed in Appendix VIII of this rule that may be generated as products of incomplete combustion. For polychlorinated dibenzo-p-dioxins and polychlorinated dibenzofurans, analyses must be performed to determine specific congeners and homologues, and the results converted to 2, 3, 7, 8-TCDD equivalent values using the procedure specified in section 4.0 of the Methods Manual for Compliance with the BIF Regulations. (See Appendix IX of this rule.)

(I) Normal Residue

Concentrations of toxic constituents of concern in normal residue shall be determined based on analyses of a minimum of 10 samples representing a minimum of 10 days of operation. Composite samples may be used to develop a sample for analysis provided that the compositing period does not exceed 24 hours. The upper tolerance limit (at 95% confidence with a 95% proportion of the sample distribution) of the concentration in the normal residue shall be considered the statistically-derived concentration in the normal residue. If changes in raw materials or fuels reduce the statistically-derived concentrations of the toxic constituents of concern in the normal residue, the statistically-derived concentrations must be revised or statistically-derived concentrations of toxic constituents in normal residue must be established for a new mode of operation with the new raw material or fuel. To determine the upper tolerance limit in the normal residue, the owner or operator shall use statistical procedures prescribed in "Statistical Methodology for Beville Residue Determinations" in Appendix IX of this rule.

(II) Waste-derived Residue

Waste-derived residue shall be sampled and analyzed as often as necessary to determine whether the residue generated during each 24-hour period has concentrations of toxic constituents that are higher than the concentrations established for the normal residue under item (I) of this subpart. If so, hazardous waste burning has significantly affected the residue and the residue shall not be excluded from the definition of a hazardous waste. Concentrations of toxic constituents of concern in the

waste-derived residue shall be determined based on analysis of one or more samples obtained over a 24-hour period. Multiple samples may be analyzed, and multiple samples may be taken to form a composite sample for analysis provided that the sampling period does not exceed 24 hours. If more than one sample is analyzed to characterize waste-derived residues generated over a 24-hour period, the concentration of each toxic constituent shall be the arithmetic mean of the concentrations in the samples. No results may be disregarded; or

(ii) Comparison of Waste-derived Residue Concentrations With Health-based Limits

(I) Nonmetal Constituents

The concentration of each nonmetal toxic constituent of concern (specified in subpart (i) of this part) in the waste-derived residue must not exceed the health-based level specified in Appendix VII of this rule, or the level of detection, whichever is higher. If a health-based limit for a constituent of concern is not listed in Appendix VII of this rule, then a limit of 0.002 micrograms per kilogram or the level of detection (which must be determined by using appropriate analytic procedures), whichever is higher, must be used. The levels specified in Appendix VII of this rule (and the default level of 0.002 micrograms per kilogram or the level of detection for constituents as identified in Note 1 of Appendix VII of this rule) are administratively stayed under the condition, for those constituents specified in subpart (i) of this part, that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in subparagraph (3)(d) of Rule 0400-12-01-.10 for F039 nonwastewaters. In complying with those alternative levels, if an owner or operator is unable to detect a constituent despite documenting use of best good-faith efforts as defined by applicable Department guidance or standards, the owner or operator is deemed to be in compliance for that constituent. Until new guidance or standards are developed, the owner or operator may demonstrate such good-faith efforts by achieving a detection limit for the constituent that does not exceed an order of magnitude above the level provided by subparagraph (3)(d) of Rule 0400-12-01-.10 for F039 nonwastewaters. In complying with the subparagraph (3)(d) of Rule 0400-12-01-.10 F039 nonwastewater levels for polychlorinated dibenzo-p-dioxins and polychlorinated dibenzo-furans, analyses must be performed for total hexachlorodibenzo-p-dioxins, total hexachlorodibenzofurans, total pentachlorodibenzo-p-dioxins, total pentachlorodibenzofurans, total tetrachlorodibenzo-p-dioxins, and total tetrachlorodibenzofurans.

(Note: The administrative stay, under the condition that the owner or operator complies with alternative levels defined as the land disposal restriction limits specified in 40 CFR § 268.43 for F039 nonwastewaters, remains in effect until further administrative action is taken and notice is published in the Federal Register and the Code of Federal Regulations.)

(II) Metal Constituents

The concentration of metals in an extract obtained using the Toxicity Characteristic Leaching Procedure of subparagraph (3)(e) of Rule 0400-12-01-.02 must not exceed the levels specified in Appendix VII of this rule; and

(III) Sampling and Analysis

Waste-derived residue shall be sampled and analyzed as often as necessary to determine whether the residue generated during each 24-

hour period has concentrations of toxic constituents that are higher than the health-based levels. Concentrations of toxic constituents of concern in the waste-derived residue shall be determined based on analysis of one or more samples obtained over a 24-hour period. Multiple samples may be analyzed, and multiple samples may be taken to form a composite sample for analysis provided that the sampling period does not exceed 24 hours. If more than one sample is analyzed to characterize waste-derived residues generated over a 24-hour period, the concentration of each toxic constituent shall be the arithmetic mean of the concentrations in the samples. No results may be disregarded; and

3. Records sufficient to document compliance with the provisions of this subparagraph shall be retained until closure of the boiler or industrial furnace unit. At a minimum, the following shall be recorded.
  - (i) Levels of constituents in Appendix VIII in paragraph (30) of Rule 0400-12-01-.02, that are present in waste-derived residues;
  - (ii) If the waste-derived residue is compared with normal residue under subpart 2(i) of this subparagraph:
    - (I) The levels of constituents in Appendix VIII in paragraph (30) of Rule 0400-12-01-.02, that are present in normal residues; and
    - (II) Data and information, including analyses of samples as necessary, obtained to determine if changes in raw materials or fuels would reduce the concentration of toxic constituents of concern in the normal residue.

Authority: T.C.A. §§ 68-212-101 et seq. and 4-5-201 et seq.

\* If a roll-call vote was necessary, the vote by the Agency on these rulemaking hearing rules was as follows:

Board Member	Aye	No	Abstain	Absent	Signature (if required)
<b>Marty Calloway</b> (Petroleum Business with at least 15 Underground Storage Tanks)	X				
<b>Stacey Cothran</b> (Solid/Hazardous Waste Management Industry)	X				
<b>Kenneth L. Donaldson</b> (Municipal Government)				X	
<b>Dr. George Hyfantis, Jr.</b> (Institution of Higher Learning)	X				
<b>Bhag Kanwar</b> (Single Facility with less than 5 Underground Storage Tanks)	X				
<b>Alan M. Leiserson</b> Environmental Interests	X				
<b>Jared L. Lynn</b> (Manufacturing experienced with Solid/Hazardous Waste)	X				
<b>David Martin</b> (Working in a field related to Agriculture)	X				
<b>Beverly Philpot</b> (Manufacturing experienced with Underground Storage Tanks/Hazardous Materials)	X				
<b>DeAnne Redman</b> (Petroleum Management Business)	X				
<b>Mayor A. Franklin Smith, III</b> (County Government)				X	
<b>Mark Williams</b> (Small Generator of Solid/Hazardous Materials representing Automotive Interests)	X				

I certify that this is an accurate and complete copy of rulemaking hearing rules, lawfully promulgated and adopted by the Underground Storage Tanks and Solid Waste Disposal Control Board on 12/02/2015, and is in compliance with the provisions of T.C.A. § 4-5-222.

I further certify the following:

Notice of Rulemaking Hearing filed with the Department of State on: 07/14/15

Rulemaking Hearing(s) Conducted on: (add more dates). 09/08/15

Date: December 2, 2015

Signature: \_\_\_\_\_

Name of Officer: Stacey Cothran

Title of Officer: Chair

Subscribed and sworn to before me on: \_\_\_\_\_

Notary Public Signature: \_\_\_\_\_

My commission expires on: \_\_\_\_\_

- Rules of the Board of Underground Storage Tanks and Solid Waste Disposal Control Board
- Chapter 0400-12-01 Hazardous Waste Management
- Rule 0400-12-01-.01 Hazardous Waste Management System: General
- Rule 0400-12-01-.02 Identification and Listing of Hazardous Waste
- Rule 0400-12-01-.03 Notification Requirements and Standards Applicable to Generators of Hazardous Waste
- Rule 0400-12-01-.05 Interim Status Standards for Owners and Operators of Existing Hazardous Waste Treatment, Storage, and Disposal Facilities
- Rule 0400-12-01-.06 Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities
- Rule 0400-12-01-.07 Permitting of Hazardous Waste Treatment, Storage, and Disposal Facilities
- Rule 0400-12-01-.08 Fee System for Transporters, Storer, Treater Disposer, and Certain Generators of Hazardous Waste and For Certain Used Oil Facilities or Transporters
- Rule 0400-12-01-.09 Standards for the Management of Specific Hazardous Wastes and Specific Types of Hazardous Waste Management Facilities

All rulemaking hearing rules provided for herein have been examined by the Attorney General and Reporter of the State of Tennessee and are approved as to legality pursuant to the provisions of the Administrative Procedures Act, Tennessee Code Annotated, Title 4, Chapter 5.

\_\_\_\_\_  
 Herbert H. Slatery III  
 Attorney General and Reporter

\_\_\_\_\_  
 Date

**Department of State Use Only**

Filed with the Department of State on: \_\_\_\_\_

Effective on: \_\_\_\_\_

\_\_\_\_\_  
 Tre Hargett  
 Secretary of State

## Public Hearing Comments

One copy of a document containing responses to comments made at the public hearing must accompany the filing pursuant to T.C.A. § 4-5-222. Agencies shall include only their responses to public hearing comments, which can be summarized. No letters of inquiry from parties questioning the rule will be accepted. When no comments are received at the public hearing, the agency need only draft a memorandum stating such and include it with the Rulemaking Hearing Rule filing. Minutes of the meeting will not be accepted. Transcripts are not acceptable.

The comments that followed urged adoption of the rules, expressed appreciation for clarifying language added by the Board to the regulations as promulgated by the federal Environmental Protection Agency (EPA), requested that the Board add more clarifying language to the rules, suggested corrections to errors in the rules, and requested that the Board respond to various potential applications of the rules.

**Comment:** A commenter recommended amending the Commissioner's verification procedure for hazardous secondary material reclaimers and intermediate facilities since it was intended to be a form of operating status similar to a permittee or licensee. The commenter was concerned that the proposed rule did not make it sufficiently clear that the Commissioner's verification was a form of license under the Uniform Administrative Procedures Act, which could be revoked for cause and was subject to enforcement action for non-compliance with the conditions determined to be necessary by the Commissioner.

**Response:** The Board agrees with the commenter and has modified the rule to include the recommended clarifications. The rules have been changed to indicate that the Commissioner will issue a Certificate to Operate to an owner or operator of a hazardous secondary material reclamation or intermediate facility instead of a verification determination to make its operating status clear. The rules were modified to reflect the change from a verification determination to the issuing of a Certificate to Operate. Paragraph (4) of Rule 0400-12-01-.01 has been modified by adding subparagraphs (h) and (i) to address causes for terminating the Certificate to Operate and for taking enforcement actions for non-compliance with the conditions in the certificate.

**Comment:** A commenter pointed out that the new definition of "hazardous secondary material generator" includes a reference to item (1)(b)1(ii)(II) of Rule 0400-12-01-.02 in the last sentence and should be deleted since the item was being reserved in the rules.

**Response:** The Board agrees and has deleted the reference to item (1)(b)1(ii)(II) of Rule 0400-12-01-.02 from the definition of "hazardous secondary material generator."

**Comment:** A commenter was concerned that the lack of clarity on the part of writers of the federal regulations has resulted in a federal definition of solid waste that could well jeopardize hundreds of millions of dollars of products, all of which are made with recycled hazardous secondary materials. The commenter supports the Board's efforts to propose rules that add clarity to this complex issue.

**Response:** The Board agrees that the issue of determining when a secondary material is discarded is very complex. The addition of clarifications in the rules will help the Department and all interested parties reach a common understanding of how these rules will be implemented, so the benefits of legitimate recycling will be realized while protecting public health and the environment.

**Comment:** The Tennessee Chamber of Commerce and Industry (TCCI) believes it is critical that Tennessee retain authorization for making solid and hazardous waste determinations and encourages the adoption of these rules with the clarifications that will assist the regulated community and the Department enforcement personnel in the implementation of these rules.

**Response:** The Board agrees that it is critical that Tennessee retain authorization for making solid and hazardous waste determinations. We agree that the addition of clarifications in the rules will help the Department and all interested parties reach a common understanding of how these rules will be implemented, so the benefits of legitimate recycling will be realized while protecting public health and the environment.

Comment: TCCI specifically supports the regulatory clarifications as follows:

- The inclusion of definitions critical to the understanding of this rule in 0400-12-01-.01: “analogous raw material”, “contained”, “hazardous secondary material”, “intermediate”, and “intermediate facility”. For example, the federal rule applies a different compliance method for “analogous” and “non-analogous material” but does not define either in the rule. The Tennessee version recognizes the importance of clarity in rulemaking.
- The further clarification of the term “non-analogous” products and clarification that process knowledge is an acceptable method to demonstrate legitimacy in Rule 0400-12-01-.01(5)(d) – legitimate recycling of hazardous secondary materials.
- The additional requirements associated with EPA’s “verified recycler exclusion” and “generator controlled exclusion” concept. In fact, Board’s requirements that the Commissioner “verify” the recyclers associated with the new variance option in the EPA rule, including the hazardous secondary material acceptance plan, are prescriptive but not unreasonable, allowing a more complete compliance plan for both the Department and the facility. For example, rules’ requirement for public participation removes the uncertainty associated with the EPA version of the rule requiring the recycler to address risk to nearby communities without clarifying how that is to be done.
- The clarification of the terms “by-product”, “spent material” and “co-product” as used in Rule 0400-12-01-.02(1)(a)3.
- The footnote associated with Table 1 in 0400-12-01-.02(1)(b) clarifying that the exclusion from the definition of solid waste for commercial chemical products when recycled is applicable not only to listed commercial chemical products but to commercial chemical products and unused manufactured items that are not listed but exhibit a characteristic of a hazardous waste.
- The clarification included in the “closed loop recycle” exclusion referenced in Rule 0400-12-01-.02(1)(d)1(viii) with inclusion of the note clarifying the term “production process”.

Response: The Board agrees that the addition of clarifications in the rules will help the Department and all interested parties to reach a common understanding of how these rules will be implemented, so the benefits of legitimate recycling will be realized while protecting public health and the environment.

Comment: When stating their support for the clarification included in Rule 0400-12-01-.02(1)(d)1(viii) through the note clarifying the term “production process”, TCCI and Dow indicated that their understanding is that the “closed loop recycle” aspect used in that subpart is not exclusive and that other legitimate recycling such as recycling that uses containers instead of or in addition to tanks or by-product returns to carry the material from the customer to the generating facility are allowed if that use is within the “production process” described as “those activities that tie directly into the manufacturing operation or those activities that are the primary operation at an establishment.”

Response: In the interest of clarity, the Board cautions the commenters that subpart (1)(d)1(viii) of Rule 0400-12-01-.02 is often referred to as “closed loop recycling” but the subpart does not use the term; “closed loop recycle” and does not apply to all methods of returning hazardous secondary materials back to the production process. Its conditions are very limited and are not expanded by the clarifying note. In contrast, the legitimate recycling criteria of subitem (5)(d)1(iv)(II) of Rule 0400-12-01-.01, which applies when there is no analogous product, recognizes that the methods described in the comment are authorized for returning the hazardous secondary material to the original process or processes from which they were generated to be reused. Production process is described the same way in both subitem (5)(d)1(iv)(II) of Rule 0400-12-01-.01 and subpart (1)(d)1(viii) of Rule 0400-12-01-.02.

Comment: TCCI pointed out that on March 31, 2015, EPA published a document referenced as Response to Frequently Asked Questions. Item 6, sub-item 2, in that document states that no testing or documentation is required for recycled products meeting the widely-recognized commodity specification and states, “for specialty products such as specialty batch chemicals or specialty metal alloys, customer specification would be sufficient.” TCCI believes it is appropriate to include this as a clarifying note at 0400-12-01.01(5)(d)1(iv)(II).

Response: The Board agrees with the EPA and the commenter and is adding the note as requested.

Comment: The federal rule states that sham recycling is prohibited and that all recycling must be legitimate and meet the four legitimacy factors, including with respect to material that is recycled pursuant to pre-2008 exclusions. However, the Preamble and guidance state that:

- EPA is not altering or amending the pre-2008 recycling exclusions;
- EPA is not requiring facilities that use pre-2008 exclusions to submit or even maintain documentation of compliance with legitimacy factors;
- EPA conducted significant legitimacy analysis during promulgation of the pre-2008 exclusions and did not find damage resulting from the use of these exclusions; and
- EPA believes that so long as the conditions of the pre-2008 exclusions are met, then the subject material is legitimately recycled and meets the legitimacy factors.

Over time, TCCI is concerned that these fundamental findings by EPA will be lost if not clarified in the Tennessee rules. A future interpretation that documentation is required would not be consistent with the intent as described in the preamble. As such, TCCI requests that a “presumption” of legitimacy be included in these rules.

- Include a specific provision in the Tennessee Rules at the end of 0400-12-01-.01(5)(d) stating the following:

(Note: Persons who meet the specific provisions included in 0400-12-01-.02(1)(b)3 Table 1, 0400-12-01-.02(1)(b)5, 0400-12-01-.02(1)(d)1(vi) through (xxii), 0400-12-01-.02(1)(f)1(ii)(III) and (IV), and 0400-12-01-.02(1)(f)1(iii)(I), are presumed to conduct legitimate recycling.)

Response: The legitimacy criteria proposed to be adopted by this rulemaking is consistent with the legitimacy criteria used by the Department to date. Provided all the regulatory or approval conditions are being met, we believe prior determinations and the regulatory exemptions adopted continue to be valid until the Department has a reason to believe otherwise, except in those rare cases involving levels of constituents that are not comparable to a legitimate product or intermediate where the recycling is legitimate, but it is necessary to document legitimacy in accordance with item (5)(d)1(iv)(III) of Rule 0400-12-01-.01. The Board agrees that it would be helpful to add the requested clarifying note to subparagraph (5)(d) of Rule 0400-12-01-.01, but with additional clarifications to read as follows:

“(Note: A person who meets the specific provisions included in 0400-12-01-.02(1)(b)3 Table 1, 0400-12-01-.02(1)(b)5, 0400-12-01-.02(1)(d)1(vi) through (xxii), 0400-12-01-.02(1)(f)1(ii)(III) and (IV), and 0400-12-01-.02(1)(f)1(iii)(I), are presumed to conduct legitimate recycling, except in those rare cases when it is necessary to document legitimacy in accordance with item 1(iv)(III) of this subparagraph. If, at any time, the Commissioner suspects that sham recycling may be occurring, in accordance with part (1)(b)6 of Rule 0400-12-01-.02, the Commissioner may require a person to demonstrate that the recycling in question is legitimate in accordance with this subparagraph.)

Comment: TCCI and Dow request that Tennessee consider a phased approach for the implementation of the rule. This is particularly important in reference to the new recordkeeping requirements applicable to pre-2008 exclusions concerning speculative accumulation. Recycling in accordance with the conditions of the pre-2008 exclusions has been used prior to and after promulgation of these exclusions in 1985. In order to educate the regulated community and provide time for development of adequate compliance methods, TCCI and Dow asks that the effective date be extended to 12 months after the rule is final. TCCI and Dow also asks the Board to consider an extended effective date for existing “verified recyclers” if capital improvements are required to comply with the new requirements and to obtain state verification.

Response: Some commenters on these amendments believed that it is critical for Tennessee to retain program authorization for making solid and hazardous waste determinations. Delaying the effective date of the new recordkeeping requirements applicable to speculative accumulation provisions would complicate that result. EPA’s new recordkeeping requirement was published on January 13, 2015, and became effective in non-authorized states on July 13, 2015. Tennessee is an authorized state and this requirement does not become immediately effective until this



rulemaking becomes effective, which will be well over a year after it was published as a final regulation by EPA in the Federal Register. The Board believes that the regulated community is aware of this pending requirement and hopes that the regulated community is acting now to become educated on this requirement and to develop compliance methods.

Since there is no existing “verified recycler” in Tennessee no extension of the effective date is appropriate.

**Comment:** TCCI and Dow believe that the regulated community would be greatly assisted if the pre-2008 exclusions that are not subject to speculative accumulation requirements are included in the rule or as a footnote to 0400-12-01-.02(1)(a)3(viii) and Dow suggested that the subpart be amended for further clarification.

**Response:** The Board believes that it would be helpful to provide a clarifying note to subpart (1)(a)3(viii) of Rule 0400-12-01-.02 alerting persons that the speculative accumulation requirements contained in the subpart are only applicable when specifically referenced by the exclusion or exemption conditions and will provide some helpful examples. The Board will add the following note to subpart (1)(a)3(viii) of Rule 0400-12-01-.02:

(Note: The speculative accumulation requirements contained in this subpart are only applicable when specifically referenced by the exclusion or exemption conditions contained in this rule and Rule 0400-12-01-.09. For example, subparts (d)1(viii), (xiii), and (xxvi) of this paragraph do not require compliance with this subpart as a condition of the exclusions; however subparts (d)1(vi) and (vii) of this paragraph and part (6)(a)3 of Rule 0400-12-01-.09 do require compliance with the subpart as a condition of the exclusion or exemption.)

The Board does not agree that amending the subpart (1)(a)3(viii) of Rule 0400-12-01-.02 is needed. The Department will confirm that even if a hazardous secondary material is being accumulated for longer than one year, the hazardous secondary material will not be considered speculatively accumulated if the person accumulating it can show that at least 75% of the hazardous secondary material in inventory on January 1 of the previous year was recycled during the previous year.

**Comment:** TCCI understands that EPA is going to publish additional guidance in the form of “Frequently Asked Questions” and asks that the Board incorporate clarifications that are useful in the future interpretation of this rule including clarification that the term “contained” does not require full RCRA permitted containment as defined in 0400-12-01-.01(1) – Contained – Item 4. In addition, TCCI expects EPA to clarify that an infrequent release from a unit (emergency vent relief, failure of overflow alarms etc.) would not automatically disqualify the unit as a method of containment.

**Response:** The Board is also monitoring EPA’s interpretations of their regulations that are similar to the rules proposed in this rulemaking. Tennessee will give careful consideration to EPA’s future interpretations and, upon request, issue a corresponding interpretation of Tennessee’s rules. Also, additional clarification can be added to the rules if needed.

**Comment:** TCCI and Dow understand from numerous statements in the preamble of the federal rule that documentation for pre-2008 exclusions is NOT required. However, in the event TDEC finds flaw with the recycling process or specifically requires documentation that constituents are statistically comparable to “virgin” material, the comparisons can be made as follows:

- The hazardous secondary material that is being recycled directly (i.e., without reclamation) versus the virgin raw material or ingredient that the hazardous secondary material is replacing; or
- The hazardous secondary material after reclamation that is being recycled versus the virgin raw material or ingredient that the reclaimed hazardous secondary material is replacing; or
- The product/intermediate that results from recycling the hazardous secondary material versus the product/intermediate that results from using the virgin raw material or ingredient that the hazardous secondary material is replacing; or
- The product/intermediate that results from recycling the hazardous secondary material versus a substitute product/intermediate that is made without the hazardous secondary material by a

different company or by the same company at a different site or through a different process.

Response: The Board agrees that these comparisons seem valid and reasonable; however, legitimacy determinations will be made on a case specific basis.

Comment: Dow understands EPA interprets 40 CFR § 260.43(a)(4)(i)(B) criteria by stating that: “One company does not know whether another company produces an analogous product or intermediate made from virgin materials” and recommended that Tennessee add a new definition for “analogous product” to clarify EPA’s intent.

Response: The Board does not agree that a definition should be added to the regulations to clarify EPA’s intent. The Board will confirm that to determine whether there is an analogous product or intermediate made with virgin raw materials, and in order to determine whether the criteria of item (5)(d)1(iv)(I) or (II) of Rule 0400-12-01-.01 applies, the hazardous secondary material recycler may use a good faith understanding of whether other companies produce the product or intermediate only with virgin materials. The recycler is not expected to know how all other analogous products are made.

Comment: Dow recommends that the Board consider allowing companies to perform legitimacy evaluations on groups of specific streams that are managed in the same industry and recycled in the same manner. This may include streams from various plants making the same product(s).

Response: Legitimacy determinations should be made on a case specific basis because there are many ways in which streams may vary. The recycler must ensure that the legitimacy evaluation addresses the hazardous secondary material being recycled. In addition, to obtain a Certificate to Operate, the reclaimer or intermediate facility will be required to develop the acceptance plan with sufficient detail to ensure that all materials being reclaimed are legitimately recycled.

Comment: Dow suggested that a clarification be added to the rules regarding the definition of “contained” stating that individual leak events are not a reason to lose the “contained” status. Overall unit integrity will be the governing factor to determine whether a unit meets the “contained” criteria and requested that the Board adopt EPA’s thoughts on “contained”.

Response: The Board does not agree that the requested clarification to the definition of contained should be added to the rules to clarify the intent. A single release does not presumptively negate the ability of the hazardous secondary material to meet subpart (5)(d)1(iiii) of Rule 0400-12-01-.01. The Department realizes that despite best management practices releases of materials, including valuable raw materials, do occur from time to time. When a release occurs, the recycler’s response to the release is a critical factor to be considered. If the recycler does not manage the hazardous secondary material as it would a valuable commodity, the hazardous secondary materials might not be legitimately recycled.

Comment: Dow recommends Tennessee add clarifications as to what is required for various aspects of complying with the legitimacy criteria and evaluations. Dow offers some text below to present clarifications that will assist the regulated community in application of these rules.

Define “Pre-2008 Exclusions” -- “Pre-2008 Exclusions” mean the exclusions from the definition of solid waste and hazardous waste exemptions in effect prior to EPA’s 2008 promulgation of revisions to the definition of solid waste to exclude certain hazardous secondary materials from hazardous waste regulation in 73 Fed. Reg. 64668, et seq., October 30, 2008, effective December 29, 2008.

Response: The Board believes adding the suggested definition to the rules would be confusing to the regulated community. The effective dates for the inclusions of exemptions to Tennessee’s rules do not correspond with EPA’s dates.

Comment: Dow recommends Tennessee add clarifications as to what is required for various aspects of complying with the legitimacy criteria and evaluations. Clarify legitimacy compliance requirements for the pre-2008 exclusions:

- A. All four legitimacy factors of § 260.43(a) apply to the pre-2008 exclusions.
- B. Documentation of legitimacy is not required for the pre-2008 exclusions, except in the rare case where the recycling is legitimate, but does not meet legitimacy factor 4 in § 260.43. (In such case, documentation, certification, and notice are required.)
- C. Except as noted in B above, pre-2008 exclusions are not subject to the notification requirements of § 260.42.
- D. Except as noted below, materials subject to the pre-2008 exclusions do not have to be contained, as defined in § 260.10. Hazardous secondary materials that have no analogous raw material, even if subject to one or more of the pre-2008 exclusions, must be contained.
- E. The requirement that a recycling facility be verified under § 261.4(a)(24) applies to recycling of those hazardous secondary materials that would otherwise be regulated as hazardous waste and does not apply to materials excluded under one or more of the pre-2008 exclusions.
- F. If a hazardous secondary material is subject to material-specific management conditions in § 261.4(a) when reclaimed, such a material is not eligible for exclusion under § 261.4(a)(23) or (24). The exclusions in § 261.4(a) that are subject to material-specific management conditions when reclaimed and are thus not eligible for exclusion under § 261.4(a)(23) or (24) are those for (1) spent wood preserving solutions (§ 261.4(a)(9)) if recycled on-site, (2) shredded circuit boards (§ 261.4(a)(14)), (3) mineral processing spent materials (§ 261.4(a)(17)), (4) spent caustic solutions from petroleum refining liquid treating processes (§ 261.4(a)(19)), (5) cathode ray tubes (§ 261.4(a)(22)).

- Response:
- A. The four legitimacy factors of part (5)(d)1 of Rule 0400-12-01-.01 apply to all recycling exclusions or exemptions. (Equivalent Tennessee rule citations used in response.)
  - B. Documentation of legitimacy is not required for persons claiming a recycling exclusion or exemption existing prior to the effective date of these amendments, except in those rare cases when it is necessary to document legitimacy in accordance with item (5)(d)1(iv)(III) of Rule 0400-12-01-.01. If, at any time, the Commissioner suspects that sham recycling may be occurring, in accordance with part (1)(b)6 of Rule 0400-12-01-.02, the Commissioner may require a person to demonstrate that the recycling in question is legitimate in accordance with this subparagraph. (Equivalent Tennessee rule citations used in response.)
  - C. Persons managing hazardous secondary material under subparagraph (4)(b) of Rule 0400-12-01-.01, or under subparts (1)(d)1(xxiii), (xxiv) or (xxvii) of Rule 0400-12-01-.02 are required to notify in accordance with subparagraph (5)(c) of Rule 0400-12-01-.01. Persons required to document legitimacy in accordance with item (5)(d)1(iv)(III) of Rule 0400-12-01-.01, are required to notify the Commissioner. (Equivalent Tennessee rule citations used in response.)
  - D. To be legitimate recycling, subpart (5)(d)1(iii) of Rule 0400-12-01-.01 requires any recycler to manage the hazardous secondary material as a valuable commodity when it is under the recycler's control. If there is an analogous raw material, the hazardous secondary material must be managed, at a minimum, in a manner consistent with the management of the raw material or in an equally protective manner. If there is no analogous raw material, the hazardous secondary material must be contained. (Equivalent Tennessee rule citations used in response.)
  - E. The requirement that a reclamation facility be verified under subpart (1)(d)1(xxiv) of Rule 0400-12-01-.02 [§ 261.4(a)(24)] does not apply to hazardous secondary materials subject to material specific management conditions under part (1)(d)1 of Rule 0400-12-01-.02 or is a spent lead-acid battery. See item (1)(d)1(xxiv)(III) of Rule 0400-12-01-.02. The same would be true for hazardous secondary materials that are not waste when legitimately

reclaimed as specified in subpart (1)(b)3(iii) of Rule 0400-12-01-.02 (i.e., non-listed sludges exhibiting a characteristic of hazardous waste, non-listed by-products exhibiting a characteristic of hazardous waste, and listed or characteristic unused commercial chemical products or unused manufactured articles). (Equivalent Tennessee rule citations used in response.)

- F. The legitimate reclamation exclusion is not applicable under subparts (1)(d)1(xxiii) and (xxiv) of Rule 0400-12-01-.02 if the hazardous secondary materials are subject to material specific management conditions under part (1)(d)1 of Rule 0400-12-01-.02 or are spent lead-acid batteries. See subitem (1)(d)1(xxiii)(II)IV and item (1)(d)1(xxiv)(III) of Rule 0400-12-01-.02. The same would be true for hazardous secondary materials that are not waste when legitimately reclaimed as specified in subpart (1)(b)3(iii) of Rule 0400-12-01-.02 (i.e., non-listed sludges exhibiting a characteristic of hazardous waste, non-listed by-products exhibiting a characteristic of hazardous waste, and listed or characteristic unused commercial chemical products or unused manufactured articles). (Equivalent Tennessee rule citations used in response.)

Comment: Dow requested clarification on general compliance with the Legitimate Recycling criteria under § 260.43(a)(4) [Rule 0400-12-01-.01(5)(d)1(iv)].

- A. Testing is not generally required under § 260.43 [Rule 0400-12-01-.01(5)d)]. As with any solid and hazardous waste determination, a person may use knowledge of the materials he uses; the hazardous secondary material, product, or intermediate he recycles; and of the recycling process to make legitimate recycling determinations.
- B. Specifically, recycling meets legitimacy factor 4 of § 260.43 [Rule 0400-12-01-.01(5)(d)1(iv)] with no testing or further demonstration of meeting this legitimacy factor required under any of the following circumstances:
1. The hazardous secondary materials are returned to the original process or processes from which they were generated, such as in concentrating metals in minerals processing.
  2. The recycled product meets widely-recognized commodity specifications and there is no analogous product made from raw materials (such as scrap metal being reclaimed into metal commodities). For specialty products such as specialty batch chemicals or specialty metal alloys, customer specifications would be sufficient.
  3. The recycled product has an analogous product made from virgin materials, but meets widely-recognized commodity specifications which address the hazardous constituents (such as spent solvents being reclaimed into solvent products). (This is in contrast to B.2, where the specifications do not need to specifically address the hazardous constituents.)
  4. The person recycling has the necessary knowledge, such as knowledge about the incoming hazardous secondary material and the recycling process, to be able to demonstrate that the product of recycling does not exhibit a hazardous characteristic and contains hazardous constituents at levels comparable to or lower than those in products made from virgin materials.
- C. The Board believes that the above statements will apply to the majority of recycling and thus, the need to test in order to determine compliance with legitimacy factor 4 of § 260.43 [Rule 0400-12-01-.01(5)(d)] will be infrequent.
- D. If the hazardous secondary materials are being returned to the original production process, then there is no analogous product and legitimacy factor 4 of § 260.43 [Rule 0400-12-01-.01(5)(d)1(iv)] is met. The person conducting the recycling does not need to do any further analysis for the purpose of determining compliance with this factor. For example, recycling that takes place under the closed loop recycling exclusion at § 261.4(a)(8) [Rule 0400-12-01-.02(1)(d)1(viii)] is an example of manufacturing that consistently includes the hazardous secondary material being returned to the original process from which it was generated and that would, therefore, automatically meet legitimacy factor 4 of § 260.43 [Rule 0400-12-01-

.02(1)(d)1(viii)]. Another example includes primary metals production where hazardous secondary materials are returned to the production process to ensure that all the valuable metals are extracted from the ore. This would be another process that would meet legitimacy factor 4 of § 260.43 [Rule 0400-12-01-.02(1)(d)1(viii)] with no further analysis needed.

- E. For the purposes of § 260.43(a)(4)(i) [Rule 0400-12-01-.01(5)(d)1(iv)(I)], analogous products or intermediates include common products or intermediates found in wide-spread markets, which may be secondary markets; such markets typically are well-known, recognized, established, mature, and large.
- F. If a chemical product made from hazardous secondary material has an analogous product made from raw materials and does not exhibit a hazardous characteristic that the analogous product does not and the concentration of hazardous constituents are comparable to those in analogous products, the fourth legitimacy factor is met (§ 260.43(a)(4)(i)) [Rule 0400-12-01-.01(5)(d)1(iv)(I)]. For example, weak acid by-products that are concentrated into stronger acids and undergo extensive QA/QC processes to assure the quality of the concentrated acids.
- G. For the purposes of § 260.43(a)(4)(i)(B) [Rule 0400-12-01-.01(5)(d)1(iv)(I)II], widely-recognized commodity standards and specifications include only those standards and specifications that are publicly available; e.g., in safety data sheets (SDSs), on-line vendor specifications, sales literature, and the like. The department considers the following scenarios to be valid comparisons for the purpose of § 260.43(a)(4)(i)(B)):
  - 1. The hazardous secondary material that is being recycled directly (i.e., without reclamation) as compared to the virgin raw material or ingredient that the hazardous secondary material is replacing;
  - 2. The hazardous secondary material after reclamation that is being recycled as compared to the virgin raw material or ingredient that the reclaimed hazardous secondary material is replacing;
  - 3. The product/intermediate that results from recycling the hazardous secondary material as compared to the product/intermediate that results from using the virgin raw material or ingredient that the hazardous secondary material is replacing;
  - 4. The product/intermediate that results from recycling the hazardous secondary material as compared to a substitute product/intermediate that is made without the hazardous secondary material by a different company or by the same company at a different site or through a different process.
- H. If a chemical product made from a hazardous secondary material has no analogous product made from raw materials, the fourth legitimacy factor is met if the product meets widely recognized standards (§ 260.43(a)(4)(ii)(A)) [Rule 0400-12-01-.01(5)(d)1(iv)(II)I]. For example, recycled methanol that is integrated into the production of a certain polymer when that polymer is a recognized commodity, or oil-bearing secondary materials used to make petroleum products, meets the requirement.
- I. The reference in § 260.43(a)(4)(ii)(B) [Rule 0400-12-01-.01(5)(d)1(iv)(II)II] to hazardous secondary materials returned to the original process is not limited to closed-loop recycling, nor must the hazardous secondary material be returned to the same unit in which it was generated. For the purposes of § 260.43(a)(4)(ii)(B) [Rule 0400-12-01-.01(5)(d)1(iv)(II)II], a hazardous secondary material is returned to the original process if it is returned to the same production process or processes where it was generated; if it is returned to other production processes from which it was derived; if it is returned via closed-loop or open-loop; if it is returned from on-site or off-site; if it is returned from second, third, or later generation use of the hazardous secondary material, product, or intermediate; or if it is returned as part of the long-established recycling of such hazardous secondary material in connection with the manufacturing or use, both on-site and off-site, of a product or intermediate made with the hazardous secondary material. Production process or processes include those activities that

tie directly into the manufacturing operation or those activities that are the primary operation at the establishment.

- J. Recycling meets legitimacy factor 4 of § 260.43 [Rule 0400-12-01-.01(5)(d)1(iv)] if the hazardous secondary material is returned to the original production process to produce a product.
- K. The Board recognizes that there may still be instances where recycling is legitimate, but the hazardous secondary material is unable to meet the technical provisions of legitimacy factor 4 of § 260.43 [Rule 0400-12-01-.01(5)(d)1(iv)] as it is written because the product of the recycling process has levels that are not comparable to analogous products or because the product of the recycling process cannot be compared to an analogous product. In this case, the recycler can document legitimacy by demonstrating that, based on lack of exposure from toxics in the product, lack of the bioavailability of the toxics in the product, or other relevant considerations that show that the recycled product does not contain levels of hazardous constituents that pose a significant human health or environmental risk, the recycling is legitimate. The recycler must also notify the Department in this case.
- L. Consider revising the language in § 260.43(a)(4) [Rule 0400-12-01-.01(5)(d)1(iv)] introduction to reduce confusion:
  - (a) Recycling of hazardous secondary materials for the purpose of the exclusions or exemptions from the hazardous waste regulations must be legitimate. ... The recycling can be shown to be legitimate based on lack of exposure from toxics in the product, lack of the bioavailability of the toxics in the product, or other relevant considerations which show that the ~~recycled~~ product made using recycled material does not contain levels of hazardous constituents that pose a significant human health or environmental risk.

- Response:
- A. The Board agrees with the commenter. See clarifying note at the end of subparagraph (5)(d) of Rule 0400-12-01-.01.
  - B. The Board agrees with these statements.
  - C. The Board agrees with this statement.
  - D. The Board agrees with this statement, however, please see response on page 271 relative to the term closed-loop recycling.
  - E. The Board agrees with this statement.
  - F. The Board agrees with this statement.
  - G. The Board partially agrees with this statement. By “widely-recognized commodity standard,” we mean a standard that is used throughout an industry to describe a certain product and that is widely-available to anyone producing the product. It is important to avoid the potential that the analogous product could be substituted with the recycled product without full disclosure of potential toxics at levels of concern. The Board is concerned that safety data sheets (SDSs), on-line vendor specifications, sales literature, and the like may not be detailed enough to satisfy this concern.
  - H. The Board agrees with this statement, but would need more details before it can agree with the examples given.
  - I. This statement is consistent with the Board intent, but more specific information about the many scenarios will be needed to give a definitive response.
  - J. The Board agrees with this general statement, but more specific information about the many different scenarios that could arise would be needed to give a definitive response.

K. The Board agrees with this statement.

L. The Board agrees that the suggested language change if made to item (5)(d)1(iv)(III) of Rule 0400-12-01-.01 instead of the introductory language to subpart (5)(d)1(iv) of Rule 0400-12-01-.01 would clarify its meaning and has amended that item accordingly.

Comment: Dow recommends changing the order of steps for determining if a recycling scenario meets Factor 4 (§ 260.43(a)(4)(i-iii)) [Rule 0400-12-01-.01(5)(d)1(iv)(I) – (III)] by switching the order of (i)-(analogous) and (ii) – (return to the generator and commodity specifications). The change is recommended to help the generator more effectively determine if it meets one of the simpler criteria before undertaking more complex reviews. This change does not change the stringency of the requirements, simply the order. And, for further clarification, Dow recommends Tennessee add a fourth statement ((§ 260.43(a)(4)(iv)) [Rule 0400-12-01-.01(5)(d)1(iv)(IV)] stating:

“The product of the recycling process is comparable to a legitimate product or intermediate if the requirements of paragraph (a)(4)(i) or (ii) or (iii) of this section are met. Once the requirements of one of these subparagraphs are met, there is no need to determine whether the requirements of any other of these subparagraphs are also met.”

Response: The Board disagrees that the order of items (5)(d)1(iv)(I) through (III) needs to be rearranged or that a new item needs to be added. The order given is the same order as the EPA regulations and will be familiar to interested parties who are accustomed to dealing with EPA regulations and want to easily find comparable Tennessee rules. The operation of item (5)(d)1(iv)(I) is predicated on the existence of an analogous product or intermediate with which to compare the recycled product or intermediate. The operation of item (5)(d)1(iv)(II) is predicated on the lack of an analogous product or intermediate with which to compare the recycled product or intermediate. Therefore, the Board does not believe that the requested statement is necessary.

## Regulatory Flexibility Addendum

Pursuant to T.C.A. §§ 4-5-401 through 4-5-404, prior to initiating the rule making process as described in T.C.A. § 4-5-202(a)(2) and T.C.A. § 4-5-203(a), all agencies shall conduct a review of whether a proposed rule or rule affects small businesses.

This rulemaking is primarily designed to amend the current hazardous waste regulations in order to revise the definition of solid waste and its related variances, exclusions and exemptions. It also deletes the exemption associated with the comparable fuels exclusion and the gasification exclusion to prevent these rules from being less stringent than the federal rules. The Department has been authorized by EPA to administer the hazardous waste program in Tennessee in lieu of the federal government. As an authorized state, Tennessee is required to amend these rules to incorporate the more stringent requirements adopted by the EPA. This rulemaking incorporates those more stringent requirements, which consist of codifying the definition of legitimate recycling, the prohibition of sham recycling, and the additional recordkeeping requirement associated with speculative accumulation. In accordance with Tenn. Code Ann. § 4-5-404, since these amendments are federally mandated, they are not included in the review below.

This rulemaking also incorporates the additional recycling variances, exclusions and exemptions associated with recycling hazardous waste and hazardous secondary materials allowed by the EPA, and exempts from being managed as hazardous waste those wastes generated primarily from processes that support the combustion of coal or other fossil fuels that are co-disposed with excluded fly ash waste, bottom ash waste, slag waste, and flue gas emission control waste generated primarily from the combustion of coal or other fossil fuels. These variances, exclusions and exemptions are less stringent than the current rules and are not federally mandated, and, therefore are included in this review. The variances, exclusions and exemptions are available to qualified persons that elect to obtain them, but no person is required to pursue any variance, exclusion or exemption.

- (1) The type or types of small business and an identification and estimate of the number of small businesses subject to the proposed rule that would bear the cost of, or directly benefit from the proposed rule.

The Department estimates that 546 businesses generating hazardous waste have the greatest potential to recycle hazardous waste or hazardous secondary material in compliance with the new variances, exclusions or exemptions. The Department estimates that about 173 of those businesses will attempt to benefit from the additional variances, exclusions and exemptions. Approximately 60 of those 173 businesses are believed to be small businesses. The additional variances, exclusions and exemptions are not mandatory and do not impose additional costs on small businesses. The Department does not believe any small business would be generating wastes primarily from processes that support the combustion of coal or other fossil fuels.

- (2) The projected reporting, recordkeeping, and other administrative costs required for compliance with the proposed rule, including the type of professional skills necessary for preparation of the report or record.

These amendments do not mandate any additional reporting, recordkeeping or administrative costs.

- (3) A statement of the probable effect on impacted small businesses and consumers.

These amendments make available additional variances, exclusions or exemptions that could result in significant savings for qualified generators and recyclers and conserve valuable resources.

- (4) A description of any less burdensome, less intrusive or less costly alternative methods of achieving the purpose and objectives of the proposed rule that may exist, and to what extent the alternative means might be less burdensome to small business.

These amendments do not mandate any additional requirements and substantially mirror the federal program but with clarifying notes.

- (5) A comparison of the proposed rule with any federal or state counterparts.

These amendments will make Tennessee's program comparable to the federal program and relative to states that do not adopt the additional variances, exclusions or exemptions, those states will be more stringent than necessary to protect public health and the environment.



- (6) Analysis of the effect of the possible exemption of small businesses from all or any part of the requirements contained in the proposed rule.

These amendments do not mandate any additional requirements on small businesses.

### **Impact on Local Governments**

Pursuant to T.C.A. §§ 4-5-220 and 4-5-228 “any rule proposed to be promulgated shall state in a simple declarative sentence, without additional comments on the merits of the policy of the rules or regulation, whether the rule or regulation may have a projected impact on local governments.” (See Public Chapter Number 1070 (<http://state.tn.us/sos/acts/106/pub/pc1070.pdf>) of the 2010 Session of the General Assembly)

The Department anticipates that this rulemaking will not result in an increase in expenditures or decrease in revenues for local governments.

## Additional Information Required by Joint Government Operations Committee

All agencies, upon filing a rule, must also submit the following pursuant to T.C.A. § 4-5-226(i)(1).

- (A)** A brief summary of the rule and a description of all relevant changes in previous regulations effectuated by such rule;

This rulemaking is primarily designed to amend the current hazardous waste rules in order to revise the definition of solid waste and its related variances, exclusions and exemptions. The Department has been authorized by EPA to administer the hazardous waste program in Tennessee in lieu of the federal government. As an authorized state, Tennessee is required amend these rules to incorporate the more stringent requirements adopted by the EPA. This rulemaking incorporates those more stringent requirements, which consist of codifying the definition of legitimate recycling, the prohibition of sham recycling and the additional recordkeeping requirement associated with speculative accumulation. This rulemaking also incorporates the additional variances, exclusions and exemptions associated with recycling hazardous waste and hazardous secondary materials allowed by the EPA. These variances, exclusions and exemptions are not mandatory but are available if a qualified generator or recycler wishes to obtain them.

On April 8, 2015, in compliance with orders issued by the U.S. Court of Appeals, EPA deleted the regulations associated with the comparable fuels exclusion and the gasification exclusion. This rulemaking makes the complying revisions (deleting those exclusions) to prevent these rules from being less stringent than the federal rules.

In accordance with the federal decision to regulate coal combustion residues under the solid waste program instead of the hazardous waste program, on April 17, 2015, EPA amended 40 CFR 261.4(b)(4) to exempt from the hazardous waste regulation wastes generated primarily from processes that support the combustion of coal or other fossil fuels that are co-disposed with excluded fly ash waste, bottom ash waste, slag waste, and flue gas emission control waste generated primarily from the combustion of coal or other fossil fuels. This rulemaking proposes to amend subpart (1)(d)2(iv) of Rule 0400-12-01-.02 to also exempt these same wastes from hazardous waste regulation.

- (B)** A citation to and brief description of any federal law or regulation or any state law or regulation mandating promulgation of such rule or establishing guidelines relevant thereto;

These rules are being promulgated under the authority of Tenn. Code Ann. §§ 68-212-101 et seq. The federal requirements adopted are compiled in 40 CFR Parts 260 and 261.

- (C)** Identification of persons, organizations, corporations or governmental entities most directly affected by this rule, and whether those persons, organizations, corporations or governmental entities urge adoption or rejection of this rule;

All generators and recyclers of hazardous waste and hazardous secondary materials are directly affected by this rulemaking. The Board has been encouraged to adopt these amendments.

- (D)** Identification of any opinions of the attorney general and reporter or any judicial ruling that directly relates to the rule;

The comparable fuels federal regulation was vacated by *Natural Resources Defense Council v. EPA*, 755 F.3d 1010 (June 27, 2014) and the gasification federal regulation was vacated by *Sierra Club v. EPA*, 755 F. 3d 968 (June 27, 2014).

- (E)** An estimate of the probable increase or decrease in state and local government revenues and expenditures, if any, resulting from the promulgation of this rule, and assumptions and reasoning upon which the estimate is based. An agency shall not state that the fiscal impact is minimal if the fiscal impact is more than two percent (2%) of the agency's annual budget or five hundred thousand dollars (\$500,000), whichever is less;

This rulemaking makes additional recycling options available to generators of hazardous secondary materials. A decrease in fee revenue is anticipated but it will take a few years before the recycling infrastructure develops to enable the full benefits of the rulemaking to be realized by the regulated community. When fully realized, the

Department estimates a decrease in fee revenue up to approximately \$284,000.

- (F) Identification of the appropriate agency representative or representatives, possessing substantial knowledge and understanding of the rule;

Jackie Okoreeh-Baah  
Division of Solid Waste Management  
William R. Snodgrass Tennessee Tower  
312 Rosa L. Parks Avenue, 14th Floor  
Nashville, Tennessee 37243  
[Jackie.Okoreeh-Baah@tn.gov](mailto:Jackie.Okoreeh-Baah@tn.gov)

- (G) Identification of the appropriate agency representative or representatives who will explain the rule at a scheduled meeting of the committees;

Lucian Geise  
Senior Counsel for Legislative Affairs  
Office of General Counsel

- (H) Office address, telephone number, and email address of the agency representative or representatives who will explain the rule at a scheduled meeting of the committees; and

Office of General Counsel  
Tennessee Department of Environment and Conservation  
William R. Snodgrass Tennessee Tower  
312 Rosa L. Parks Avenue, 2nd Floor  
Nashville, Tennessee 37243  
(615) 532-0108  
[Lucian.Geise@tn.gov](mailto:Lucian.Geise@tn.gov)

- (I) Any additional information relevant to the rule proposed for continuation that the committee requests.

The Department is not aware of any additional relevant information requested.